

A Review of Traffic Light Protocol for Induced Seismicity and Its Effectiveness in Canada

Honn Kao

Geological Survey of Canada, NRCan
Also at School of Earth and Ocean Sciences, University of Victoria

³ Geoscience BC

⁴ Western University

NATURAL RESOURCES CANADA - INVENTIVE BY NATURE





Outline


- Definition of a Traffic Light Protocol (TLP)
- Historical development of the TLP for induced seismicity (IS-TLP).
- IS-TLP in Canada.
- Case studies of red-light events in BC and AB.
- Summary and implications.





What is a Traffic Light Protocol?


- A TLP is a site-specific, real-time, risk management system with multiple discrete response levels.
- Each TLP level is determined using observable criteria and invokes specific actions designed to mitigate the associated risk.
- Most IS-TLPs work by providing a feedback system that allows for an operational response to the nearby occurrence of seismic events exceeding a prescribed set of criteria.





IS-TLP from Regulator's Perspective

- Identification, analysis, and treatment of seismic risk associated with induced seismicity.
- IS-TLP is considered a reactive risk management tool in the "treatment" catagory.
- In general, seismic damage starts when peak ground acceleration (PGA) exceeds 5–10% of Earth's gravity (g).
- Ultimate goal: To ensure a quick and effective reduction in both the number and size of induced earthquakes.





IS-TLP from Operator and Service Provider's Perspective

- CAPP Publication 2012-0024 "CAPP Hydraulic Fracturing Operation Practice: Anomalous induced seismicity: assessment, monitoring, mitigation and response"
- IS-TLP is part of the "monitoring, mitigation and response" category.
- For the industry, IS-TLP is part of the decision-making process.
 Thus, it must be easy to understand, communicate, develop, and implement.
- Ultimately, the economic reality is the bottom line.





The First IS-TLP

- Proposed for the operations of hydraulic stimulations of enhanced geothermal systems in eastern El Salvador, Central America (Bommer et al. 2006).
- Based on peak ground velocity (PGV).
 - Green: Ground motion below the threshold of general detectability, or the occurrence rate of seismicity lower than the already established background level.
 - Amber: Ground motion can be felt, but damage is unlikely.
 - Red: Damage to buildings is expected to set in.





IS-TLP in Europe


- Enhanced Geothermal System, Basel, Switzerland (Haring et al., 2008).
 - Green: PGV <0.5 mm/s, M_L <2.3, no felt report (Proceed as planned)
 - Yellow: PGV ≤2.0 mm/s, M_L ≥2.3, few felt report (Inform regulators, stop increasing rate)
 - Amber: PGV \leq 5.0 mm/s, $M_1 \leq$ 2.9, many felt reports (Reduce pumping rate)
 - Red: PGV >5.0 mm/s, M_L >2.9, generally felt (Stop pumping, bleed wells)
- Hydraulic Fracturing of Shale Gas, UK (https://www.gov.uk)
 - Green: M_L ≤0.0 (Proceed as planned)
 - Amber: M_L between 0 and 0.5 (Proceed with caution, lower rates, intensify monitoring)
 - Red: M₁ >0.5 (Suspend injection immediately)





IS-TLP in USA

- CO (Wong et al., 2015)
 - Yellow: Felt at the surface (Modify operations)
 - Red: M₁ ≥4.5 (Suspend operations)
- OK (Stoplight System, http://earthquakes.ok.gov)
 - Escalating review of operator's mitigation procedures as $M_L \ge 2.5, \ge 3.0$. Suspend operations when $M_L \ge 3.5$.
- OH (Brudzinski et al., 2017; Dade, 2017)
 - M₁ <1.5 (Proceed as planned)
 - M₁ ≥1.5 (Inform regulator)
 - M₁ between 2.0 and 2.4 (Modify operations)
 - M₁ ≥2.5 (Temporary halt completions on lateral)
 - $M_1 \ge 3.0$ (Suspend operation)





IS-TLP in AB, Canada


- Subsurface Order #2, issued on February 19, 2015.
 - Applicable to the Duvernay Zone within the Fox Creek area.
 - Green: M_L <2.0 (Proceed as planned)
 - Yellow: M_L between 2 and 4 within 5 km of an injection well (Immediately report to AER, implement mitigating plan)
 - Red: M_L ≥4 within 5 km of an injection well (Immediately report to AER and cease hydraulic fracturing operations)





IS-TLP in BC, Canada


- Section 21.1 of the Drilling and Production Regulation (since June 2015, presented as site-specific permit condition since October 2012).
 - A stoplight system, no escalating levels.
 - Applicable to all injection operations in BC.
 - Red: M_L ≥4 within 3 km of the drilling pad, or a ground motion felt on the surface by any individual within the 3 km radius (Suspend operations).





Major Deficiencies of Magnitude-based IS-TLP

- Possible confusion due to magnitude uncertainty.
 - Different scales and/or methodology (M_L, M_w, M_n, etc.)
 - Different choice/availability of data (local array vs. regional networks)
 - Different source characteristics (moment scaling, stress drop, focal mechanism)
 - Different attenuation/distance corrections
 - Different site effects
- Not linked to the impact/consequences of reported events.
- Completely ignore other potential useful indicators (e.g., change of earthquake occurrence rate, migration of hypocenters, correlation with geological structures).





Designated Ground Motion Monitoring Areas in BC


- New permit condition for wells in two designated areas.
- Require presence of adequate monitoring of ground motion during hydraulic fracturing.
 - Minimum of 1 ground motion monitor within 3 km of the common drilling pad.
 - Instrument with a dynamic range of +/-2g and a minimum detectability of 0.02g.
- Submit ground motion monitoring report within 30 days of completion.
- Seismic data for any ground motions exceeding 0.02g must be submitted.

(BC OGC Industry Bulletin 2016-19)






Distribution of Regional Seismicity in northeast BC and west AB




- 4919 events in total.
- 3030 (~62%) occurred in the designated monitoring areas.
- Green: ~81.5%, Yellow: ~18.3%, Red: <0.2%





Ressources naturelles Canada






Red-Light Events in BC and AB

- 1. August 4, 2014, M_w 4.5 (M₁ 4.1)
- 2. January 23, 2015, M_w 4.4 (M₁ 4.1)
 - * M_w 3.6 (Schultz et al., 2017).
- 3. June 13, 2015, M_w 4.6 (M_t 4.3)
 - * M_w 3.9 (Wang et al., 2016), M_L 4.4 (AGS).
- 4. August 17, 2015, M_w 4.6 (M₁ 4.9)
- 5. January 12, 2016, M_w 4.4 (M_L 4.6)
 - * M_w 4.1 (Schultz *et al.*, 2017), M_L 4.8 (AGS).
- 6. July 12, 2016, M_w 3.9 (M, 4.0)



Natural Resources Canada Ressources naturelles Canada







Event 1, M_w 4.5 (M_L 4.1) August 4, 2014 northern Montney, BC

- Active HF and WD during 7/25 8/07.
- One yellow-light (M_w 3.8) event occurred on 7/30.
 - The red-light event occurred with reduced injection rate and pressure.
 - Prior, during, and post-injection earthquake rates are 0, 0.14, and 0 event per day, respectively.
 - No more M4+ event afterwards.








Event 3, M_w 4.6 (M_L 4.3) June 13, 2015 Fox Creek, AB

- Active HF during 5/22 6/07 at 6 nearby wells.
- Among the highest daily injection volume.
- One yellow-light event occurred on 5/27.
 - Prior, during, and post-injection earthquake rates are 0, 0.18, and 0.01 event per day, respectively.
- No more M4+ event afterwards.
- Another example of "delayed" triggering.

(Schultz et al., 2017)






Event 4, Event 4, M_w 4.6 (M_L 4.9) August 17, 2015 northern Montney, BC

- Active HF and WD during 8/11 8/28.
- One green but NO yellow-light event occurred since the injection began before the M_w 4.6 event.
- Seismicity continued for ~one week.
- Prior, during, and post-injection earthquake rates are 0.03, 0.59, and 0.19 events per day, respectively.
- No more M4+ event afterwards.

(Babaie Mahani et al., 2017a, 2017b) Canada




Event 5, M_w 4.4 (M_L 4.6) January 12, 2016 Fox Creek, AB

- Same general area of the January 23, 2015, M_w 4.4, red-light event.
- Active HF started on 1/04, stopped right after the red-light event, never resumed.
- Two yellow-light events occurred on 1/09 and 1/10.
- Prior, during, and post-injection earthquake rates are 0.08, 1.11, and 0.21 events per day, respectively.
- No more M4+ event afterwards. But scattered M<4 seismicity continued till the end of our study period.

(Schultz et al., 2017; Wang et al., 2017)

Canada



Event 6, M_w 3.9 (M_L 4.0) July 12, 2016 northern Montney, BC

- Initially reported $M_L = 4.0$, later revised to $M_W = 3.9$
- Active HF started on 7/08.
- No event occurred before this red-light event.
- Prior, during, and post earthquake rates are <0.001, 0.6, and 0.23 events per day, respectively.
- No more M4+ event afterwards.



Key Observations About Red-Light Events in BC and AB

Key Features	Event 1 (BC)	Event 2 (AB)	Event 3 (AB)	Event 4 (BC)	Event 5 (AB)	Event 6 (BC)
Total number of events during injection stage	2	12	4	10	10	3
Precursory seismicity during injection stage	(YLE)	YLE+GLE	YLE+GLE	GLE	YLE+GLE	None
Rate of seismicity before the start of injection	0.00	<0.01	0.00	0.03	0.08	<0.01
Rate of seismicity during the injection	0.14	0.32	0.18	0.59	1.11	0.60
Rate of seismicity after the injection	0.00	0.21	0.01	0.19	0.21	0.23
Seismicity responding to injection adjustment	Yes	N/A	N/A	Yes	Yes	Yes
Followed by a larger event causing damage	No	No	No	No	No	No





Summary and Implications

- An IS-TLP based on escalating magnitude (green -> yellow -> red) is more applicable to AB than BC.
- Background seismicity may be a useful reference in forecasting the overall seismic response to injections.
 - Low pre-injection seismicity rate ~ Low seismicity rate during injection
- A clear jump in the seismicity rate from the pre-injection period to the injection period, especially after 2015.
- The phenomenon of "delayed triggering" (two red-light events in AB) can be a problem for the effectiveness of the IS-TLP and should be carefully considered
- Existing IS-TLP for induced seismicity in both BC and AB appear to be working in the sense that it prevents any damaging earthquakes (M>5.5) from happening.





Questions or Comments?

Send your questions or comments to

Dr. Honn Kao

Project Leader, Induced Seismicity Research

Geological Survey of Canada

(250) 363-6625

Honn.Kao@canada.ca

