

2 KM=-----

N.W. S.E.
1029 SP. ESSO RESOURCES CANADA LTD. 1213 SP.
GEOPHYSICS, DATA PROCESSING
CALGARY, ALBERTA

LINE 83739 AREA NORMAN WELLS N.W.T.
PART ONE OF ONE DATE 81-06-23

FIELD RECORDING - LAND

CONTRACTOR WESTERN GEO. PTY NO. 81-E34
DATE SHOT FEB. 1981

ENERGY SOURCE

TYPE DYNAMITE
ARRAY SINGLE HOLE LENGTH
SHOT INTERVAL 128 M.

SURVEY LOCATION

START OF LINE LAT 65 15' LONG 127 10'
DIRECTION OF SHOOTING SOUTHEAST

GEOPHONES

TYPE GEOSPACE 20D/10HZ NO. GROUPS 48
GEOPHONES/GROUP 9 GROUP INTERVAL 32 M.
ARRAY INLINE LENGTH 64 M.
.48 25. SP .24 1 .

736 64 736

RECORDING CONFIGURATION 24/24 SPLIT SPREAD
DISTANCES IN ☐ FEET ☒ METRES

RECORDING INSTRUMENTS

SYSTEM SERCEL 338B NO. CHANNELS 48
FORMAT SEG B GAIN TYPE IFP
RECORD LENGTH 3 0 SEC. SAMPLE RATE 2 MS.
RECORD FILTERS LO 12 HZ SLOPE 12 DB/OCTAVE
HI 125 HZ SLOPE 72 DB/OCTAVE

FIELD POLARITY COMPRESSIONAL WAVE
RECORDED AS NEG. VALUES

PROCESSING SEQUENCE

- 1 DEMULT.
- 9 DATUM 0 M. DATUM VEL. 3048 M/SEC
- 5 STATICS COMGAT-COMSTA SHOT& GEO STATICS
- 10 STATICS AUTSTA WINDOW 300-800 SEC.
- 2 GAIN ☒ EXPONENTIAL ☐ GEOCOR
- ☐ VERTICAL SUMMATION TO 1
- ☐ HORIZONTAL SUMMATION TO 1
- ☐ BIMATION TO MS.
- 4 DECON BEFORE STACK CAMFIL
OPERATOR LENGTH 60 MS.
DESIGN GATE 200-1500 MS.
- ☐ FILTER
- 6 VELOCITY ANALYSIS MANUAL LONG SPREAD&CDP GATHER
- 8 NMO
- 11 6 IS FOLD CDP STACK. SB INTERVAL 16 M.
DECON AFTER STACK
OPERATOR LENGTH MS.
DESIGN GATE MS.
- 3 FILTER 18-24/72-80
- 2 MUTE 0-224-256-768 AT 0-0-200-350
- 12 FILTER 12-18/72-80 HZ.
- 14 FLATTENING
- ☐
- ☐
- ☐ PHASE CORRECTION FILTER
- ☐ TRACE NORMALIZE
- 13 AGC 600 MS.

DISPLAY PARAMETERS

64.0 TR./INCH ☒ -VE ☐ +VE
TAPE NAME (OUT) PROD GDP #83739 ADBNSBR1
PROCESSED BY SJ DHANANI

REMARKS

STATICS WINDOW 250-1300 MS.
FAR TRACE DECON DESIGN 400-1500 MS.

81-E34 83739 (1/1)

