



2080 Wabigoon Rd.
Ottawa, Ont.
Canada K1C 9P5
Tel: (613) 731-9671
Fax: (613) 731-0453

PROJ. NO. 9 2 2 7 - 0 2 2 - 1 D A

LINE NO. C C 0 - 4

PART NO. 1 OF 1

R.R. 8X



9227-022-1DA

OCELOT ENERGY INC.

EAST
FORT LIARD, NWT.
REVERSE POLARITY

LINE: CCO-4
S+P: 1 - 42
DMO MIGRATION STACK

LOCATION: SP 1 60.7 N 123.2 W
SP 42 60.7 N 123.5 W
DATUM: 500 M
REPL VEL: 4000 M/SEC

PROCESSED BY: GECO - PRAKLA
DATE PROCESSED: JUNE 1995

FIELD RECORDING

SHOT FOR: PAN AMERICAN PETROLEUM CORP
SHOT BY: N/A
DATE: JANUARY 1969
GROUP INT: 125 M
SHOT INT: 275 M
SPREAD: 2187.5--62.5--X--62.5--2187.5 M
TRACE NO: 1 18 19 36
SOURCE
TYPE: DYNAMITE
PATTERN: 2 HOLES
CHARGE DEPTH: 14.3 M
CHARGE SIZE: 2.3 KG
RECEIVERS
TYPE: L2-A 14 HZ
PATTERN: 12 PHONES PER GROUP
INSTRUMENTS
TYPE: T-401
TOTAL CHANNELS: 36
FIELD FILTER: 5 - 570 HZ, NOTCH N/A
FORMAT: ANALOG
SAMPLE RATE: 2 MS
RECORD LENGTH: 5 SEC

PROCESSING SEQUENCE

1. SEG Y REFORMAT
4.0 SEC
2. TRUE AMPLITUDE GAIN RECOVERY
3. DECONVOLUTION
TYPE: PREDICTIVE
OPERATOR LENGTH: 100 MS
PRE-WHITENING: 1.0 Z
DESIGN GATE: 60 H: 500 - 3000 MS
2000 H: 1000 - 2000 MS
4. TRACE EQUALIZATION
WINDOW: 2000 MS
5. ELEVATION AND WEATHERING CORRECTION
REPLACEMENT VELOCITY 4000 M/SEC
DATUM: 500 M ASL
6. CDP TRACE GATHER
STRAIGHT LINE BUNNING
7. VELOCITY ANALYSIS
8. NORMAL MOVEOUT CORRECTION
REFERENCED TO FLOATING DATUM
9. SURFACE CONSISTENT STATICS
MAX. STATIC: +/- 24 MS
WINDOW: 500 - 2000 MS
10. VELOCITY ANALYSIS
11. NORMAL MOVEOUT CORRECTION
REFERENCED TO FLOATING DATUM
12. SURFACE CONSISTENT STATICS
MAX. STATIC: +/- 30 MS
WINDOW: 400 - 2000 MS
13. COMMON OFFSET F-K DMO
14. VELOCITY ANALYSIS
15. FRONT MUTE
AUTOMATIC STRETCH MUTE
MAX STRETCH ALLOWED - 35%
16. TRIM STATICS
MAX. STATIC: +/- 6 MS
WINDOW: 400 - 2000 MS
17. STACK
AVERAGE FOLD: 6
18. STEEP DIP FINITE DIFFERENCE MIGRATION
BOX STACKING VELOCITY
90 DEGREE ANGLE
19. BANDPASS FILTER
10/15 - 75/85 HZ
20. EQUALIZATION
WINDOW(MS): 0-600
300-900
600-1200
900-1600
1600-4000

FILM DISPLAY BY: EXSSEL
FILM DATE: APRIL 1996
QUALITY CONTROL: PC

DISPLAY PARAMETERS: OVERLAP 0.70 TRACES
VERT 3.75 IN/SEC HORIZ 12.00 TR/IN PRESAMPLE 1.00

EXPLORATION SEISMIC

