

0227-R36-1DA



NORMAL POLARITY NOISE ATTENUATED MIGRATED STACK

LINE : NAE-63-05
PROSPECT NAME : FT. NORMAN
STATIONS : SP 1352 (NW) ... SP 345 (SE)
LOCATION : EL372
DATUM : 500 M ASL
R.V. : 3048 M/S

DATE PROCESSED : AUGUST 1995 DATE SHOT : DECEMBER 1968
SHOT BY : RAY GEOPHYSICAL LTD.
SHOT FOR : MOBIL OIL CANADA

FIELD PARAMETERS

SOURCE TYPE DYNAMITE
LAYOUT TWO HOLES OVER 91.4
SOURCE INTERVAL 91.4 M
GROUP INTERVAL 45.7 M
CHARGE SIZE/DEPTH 2 X 1.1 KG / 15.2 M
SPREAD COVERAGE 600%
SPREAD TRACE 1 12 S/P 13 24
DISTANCE 548.4 45.7 0 45.7 548.4
RECEIVER TYPE EVS 20...
LAYOUT 9 GEOPHONES OVER 45.7 M
INSTRUMENT MODEL TI 10,000
FIELD FILTER 17 - 70 HZ
TAPE FORMAT TIA
RECORD LENGTH 3 SEC
SAMPLE RATE 2 MS



VERITAS SEISMIC

PROCESSING PARAMETERS

- DEMULITEX
PROCESSED LENGTH: 2000 MB
SAMPLE RATE: 2 MB
- AMPLITUDE RECOVERY
TYPE: T-SQUARE FUNCTION
A-T-T-M H=0.002 A=1.0
- GEOMETRY
TYPE: CROOKED LINE
- DECONVOLUTION
PASS (1): SURFACE CONSISTENT SPIKING
OPERATOR LENGTH: 80 M
PREHINTING: 250 - 1700 MB AT 91 M OFFSET
DESIGN DATE 1: 250 - 1300 MB AT 548 M OFFSET
PASS (2): ZERO-PHASE (POST NORMAL MOVEOUT)
OPERATOR LENGTH: 40 M
PREHINTING: 250 - 1700 MB AT 45 M OFFSET
DESIGN DATE 1: 400 - 1800 MB AT 548 M OFFSET
DESIGN DATE 2:
- RESIDUAL AMPLITUDE ANALYSIS
TYPE: APPLICATION TIME AND DISTANT DEPENDENT
- STRUCTURE STATICS
METHOD: C.L.I.
WEATHERING VELOCITY: 900 M/S
DATUM ELEVATION: 500 M ASL
REPLACEMENT VELOCITY: 3048 M/S
PROCESSING DATUM: SURFACE
- TRACE GATHER
MAXIMUM FOLD: 900 %
- PRELIMINARY VELOCITY ANALYSIS
TYPE: VERITAS INTERACTIVE VELOCITY ANALYSIS
REFERENCE: PROCESSING DATUM
- STATICS - AUTOMATIC SURFACE CONSISTENT
WINDOW: 500 - 1800 MB
FILTER: 10/15 - 70/85 HZ
MAX. STATIC: +/- 30 MB
- MANUAL TRACE EDITS
- FINAL VELOCITY ANALYSIS
TYPE: VERITAS INTERACTIVE VELOCITY ANALYSIS
REFERENCE: PROCESSING DATUM
FREQUENCY SPACING: EVERY 45 COMMON DEPTH POINTS
OFFSET DESIGN: 45.7 TO 548.4 BY 45.7
OFFSET WIDTH:
- SPIKE ATTENUATOR (BLAST)
THRESHOLD: 4:1
- STATICS - CDP TRIM
WINDOW: 500 - 1800 MB
FILTER: 10/15 - 80/90 HZ
MAX. STATIC: +/- 12 MB
- VELOCITY VERIFICATION
METHOD: COMMON OFFSET STACKS WITH N.M.O.
AND STATICS APPLIED
- FIRST BREAK MUTES
DISTANCE: 270 288 550 M
TIME: 4 300 500 MB
- STACK
MAXIMUM FOLD: 900 %
- FINITE DIFFERENCE MIGRATION
STACKING VELOCITIES: 100 %
- NOISE ATTENUATION (F-X DECON.)
FREQUENCY RANGE: 10 - 100 HZ
- FILTER - DIGITAL BANDPASS
TYPE: APPLICATION DATE (MB)
10/15-80/95 0 - 2000
- AMPLITUDE EQUALIZATION
TYPE: MEAN SCALING
DESIGN DATE: 250 - 500 APPLICATION TIME (MB)
500 - 2000 0 500 0 500

DISPLAY PARAMETERS

HORIZONTAL SCALE 16.32 TRACES PER INCH
VERTICAL SCALE 7.5 INCHES PER SECOND

17 OCT 1995

17 OCT 1995

