

INTERPRETED SECTION JRS
RANGER OIL
OCT /96

RANGER OIL LTD.

9229-B59-4E

FT. LIARD

LINE NAD-07
SPS: 332-103

PRE STACK MIGRATION

DISPLAY POLARITY
NORMAL

STATICS PARAMETERS
DATUM: 500 M REPL VEL: 4000 M/

FIELD PARAMETERS
SHOT FOR: NORTHCOR , MARCH 1984
SHOT BY: SEISL GEOPHYSICAL LTD. , PARTY-501
INSTRUMENTS
MAKE/MODEL: MDS-10
S.R.: 2 MS LENGTH: 6 SEC
FILTER: 10-125 NOTCH OUT
FORMAT: SEG-B
SOURCE
TYPE: DYNAMITE
CHARGE SIZE: 6 KG. VARIES
CHARGE DEPTH: 6 M. VARIES
NO. IN LINE: 1
GEOPHONES
TYPE: MARK L-15A- 10 HZ
DAMPING: 0.7
NUMBER/GROUP: 10
GROUP LGTH: 50 M
SPREAD
FOLD: 48
SHOT POINT INT: 40 M.
GROUP INT: 40 M.
SPREAD CONFIGURATION
TRACES: 1-48-+-49-96 TRACE 1 NORTHEAST
1508-40-+-40-1508 M

PROCESSED APRIL 1996 BY
KELMAN SEISMIC PROCESSING

PROCESSING SEQUENCE

DEMULTIPLEX
PROCESS SAMPLE RATE: 2.0 MS
PROCESS RECORD LENGTH: 4.0 SEC
AMPLITUDE RECOVERY
TEMPERATURE DATA CURVE: MI7PURENX(EXPERT3) R=1 A=0 N=2
TRACE EDITING
PHASE COMPENSATION
INSTRUMENT AND GEOPHONE
DECONVOLUTION
TYPE: SURFACE CONSISTENT SPIKING
OPERATOR LENGTH: 80 MS
PREWHITENING: 1.0%
DESIGN GATE: 600 - 3000 MS AT 4M OFFSET
1500 - 3000 MS AT 1508M OFFSET
OFFSET RANGE: 100 - 1508 M
PARTIAL SPECTRAL BALANCING
FREQUENCY: 8 - 128 HZ
EQUALIZATION
DESIGN GATE: SAME WINDOW AS DECON
STATICS (REFRACTION)
METHOD: GLI
SHOT POINT SPACING: EVERY SHOT
DATUM ELEVATION: 500 M
WEATHERING VELOCITY: 2500 M/SEC
REPLACEMENT VELOCITY: 4000 M/SEC
SORT
TO COMMON DEPTH POINT
VELOCITY ANALYSIS
TYPE: CONSTANT PERCENTAGE REMOVOUT
STATICS (RESIDUAL)
TYPE: AUTOMATIC SURFACE CONSISTENT
CORRELATION WINDOW: 600 - 3000 MS
MAXIMUM SHIFT: +/- 32 MS
CORRELATIONS PER TRACE: 15
NUMBER OF ITERATIONS: 2
VELOCITY ANALYSIS
TYPE: CONSTANT PERCENTAGE REMOVOUT
STATICS (RESIDUAL)-SECOND PASS
TYPE: AUTOMATIC SURFACE CONSISTENT
CORRELATION WINDOW: 300 - 3000 MS
MAXIMUM SHIFT: +/- 16 MS
CORRELATIONS PER TRACE: 15
NUMBER OF ITERATIONS: 2
PRE-STK MIG. VEL. ANALYSIS
TYPE: CONSTANT PERCENTAGE REMOVOUT
MUTE PATTERN
DISTANCE: 400 440 1500 5000 M
TIME: -300 400 1200 2000 MS
EQUALIZATION
DESIGN WINDOW: 500 MS AGC
FULL PRE-STACK MIGRATION
TYPE: KIRCHHOFF SUMMATION
DATUM REFERENCED: TO PLOTTED WEATHERING REPLACED SURFACE.
SEPARATELY AT SHOT AND RECEIVER
STACK
SPIKE SUPRESSION: 3:1 THRESHOLD
FOLD: 48
FILTER
FREQUENCY: 18/15 - 45/55 HZ
EQUALIZATION
DESIGN WINDOW: 600 MS AGC
FINAL DISPLAY

1KM BLIP INCREMENT

DISPLAY PARAMETERS
HORIZONTAL: 20.0 TRACES/INCH VERTICAL: 5 INCHES/SECOND
400 M/INCH 400 M/INCH

terra survey ltd.
2060 Walney Rd. Ottawa, Ont.
Canada K1G 3P5
Tel (613) 731-9571
Fax. (613) 731-0453

PROJ. NO. 9229-B59-2E

LINE NO. NAD-07

PART NO. 1 OF 1

R.R. 8X