

RANGER OIL LTD.

9229-B59-5E
FT. LIARD

LINE NAP-003
SPS: 93 - 547

POST STACK MIGRATION

DISPLAY POLARITY
NORMAL

STATICS PARAMETERS
DATUM: 500 M REPL VEL: 4000 M/S

FIELD PARAMETERS

SHOT FOR: RANGER OIL LTD. / APRIL 1997
SHOT BY: GECO-PRAKLA / PARTY-1254

INSTRUMENTS
MAKE/MODEL: I/O II
S.R.: 2 MS LENGTH: 5 SEC
FILTER: 3-195 NOTCH OUT
FORMAT: SEG-D

GEOPHONES
TYPE: OYO GS20DX- 10 HZ
DAMPING: 0.7
NUMBER/GROUP: 9
GROUP LTH: 20 M

SOURCE
TYPE : VIBROSEIS
MODEL : 4 X 4
SWEEP : 18-108 HZ
LENGTH : 10 SEC

SPREAD
FOLD : 6000 PCT
S.P. INT : 40 M
GRP. INT : 20 M

SPREAD CONFIGURATION
TRACES: 1----------323 TRACE 1 NORTHERST
3220.0----------3220.0 M

PROCESSED JULY 1997 BY

KELMAN SEISMIC PROCESSING

PROCESSING SEQUENCE

DEMULTIPLEX
PROCESS SAMPLE RATE: 2.0 MS
PROCESS RECORD LENGTH: 5.0 SEC

AMPLITUDE RECOVERY
EXPONENTIAL GAIN CURVE: KE1TPUREX0(EXPLRT3) R=1 B=0 N=2

TRACE EDITING

PHASE COMPENSATION
TYPE: GEOPHONE

VIBROSEIS PHASE COMPENSATION:
METHOD: CLUNDER WAVELET TO MINIMUM PHASE

DECONVOLUTION
TYPE: SURFACE CONSISTENT SPIKING
OPERATOR LENGTH: 88 MS
PREWHITENING: 1.0%
DESIGN GATE: 1400 - 2300 MS AT ZERO OFFSET
1400 - 2300 MS AT 3000M OFFSET
OFFSET RANGE: 600 - 1500 M

PARTIAL SPECTRAL BALANCING
FREQUENCY: 18 - 108 HZ

EQUALIZATION
DESIGN GATE: SAME WINDOW AS DECON

STATICS (REFRACTION)
METHOD: GLI
FREQUENCY SMOKING: EVERY SHOT
DATUM ELEVATION: 500 M
WEATHERING VELOCITY: 750 M/SEC
REPLACEMENT VELOCITY: 4000 M/SEC

SORT
TO COMMON DEPTH POINT

VELOCITY ANALYSIS
TYPE: CONSTANT PERCENTAGE MOVEOUT

STATICS (RESIDUAL)
TYPE: AUTOMATIC SURFACE CONSISTENT
CORRELATION WINDOW: 300 - 3000 MS
MAXIMUM SHIFT: +/- 32 MS
CORRELATIONS PER TRACE: 15
NUMBER OF ITERATIONS: 2

VELOCITY ANALYSIS
TYPE: CONSTANT PERCENTAGE MOVEOUT

STATICS (RESIDUAL)-SECOND PASS
TYPE: AUTOMATIC SURFACE CONSISTENT
CORRELATION WINDOW: 300 - 3000 MS
MAXIMUM SHIFT: +/- 16 MS
CORRELATIONS PER TRACE: 15
NUMBER OF ITERATIONS: 2

NORMAL MOVEOUT CORRECTION:
DATUM REFERENCED, TO PLOTTED WEATHERING REPLACED SURFACE, SEPARATELY AT SHOT AND RECEIVER

MUTE PATTERN
DISTANCE: 440 640 3020 M
TIME: -300 500 800 MS

STACK
SPIKE SUPRESSION: 3:1 THRESHOLD
FOLD: 88

MIGRATION
TYPE: KIRCHHOFF SUMMATION
VELS: 100 PCT SMOOTHED STACKING

FILTER
FREQUENCY: 18/15 - 45/55 HZ

EQUALIZATION
DESIGN WINDOW: 600 MS AGC

FINAL DISPLAY

1KM BLIP INCREMENT

DISPLAY PARAMETERS
HORIZONTAL: 48 TRACES/INCH VERTICAL: 5 INCHES/SECOND
400 M/INCH 400 M/INCH

TRIATHLON
PROJ. NO. 9229 B59 5E
LINE NO. NAP-3
PART NO. 1 OF 1
R.R. 8X