

LINE 33 106-H-NE
PROSPECT FT. GOOD HOPE

PROFILES 3500-4154
PROVINCE N.W.T. CANADA
CHEVRON CANADA RESOURCES FRONTIER DIV.
PROCESSED BY CHEVRON GEOSCIENCES COMPANY
DIVISION OF CHEVRON INDUSTRIES INC.
HOUSTON DATA PROCESSING SYSTEM

RECORDING PARAMETERS

DATE=APRIL/1989 CREW=CEPS #6 RECD 5->N TR=PRFILE=128 COV= 280PS
SPREAD= 1218- 38-SP= 38- 1218 M. SP INT= 60 M. GRP INT= 20 M.
DYNAMITE 1 HOLE 1.0 KG/HOLE HOLE DEPTH= 5 M.
GEOPHONE TYPE=SM-7 NAT FREQ=38 HZ PHONES/GRP= 9 2.2 M. APART
INST=DFS 5 REC LEN=4 S SI=2 MS FILTER=12/18-120/72 HZ
NOTCH=OUT TAPE FMT=SEC 8

[illegible]

```

OUTPUT DSSK64 PARTIAL SPECTRAL DATA (DSSKOUT 178018) CPMBS/SEC/1989 21.48.52
DSSKOUT 178018 CPMBS/SEC/1989 21.48.52 DSSKIN=178018 DSSKOUT=178018
AUTOREGRESSORS=4096025S TIME=21.44.13.33 1989-05-20 22:18:57
AUTOREGRESSORS=4096025S TIME=21.44.13.33 1989-05-20 22:18:57
BINSIZE 8192S UZF64 UZF6413A CHEST
BINSIZE 8192S UZF64 UZF6413A CHEST 1989-05-20 22:18:57
NOTE: APPLICATION: SORTED UZF64 UZF6413A CHEST
NOTE: ON SORT ATTRIB 13 SPKES
DATA SELECTION: WINDOW UZF64 UZF6413A CHEST
GROUPS SELECTED: 1
MARKER: MARK1: SORTED UZF64 UZF6413A CHEST
GROUPS COMPILED: UZF64 UZF6413A CHEST 1989-06-07 28:05:51
AMPLITUDE CORRECTION: AMPCOR UZF64 UZF6413A CHEST
CORRECTION: SINCORRECTION CORRECTION
EXPONENTIAL_GAIN CORRECTION 6.0 DB/S
CORRECTION: HECOR UZF64 UZF6413A CHEST 1989-06-07 28:05:52

```

```

RECONSTRUCTION: SECON  U280 V2P4P157 CHESTST      1989-06-07 20:05:53
SPINLE
STABILIZATION FACTOR: 1.00 PERCENT
NUMBER OF OPERATORS: 1
OPERATOR LENGTH: 0.064
OFFSETS: 30. 1210.
BEGIN DESIGN CATES: 0.200 0.000
END DESIGN CATES: 2.000 2.000
END APPLICATION: END OF DATA
FILTER: FPFILT U280 V2P4P157 CHESTST
TYPE: SHAPES PHASE: XEROX      1989-06-07 20:05:53
LOW CUT SLOPE: 24

```

```

HIGH CUT SLOPE: 36
SPED TIME LOW CUT ATTENUATION HIGH CUT ATTENUATION
1 8-88 18-88 48-
GORT: ZONT WIRL UZP6F157 CHEST 128-88 48- 1989-06-07 20:17:59
CAP GORT:
FIELD STATICS: 885 UPHOT TIME= 89-44.33 DATE= 89-149
STATICS APPLIED: STAT UZ6R UZP6F157 CHEST 1989-06-07 20:18:01
FIELD STATICS
MULTIPLY SCAN CONNECTION
BATUM SHUT
NUMBER OF SPRTIAL LOCATIONS: 2 (ONLY FIRST LOCATION SHOWN)

```

```

SP LOCATION: 2 -0.163
DATA SWIFT:
SPECTRAL UNITING: CALF15 VIMS UPGRA157 CHEST 1989-06-07 20:11:04
NUMBER OF FILTERS: 0
NUMBER OF FILTER POINTS: 181 FILTER WIDTH: 18.00 HZ
FIRST FREQUENCY: 25.00 HZ
OPERATOR LENGTHS: 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000
NORMAL POLAROID REFRAIND INDEX USR1 UPGRA159 CHEST 1989-06-20 20:11:49
NUMBER OF SPECTRAL LOCATIONS: 2
VELOCITY TYPE: STRUCKING
END RECORD
BLINDING CALIBRATION: ARKST VIMS UPGRA159 CHEST 1989-06-20 20:11:49

```

```

REGIONAL STATISTICS CALCULATED AT REQUEST URGZ UZP6F159 CHEST 1989-06-25 20:11:49
CORRELATION METHOD: TRAC TO TRAC
CORRELATION LENGTH: 0.182 SECONDS
NUMBER OF SPATIAL LOCATIONS: 2 ONLY FIRST LOCATION KNOWN
CMP LOCATION: 2
CELL LENGTH: 240.000
CELL OVERLAP: 50.0 N
CORRELATION BEGIN TIME: 1.000
CORRELATION END TIME: 1.400

STATISTICS APPLIED: STAT URGZ UZP6F159 CHEST 1989-06-25 20:11:52
REGIONAL_RISK_STATISTICS

```

```

RESIDUAL PILOT STATICS
FIRST BREAK MUTE: MUTE      V30R U2P6F159 CHEST      1989-06-25 20:11:53
MUTE APPLY: YES
TIME-OFFSET: 0.000-      0. 0.150- 418- 0.300- 415-
STACK: STACK U40T U0V6F159 CHEST      1989-06-25 20:11:54
TYPE: PEAN STACK
FILTER: PFFILT V20R U2P6F159 CHEST
TYPE: B00KPASS      PHRASE: ZERO
LOW CUT SLOPE: 12
HIGH CUT SLOPE: 72

```

```

CMP TIME LOW CPU ATTENUATION HIGH CPU ATTENUATION
7 8.88 18.88 48.88 58.88 48
BOSSCH SETSSI=12489932 TIME=19.13.39 DATE=89.17.08
SCALE DATA ARE B. SCALED TO THE PWD IN ZONE
TIME= 8.388 72= 1.488 REGIM=1ST DP END=LAST DP
BOSSCH SETSSI=12489144 TIME=19.16.38 DATE=89.17.08
NTRK=24 MSKIP=12 INCRPT=12 MS INSECT=7 MINDP=1 -36 MS TX=48 MS NITER= 1
TIME= 8.188 SEC 72= 2.888 SEC INCF= 8
THRESH=0.128
NO TRACE EQUALIZATION PERFORMED
ERROR FLAG PLOT TYPE CREATED
TRACER SETSSI=12489144 TIME=19.16.38 DATE=89.17.08

```

```

TIMERS SETS1=15551800 TIME=21.16-52 DATE=89.181
SPINING AND TYPING AND PRINTING AND DRIVING OFFICE
      NTWS= 8 * NSPP= 188
GEARIN RIGATED 89.181 22.16.82 TIME=16080112 START= 18
SCALE DATA ARE SCALED TO THE MAX IN EACH
      T1= 8.388 T2= 1.468 BEGIN=151 DP END=LAST DP
STAT SETS1=09581195 TIME=22.21.55 DATE=89.181
ELEVAT TIME=22.23.60 DATE=89.181
PLOT 89.181 22.23.55 18385142
FLONTING POINT DATA
*****
* CONFIDENTIAL-RESTRICTED TO SOCIAL USE *

```

* PERMANENT DATA SETS *
* RESU-VZ6-P5083876-BIN29-U943383 *
* CALGRY-VZ6-P5083876-SFMT0-U943381 * (STATICS)
* CALGRY-VZ6-P5083876-SFMT-U943381 * (CHESS, STAKE)
* CH959812-P5083876-STRT-U633381 * (RESORT TIME)
* CH959812-P5083876-STRT-U633382 * (RESORT TIME)

```

* WINDUP ..... APPLIED INSTRUMENT DEPHASE FILTER *
* UPSHOT FIELD STATICS APPLIED ... *
*
* BATHYM ..... 488 METERS *
* WEATHERING VELOCITY ..... 788 METERS PER SECOND *
* REPLACEMENT VELOCITY ..... 3788 METERS PER SECOND *
*
* TOTAL WND VELOCITY FUNCTION ... *
*
* S.P. 2651 *
* (S. 10. 2650) (S. 10. 2650) (S. 10. 2650)

```

[illegible]

```

*
* (1.40,5198),(1.60,5207),(2.00,5300)
* (3.00,5400)
*
* FLOATING DATUM PUT IN ...
*
* AT CDP = 2 DATUM SHIFT = -0.162 SECONDS
* AT CDP = 1302 DATUM SHIFT = -0.170 SECONDS
*
* FLOATING DATUM REMOVED ...
*
* AT CDP = 2 DATUM SHIFT = +0.162 SECONDS

```

```

* AT CDP = 1202 DATUM SHIFT = +0.170 SECONDS *
* *
* RASP PREPROCESSING ... *
* *
* MUTE... OFFSET 0.0, 410, 415, 1210 METERS *
* *
* TIME .000, .150, .300, .600 SECONDS *
* *
* ***** PLOT PARAMETERS ***** *
* *
* PLOT DIRECTION = LEFT *
* PLOT ANGLE USE = 3600 *

```

```

*      PLOT AMPLITUDE = 3400      *
*      TSC = 7.5 TRSP = 30      *
*      HORIZONTAL SCALE --> 300 M PER INCH      *
*      VERTICAL SCALE --> 7.5 INCHES PER SECOVD      *
*
*****

```

[illegible]



2080 Valley Rd
Caledonia, Ont.
Canada N1S 3P7
Tel: (519) 335-3821
Telex: 055-3802
Cable: TERRA

PROJ. NO.

9

2

2

9

-

C

4

-

8

E

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

.

PART NO.

2

OF

2

.

.

.

.

.

.

.

.

.

.

R.R. 10X

3503 3521 3542 3560 3579 3599 3617 3635 3653 3671 3690 3710 3728 3746 3764

3809 3827 3848 3869 3887 3905 3926 3944 3963 3981 4001 4019 4037 4059 4079

LINE 33
PROSPECT FT.GOOD HOPE

PROFILES 3500-4154
PROVINCE N.W.T. CANADA
CHEVRON CANADA RESOURCES FRONTIER DIV.
PROCESSED BY CHEVRON GEOSCIENCES COMPANY
DIVISION OF CHEVRON INDUSTRIES INC.
HOUSTON DATA PROCESSING SYSTEM

RECORDING PARAMETERS

DATE=APRIL/1989 CREW=CEPS AG RECD 5-3M TR/PPFILE=128 COU=2000M
SPREAD=1218- 38-50- 38- 1218 M. SP INT=08 M. SP INT= 28 M.
DYNAMITE 1.0 HOLE 1.0 KG/HOLE HOLE DEPTH= 5 M.
GEOPHONE TYPE=BN-7 ANT PREG=38 HZ PHONES/GPP= 9 2.22 M. SPART
INST=SPS 5 REC LEN=4 S 51-2 HG FILTER=12/18-120/2 HZ
NOTCH=OUT TAPE INT=SEC 8
EDITED
PRINTED=UNCHECKED
PLOT 00-101 22-02-90

120
85
50
15
100
200
300
400
500
600
700
800
900
1000
1100
1200
1300
1400
1500
1600
1700
1800
1900
2000
2100
2200
2300
2400
2500
2600
2700
2800
2900
3000

