

303

273

243

213

183

153

124

STN.

9229 - C20 - 13

LINE: 85-371

WESTERN GEOPHYSICAL LTD.
CALGARY ALBERTA
PROCESSING DATE: APRIL 1986
PROCESSED FOR: CANADIAN SUPERIOR OIL LTD.

AREA: CAMERON HILLS
LINE: 85-371
S.P.: 101 - 477
DIR.: NORTH - SOUTH
NTS GRID: 84 N-13/14
NTS GRID: 85 C-3/4
LOCATION: T126 R18-21 WSM+NNT
POLARITY: NORMAL
AFE: G3 - 634
DATUM ELEV.: 750 M
REF. VEL.: 2250 M/S

COMMON OFFSET STACK

FIELD PARAMETERS

SHOT FOR: CANADIAN SUPERIOR OIL LTD.
SHOT BY: SONIX EXPLORATION LTD.
DATE: MARCH 1986

SPREAD
SHOOTING DIRECTION: N - S
FOUR: 1500Z
STATION INT.: 18 M
SHOT PT. INT.: 72 M
SPREAD: (TR) 1 60 61 120
DIST: (M) 1152 -- 90 X 90 --- 1152

RECEIVER
MAKE/MODEL/TYPE: OYO / 14HZ
NUMBER PER GROUP: 9
SPACING: 2.25M
ARRAY: INLINE

SOURCE
TYPE: VIBROSEIS
VIBRATOR MODEL: LRS-315
NUMBER OF SOURCES: 3
DRAG LENGTH: 7 MOVES OF 5.14 M
SWEEP FREQUENCY: VARI-SWEEP (8 SWEEPS)
1. 15 - 75 HZ
2. 20 - 80 HZ
3. 25 - 85 HZ
4. 27 - 87 HZ
5. 30 - 90 HZ
6. 33 - 93 HZ
7. 35 - 95 HZ
8. 40 - 100 HZ
SWEEP LENGTH: 12 SEC

INSTRUMENTS
MAKE/MODEL: FTI - DFS-V
RECORD LENGTH: 2 SEC
SAMPLE RATE: 2 MS
FILTER: 8 - 128 HZ
NOTCH: OUT
TAPE FORMAT: SEG B
TAPE DENSITY: 1600 BPI

PROCESSED BY WESTERN GEOPHYSICAL DIVISION OF LITTON INDUSTRIES

PROCESSING PARAMETERS

- DEMUTIPLEX
OUTPUT SAMPLE RATE: 2 MS
OUTPUT DATA LENGTH: 2 SECONDS
- GEOMETRY
LINE, PATTERN, SOURCE, ELEVATION STATIC
- AMPLITUDE RECOVERY
TYPE: SPHERICAL DIVERGENCE
- DEPHASING
GEOPHONES: 14 HZ 60Z DAMPING
- DECONVOLUTION
TYPE: PREDICTIVE
PREDICTION DISTANCE: 12 MS
OPERATOR LENGTH: 60 MS
PREWHITENING: 0.12
APPLICATION WINDOW: 0 - 2000 MS
DESIGN WINDOW (NEAR OFFSET- 90 M): 200 - 1200 MS
DESIGN WINDOW (FAR OFFSET-1152 M): 800 - 1200 MS
- CDP GATHERS
- STATICS
INTERACTIVE REFRACTION ANALYSIS
DRIFT AND WEATHERING CORRECTIONS
- VELOCITY ANALYSIS (VELAN)
REFERENCED TO SURFACE
- NORMAL MOVEOUT APPLICATION
REFERENCED TO SURFACE
- AUTOMATIC SURFACE CONSISTENT STATICS (MISER)
WINDOW: 350 - 1100 MS
MAXIMUM SHIFT: +/- 24 MS
NO. OF ITERATIONS: 3
- RE-ITERATION OF 8 AND 9
STANDOUT AFTER GAIN: 1.75
- AUTOMATIC TRIM STATICS (C.D.P.)
WINDOW: 350 - 1100 MS
MAXIMUM SHIFT: +/- 24MS
MODEL TRACES: 5 TRACES
- COMMON OFFSET STACK
- FILTER APPLICATION
TYPE: BANDPASS
PASSBAND: 18/18 - 60/36
DOMAIN: FREQUENCY
APPLICATION: 0 - 2000 MS
- GAIN (RMS)
LENGTH OF FIRST GAIN ZONE: 400 MS
LENGTH OF LONGEST GAIN ZONE: 400 MS
2000 RMS AMPLITUDE
- DISPLAY SCALE
HORIZONTAL SCALE: 12 TRAC 5/INCH
VERTICAL SCALE: 7.5 INCHES/SEC
GEOSPACE PLOTTING GAIN: 1100C 21 1986
1 INCH = 216 METERS

O.C. GEOPHYSICIST: R.E. DIMENT



2080 Valley Rd.
Calgary, Alberta T2C 3P5
Tel: (403) 231-9271
Telex: 083-3902
Cable: TERMA

PROJ. NO. 9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13

9229 - C20 - 13



2000 Highway Rd.
Ottawa, Ont.
Canada K1G 3P9
Tel: (613) 731-9571
Cable: TERRA
Fax: (613) 731-9572

PROJ. NO.

9 2 2 9 - C 2 0 - 1 E

LINE NO.

8 5 - 3 7 1

PART NO.

2 OF 2

R.R. 8X



453 423 393 363 333 303 273 243 213

