

CANADIAN
FOREST
OIL LTD.

92-29-C131-2E

MAXHAMISH

LINE: 99-EL380-12
SPS: 107 - 605

PRE-STACK MIGRATION

NORMAL POLARITY

STATICS PARAMETERS
DATUM: 500 M REPL VEL: 4000 M/S

FIELD PARAMETERS

SHOT FOR : CANADIAN FOREST OIL LTD. SEPT, 1999
SHOT BY : POLARIS EXPLORER LTD. CREW 2

```
INSTRUMENTS
NAME/MODEL : MARK 24 MARK-1
TYPE : 2 M
LENGTH : 15 SEC
FILTER : 3 - 164 HZ
NOTCH : 0 OUT
FORMAT : SEC-Y

SOURCE
TYPE : DYNAMITE
CHARGE : 200 KG
DEPTH : 0 M
NO. IN LINE : 1

GEOPHONES
TYPE : 1 OYO 6530
FREQUENCY : 10 HZ
DIPPING :
NUMBER/GROUP : 5
SPACING : 3 M
GROUP LENGTH : 15 M

SPREAD
FOLD : 4000 PCT
S.P. INT : 100 M
GPR. INT : 15 M
```

CONFIGURATION
3600--15--15--3600 M
1--240--241--480

PROCESSED SEPTEMBER 1999 BY

KELMAN SEISMIC
PROCESSING

PROCESSING SEQUENCE

[illegible]

DISPLAY PARAMETERS