

PETREL CONSULTANTS LTD.

PROCESSED FOR
NSM RESOURCES LTD.
REVERSE POLARITY
AREA: LITTLE BEAR
LINE: 113
LOCATION: N.W.T.
SW 1129 SHOT POINTS 101 NE

FIELD RECORDING

DATE: MARCH 1993
RECORDED BY: WESTERN GEOPHYSICAL
ENERGY SOURCE: DYNAMITE 1 HOLE AT 14 M
RECORDER TYPE: DFS-U SAMPLE RATE 2 NS.
GAIN CONTROL: FLOATING POINT
FIELD FILTER: 12 - 128 HZ
GEOPHONES/GROUP: 9 AT 3.75 M TYPE: MARK 14 HZ
COVERAGE 12800' SHOT INT. 134 M GROUP INT. 33.5 M
1600 - 33.5 X 33.5 - 1600

COMPUTATIONS

STRUCTURAL DATUM 500 M
REPLACEMENT VELOCITY 3040 M/SEC

PROCESSING PARAMETERS

1. DEMULTIPLY SAMPLE RATE 4 NS.
DATE: MAY 1993
2. TRACE CATHER
3. AMPLITUDE RECOVERY
4. DECONVOLUTION TYPE: SPIKING
GATE: 600 - 2000 NS.
OPERATOR LENGTH: 72 NS.
PRE-WHITENING: 5 %
5. NMO WELL TOT
6. STATIC CORRECTIONS ELEV/TUN/DRIFT
7. BRUTE STACK
8. COMMON OFFSET STACK
9. NMO
10. AUTOMATIC RESIDUAL STATICS
GATE: 500 - 2000 NS.
11. FIRST BREAK HUTE TIME 0 DIST. 272
TIME 450 DIST. 306
TIME 770 DIST. 544
TIME 1400 DIST. 1632
12. STACK 12800
13. FILTER 0-1050 NS., 20/25-70/85
1250-3000 NS., 16/23-65/75
14. TRACE EQUALIZATION
15. FILM DISPLAY 24 TR/IN 7.5 IN/SEC

9200-ND-00 4



