

PETREL CONSULTANTS LTD.

PROCESSED FOR

NSM RESOURCES LTD.

NORMAL POLARITY

AREA: LITTLE BEAR
LINE: 102
LOCATION: N.W.T.
SW 393 SHOT POINTS 101 NE

FIELD RECORDING

DATE: MARCH 1983
RECORDED BY: WESTERN GEOPHYSICAL
ENERGY SOURCE: DYNAMITE 1 HOLE AT 14 M
RECORDER TYPE: DFS-V SAMPLE RATE 2 MS.
GAIN CONTROL: FLOATING POINT
FIELD FILTER: 12 - 128 HZ
GEOPHONES/GROUP: 9 AT 3.75 M TYPE: MARK 14 HZ
COVERAGE 1200% SHOT INT. 134 M GROUP INT. 33.5 M
1600 - 33.5 X 33.5 - 1600

COMPUTATIONS

STRUCTURAL DATUM 500 M
REPLACEMENT VELOCITY 3040 M/SEC

PROCESSING PARAMETERS

DATE: MAY 1983
1. DEMULTIPLEX SAMPLE RATE 4 MS.
2. TRACE GATHER
3. AMPLITUDE RECOVERY
4. DECONVOLUTION TYPE: SPIKING
GATE: 800 - 2200 MS.
OPERATOR LENGTH: 72 MS.
PRE-WHITENING: 5 %
5. NMO WELL TDT
6. STATIC CORRECTIONS ELEV/TOW/DRIFT
7. BRUTE STACK
8. COMMON OFFSET STACK
9. RMNO
10. AUTOMATIC RESIDUAL STATICS
GATE: 500 - 2800 MS.
11. FIRST BREAK MUTE TIME 0 DIST. 272
TIME 450 DIST. 386
TIME 770 DIST. 544
TIME 1400 DIST. 1632
12. STACK 1200%
13. FILTER 0-1050 MS.: 20/26-70/85
1250-3000 MS.: 16/23-65/75
14. TRACE EQUALIZATION
15. FILM DISPLAY 24 TR/IN 7.5 IN/SEC

9229-N9-3E

2060 Walkley Rd. Ottawa, Ont.
Canada K1G 3P5
Tel. (613) 731-9571
Telex: 053-3502 Cable: TERRA

PROJ. NO. 9229-N9-3E

LINE NO. 102

PART NO. 1 OF 1

R.R. 10X