

2080 Valley Rd. Ottawa, Ont.
Canada K1G 3P5
Tel: (613) 731-3571
Telex: 053-3502
Cable: TERRA


PROJ. NO. 9 2 2 9

N 9 - 3 E

LINE NO. 1 0 2

PART NO. 1 OF 1

R.R. 10X



PETREL CONSULTANTS LTD.

PROCESSED FOR
NSM RESOURCES LTD.
REVERSE POLARITY
AREA: LITTLE BEAR
LINE: 102
LOCATION: N.W.T.
SW 393 SHOT POINTS 101 NE

FIELD RECORDING

DATE: MARCH 1983
RECORDED BY: WESTERN GEOPHYSICAL
ENERGY SOURCE: DYNAMITE 1 HOLE AT 14 M
RECORDER TYPE: DFG-V SAMPLE RATE 2 NS.
GAIN CONTROL: FLOATING POINT
FIELD FILTER: 12 - 120 HZ
GEOPHONES/GROUP: 9 AT 3.75 M TYPE: MARK 14 HZ
COVERAGE 1200% SHOT INT. 134 M GROUP INT. 33.5 M
1600 - 33.5 X 33.5 - 1600

COMPUTATIONS

STRUCTURAL DATUM 500 M
REPLACEMENT VELOCITY 3040 M/SEC

PROCESSING PARAMETERS

DATE: MAY 1983
1. DEMULTIPLEX SAMPLE RATE 4 NS.
2. TRACE GATHER
3. AMPLITUDE RECOVERY TYPE: SPIKING
4. DECONVOLUTION GATE: 000 - 2000 NS.
OPERATOR LENGTH: 72 NS.
PRE-WHITENING: 5 %
5. NMO WELL TOT
6. STATIC CORRECTIONS ELEV/TUR/DRIFT
7. BRUTE STACK
8. COMMON OFFSET STACK
9. SURE
10. AUTOMATIC RESIDUAL STATICS
11. FIRST BREAK NUTE GATE: 500 - 2000 NS.
TIME 0 DIST. 272
TIME 450 DIST. 306
TIME 770 DIST. 544
TIME 1400 DIST. 1632
12. STACK 1200%
13. FILTER 0-1050 NS., 20/25-70/85
1250-3000 NS., 16/23-65/75
14. TRACE EQUALIZATION
15. WAVE EQUATION MIGRATION 90% OF RMS VELOCITIES
16. FILM DISPLAY 24 TR/IN 7.5 IN/SEC

9 2 2 9 - N 9 - 3 E