




PROJ. NO: 9 2 2 9 N 9 3 E LINE NO: 1 1 2 A PART NO: 1 of 3 R.R. 10 x





PETREL CONSULTANTS LTD.

PROCESSED FOR
NSM RESOURCES LTD.
REVERSE POLARITY

AREA: LITTLE BEAR
LINE: 112A
LOCATION: N.W.T.
SW 293 SHOT POINTS 181 NE

FIELD RECORDING

DATE: MARCH 1983
RECORDED BY: WESTERN GEOPHYSICAL
ENERGY SOURCE: DYNAMITE 1 HOLE AT 14 M
RECORDER TYPE: DFS-V SAMPLE RATE 2 NS.
GAIN CONTROL: FLOATING POINT
FIELD FILTER: 12 - 128 HZ
GEOPHONES/GROUP: 9 AT 3.75 M TYPE: MARK 14 HZ
COVERAGE 1200% SHOT INT. 134 M GROUP INT. 33.5 M
1600 - 33.5 X 33.5 - 1600

COMPUTATIONS

STRUCTURAL DATUM 588 M
REPLACEMENT VELOCITY 3848 M/SEC

PROCESSING PARAMETERS

DATE: MAY 1983
1. DEMULTIPLY SAMPLE RATE 4 NS.
2. TRACE GATHER
3. AMPLITUDE RECOVERY
4. DECONVOLUTION TYPE: SPIKING
GATE: 800 - 2200 NS.
OPERATOR LENGTH: 72 NS.
PRE-WHITENING: 5 S
WELL TOT
5. RMS
6. STATIC CORRECTIONS ECG/TUM/DRIFT
7. BRUTE STACK
8. COMMON OFFSET STACK
9. RMS
10. AUTOMATIC RESIDUAL STATICS
11. FIRST BREAK MUTE GATE: 500 - 2000 NS.
TIME 0 DIST. 272
TIME 450 DIST. 386
TIME 770 DIST. 544
TIME 1400 DIST. 1632
12. STACK 1200%
13. FILTER 0-1000 NS., 20/26-70/95
1250-2000 NS., 16/23-65/75
14. TRACE EQUALIZATION
15. WAVE EQUATION MIGRATION
16. FILM DISPLAY 24 TR/IN 7.5 IN/SEC

9 2 2 9 - N 9 - 3 E

