

LINE NIR-13
S.P. 101-521
EAST

MIGRATED STRUCTURAL STACK

NORTHCOR ENERGY LTD
ISLAND RIVER

 SEFEL GEOPHYSICAL SEISMIC DATA PROCESSING CALGARY, CANADA	DATE PROCESSED JAN.-FEB., 1984 O.C. TCS
--	---

FIELD RECORDING	
DATE SHOT	JAN.-FEB., 1984
SHOT BY	SEFEL GEOPHYSICAL LTD.
SOURCE TYPE	DYNAMITE
SOURCE PATTERN	SINGLE HOLE
CHARGE SIZE	2 KG AT 12 M
GEOPHONE TYPE	MARK-10 HZ
GEOPHONE PATTERN	9 AT 3 M INTERVALS
INSTRUMENTS	MDS-10 96 TRACES
FORMAT	SEGB
RECORDING FILTER	12/18 - 125/72 HZ
RECORD LENGTH	3 SEC
SAMPLE INTERVAL	2 MS
GROUP INTERVAL	25 M
SHOT POINT INTERVAL	100 M
SPREAD GEOMETRY	1200-25-X-25-1200

DIGITAL PROCESSING	
1 DEMULTIPLY WITH GAIN REMOVAL	
PROCESSING SAMPLE RATE	2 MS
2 INSTRUMENT PHASE COMPENSATION	
3 GEOPHONE PHASE COMPENSATION	1200 PERCENT
4 CDP TRACE GATHERS	
5 AUTOMATIC GAIN CURVE APPLICATION	
6 SPIKING DECONVOLUTION	
OPERATOR DESIGN WINDOW	
MIN OFFSET	300-1300 MS
MAX OFFSET	800-1800 MS
OPERATOR LENGTH	60 MS
PREWHITENING	1 PERCENT
7 HEATHERING STATICS	
DATUM ELEVATION	700 M ASL
DATUM VELOCITY	2750 M/SEC
HEATHERING VELOCITY	610 M/SEC
8 VELOCITY ANALYSIS	
9 NMO	
10 AUTOMATIC RESIDUAL STATICS	
MAX CORRELATION LAG	1-30 MS
WINDOW	400-1100 MS
11 COMMON OFFSET STACK	
RESIDUAL NMO	
12 MUTE	
13 STACK	1200 PERCENT
14 WAVE EQUATION MIGRATION	
BANDPASS FILTER	8/16 - 100/120 HZ
17 EQUALIZATION	
WINDOW	400-1400 MS
18 FILM DISPLAY	16 TRACES/IN 7.5 INCHES/SEC

NORMAL POLARITY (POSITIVE VALUE PEAK)

PROCESSING PARAMETERS SELECTED BY
EMPRESS EXPLORATION CONSULTANTS