



2050 Valley Rd.
Calgary, Alberta T2C 1G3
Tel: (403) 243-9871
Telex: 053-3502
Cable: TERRA

PROJ. NO. 9229-N10-95

LINE NO. N10-95

LINE NO. N1R-22

PART NO. 1 OF 2

R.R. 8X

LINE NIR-22
S.P. 101-617
S.E.

9229-N10-95

MIGRATED STRUCTURAL STACK

NORTHCOR ENERGY LTD

ISLAND RIVER



SEFEL GEOPHYSICAL
SEISMIC DATA PROCESSING
CALGARY CANADA

DATE PROCESSED
JAN.-FEB., 1984
Q.C. TCS

FIELD RECORDING

DATE SHOT	JAN.-FEB., 1984
SHOT BY	SEFEL GEOPHYSICAL LTD.
SOURCE TYPE	PARTY NO. 501
SOURCE PATTERN	DYNAMITE
CHARGE SIZE	SINGLE HOLE
GEOPHONE TYPE	2 KG AT 12 M
GEOPHONE PATTERN	MARK-10 HZ
INSTRUMENTS	9 AT 3 M INTERVALS
FORMAT	MOS-10 96 TRACES
RECORDING FILTER	12/18 - 125/72 HZ
RECORD LENGTH	3 SEC
SAMPLE INTERVAL	2 MS
GROUP INTERVAL	25 M
SHOT POINT INTERVAL	100 M
SPREAD GEOMETRY	1200-25-X-25-1200

DIGITAL PROCESSING

1 DEMULTIPLEX WITH GAIN REMOVAL	
PROCESSING SAMPLE RATE	2 MS
2 INSTRUMENT PHASE COMPENSATION	
3 GEOPHONE PHASE COMPENSATION	
4 CDP TRACE GATHERS	1200 PERCENT
5 AUTOMATIC GAIN CURVE APPLICATION	
6 SPIKING DECONVOLUTION	
OPERATOR DESIGN WINDOW	
MIN OFFSET	300-1300 MS
MAX OFFSET	800-1800 MS
OPERATOR LENGTH	60 MS
PREWHITENING	1 PERCENT
7 WEATHERING STATICS	
DATUM ELEVATION	700 M ASL
DATUM VELOCITY	2750 M/SEC
WEATHERING VELOCITY	610 M/SEC
8 VELOCITY ANALYSIS	
9 NMO	
10 AUTOMATIC RESIDUAL STATICS	
MAX CORRELATION LAG	+30 MS
WINDOW	400-1100 MS
11 COMMON OFFSET STACK	
12 RESIDUAL NMO	
13 MUTE	
14 STACK	1200 PERCENT
15 HAVE EQUATION MIGRATION	
16 BANDPASS FILTER	8/16 - 100/120 HZ
17 EQUALIZATION	
WINDOW	400-1400 MS
18 FILM DISPLAY	16 TRACES/IN 7.5 INCHES/SEC

NORMAL POLARITY (POSITIVE VALUE PEAK)

PROCESSING PARAMETERS SELECTED BY
EMPRESS EXPLORATION CONSULTANTS



