

9229 P28 2E

Canada Oil and Gas Lands Administration
Administration des sociétés et des gaz des terres du Canada
MAY 1 1985
Geoscience Evaluation Branch
Direction des évaluations des ressources
Program #

PETRO-CANADA

AREA: BLACKWATER LAKE

LINE: 32X NORTHEAST ▶
SP 460 - 341

SECTION TYPE: STRUCTURAL STACK

POLARITY: NORMAL (FIRST BREAKS TURN DOWN)

LOCATION: NTS 96B

RECORDING

RECORDED BY : WESTERN GEOPHYSICAL PARTY : 362
ENERGY SOURCE : DYNAMITE CHARGE SIZE : 2 KG
DATE : APRIL 1984
INSTRUMENTS : DFS V RECORD LENGTH : 6 SEC
FIELD FILTER : 8 - 120 SAMPLE RATE : 2 MS
GAIN : FLOATING POINT TRACES/SHOT : 96
SOURCE ARRAY : SINGLE HOLE PATTERN

SHOT DEPTH : 18M
GEOPHONE ARRAY : 9 AT 7.5 METERS
SPREAD DESCRIPTION :
1961617M - 1481668M - X - 1481668M - 1111617M
GEOPHONE TYPE : LRS 14 HZ
GROUP INTERVAL : 33 M FOLD : 1200 %
SHOT INTERVAL : 132 M VIBROSEIS :
SWEEP LENGTH :
SWEEP :

PROCESSING DESCRIPTION

DATE : JUNE 1984
1 DEMULTIPLEX/DISPLAY: 2 MS SAMPLE RATE
2 EDIT
3 AMPLITUDE RECOVERY
EXP. GAIN

4 DECONVOLUTION - TYPE : SPIKING

OPERATOR LENGTH : 80 MS PREWHITENING 1%
DESIGN WINDOW : 250 TO 2950 AT 33 M OFFSET
900 TO 3600 AT 1617 M OFFSET

5 STRUCTURAL CORRECTIONS - UPHOLE / ELEVATIONS
DATUM : 305 M DATUM VELOCITY : 2450 M/SEC
6 VELOCITY SPECTRA

7 AUTOSTAT/ANSRC - SURFACE CONSISTENT RESIDUAL STATICS
DESIGN WINDOW : 100 - 1000 MS.
8 SHOT GEOPHONE STACK
9 VELOCITY SPECTRA
10 NMO
11 COMMON RANGE STACK
12 AAC - AUTOMATIC AMPLITUDE CONTROL 750 MS. WINDOW

13 TRACE MUTING

DISTANCE (M)	0	395	429	1617
TIME (MS)	0	0	500	1300

14 STACK : 1200%

15 FILTER
14/120 - 80/120

16 BASE LEVEL SCALING

17 DISPLAY TO FILM
SCALE: HORZ 40 TR/IN VERT 3.75 IPS
CDP INTERVAL 16.5 M
JOB NUMBER : 84140B

Petro-Canada
2050 Walkley Rd.
Ottawa, Ont.
Canada K1G 3P5
Tel. (613) 731-9571
Telex: 053-3502 Cable: TERRA

PROJ. NO. 9229-P28-2E

LINE NO. 32X

PART NO. 1 OF 1

R.R. 10X