



26

29.

822

911

1

LINE N

8
9

• P E

8.
.
R


024

PART NO.

1 OF

R.R.

8X



PROCESSED BY GEO-Y DATE: MAR 1986	 GEO-X SYSTEMS LTD.	JTB
DIGITAL CONVERSION	(DATE) (BT)	
AMPLITUDE RECOVERY	TYPE: ZERO-PHASE	
DECONVOLUTION	OPERATOR LENGTH: 60 NS.	
	PREHINTING: 1 S	
	GATE: 200-1000 NS	
	450-1030 NS AT 630 M OFFSET	
STRUCTURAL CORRECTIONS	BATHY ELEVATION: 300 M	
	DATUM VELOCITY: 4500 M/SEC.	
	PROCESSING DATUM: -100 MS.	
	ELEVATION, WEATHERING, AND DRIFT	
	(DYNAMIC REFRACTION SURVEY)	
ANALYSIS	PRELIMINARY VELOCITIES AND STATICS	
STATICS	SURFACE STACK RESIDUAL	
TRACE NELS		
VELOCITY ANALYSIS		
FINAL MOVEOUT		
NEAR SCALING	100-850 NS.	
MUTE	DISTANCE (MI)	
	TIME (MS)	
	400 1260	
	210 1000	
STATICS	SURFACE CONSISTENT RESIDUAL	
	WIND: 100-850 NS.	
TRACE GATHER	FOLD: 12	
STATICS	CDP CROSS CORRELATION	
STACK		
PREDICTIVE	OPERATOR LENGTH: 60 NS.	
DECONVOLUTION	PREDICTION DISTANCE: 30 NS.	
	WIND: 50-850 NS.	
MIGRATION	K-M MIGRATION	
	800 STACKING VELOCITIES	
FILTER	14/18 - 80/90 HZ	
EQUALIZATION	NEAR WIND: 100-850 NS.	
DISPLAY	HORIZONTAL SCALE = 36 TR./IN.	
	VERTICAL SCALE = 2.5 IN./SEC.	