




VERITAS SEISMIC LTD.

FIELD POLARITY
MIGRATED STACK

LINE NO: 85-5 DIRECTION: NE
AREA: TROUT LAKE
DATUM: 610 m A.S.L.

PROCESSED FOR:
SULPETRO LTD.
DATE PROCESSED: APR. 1985 DATE SHOT: MAR. 1985
SHOT BY: NORTHERN GEOPHYSICAL LTD.

FIELD PARAMETERS

SOURCE TYPE	Dynaflo	GEOPHONE TYPE	24 Hz
SOURCE INTERVAL	100 m	GROUP INTERVAL	25 m
SOURCE LAYOUT	single hole	GEOPHONE LAYOUT	5 over 25 m
AVG. CHARGE SIZE	1 kg	AVG. HOLE DEPTH	15 m
INSTRUMENTATION	SFS V	DATA MODE	I.F.P.
FIELD FILTER	120/120 Hz Notch Out	COVERAGE	1200 x
RECORD LENGTH	3 sec	SAMPLE INTERVAL	2 ms
SPREAD TRACE	1 - 40 SP 45 - 96		
DISTANCE	1225 - 50	50 - 1225 m	

DISPLAY PARAMETERS

TRACES/INCH	12	INCHES/SECOND	7.5
-------------	----	---------------	-----

PROCESSING PARAMETERS

1 DEMULTIPLY
Recorded Length 3800 ms Sample Rate 2 ms
Processed Length 2800 ms Sample Rate 2 ms

2 AMPLITUDE RECOVERY - EXPONENTIAL CURVE

3 GEOMETRY - STRAIGHT LINE

4 DEPHASING - INSTRUMENT & GEOPHONE

5 DECONVOLUTION - SPIKING
OPERATOR 08 ms PREWHITENING 5.0 Z
FILTER Distance Design Gate Appl. Gate
1 50 m 300 - 1500 0 - 2000 ms
2 1225 m 000 - 1700 0 - 2000 ms

6 RESIDUAL AMPLITUDE ANALYSIS and APPLICATION

7 STRUCTURE STATICS - 2 LAYER DRIFT COMPUTATION
Drift 610 m A.S.L.
Replacement Velocity 2440 m/s

8 TRACE GATHER

9 NORMAL MOVEOUT

10 STATICS - AUTOMATIC SURFACE CONSISTENT
Window 300 - 1500 ms

11 FIRST BREAK MUTES
Distance 275 1225 2450 m
Rate 320 800 1500 ms

12 STATICS - TRIM
Correlation Window 400 - 1400 ms

13 STACK

14 FILTER - BANDPASS
FILTER 1 Pass Band 15/20 - 70/80 Appl. Gate 0 - 2000 ms

15 AMPLITUDE EQUALIZATION - MEAN SCALE
Window 400 - 1400 ms

16 MIGRATION

