

0-00-05-1E



VERITAS SEISMIC LTD.

FIELD POLARITY
MIGRATED STACK

LINE NO: 85-4 DIRECTION: NE
AREA: TROUT LAKE
DATUM: 610 m A.S.L.

PROCESSED FOR:
SULPETRO LTD.

DATE PROCESSED: APR. 1995 DATE SHOT: MAR. 1995
SHOT BY: NORTHERN GEOPHYSICAL LTD.

FIELD PARAMETERS


SOURCE TYPE	Dynaflo	GEOPHONE TYPE	14 Hz
SOURCE INTERVAL	100 m	GROUP INTERVAL	25 m
SOURCE LAYOUT	single hole	GEOPHONE LAYOUT	8 over 25 m
AVG. CHARGE SIZE	1 kg	AVG. HOLE DEPTH	15 m
INSTRUMENTATION	QFS V	GRIN CODE	I.F.P.
FIELD FILTER	12/120 Hz Notch Out	COVERAGE	1200 Z
RECORD LENGTH	2 sec	SAMPLE INTERVAL	2 ms
SPEED TIME	1 - 40 SP 40 - 50		
DISTANCE	1225 - 50 50 - 1225 m		

DISPLAY PARAMETERS

TRACES/INCH 12 INCHES/SECOND 7.5

PROCESSING PARAMETERS

- DEMULITPLEX
Recorded Length 3000 ms Sample Rate 2 ms
Processed Length 2000 ms Sample Rate 2 ms
- AMPLITUDE RECOVERY - EXPONENTIAL CURVE
- GEOMETRY - STRAIGHT LINE
- DEPHASING - INSTRUMENT & GEOPHONE
- DECONVOLUTION - SPIKING
OPERATOR 88 ms PREWITTEING 5.0 Z
FILTER Distance Design Gate Appl. Gate
1 50 m 800 - 1600 0 - 2000 ms
2 1225 m 800 - 1700 0 - 2000 ms
- RESIDUAL AMPLITUDE ANALYSIS and APPLICATION
- STRUCTURE STATICS - 2 LAYER DRIFT COMPUTATION
Datum 610 m A.S.L.
Replacement Velocity 2400 m/s
- TRACE GATHER
- NORMAL MOVEOUT
- STATICS - AUTOMATIC SURFACE CONSISTENT
Window 300 - 1500 ms
- FIRST BREAK MUTES
Distance 275 1225 2450 m
Gate 320 800 1600 ms
- STATICS - TRIM
Correlation Window 400 - 1400 ms
- STACK
- FILTER - BANDPASS
FILTER 1 Pass Band 15/20 - 70/80 Appl. Gate 0 - 2000 ms
- AMPLITUDE EQUALIZATION - MEAN SCALE
Window 400 - 1400 ms
- MIGRATION



STACKING
FOLD

