

ENCLOSURE IV
SEISMIC LINE A00 66 00025

Shell Canada Limited

A006600025

MIGRATED STACK
NORMAL POLARITY

SP 411 TO 1046
W <----------> E

AREA: THINAHTEA

9229-56-GE

FOLD: 60
DATUM: 550M VCOR: 3050 M/S
SHOT BY: SONIC EXPLORATION
DATE: FEB, 1989

Canada Oil and Gas Lands Administration
Administration du pétrole et du gaz des terres du Canada
MAR 23 1991
Resource Evaluation Branch
Direction de l'évaluation des ressources
Project #

FIELD PARAMETERS:

RECORDING INSTRUMENT:
RECORDER: DFSV-MVR
HIGH CUT FILTER: 180 HZ 72 DB/OCT
RECORD LENGTH: 3.0 SEC
DIGI. INTERVAL: 2 MS
TAPE FORMAT: SEGD

GEOPHONE ARRAY:
1 STRING OF 10 LIN.
6 & 7 EQUIDIST GEOPHONES
5 & 7HZ NATURAL FREQUENCY
0.6 DAMPING FACTOR

SOURCE:
NON-LINEAR VIBROSEIS:
SWEEP FREQUENCIES: 6 - 74 HZ
SWEEP LENGTH: 16 S
SLOT: ABOVE
BOTTOM FREQUENCY: 8 HZ
VP OFFSET: 12.5 M TOWARD ASCENDING STATION

SPREAD GEOMETRY:
DIRECTION SHOT: W ---------- E
STATION SPACING: 25.0M SOURCE SPACING: 25.0M

SPREAD DIAGRAM - VP 731

TRN	1	60	61	120
STN	670	729	734	793
	-1537.5M	-62.5M	62.5M	1537.5M

PROCESSING SEQUENCE:

- DEMULTIPLEX
- GEOMETRY
- DERIVE REFRACTION STATICS
- DESPIKE
- ANTI-ALIAS FILTER
- RESAMPLE TO 4 MS
- EDIT BAD TRACES
- EXPONENTIAL GAIN CORRECTION
- HF FILTER
  VELOCITY LIMITS -1500, 1500 M/S
- DEABSORPTION
- DECONVOLUTION
  WHITE NOISE: 0.0100%
  DERIVE GATE 2: 400 TO 1500 MS
  APPLY GATE 2: 400 TO 5000 MS
  FILTER LENGTH: 120 MS
- SORT TO CMP ADIST
- VELOCITY ANALYSIS WITH RESPECT TO SURFACE
- COMPUTE SURFACE CONSISTENT STATICS
  REFERENCE METHOD
  DERIVE GATE: 500 - 1300 MS
  MAXIMUM SHIFT 28 MS
- MULTIPLES ATTENUATED
- COMPUTE SURFACE CONSISTENT STATICS
  REFERENCE METHOD
  DERIVE GATE: 500 - 1300 MS
  MAXIMUM SHIFT 20 MS
- NMO CORRECT AND APPLY STATICS
- APPLY ELEVATION CORRECTION
- APPLY MUTING
- TRACE BY TRACE RMS NORMALIZATION
  DERIVE WINDOW: 600 TO 1500 MS LEVEL 2000
- CMP STACK
- WAVE EQUATION (KIRCHOFF) MIGRATION
  100% STACKING VELOCITY
- RESAMPLE TO 1 MS
- WHITENING DECONVOLUTION
- FINAL DISPLAY FILTER
  15/3 - 65/10 HZ

DISPLAY PARAMETERS:
HORIZONTAL SCALE 12 TR/IN
VERTICAL SCALE 7.50 IN/SEC

INTERPRETER: LEAVY
PROCESSOR: JONGERIUS
DATE: MAY-1989

QUALITY CONTROL: L. JOHNSON

Terra Resource Services
2060 Walkley Rd. Ottawa, Ont. Canada K1G 3P5
Tel. (613) 731-9571
Telex: 053-3602 Cable: TERRA

PROJ. NO. 0220-S0-0E

LINE NO. A006600025

PART NO. 1 OF 3

R.R. 8X

terra surveys ltd
2060 Walkley Rd. Ottawa, Ont.
Canada K1G 3P5
Tel. (613) 731-9571
Telex: 053-3502 Cable: TERRA

PROJ. NO. 0 2 2 0 - S 6 - 6 E

LINE NO. A 0 0 6 6 0 0 0 2 5

PART NO. 2 OF 3

R.R. 8X



Terra Survey Inc.
2090 Walkley Rd.
Ottawa, Ont.
Canada K1G 3P5
Tel. (613) 731-9571
Telex: 053-3502
Cable: TERRA

PROJ. NO. 9229-S6-6E

LINE NO. A0066000

PART NO. 3 OF 3

R.R. 8X