# 68–94

NW – SE
1km
NETLA




9229-S6-9E

## Shell Canada Limited

NETLA
A006800094

DMO STACK
NORMAL POLARITY
SP: 1180 – 400
NW <——> SE

### ACQUISITION PARAMETERS

SHOT BY : GEO-PRAKLA
DATE : MARCH, 1995
FOLD : 100

### FIELD PARAMETERS:

– RECORDING INSTRUMENT:
RECORDER : I/O II
LOW CUT FILTER : 3 HZ 12 DB/OCT
HIGH CUT FILTER : 189 HZ
RECORD LENGTH : 4.0 SEC
DIGI. INTERVAL : 2 MS
TAPE FORMAT : SEGD
NUMBER OF CHANNELS: 400

– SOURCE:
NON-LINEAR VIBROSEIS:
SWEEP FREQUENCIES : 6 – 84 HZ
SWEEP LENGTH : 24 S
SWEEP DESCRIPTION : LINEAR

– GEOPHONE ARRAY:
M BETWEEN GEOPHONES
14 HZ RESONANT FREQUENCY

– SPREAD GEOMETRY:
STATION SPACING : 15.0 M
SOURCE SPACING : 30.0 M
SOURCE OFFSET 7.5 M TOWARD ASC STATION

TRN 1 200 201 400
STN 601 800 801 1000
X X S X X
SHOT 800
OFFSET -2992.5 -7.5 7.5 2992.5 METERS

### PROCESSING SEQUENCE

IDENTING AND REFRACTION STATICS : C & C
– PROCESSING DATUM : 735 M
– REPLACEMENT VELOCITY : 2700 M/S.

SHELL PROCESSING SEQUENCE
– REFRACTION STATICS
– GAIN RECOVERY
– TRACE EDITS
– SURFACE CONSISTENT RESIDUAL STATICS
– KF FILTER
– DEABSORPTION:
– SURFACE CONSISTENT DECONVOLUTION
– SURFACE CONSISTENT RESIDUAL STATICS
– VELOCITY ANALYSIS
– SURFACE CONSISTENT RESIDUAL STATICS:
– DIP MOVEOUT CORRECTION
– CMP STACK
– POST STACK WHITENING
– DISPLAY FILTER : 11/4 – 65/12 HZ

DISPLAY PARAMETERS:
HORIZONTAL SCALE : 1:20000
VERTICAL SCALE : 7.5 IPS

INTERPRETER : A.ADRIAN
PROCESSOR : TRINH/BEATTIE
DATE : OCTOBER 1995

VERSION: 1


Ottawa, Ont.
2060 Walkley Rd.
Canada K1G 3P5
Tel. (613) 731-9571
Fax: (613) 731-0463


PROJ. NO. 9229-S6-9E
LINE NO. 68-94
PART NO. 1 OF 1