68–96

NW – SE
1km
NETLA



9229-S6-9E

Shell Canada Limited

NETLA
A006800096

DMO STACK
NORMAL POLARITY
SP: 1260 – 362
NW <——————> SE

ACQUISITION PARAMETERS

SHOT BY : GEO-PRAKLA
DATE : MARCH, 1995
FOLD : 100

FIELD PARAMETERS:

– RECORDING INSTRUMENT:
RECORDER : I/O I1
LOW CUT FILTER : 12 HZ 12 DB/OCT
HIGH CUT FILTER : 148 HZ
RECORD LENGTH : 8.0 SEC
DIGI. INTERVAL : 2 MS
TAPE FORMAT : SEGD
NUMBER OF CHANNELS: 400

– SOURCE:
NON-LINEAR VIBROSEIS:
SWEEP FREQUENCIES : 8 – 84 HZ
SWEEP LENGTH : 8 S.
SWEEP DESCRIPTION : LINEAR

– GEOPHONE ARRAY:
M BETWEEN GEOPHONES
14 HZ RESONANT FREQUENCY

– SPREAD GEOMETRY:
STATION SPACING : 15.0 M
SOURCE SPACING : 30.0 M
SOURCE OFFSET 7.5 M TOWARD ASC STATION

TRN	1	200	201	400	
STN	601	800	801	1000	
	X	X S	X	X	
SHOT		600			
OFFSET	-2992.5	-7.5	7.5	2992.5 METERS	

PROCESSING SEQUENCE

IDENTING AND REFRACTION STATICS : C & C
– PROCESSING DATUM : 600 M
– REPLACEMENT VELOCITY : 2700 M/S.

SHELL PROCESSING SEQUENCE
– REFRACTION STATICS
– GAIN RECOVERY
– TRACE EDITS
– SURFACE CONSISTENT RESIDUAL STATICS
– KF FILTER
– DEABSORPTION:
– SURFACE CONSISTENT DECONVOLUTION
– SURFACE CONSISTENT RESIDUAL STATICS
– VELOCITY ANALYSIS
– SURFACE CONSISTENT RESIDUAL STATICS:
– DIP MOVEOUT CORRECTION
– CMP STACK
– POST STACK WHITENING
– DISPLAY FILTER : 11/4 – 65/12 HZ

DISPLAY PARAMETERS:
HORIZONTAL SCALE : 1:20000
VERTICAL SCALE : 7.5 IPS

INTERPRETER : A.ADRIAN
PROCESSOR : TRINH/BEATTIE
DATE : OCTOBER 1995

VERSION: 1

2060 Walkley Rd.
Ottawa, Ont.
Canada K1G 3P5
Tel. (613) 731-9571
Fax: (613) 731-0453

PROJ. NO. 9229-S6-9E

LINE NO. 68-96

PART NO. 1 OF 1