

explor DATA LTD.

630 FIFTH AVE. SW, SUITE 1900
CALGARY, ALBERTA T2P 0M9
TELEPHONE (403)263-5080
FACSIMILE (403)290-0252

MIGRATED SECTION
NORMAL POLARITY

LINE:	DLN-02
PROSPECT NAME:	CENTRAL MCKENZIE SAHTU
STATIONS:	SP 1373 (NW) ... SP 101 (SE)
LOCATION:	N/A
DATUM:	300 M ASL
UTM:	10
R.V.:	3300 M/S

DATE PROCESSED: MARCH 2006 DATE SHOT: FEBRUARY 2006
SHOT BY: VERITAS DGC LAND
SHOT FOR: EXPLORE DATA

FIELD PARAMETERS

SOURCE:
TYPE: VIBROGEIS
LAYOUT: 3 VIBS / TOTAL DRAG = 30 M
SWEEP: 18 SEC
SWEEP FREQUENCY: 6 - 150 HZ (LINEAR)

SPREAD GEOMETRY:
COVERAGE: 3000%
GROUP SPACING: 200 S/P 201 400
DISTANCE: 3960 10 8 10 3900 M
GROUP INTERVAL: 20 M
SOURCE INTERVAL: 20 M
NUMBER OF GROUPS: 400

RECEIVERS:
TYPE: OYO GS30CT / 10HZ
LAYOUT: 8 GEOPHONES OVER 20 M

RECORDING UNIT:
INSTRUMENT: SERCEL 408XL
FIELD FILTER: 3 HZ - 0.6 MINIMUM PHASE / NOTCH N/A
TAPE FORMAT: SEG-D
RECORD LENGTH: 8 SEC
SAMPLE RATE: 2 MS

VERITAS GeoServices Ltd.

PROCESSING PARAMETERS

1. DEMULTIPLEX/REFORMAT
2. GEOMETRY
   TYPE: 4THIGHT LINE
3. MANUAL TRACE EDITS
4. AMPLITUDE RECOVERY
   TYPE: T-SQUARE FUNCTION
   4TH PWR WTD WIN
5. DECON/DOLUTION - SURFACE CONSISTENT
   OPERATOR LENGTH: 160 MS
   DEWHITENING: 81 %
6. TRACE GATHER - FULL FOLD
7. SPECTRAL BALANCING
   FREQUENCY: 5-10 - 100-150 HZ
8. STRUCTURE STATICS - 2 LAYER DRIFT COMPUTATION
   WAVELOSS METHOD: GLS
   REFRACTOR VELOCITY: 5000 M/S
   DATUM ELEVATION: 300 M ASL
   REPLACEMENT VELOCITY: 3300 M/S
   APPLICATION: SURFACE CONSISTENT SHORT WAVELENGTH COMPONENT ONLY
9. PRELIMINARY VELOCITY ANALYSIS
   TYPE: VELOCITY ANALYSIS
   REFERENCE: SURFACE
10. STATICS - AUTOMATIC SURFACE CONSISTENT
    DESIGN WINDOW: 800 - 1500 MS
    DESIGN FILTER: 8/12 - 50 MS HZ
    MAX. STATIC: +/- 25 MS
11. FINAL VELOCITY ANALYSIS
    TYPE: VELOCITY ANALYSIS
    REFERENCE: SURFACE
12. STATICS - AUTOMATIC SURFACE CONSISTENT
    DESIGN WINDOW: 800 - 1500 MS
    DESIGN FILTER: 8/12 - 50 MS HZ
    MAX. STATIC: +/- 24 MS
13. NORMAL MOVEOUT CORRECTION FROM SURFACE
14. FIRST BREAK MUTE
15. STRUCTURE STATICS
    WAVELOSS METHOD: GLS
    APPLICATION: LONG WAVELENGTH COMPONENT
16. STATICS - TRIM
    DESIGN WINDOW: 500 - 1500 MS
    DESIGN FILTER: 8/18 - 50 MS HZ
    MAX. STATIC: +/- 12 MS
17. STACK - FULL FOLD
18. NOISE ATTENUATION
    TYPE: FX DECONVOLUTION
    FREQUENCY RANGE: 5 - 150 HZ
19. FINITE DIFFERENCE MIGRATION
    VELOCITY: MULTIPLIER 0.9
20. NOISE ATTENUATION
    METHOD: SEMBLANCE WEIGHTED SLANT STACK
21. BANDPASS FILTER - TIME VARIANT
    WINDOW 1: 8/12 - 90/110 HZ 0 - 1000 MS
    WINDOW 2: 8/12 - 70/90 HZ 1000 - 2000 MS
    WINDOW 3: 8/12 - 50/70 HZ 2000 - 8000 MS
22. TRACE SCALING - AGC
    TYPE: 0 500 500 3000 3000 8000
    WINDOW: 700 500 1000
    LENGTH:

DISPLAY PARAMETERS

HORIZONTAL SCALE: 24 TRACES PER INCH
VERTICAL SCALE: 3.75 INCHES PER SECOND



14 APR 2006