

SUMMARY OF WELL DATA

Well Name: Decalta Et Al., Rond Lake No. 1

Location: Approximately,
57° 04' 51" N. Latitude
128° 28' 18" W., Longitude

Elevation: Ground 391'
K. B. 399'

Spudded: January 7 1960

Suspended: February 17, 1960

Abandoned: March 19, 1960

Total Depth: 1,497'

Surface Casing: 247' of 6 5/8", J-55, 24 lb. casing,
cemented with 40 sax, set at 255' K. B.

Logs: E-log (point curve)

Classification: Stratigraphic Test

Abandonment: Plug No. 1, 980' to 1200'. 27 sax,
plug did not hold.

Plug No. 2, 990' to 1080', 11 sax,
plug at 1040'.

Plug No. 3, bailed hole to base of
surface casing and dumped in 12
sax cement.

Welded plate with 2" pipe on top of
surface casing, marked R. L. #1.

-2-

<u>Markers</u>	<u>Depth</u>	<u>Subsea</u>	<u>Thickness</u>
Drift			173'
Lower Ramparts	173'	+226'	289'
Bear Rock	462'	- 63'	808'
Silurian	1270'	-871'	

Summary Of Cores


Core #1	959' to 979' Rec. 10 feet limestone, vugs, fractures some permeability, oil stain.
Core #2	995' to 1005' Rec. 10 feet. tight limestone minor shale.
Core #3	1101' to 1109' Rec. 8 feet. limestone, some porosity and fractures no oil stain.
Core #4	1280' to 1290' Rec 10 feet. dolomite.
Core #5	1347' to 1351' Rec. 4 feet. fractured, vuggy dolomite.

Summary Of Formation Tests

DST #1	944' to 969' misrun, disk plugged.
DST #2	900' to 1005' VO 60 min, steady weak blow. Recovered 500' mud. HH 418 lbs., Min. FP 10 lbs., Max. FP 238 lbs. Packer rubber damaged.

-3-

DST #3	935' to 1005' misrun, packer failed to seat.
DST #4	940' to 1005' misrun, packer failed to seat.
DST #5	930' to 1005' misrun, packer failed to seat.
DST #6	1326' to 1351' VO 80 min. flowed fresh water in 1 hr. 15 min. HH 694 lbs. Min. FP 190 lbs. Max. FP 630 lbs.
<u>Bailing</u>	February 18, 1960. Plug top at 1046'. Bailed hole to 600' $\frac{1}{2}$. recovered sulphur water, oil cut. Fluid level rose to 45' K. B. in three days.
	March 7, 1960. Bailed to 600', recovered oil cut sulphur water. Fluid level rose to 60' K. B. in 24 hours.



CROSS SECTION WELLS 1 to 4

Scale Vertical - 1" to 400'
 Horizontal - 1" to Approx 3300'
 (Photo scale)

SAMPLE AND CORE DESCRIPTION

0' - 173' Sand and gravel - grains and fragments of quartz, igneous rock, limestone, dolomite, sandstone, hard green shale, grey shale with spores, rare black chert. Rock appears to be mainly medium to coarse grained sand of quartz with some igneous grains which are very well rounded, layers of gravel and boulders occur throughout the section. Cuttings of sandstone are usually porous and oil stained.

173' Lower Ramparts.

173' - 190' Limestone - brownish grey, argillaceous, very fine crystalline, rich in fossils - ostracodes, brachiopods and gastropods.

190' - 195' Limestone - as above 90%.

Shale - brownish grey, calcareous, rounded fragments of limestone, probably fossils, 10%

195' - 205' Limestone - as above 90%.

Limestone - brown, vitreous, clean, probably coral material 10%.

205' - 220' Limestone - brownish grey, argillaceous, ostracodes and brachiopod fragments, brown shaly partings, some with crinoids, traces of clean, fine crystalline limestone (corals?).

220' - 255' (Cavings fairly bad)

Limestone - light brownish grey, very fine, nearly dense, tiny broken fossil debris scattered throughout. Trace of green calcareous shale and greenish grey argillaceous limestone (some of the argillaceous material is up to fine silt size). Pyrite common at top, minor amounts throughout.

(End of bad cavings)

255' - 300' Limestone - as above but fewer fragments 50%. Shaly limestone and limy shale - gradational from shale to limestone - greenish, calcareous, soft and flaky to hard, 50%.

300' - 462' Limestone - greenish to brownish grey, the brown limestone is fragmental and fossiliferous, fragments of crinoids, brachiopods and ostracodes. greenish limestone is argillaceous, 80%.

300' - 462' (cont'd.)

In places fossils make up to 20% of the limestone.

Shale - green, calcareous, 20%

462'

Bear Rock.

462' - 505'

Limestone - brown, very fine crystalline to dense, texture often shows pellet like structure, very fine to medium, round, forms in a clear matrix, may be bahamite or algal texture, this texture varies from very faint to pronounced.

505' - 525'

Limestone - tan, brown to grey, sub-lithographic, some brown limestone as above, thin partings of hard, dark grey argillaceous material.

525' - 590'

Limestone - tan, some grey, sub-lithographic, 50%.

Limestone - brown, very fine crystalline, clear calcite network or inclusions, traces of bahamite or algal texture, 50% ⁺. Dark argillaceous partings and stylolites, these may be bituminous but have negative CC/4 reaction.

590' - 712' **Gradational with above.**

Limestone - grey to brown, very fine crystalline to nearly dense, traces of sub-lithographic limestone, algal (?) texture common in upper part, outlined by clear calcite, becomes rare downward; argillaceous partings or stylolites abundant.

630' Trace of clear calcite crystals.

650' Trace of clear calcite crystals.

695' Traces of green shale.

712' - 722' Drilling break, possibly caused by presence of shale. Trace of shale-green, calcareous, disintegrates quickly in water.

Limestone - brown and grey, mostly micro-crystalline to sub-lithographic, practically no change from above. Algal texture very rare.

722' - 900' Limestone - as above.

Traces of shale - dark and bright green, slightly to non-calcareous, hard(disintegrates quickly in water).

722' - 900' (cont'd.)

Some of the shale contains what appears to be rounded limestone grains, also pyrite.

840' Trace of pin point porosity.

Some of the limestone has a slight greenish cast and contains a small amount of very fine silt and argillaceous material.

900' - 937' Limestone - as above, some waxy green shale with rounded limestone grains, algal texture more common.

910' Trace of pin point porosity with oil stain.

937' - 965' Limestone - as above 50%
Dolomite - light brownish grey, very fine crystalline, granular, 50%.

Trace of pin point porosity with oil stain occurs at 940' and below.

965' - 969' Limestone - as below - slight granular texture, brown to grey, micro-crystalline, partings and stylolites of grey and green shale.

CORE #1 969' - 979'

969' - 979' Limestone - light brownish grey, micro-crystalline, very homogeneous, tight. Many tiny stylolites, a few partings up to 1/4" thick of green and grey, laminated, slightly calcareous shale. A few fractures, lined by coarse crystalline calcite - some porosity and oil stain associated with the fractures.

979' - 995' Limestone - as above, no oil stain.

CORE #2 995' - 1005'

995' - 1005' Limestone - light brownish grey, micro-crystalline, some nearly sub-lithographic(lime mud) many dark, thin argillaceous partings. One fracture tightly sealed with calcite. One tiny oil stained vug.

1005' - 1070' Limestone - light grey to brown, micro-crystalline, traces of calcite and green shale.

1070' - 1075' Limestone - brown, micro-crystalline, dark to black shale partings (brown streak).

1075'-1085' Limestone - as above 1070', traces of the dark partings.

1085'-1101' Limestone - as above, some limestone - light grey, very fine crystalline, some pin point and inter-crystalline porosity. Porosity only a trace except below 1095'.

CORE #3 1101' - 1109'

1101'-1109' Limestone - light grey, micro-crystalline, very fine stylolites. Rare fractures lined with medium sized cal.ite crystals, some very fine limestone associated with the fractures - probably permeable.

1109'-1118' Limestone - light grey, micro-crystalline. (As in core above)

1118'-1125' Limestone - brownish grey, fine crystalline, some porosity. Some limestone as above.

1125'-1150' Limestone - light grey and brownish grey, micro-crystalline, some light and some brownish grey, fine crystalline porous limestone.

1150'-1180' Limestone - light grey and brownish grey, micro-crystalline, mere traces of pin point porosity. Traces of dark green shale, a few very thin stylolites, a few calcite crystals.

1180'-1215' Limestone - as above but no trace of porosity. Trace of darker limestone with pyrite at the base.

1215'-1225' Limestone - brown, fine granular, trace of calcite.

1225'-1235' Limestone - brown, micro-crystalline.

1235'-1270' Limestone - light grey to brown, micro-crystalline, in part has a chalky appearance, a few dark shale partings.

1270' Silurian

1270'-1280' Dolomite - brown, very fine to fine crystalline very slightly silty, tight, pyrite, trace of green waxy shale, some white vein dolomite.

CORE #4 1280' - 1290'

1280'-1290' Rec. 10'

Dolomite - brown, slightly mottled, very fine crystalline, very slightly silty, many fine fractures tightly sealed with clear dolomite, larger fracture shows minor brecciation.

1290'-1337' Dolomite - brown to light brownish grey, traces of small drusy vugs, traces of porosity with oil stain at 1330'.

1337' - 1347' Dolomite - as above, traces of porosity to 1342', below 1342' considerable fine crystalline dolomite with good inter-crystalline porosity.

CORE #5 1347' - 1351'

1347'-1351' Rec. 4'

Dolomite - brown, very fine crystalline, very hard, many small vugs up to 3/8" and irregular fractures. Lining vugs is fine to medium crystalline dolomite with good porosity - excellent permeability. Some mottling and texture which probably represents organisms, possibly a reef or reef breccia.

1351'-1365' Dolomite - as above, considerable amount of good porosity, some limy dolomite.

1365'-1420' Dolomite - brown and light brown, very fine crystalline, some with a lighter and softer appearance, generally tight, trace of porosity as seen above. Small amount of very fine silt.

1420'-1440' Dolomite - as above 70%.
Dolomite - fine crystalline, excellent inter-
crystalline porosity, 30%.

1440'-1455' Dolomite - brown, fine to very fine crystalline, very slightly silty, traces of intercrystalline porosity, white, coarse crystalline dolomite, probably from vug or fracture filling.

1455'-1485' Dolomite - brown to light brownish grey, very fine crystalline, very slightly silty, trace of porosity, signs of drusy vugs, some white dolomite crystals.

1485'-1497' Dolomite - brown, very fine crystalline, rare trace of porosity.

STRATIGRAPHY

GENERAL

In the Rond Lake area, the upper part of the Stratigraphic Section is as follows.

Glacial Deposits

Till and lake sands, up to 200', nearly everywhere present.

Cretaceous

Poorly consolidated quartz sand, thin, random, patchy distribution.

Middle Devonian - Ramparts Formation

Upper Ramparts Limestone - 200' ⁺ not present in any of the wells drilled, forms the scarp west of Rond Lake.

Middle Ramparts Shale; also called Hare Indian River Shale - 600' to 700' of green shale, 30' at base contains interbedded dark brown shale.

Lower Ramparts Limestone - 300 feet minus, fossiliferous limestone.

Bear Rock Formation

800'⁺, very fine algal rich limestone, equivalent to the dolomite breccia of the Norman Wells area.

Silurian

Thickness unknown, dolomite with reefs.

PLEISTOCENE AND RECENT

Rond Lake No. 1 encountered 173 feet of glacial deposits - sand and pebbles in a clay matrix. The deposits are chiefly medium to coarse grained quartz sand, with layers of gravel composed of a variety of sedimentary rocks of local derivation as well as a few grains of igneous rock.

LOWER RAMPARTS LIMESTONE

The Lower Ramparts limestone consists of argillaceous, fossiliferous limestone with interbedded green, calcareous shale. Brachiopods, ostracods and cup-corals are common throughout. The upper 82 feet are predominantly limestone, much of which is formed from layers of colonial corals. The lower 207 feet contain more interbedded shale.

In Rond Lake No. 1, the Lower Ramparts is 289 feet thick, this is 17 feet thicker than in Rond Lake No. 2, the only other well to penetrate the full section. Two hundred eighty nine feet is probably not the full thickness of the Lower Ramparts, as glacial deposits directly overlie the limestone. From a comparison of E-logs in wells No. 1 and No. 2, it can be seen that in well No. 1 the lower part of the section, between 312 feet and 462 feet, thins gradually from 150 feet in No. 1 to 138 feet in No. 2, accounting for 12 of the 17 foot difference.

BEAR ROCK

Rond Lake No. 1 penetrated the full Bear Rock section between 462 and 1270 feet. The formation is 808 feet thick and is composed predominantly of clean, very fine, nearly dense limestone. There are many stylolites and thin partings of brown shale. The texture of the rock indicates that it probably originated as a lime mud bound together by algal material. Ostracods are common throughout the section aside from ostracods and algae, there is no trace of organic material. A characteristic of the Bear Rock formation is the presence, throughout the section of quartz in the form of tiny euhedral crystals.

Traces of pin point porosity occur throughout the lower 430 feet of the formation. Some poor porosity occurs in the layers from 937 to 965 feet and from 1150 to 1180 feet; the layer from 937 to 965 is in part granular dolomite. Better porosity, associated with fractures, occurs from 1095 to 1109 feet and from 1118 to 1125 feet. Good intercrystalline porosity is present between 1125 to 1150 feet.

The oil stained porous layer from 940 to 965 feet was tested by Drill Stem Test No. 2 and by later bailing operations, oil cut sulphur water was obtained. Lower porous layers were not oil stained and were not tested.

SILURIAN

The Silurian was encountered at a depth of 1270 feet and 227 feet were drilled; the total thickness of the Silurian is unknown. The drilled section consists of brown, fine crystalline dolomite, very fine detrital silt is present throughout. Core No. 4, taken near the top of the Silurian shows that the dolomite has a mottled appearance, it is cut by several fractures tightly sealed by crystalline dolomite, minor brecciation is associated with the larger fractures.

Porous layers occur between 1342 and 1365 feet and between 1420 and 1440 feet. In addition traces of porosity are present throughout the section below 1337 feet. Core No. 5 was cut in the upper porous section; good inter-

crystalline porosity is associated with many small vugs and fractures, these vugs and porous patches occur within a body of tight hard, fine dolomite, however the permeability is excellent. The lower porous layer has excellent inter-crystalline porosity.

No recognizable fossils were seen in the cores or samples, however the arrangement and shape of the vugs gives an impression of organic material.

The upper porous zone was tested and contained sulphur water.

WELL NAME	OWNER	YR	CORE	TOP	BOTTOM	LOCATION	TYPE
ROND LAKE NO.1	DECALTA	60	2 5	997 1350		C-13733 C-13734	PALYN

WELL NAME	OWNER	YR	CORE	TOP	BOTTOM	LOCATION	TYPE
RUND LAKE NO.6	DECALTA&A	60	1	997			PYROL
				5	1350		

WELL NAME	OWNER	YR CORE	TOP	BOTTOM	LOCATION	TYPE
ROND LAKE NO.5	DECALTA	60	552		C-24415	PALYN

FORM "B"

DEPARTMENT OF NORTHERN AFFAIRS AND NATIONAL RESOURCES
NORTHERN ADMINISTRATION BRANCH
RESOURCES DIVISION

For the period from

to

COMPLETION
REWORK
REPORT of RECOMPLETION of a Well
SUSPENSION
ABANDONMENT

Permit No. 1424.

Name of well Desalta Et. Al., Road. Lake No. 1 Lease No.

Registered owner Western Decalta Petroleum Drilling Company Big Indian . . .

Location $67^{\circ} 04' 51''$ N. Lat. $128^{\circ} 28' 18''$ W. Long.

Survey description, if available

Kelly bushing . . . 399 . . . Present depth . . . 1497

Spudded January 7, 1960 Finished drilling Feb. 17 Rig Released

Deviations from vertical . ~~969°~~^{79°} - 3 1/4°, 1100° - 3 1/4°, 1240° + 3 1/4°, 1370° - 5 1/4°,
. 1496° - 5°, . . . 526° - 1/2°, ~~etc~~

CASING RECORD

<u>Date</u>	<u>Size O.D.</u>	<u>Weight lbs/ft</u>	<u>Grade</u>	<u>Set at feet</u>	<u>Sacks Cement</u>	<u>Top of Cement</u>
1 Jan. 15	6 5/8	24	J-55	255	46	Surface
2						
3						
4						

TUBING RECORD

Size	Wt. Lbs/foot	Grade	Amount	Landed Depth	Remarks
------	--------------	-------	--------	--------------	---------

Wellhead (Manufacturer) (Size) (Series)

.....

Velocity log 9-1497

The above logs (will be) submitted in accordance with Section 65 of the Regulations.

DRILL STEM TESTS

(If space insufficient, attach further sheet)

(Strike out the non-applicable) (Complainant) (Respondent) (Nonappellant)

Shootings

Hydraulic fracturing

Chemical treatment

Date initial production tests

Pumping or flowing
Plug back
Other
.
.
.
.
.

CEMENT PLUGS SET

<u>Date</u>	<u>Plug set at</u>	<u>Sacks cement</u>	<u>Method</u>	<u>Top found at</u>
Feb. 13	980-1200	.27	Mud. Pump . .	Did Not Hold.
Feb. 15.	990-1080	.11	Mud. Pump . .	1046.
March 19	Bailed to base of surface casing & dumped.	12 sack	
March 19	5. sack on top
...

Washed well samples have been sent to Geological Survey of Canada, Calgary
~~xxxxxxxxxx~~

Cores will be stored at . **Western Decalts, Calgary**

Core analysis (was made) of the Intervals
(to be made)

Oil analysis (was made) of the Intervals.
(to be made)

Gas analysis (was made) of the Intervals.
(to be made)

Water analysis (was made) of the Intervals. **above 1046, 1326-1351** . . .
~~(xxxxxxxxxx)~~

The above analyses (will be) submitted in accordance with Section 70(2) of
the Regulations.

ADDITIONAL DETAILS AND COMMENTS

Well suspended after running plug 990-1080 awaiting bailing equipment . . .

Feb. 18, bailed to 600', oil cut sulphur water.


March 7, bailed to 600', oil cut sulphur water.

Natural fluid level 45' KB.

Signed. *J. J. Williams* Address **627 - 8th Ave. S.W., CALGARY.**

Date **May 1, 1966**

(To be submitted in triplicate in accordance with Sections
68, 69, 70 and 71, of the Territorial Oil and Gas Regulations
to the Oil Conservation Engineer at Calgary, Alberta.)





DRILLING REPORT

DEC ALTA ET AL., ROND LAKE NO. 1

N.W.T.

D. BRUCE BULLOCK & ASSOCIATES LTD.

CONSULTING GEOLOGISTS

MARCH, 1960

TABLE OF CONTENTS

Summary of Well Data	1
Markers	2
Cores	2
Formation Tests	2
Daily Progress Reports	4
Time Drilling Record	20
Mud Record	25
Bit Record	27
Drill Stem Tests	29
Breakdown of Time Spent on The Hole	35
Sample and Core Description	36
Stratigraphy	46
General	46
Pleistocene and Recent	47
Lower Ramparts	48
Bear Rock	49
Silurian	50
Discussion	52

Appendix - Water analyses

SUMMARY OF WELL DATA

Well Name: Decalta Et Al., Rond Lake No. 1

Location: Approximately,
57° 04' 51" N. Latitude
128° 28' 18" W., Longitude

Elevation: Ground 391'
K. B. 399'

Spudded: January 7 1960

Suspended: February 17, 1960

Abandoned: March 19, 1960

Total Depth: 1,497'

Surface Casing: 247' of 6 5/8", J-55, 24 lb. casing,
cemented with 46 sax, set at 255' K. B.

Logs: F-log (point curve)

Classification: Stratigraphic Test

Abandonment: Plug No. 1, 980' to 1200', 27 sax,
plug did not hold.

Plug No. 2, 990' to 1080', 11 sax,
plug at 1046'.

Plug No. 3, bailed hole to base of
surface casing and dumped in 12
sax cement.

Welded plate with 2" pipe on top of
surface casing, marked R L #1.

ILLUSTRATIONS

Map Showing Location of Wells
Relative to Rond Lake

Next Page

Cross Section, Wells 1 to 4

After Page 45


E-log

In Pocket

Strip Log

In Pocket






MAP SHOWING LOCATION OF WELLS
RELATIVE TO ROND LAKE

SCALE 1" to Approx. 3300'
(Photo Scale)

— ROAD
- - - CUT LINE



CROSS SECTION WELLS 1 to 4

Scale - Vertical - 1" to 400'
Horizontal - 1" to Approx. 3300'
(Photo scale)

<u>Markers</u>	<u>Depth</u>	<u>Subsea</u>	<u>Thickness</u>
Drift			173'
Lower Ramparts	173'	+225'	289'
Bear Rock	462'	- 63'	808'
Silurian	1270'	- 871'	

Summary Of Cores

Core #1	959' to 979' Rec. 10 feet limestone, vugs, fractures some permeability, oil stain.
Core #2	995' to 1005' Rec. 10 feet. tight limestone minor shale.
Core #3	1101' to 1109' Rec. 8 feet. limestone, some porosity and fractures no oil stain.
Core #4	1280' to 1290' Rec 10 feet. dolomite.
Core #5	1347' to 1351' Rec. 4 feet. fractured, vuggy dolomite.

Summary Of Formation Tests

DS I #1	944' to 969' misrun, disk plugged.
DS I #2	900' to 1005' VO 60 min, steady weak blow. Recovered 500' mud. HH 418 lbs., Min. FP 10 lbs., Max. FP 238 lbs. Packer rubber damaged.

- 3 -

DS1 #3 935' to 1005' misrun, packer failed to seat.

DS F #4 940' to 1005' misrun, packer failed to seat.

DS F #5 930' to 1005' misrun, packer failed to seat.

DS F #6 1326' to 1351' VO 80 min. flowed
fresh water in 1 hr. 15 min.
HH 694 lbs.
Min. FP 190 lbs.
Max. FP 630 lbs.

Bailing February 18, 1950. Plug top at 1046'. Bailed hole to 600' $\frac{1}{2}$, recovered sulphur water, oil cut. Fluid level rose to 45' K. B. in three days.

March 7, 1960. Bailed to 300', recovered oil cut sulphur water. Fluid level rose to 50' K. B. in 24 hours.



DAILY PROGRESS REPORTS

January 7, 1960

Mud: Wt. 8.6, Vis. 43, add. 700 lbs. gel.
Current Operation: Drilling 4 3/4". (Spud 6:00 P. M.)
Depth: 95' 6 hrs. drilling.
Operations: Drill; from 0' to 95'
Rock Types Penetrated: From 0' to 95', drift (permafrost)

January 8.

Mud: Wt. 9.6, Vis. 47.
Current Operation: Drilling 4 3/4"
Depth: 207' 18 3/4 hrs. drilling
2 1/4 hrs. repairs
1 hr. trip
1 hr. service
1 hr. ream tight hole
Operations: Drill 4 3/4" from 95' to 207'
Rock Types Penetrated: From 95' to 173' drift (permafrost)
From 173' - 207' dense limestone.

January 9:

Mud: Wt. 10.3, Vis. 55.
Current Operation: Stuck pipe.
Depth: 222' 4 1/4 hrs. drilling
11 3/4 hrs. cleaning pump and mud lines
8 hrs. working pipe
Operations: Drill from 207' to 222'
Rock Types Penetrated: From 207' to 222' - dense limestone.

January 10.

Mud: Wt. 8.7, Vis. 32, WL 60+add.
100 lbs. Calcium Chloride.
Current Operation: Circulating.
Depth: 222' 22 hrs. working pipe
2 hrs. circulating

January 11.

Mud: Wt. 9.9, Vis. 76, add 750 lbs. gel.,
20 lbs. spersene, 8 lbs. caustic.
Current Operation: Conditioning mud.
Depth: 253'
Operations: 2 hrs. ream 4 3/4"
8 1/4 hrs. drill 4 3/4"
4 hrs. repairs
1/4 hrs. service
3 1/2 hrs. circulate
4 hrs. trips
2 hrs. ream to 8 5/8"
Drill 4 3/4" 222' to 253'
Ream 8 5/8" 0' to 10'
Rock Types Penetrated: From 222' to 253' - limestone and
minor shale.

January 12.

Mud: Wt. 9.7, Vis. 45, add 1100 lbs. gel.
Current Operations: Reaming to 8 5/8"
Depth: 253'
Operations: 15 hrs. ream
7 hrs. work on mud system
1 hr. service
1 hr. trip
Ream 8 5/8" 10' to 180'

January 13.

Mud: Wt. 10.5, Vis. 48.
Current Operation: Pit heater constructed and working.
Depth: 253'
Operations: Reaming to 8 5/8"
20 1/4 hrs. reaming
1/2 hr. service
2 1/4 hrs. trip
1/2 hr. repairs
1/2 hr. move pump
Ream from 180' to 211'

-6-

January 14.

Mud: Wt. 10.6, Vis. 48.
Current Operation: Preparing to run surface casing.
Depth: 255' 16 1/2 hrs. ream
Operations: 1/2 hr. service
1 hr. circulate
3 hr. work on light plant.
3 hrs. trip and lay down pipe.
Ream from 211' to 253'
Drill from 253' to 255'

January 15.

Current Operation: Waiting on cement.
Depth: 255' 5 1/2 hrs. run casing
Operations: 1 3/4 hrs. cement casing
16 3/4 hrs. waiting on cement
Set 247', 6 5/8", 24 lb., J-55 with
46 sax set at 255 K. B.

January 16.

Mud: Wt. 9.3, Vis. 34, W. L. 33, pH 9.2,
Current Operations: add 100 lbs. Bicarbonate of soda.
Depth: 255' Thawing mud lines.
6 hrs. W. O. C. and nippling up.
1/2 hr. service
2 1/2 hrs. trip
10 1/2 hrs. thawing mud lines
1 3/4" circulate and pressure up
2 3/4" drill out plug

January 17.

Mud: Wt. 9.8, Vis. 40, W. L. 16, pH 10.5,
Current Operation: add 10 lbs. Quebracho, 5 lbs. caustic.
Depth: 387' Drilling.
Operations: 19 3/4 hrs. drilling
1/2 hr. service
1 3/4 hrs. trip
2 hrs. pressure up
Drill from 255' to 387'
Rock types Penetrated: From 255' to 387' - limestone and shale.

January 18.

Mud: Wt. 10, Vis. 42, W. L. 11.8, pH 10,
add 200 lbs. gel, 15 lbs. Quebracho,
5 lbs. caustic, 25 gals. water.

Current Operation: Drilling

Depth: 474' 22 hrs. drilling
1/4 hr. service
1 3/4 hrs. trip

Operations: Drill from 387' to 474'

Rock Types Penetrated: From 387' - 462' - limestone and shale.
From 462' to 474' - fine to dense lime-
stone.

January 19.

Mud: Wt. 9.8, Vis. 37, W. L. 7.6, pH 10,
add 50 lbs. bicarbonate, 10 lbs.
Quebracho, 5 lbs. caustic.

Current Operation: Drilling

Depth: 526" 22 1/2 hrs. drilling
1/2 hr. service
1 hr. trip

Operations: Drill, from 474' to 526'

Rock Type Penetrated: From 474' to 526' - dense limestone.

January 20.

Mud: Wt. 9.7, Vis. 36, W. L. 10, pH 10,
add 50 lbs. bicarbonate, 50 lbs.
Anti - Gyp.

Current Operation: Drilling

Depth: 578' 22 1/4 hrs. drilling
1 1/4 hrs. trip
1/2 hr. service

Operations: Drill from 526' to 578'

Rock Types Penetrated: From 526' to 578' - dense limestone

January 21.

Mud: Wt. 9.7, Vis. 37, W.L. 9.8, pH 10,
Current Operation: Drilling
Depth: 614' 19 1/2 hrs. drilling
Operations: 3 hrs. trips
Rock types penetrated: Drill from 578' to 614'
Rock types penetrated: From 578' to 614' - dense limestone.

January 22.

Mud: Wt. 9.5, Vis. 38, W.L. 9.2, pH 9.4,
add 450 lbs. gel.
Current Operation: Drilling
Depth: 654' 21 1/2 hrs. drilling
Operations: 1/2 hr. service
Rock Types Penetrated: Drill from 614' to 654'
Rock Types Penetrated: From 614 to 654' - dense limestone.

January 23.

Mud: Wt. 9.4, Vis. 40, WH 9.3, pH 9.5,
Current Operation: Drilling.
Depth: 696' 22 1/4 hrs. drilling
Rock Types Penetrated: 1/2 hr. service
From 654' to 694' - dense limestone.
1 1/4 hrs. trip

January 24.

Mud: Wt. 9.4, Vis. 43, WL 9.4, pH 9.2,
add 250 lbs. gel.
Current Operation: Drilling

January 24. (cont'd.)

Depth: 757' 23 1/2 hrs. drilling
1/2 hr. service
Rock Type Penetrated: From 696' to 757' - dense limestone.

January 25.


Mud: Wt. 9.4, Vis. 42, WL 9.3, pH 9.5,
add 5 lbs Quebracho, 2 lbs. caustic.
Current Operation: Drilling.
Depth: 816' 20 1/4 hrs. drilling
1 1/2 hrs. trip
1 hr. service
1 1/4 hrs. repairs
Operations: Drill from 757' to 816'
Rock Types Penetrated: From 757' to 816' - dense limestone.

January 26.

Mud: Wt. 9.5, Vis. 42, WL 8.4, pH 9.5,
Current Operation: Drilling
Depth: 881' 22 1/4 hrs. drilling
1 1/2 hrs. trip
1/4 hr. service
Operations: Drill from 816' to 881'.
Rock Types Penetrated: From 816' to 881' - dense limestone.

January 27.

Mud: Wt. 9.5, Vis. 45, WL 7.2, pH 9.5,
add 600 lbs. gel., 10 lbs. Quebracho,
5 lbs caustic.
Current Operation: Drilling.
Depth: 941' 19 1/4 hrs. Drilling
1 3/4 hrs. trip
1/2 hr. service
2 1/2 hrs. repairs
Operations: Drill from 881' to 941'
Rock Types Penetrated: From 881' to 937' - dense limestone,
minor shale.
From 937' to 941' - tight dolomite.



-10-

January 28.

Mud:

Current Operation:

Depth: 969'

Wt. 9.5, Vis. 64, WL 7.0, pH 9.5,
add 2 1/2 lbs. high viscosity driscose.

Coring and testing.

11 1/4 hrs. drilling

1 3/4 hrs. circulate

7 hrs. trip and test

3 3/4 hrs. trip and rig to core

1/4 hr. core

Drillstem test No. 1, 944' to 969',
misrun, disk pierced but not shattered.
plugged.

January 29.

Mud:

Current Operation:

Depth: 1005'

Wt. 9.5, Vis. 52, WL 7.4, pH 9.5.

Coring

3 1/2 hrs. coring

1 hr. preparing to core

7 1/2 hrs. trips

3 1/2 hrs. log and survey

1 1/4 hrs. circulate

1 1/4 hrs. ream

5 hrs. drilling

1/2 hr. repairs

1/2 hr. service

Core; from 969' to 979'

Drill; from 979' to 995'

Core; from 995' to 1005'

From 969' to 1005', tight limestone.

Operations:

Rock types Penetrated:

Core #1

From 969' to 979'

Recovered 10' tight limestone, few
vugs and fractures.

Core #2

From 995' to 1005'

Recovered 10' tight limestone,
minor shale.

Survey at 969' - 3/4°

January 30.

Mud:

Wt. 9.4, Vis. 42, WL 7.8, pH 9,
(after test)

Current Operation:

Testing.

Depth: 1005'

9 1/4 hrs. trips

1/2 hr. handling core

2 1/4 hrs. ream

1 1/2 hrs. rig to test

1 hr. test

1 1/2 hrs. wait on orders

7 1/2 hrs. circulate

1/2 hr. repairs

900' to 1005'

VO one hour, Initial puff, steady weak blow, recovered 500' mud, Hydrostatic pressure 418 lbs.

Min. flow pressure 10 lbs.

Max. flow pressure 238 lbs.

Packer rubber damaged.

Test #2

January 31.

Mud:

Wt. 9.3, Vis. 54, WL 6.8, pH 8.5,
add 200 lbs gel., 5 lbs. High Viscosity Driscose.

Current Operation:

Testing

Depth: 1005'

12 hrs. circulating

12 hrs. trips for DST 3 and 4

Test #3

935' to 1005' misrun, packer seat failure (Tool run without dart)

Test #4

940' to 1005' misrun, packer failed to seat (tool run without dart)

February 1, 1960.

Mud: Wt. 9.5, Vis. 48, WL 6.1, pH 9.0,
add 20 lbs. spersene, 10 lbs.caustic.

Current Operation: Test and drilling.

Depth: 1035' 4 1/2 hrs. circulate

7 hrs. trips and attempt to test

1/2 hr. service

1 1/2 hrs. ream bottom 40'

3/4 hr. repairs

9 3/4 hrs. drill

Operations: Drill from 1005' to 1035'

Rock Type Penetrated: From 1005' to 1035' - tight limestone.

Test #5 930' to 1005' misrun, packer failed to seat.

February 2.

Mud: Wt. 9.6, Vis. 48, WL 6.5, pH 10.

Current Operation: Drilling

Depth: 1088' 18 3/4 hrs. drill

1/2 hr. service

2 3/4 hrs. trip

2 hrs. repair

Operations: Drill from 1035' to 1088'

Rock Types Penetrated: From 1035' to 1088' - tight limestone.

February 3.

Mud: Wt. 9.8, Vis. 46, WL 6.3, pH 10.

Current Operation: Drilling, coring.

Depth: 1133' 12 hrs. drill

5 1/2 hrs. trips

2 1/4 hrs. core

1 hr. handle core

1/2 hr. service

1 3/4 hrs. ream

Operations: Drill from 1088' to 1101'

Drill from 1109' to 1133'

Core from 1101' to 1109'

February 3 (cont'd.)

Rock Types Penetrated: From 1088' to 1133' - tight limestone with thin layers of porosity, few fractures.

Core #3 From 1101' to 1109'. Recovered 8' limestone, a few fractures, some crystal lined - no oil stain.

February 4.

Mud: Wt. 9.8, Vis. 43, WL 6.6, pH 9.5, add 100 lbs. gel.

Current Operation: Drilling

Depth: 1197' 21 1/2 hrs. drilling
1/2 hr. service
2 hrs. trip

Operations: Drill from 1133' to 1197'.

Rock Types Penetrated: From 1133' to 1197' - tight limestone.

February 5.

Mud: Wt. 9.9, Vis. 45, WL 6.8, pH 8.5, add 300 lbs. gel.

Current Operation: Drilling

Depth: 1255' 19 hrs. drilling
2 hrs. trip
1/2 hr. service
2 1/2 hrs. repair

Operations: Drill from 1197' to 1255'

Rock Types Penetrated: Tight limestone.

February 6.

Mud: Wt. 9.9, Vis. 55, WL 7.1, pH 9.3, add 5 lbs. caustic, 20 lbs. spersene, 2 1/2 lbs. High Viscosity Driscose.

Current Operation: Drilling, coring.

February 6 (cont'd.)

Depth: 1290' 12 1/4 hrs. drill
 1 1/2 hrs. repair
 1/2 hr. service
 1 1/2 hrs. circulate and condition mud
 5 hrs. trips
 2 1/4 hrs. core
 1 hr. ream

Operations: Drill from 1255' to 1280'
 Core from 1280' to 1290'

Rock Types Penetrated: From 1255' to 1270' - tight limestone.
 1270' to 1290' - tight fine dolomite.
 Silurian at 1270'

Core #4 From 1280' to 1290'. Rec. 10',
 brown, very fine crystalline mottled
 dolomite, several small fractures
 sealed by coarse crystalline dolomite.

February 7.

Mud: Wt. 10.1, Vis. 54, WL 6.6, pH 9.3,
 add 500 lbs. Antigyp.

Current Operation: Drilling

Depth: 1320' 17 1/2 hrs. drill
 1/2 hr. service
 3 hrs. trip
 3 hrs. repair

Operations: Drill from 1284' to 1320'.

Rock Types Penetrated: Tight dolomite.

February 8.

Mud: Wt. 9.9, Vis. 56, WL 6.5, pH 8.5,
 add 5 lbs High Viscosity.

Current Operation: Drilling and coring.

February 8 (cont'd.)

Depth: 1351' 12 3/4 hrs. drilling
 2 hrs. mix mud and circulate
 1/2 hr. service
 6 hrs. trips
 1 1/2 hrs. repairs
 1 1/4 hrs. core
Operations: Drill from 1320' to 1347'
 Core from 1347' to 1351'
Rock Types Penetrated: From 1320' to 1337' - tight dolomite
 From 1337' to 1347' - some porosity

Core #5 1347' to 1351' (core jammed) Rec. 4'
 Dolomite with good porosity and
 excellent permeability.

February 9.

Mud: Wt. 10 lbs., Vis. 54, WL 7.2, pH 8,
 add 400 lbs. gel.
Current Operations: Test and drill.
Depth: 1365' 1 hr. mix mud
 3/4 hr. ream
 1 1/4 hrs. circulate
 8 1/4 hrs. trips
 1 1/2 hrs. rig to test
 2 1/2 hrs. test
 3 hrs. work on mud lines
 5 1/4 hrs. drill
 1/2 hr. repair
Operations: Ream from 1347' to 1351'
 Test from 1326' to 1351'
 Drill from 1351' to 1365'



-16-

Test No. 6

1326' to 1351'

Valve open 1 hr. and 20 min.

Steady blow, drill pipe filled with sulphur water to within a few feet of the surface. When packer pulled loose, main valve stuck open, allowed mud to displace all water from the pipe.

Hydrostatic head 694 lbs.

Initial flow pressure 190 lbs.

Final flow pressure 630 lbs.

Rock Types Penetrated: From 1351' to 1365' - dolomite with interbedded zones of good porosity.

February 10.

Mud:

Wt. 9.9, Vis. 47, WL 6.4, pH 8.5,
add 20 lbs. Quebracho, 10 lbs. caustic.

Current Operation:

Drilling.

Depth: 1412'

20 3/4 hrs. drilling

1/2 hr. service

2 3/4 hrs. trip

Operations:

Drill from 1365' to 1412'

Rock Types Penetrated: Brown, fine dolomite, mostly tight,
some porosity.

February 11.

Mud:

Wt. 9.9, Vis. 43, WL 6.4, pH 9.5.

Current Operation:

Drilling

Depth: 1449'

19 1/2 hrs. drilling

1/2 hr. service

1 hr. repairs

3 hrs. trip

Operations:

Drill from 1412' to 1449'

Rock Types Penetrated: From 1412' to 1449' - brown fine
crystalline dolomite, some porosity.

February 12.

Mud: Wt. 10.1, Vis. 47, WL 6.8, pH 8.5,
Current Operation: Drilling
Depth: 1486' 20 1/4 hrs. drilling
Operations: 3 1/4 hrs. trip
Rock Types Penetrated: Drill from 1449' to 1486'
From 1449' to 1486' - brown to
grey dolomite, trace of porosity.

February 13.

Mud: Wt. 10.1, Vis. 46, WL 6.6, pH 8.5.
Current Operation: Logging and velocity survey.
Depth: 1497' 7 hrs. drilling
Operations: 3 hrs. trip
7 1/2 hrs. log
5 hrs. velocity survey
1 1/2 hrs. plug
Drill from 1486' to 1497'
Log hole
Run velocity survey
Run Plug No. 1, 980' - 1200'
27 sax, displaced with
3 barrels of mud.
Rock Types Penetrated: From 1486' to 1497' - fine brown dolomite.

Surveys 1400' - 3/4°
1240' - 6 3/4°
1370' - 5 3/4°
1496' - 5°

February 14.

Mud: Add 400 lbs. bicarbonate.
Current Operation: Waiting on cement, feel for plug.
Depth: 1497' 12 hrs. circulate, W.O. C.
2 hrs. circulate trip
8 hrs. circulate and treat mud.

Plug not set, mud contaminated,
ran into 1080' for plug No. 2.

February 15.

Mud: Wt. 9.6, Vis. 57.
Current Operation: Set plug No. 2.
Depth: 1497' 5 1/2 hrs. circulate and treat, mud.
5 hrs. trips
1 1/2 hrs. Plug No. 2
11 1/2 hrs. W.O.C.
1/2 hr. feel plug
Operations: Bypassed contaminated mud and treated remainder, cleaned hole to 1080'.
Ran plug No. 2, 990' to 1080', 11 sax cement, displaced with 2 3/4 barrels water, ran 2 barrels water ahead of plug.
Circulated W.O.C.
Tried to feel plug at midnight, still soft.

February 16.

Mud: Mixed 420 lbs. Calcium Chloride in water and displaced mud.
Current Operation: Bailing.
Depth: 1497' 3 hrs. trips
8 hrs. W.O.C. & cleaning pits
1 1/2 hrs. trip to feel plug
3 hrs. displace mud
2 1/2 hrs. repair B.O.P.
6 hrs. bail
Operations: Feel plug No. 2 at 1046', took full weight. Bailed, using float upside down in drill collar, using drill pipe.

February 17.

Current Operation: Rig down.
Depth: 1497'

-19-

February 17 (cont'd.)

10 hrs. bail
 1/2 hr. service
 2 1/2 hrs. lay down pipe
11 hrs. rig down and move


Bailed 16 1/2 barrels, fluid level
should be at 710', last trip in-
dicated possibly 465' of fluid.

TIME DRILLING RECORD

1 Foot Intervals

186' - 190'	*12, 32, 13, 13.
190' - 200'	18, 15, 13, 19, 17, 29, 18, 16, 17, 15.
200' - 210'	16, 15, 24, 24, 31, 22, 20, 22, 13, 15.
210' - 220'	12, 17, 17, 18, 22, 14, 14, 11, 12, 11.
220' - 230'	11, 12, *6, 13, 15, 11, 19, 15, 13, 12.
230' - 240'	12, 13, 31, 24, 16, 13, 8, 8, 11, 10.
240' - 250'	13, 9, 9, 8, 9, 9, 12, 16, 23, 30.
250' - 260'	40, 30, 15, -, -, *7, 5, 7, 4, 5.
260' - 270'	6, 8, 6, 7, 8, 9, 5, 5, 5, 5, 4.
270' - 280'	9, 10, 10, 6, 7, 6, 9, 6, 6, 6, 5.
280' - 290'	6, 6, 8, 5, 8, 6, 7, 8, 7, 9.
290' - 300'	11, 9, 6, 5, 5, 5, 5, 4, 6, 9.
300' - 310'	6, 10, 16, 8, 16, 18, 14, 10, 12, 15.
310' - 320'	19, 20, 12, 8, 8, 7, 8, 9, 12, 10.
320' - 330'	10, 9, 11, 12, 8, 9, 19, 13, 12, 9.
330' - 340'	13, 16, 15, 13, 13, 10, 13, 11, 9, 6.
340' - 350'	10, 13, 10, 13, 12, 11, 11, 12, 17, 12.
350' - 360'	14, 12, 12, 11, 9, 9, 10, 11, 13, 13.
360' - 370'	15, *5, 5, 5, 5, 8, 8, 8, 7, 7.
370' - 380'	8, 9, 7, 5, 5, 7, 6, 5, 7, 7.
380' - 390'	9, 7, 7, 8, 9, 12, 11, 10, 7, 7.
390' - 400'	8, 8, 9, 13, 8, 9, 5, 7, 7, 8.
400' - 410'	7, 6, 8, 9, 10, 11, 9, 10, 11, 8.
410' - 420'	8, 9, 13, 13, 21, 9, 8, 8, 10, 15.
420' - 430'	15, 11, 7, 8, 9, 10, 14, 16, 12, 12.
430' - 440'	13, 13, 13, 12, 14, 11, 10, 9, 10, 13.
440' - 450'	18, 18, 17, 12, 7, 12, 10, 9, 10, 11.
450' - 460'	12, 14, 17, 16, 23, 16, 10, 12, 17, 15.
460' - 470'	17, 18, 25, 35, 25, 37, 45, 50, 30, 45.
470' - 480'	*15, 16, 20, 20, 22, 18, 10, 15, 20, 20.
480' - 490'	20, 22, 23, 20, 21, 24, 22, 27, 10, 11.
490' - 500'	20, 25, 15, 18, 29, 36, 27, 22, 34, 33.
500' - 510'	27, 34, 35, 33, 35, 30, 30, 34, 37, 34.
510' - 520'	37, 31, 41, 32, 10, 20, 37, 38, 35, 22.
520' - 530'	26, 28, 49, 15, 17, 30, *20, 25, 27, 23.

* New Bit



530' - 540'	21, 22, 20, 20, 20, 21, 22, 20, 22, 25.
540' - 550'	27, 33, 35, 31, 24, 18, 21, 35, 36, 36.
550' - 560'	40, 32, 38, 21, 26, 27, 25, 31, 35, 33.
560' - 570'	20, 37, 33, 30, 25, 25, 32, 21, 19, 10.
570' - 580'	12, 19, 22, 23, 26, 20, 18, 18, 17, 17.
580' - 590'	20, 19, 24, *25, 30, 30, 30, 37, 39, 50.
590' - 600'	44, 42, 33, 30, 25, 35, 55, 50, 45, 55.
600' - 610'	40, 36, *25, 30, 34, 25, 32, 29, 34, 29.
610' - 620'	33, 25, 14, 18, 20, 18, 20, 25, 30, 35.
620' - 630'	30, 35, 32, 35, 36, 32, 20, 30, 30, 35.
630' - 640'	32, 25, 28, 27, 34, 35, 37, 36, 32, 24.
640' - 650'	48, 30, 31, 34, 45, 45, 37, 45, *18, 27.
650' - 660'	27, 18, 16, 28, 28, 27, 20, 31, 32, 24.
660' - 670'	29, 29, 30, 32, 28, 35, 28, 30, 37, 30.
670' - 680'	30, 34, 14, 18, 24, 35, 30, 29, 31, 40.
680' - 690'	30, 37, 31, 31, 41, 45, 39, 38, 38, 55.
690' - 700'	45, 45, 30, 30, *20, 20, 15, 15, 17, 18.
700' - 710'	20, 24, 19, 22, 25, 27, 18, 20, 25, 20.
710' - 720'	20, 15, 11, 10, 11, 9, 10, 9, 9, 10.
720' - 730'	7, 8, 18, 8, 11, 12, 20, 28, 17, 21.
730' - 740'	23, 31, 32, 32, 34, 20, 26, 36, 41, 34.
740' - 750'	27, 40, 50, 33, 33, 39, 44, 36, 32, 30.
750' - 760'	28, 22, 16, 24, 23, 22, 21, *12, 15, 14.
760' - 770'	18, 13, 15, 17, 15, 15, 15, 15, 14, 16.
770' - 780'	15, 12, 18, 16, 14, 17, 18, 20, 20, 20.
780' - 790'	25, 13, 19, 22, 24, 24, 28, 24, 21, 20.
790' - 800'	21, 26, 16, 20, 27, 30, 14, 22, 20, 16.
800' - 810'	13, 15, 25, 38, 27, 40, 20, 17, 15, 10.
810' - 820'	25, 21, 19, 25, 30, 25, 27, 22, 18, 17.
820' - 830'	15, 17, 18, 25, 30, 30, 25, *13, 17, 20.
830' - 840'	18, 14, 12, 16, 20, 15, 20, 17, 18, 21.
840' - 850'	21, 20, 21, 21, 22, 22, 22, 17, 14, 14.
850' - 860'	23, 22, 20, 18, 16, 13, 12, 15, 23, 21.
860' - 870'	31, 28, 31, 22, 26, 23, 18, 15, 12, 16.
870' - 880'	30, 21, 18, 18, 19, 20, 19, 22, 22, 24.
880' - 890'	23, 25, 23, 22, 21, 20, 17, 22, 21, 27.
890' - 900'	23, 28, 22, 19, 21, 25, 30, 30, *15, 11.

* New Bit

900' - 910'	5, 11, 9, 10, 10, 10, 10, 9, 11, 14.
910' - 920'	17, 14, 11, 13, 18, 19, 19, 15, 14, 15.
920' - 930'	16, 15, 18, 23, 23, 27, 23, 20, 15, 21.
930' - 940'	24, 24, 16, 21, 19, 14, 26, 21, 22, 32.
940' - 950'	35, 30, 43, 27, 28, 27, 15, 18, 20, 20.
950' - 960'	14, 16, 28, 28, 18, 22, 27, 28, 20, 21.
960' - 970'	19, 17, 22, 18, 23, 26, 25, 25, 22, -.

Coring Time

969' - 979' 8, 9, 9, 10, 9, 11, 13, 10, 14, 14.

Reaming Time

969' - 979' 6, 5, 8, 8, 8, 7, 10, 9, 9, 9.

Drilling Time

980' - 990'	----- 16.
990' - 1000'	25, 26, 25, 24, 26, 20, 21, 12, 11, 12.
1000' - 1010'	13, 15, 15, 14, 11, - - - - -

Coring Time

995' - 1005' 9, 8, 9, 9, 9, 10, 10, 10, 10.

Drilling Time

1005' - 1010'	20, 19, 19, 18, 19, -- -- -- -- -
1010' - 1020'	23, 17, 24, 25, 20, 22, 15, 15, 15, 18.
1020' - 1030'	17, 22, 25, 21, 15, 18, 21, 20, 20, 21.
1030' - 1040'	20, 18, 18, 19, 18, 20, 21, 22, 18, 17.
1040' - 1050'	18, 22, 20, 23, 20, 20, 18, 19, 18, 19.
1050' - 1060'	16, 19, 21, 16, 19, 22, 23, 25, 23, 18.
1060' - 1070'	23, 27, 35, 27, 23, 34, 23, 20, 33, 28.
1070' - 1080'	20, 36, 50, *12, 14, 14, 17, 15, 18, 19.
1080' - 1090'	18, 18, 17, 18, 15, 13, 14, 18, 19, 19.
1090' - 1100'	22, 21, 24, 15, 15, 20, 17, 16, 16, 18.
1100' - 1110'	22 - - - - - - - - -

* New Bit

Coring Time

- , 14, 15, 11, 15, 14, 13, 10, 11, - .
(Core Jammed)

Drilling Time

Coring Time

1280'-1290' 6, 6, 7, 9, 8, 9, 8, 9, 10, 9.

Reaming Time

1280'-1290' 15, 16, 14, 13, 17, 16, 19, 16, 16, 16.

Drilling Time

1290'-1300'	27, 32, 28, 31, 21, 17, 25, 26, 25, 24.
1300'-1310'	25, 34, 33, 23, 18, 24, 27, 19, 31, 36.
1310'-1320'	32, 40, 65, 46, 48, 50,*20, 30, 28, 22.
1320'-1330'	25, 23, 24, 23, 27, 25, 25, 20, 28, 33.
1330'-1340'	24, 38, 44, 43, 40, 38, 37, 23, 18, 20.

1340'-1350' 28, 33, 23, 15, 27, 25, 30.

Coring Time

1347'-1351' 6, 7, 7, 9.
(Core Jammed)

Drilling Time

1350'-1360'	-, 30, 20, 19, 20, 25, 12, 13, 12, 18.
1360'-1370'	28, 20, 20, 24, 25, 27, 27, 26, 22, 19.
1320'-1380'	20, 23, 23, 23, 28, 28, 28, 27, 29, 26.
1380'-1390'	28, 26, 12, 12, 18, 21, 19, 21, 20, 21.
1390'-1400'	19, 27, 29, 32, 37, 35, 29, 30, 23, 19.
1400'-1410'	26, 32, 36, 30, 29, 31, 36, 35, 26, 23
1410'-1420'	*17, 24, 24, 25, 28, 34, 41, 32, 23, 41.
1420' - 1430'	29, 35, 32, 25, 21, 26, 27, 21, 28, 29.
1430'-1440'	26, 30, 28, 34, 29, 30, 31, 28, 24, 23.
1440'-1450'	28, 32, 28, 34, 35, 35, 61, 55, 50,*33.
1450'-1460'	37, 29, 29, 35, 37, 29, 36, 29, 28, 27.
1460'-1470'	36, 40, 35, 16, 17, 20, 28, 21, 29, 26.
1470'-1480'	27, 27, 28, 32, 25, 26, 39, 41, 35, 43.
1480'-1490'	*44, 34, 37, 43, 40, 45, 39, 39, 39, 36.
1490'-1500'	37, 40, 43, 32, 45, 39, 38, - - -

MUD RECORD

<u>Date</u>	<u>Wt.</u>	<u>Vis.</u>	<u>W. L.</u>	<u>pH</u>	<u>Additives</u>
Jan. 7	8.6	43			700 lbs. gel.
8	9.6	47			
9	10.3	55			
10	8.7	32	60+		800 lbs. calcium chloride
11	9.9	76			750 lbs. gel.
12	9.7	45			1100 lbs. gel. (started using two mud pits).
13	10.5	48			
14	10.6	48			
15					
16	9.3	34	33	9.2	100 lbs. bicarbonate
17	9.8	40	16	10.5	10 lbs. quebracho, 5 lbs. caustic.
18	10	42	11.8	10	200 lbs. gel, 15 lbs. quebracho & 5 lbs. caustic.
19	9.8	37	7.6	10	50 lbs. bicarbonate, 10 lbs. quebracho, 5 lbs. caustic.
20	9.7	36	10	9.7	50 lbs. bicarbonate, 50 lbs. Anti. Gyp.
21	9.7	37	9.8	10	
22	9.5	38	9.2	9.4	450 lbs. gel.
23	9.4	40	9.3	9.5	
24	9.4	43	9.4	9.2	250 lbs. gel.
25	9.4	42	9.3	9.5	5 lbs. quebracho, 2 lbs. caustic.
26	9.5	42	8.4	9.5	
27	9.4	45	7.2	9.5	600 lbs. gel., 10 lbs. quebracho, 5 lbs. caustic
28	9.5	64	7.0	9.5	2 1/2 lbs. High Viscosity Driscose.
29	9.5	52	7.4	9.5	
30	9.4	42	7.8	9	
31	9.3	54	6.8	8.5	200 lbs. gel, 5 lbs. High Vis.

MUD RECORD

<u>Date</u>	<u>Wt.</u>	<u>Vis.</u>	<u>W. L.</u>	<u>pH</u>	<u>Additives</u>
Feb. 1	9.5	48	6.1	9.0	20 lbs. Spersene, 10 lbs. caustic.
2	9.6	48	6.5	10	
3	9.8	46	6.3	10	
4	9.8	43	6.6	9.5	100 lbs. gel.
5	9.9	45	6.8	8.5	300 lbs. gel.
6	9.9	55	7.1	9.3	20 lbs. Spersene, 5 lbs. caustic, 2 1/2 lbs. High Viscosity.
7	10.1	65	5.4	6.6	500 lbs. Anti. Gyp. (Sand 9.3)
8	9.9	56	6.5	8.5	5 lbs. High Viscosity
9	10	54	7.2	8	400 lbs. gel.
10	9.9	47	6.4	8.5	20 lbs. quebracho, 10 lbs. caustic
11	9.9	43	6.4	9.5	
12	10.1	47	6.8	8.5	
13	10.1	46	6.6	8.5	
14					400 lbs. bicarbonate of soda.
15	9.6	57			
16					420 lbs. calcium chloride.

NO.	SERIAL	SIZE	MAKE	TYPE	FROM	TO	FEET	HOURS	REMARKS
1	9726	4 3/4	Williams	K2	0		175	14	Good
2	7743	4 3/4	Williams	K1	175		185	4	Near new
3	3105	4 3/4	Varel	V1	185		222	12	Good
4	3095	4 3/4	Varel	V1	222		253	31	Bearings loose
5	62811	8 5/8	Hughes	OWV	0		202	20 1/2	Fair
6	54963	8 5/8	Hughes	OWV	202		255	53	Bearings loose
7	9725	4 3/4	Williams	K2	255		361	106	20 1/4
8	9729	4 3/4	Williams	K2	361		470	109	Bearings loose, dull teeth good.
9	9728	4 3/4	Williams	K2	470		526	56	24 1/4
10	9727	4 3/4	Williams	K2	526		583	57	24 1/4
11	3059	4 3/4	Varel	V1	583		602	19	11 3/4
12	9724	4 3/4	Williams	K2	302		648	46	24 3/4
13	571	4 3/4	Williams	K2	648		694	46	24
14	573	4 3/4	Williams	K2	694		757	63	24 1/4
15	572	4 3/4	Williams	K2	757		827	70	24 1/4
16	570	4 3/4	Williams	K2	827		898	71	24 3/4
17	569	4 3/4	Williams	K2	898		969	71	24
	Core				969		979	10	1 3/4
18	607	4 3/4	Williams	K2	979		995	16	10 1/2
	Core				995		1005	20	3 1/2
19	9284	4 3/4	Williams	K3	1005		1074	69	24
20	9281	4 3/4	Williams	K3	1074		1152	78	24
21	9285	4 3/4	Williams	K3	1152		1222	70	24 1/2
22	9282	4 3/4	Williams	K3	1222		1280	58	22 1/4
23	568	4 3/4	Williams	K2	1280		1290	10	Reaming
					1290		1316	26	16 1/4
									Dull, loose

-27-

BIT RECORD



BIT RECORD (cont'd.)


NO.	SERIAL	SIZE	MAKE	TYPE	FROM	TO	FEET	HOURS	REMARKS
24	9411	4 3/4	Williams	K2	1316	1347	31	14 3/4	
24	9411				1347	1351	4		Reaming
25	8659	4 3/4	Varel	V1	1351	1410	59	25 1/4	Dull & loose
26	3008	4 3/4	Varel	V1	1410	1449	39	20 1/4	Drill
27	7444	4 3/4	Williams	K1	1449	1480	31	16 1/4	Very dull, loose
28	7746	4 3/4	Williams	K1	1480	1497	18	11	

DRILL STEM TEST NO. 1

Date - January 28, 1960
Type of tool - Made by Drill Stem Testers Ltd.
Formation tested - Bear Rock.
Size of hole - 4 3/4"
Size of rubber - 3 5/8"
Length of tail pipe - 25'
Perforations - 25'
Depth - 969'
Interval tested - 944' to 969'
Remarks - Misrun, dart made a clean hole
through disk, causing disk to
plug.

DRILL STEM TEST NO. 2

<u>Date</u> -	January 30, 1960
<u>Type Of Pool</u> -	Made by Drill Stem Testers Ltd.
<u>Formation Tested</u> -	Bear Rock
<u>Size Of Hole</u> -	4 3/4"
<u>Size Of Rubber</u> -	3 5/8"
<u>Length Of Tail Pipe</u> -	105'
<u>Perforations</u> -	25'
<u>Depth</u> -	1,005'
<u>Valve Open</u> -	1 hour
<u>Shut In</u> -	Nil
<u>Nature Of Blow</u> -	Good initial puff, steady weak blow.
<u>Interval Tested</u> -	900' - 1,005'
Initial flowing pressure - 10 lbs.	
Final flowing pressure - 238 lbs.	
Hydrostatic pressure - 418 lbs.	
<u>Recovery</u> -	500' of watery mud, sulphur odour, no salt.
<u>Remarks</u> -	Packer broke 4" from top and telescoped, necessary to rotate to pull loose. Tool run without disk sub.



DRILL STEM TEST NO. 3

Date - January 31, 1960.

Type of tool - Made by Drill Stem Testers Ltd.

Formation tested - Bear Rock

Size of hole - 4 3/4"

Size of rubber - 3 5/8"

Length of tail pipe - 70'

Perforations - 20'

Depth - 1005'

Interval tested - 935' to 1005'

Remarks - Misrun, packer failed to seat,
tool run without disk sub.

DRILL STEM TEST NO. 4

Date - January 31, 1960

Type of tool - Made by Drill Stem Testers Ltd.

Formation tested - Bear Rock

Size of hole - 4 3/4"

Size of rubber - 3 5/8"

Length of tail pipe - 65'

Perforations - 25'

Depth - 1005'

Interval tested - 940' to 1005'


Remarks - Misrun, packer failed to seat,
tool run with disk sub.

DRILL STEM TEST NO. 5

<u>Date</u> -	February 1, 1960
<u>Type of tool</u> -	Made by Drill Stem Testers Ltd.
<u>Formation tested</u> -	Bear Rock
<u>Size of hole</u> -	4 3/4"
<u>Size of rubber</u> -	3 5/8"
<u>Length of tail pipe</u> -	75'
<u>Perforations</u> -	25'
<u>Depth</u> -	1005'
<u>Remarks</u> -	Misrun, packer failed to seat, tool run with disk sub.

DRILL STEM TEST NO. 6

<u>Date</u> -	February 9, 1960
<u>Type Of Tool</u> -	Made by Drill Stem Testers Ltd.
<u>Formation Tested</u> -	Silurian
<u>Size Of Hole</u> -	4 3/4"
<u>Size Of Rubber</u> -	3 5/8"
<u>Length Of Tail Pipe</u> -	25'
<u>Perforations</u> -	25'
<u>Depth</u> -	1, 351'
<u>Valve Open</u> -	80 minutes
<u>Shut In</u> -	Nil
<u>Nature Of Blow</u> -	Good initial puff, weak steady blow.
<u>Interval Tested</u> -	1, 326' to 1, 351'
Initial flowing pressure	- 190 lbs.
Final flowing pressure	- 630 lbs.
Hydrostatic pressure	- 694 lbs.
<u>Recovery</u> -	full string of sulphur water.
<u>Remarks</u> -	When packer was pulled loose the main valve remained open, mud displaced the water which began to flow from the hose immediately indicating the pipe was nearly full of water.



BREAKDOWN OF TIME SPENT ON THE HOLE

Drilling 4 3/4"	484 3/4 hours
Reaming tight hole	4 1/2 hours
Reaming to 8 5/8"	53 3/4 hours
Setting surface casing, W.O.C., drilling out, pressuring up	36 1/2 hours
Circulating	6 1/2 hours
Trips	62 hours
Testing, including trips, conditioning mud, waiting for daylight	71 hours
Coring, including trips, conditioning mud, handling core	53 1/2 hours
Repairs	34 1/2 hours
Service	15 3/4 hours
Logging, including velocity log	16 hours
Cement plugs, including W.O.C.	65 hours
Bailing	16 hours
Stuck in hole	30 hours
Time lost due to freezing mud lines	<u>29 1/4 hours</u>
TOTAL TIME ON HOLE	979 hours

SAMPLE AND CORE DESCRIPTION

0' - 173' Sand and gravel - grains and fragments of quartz, igneous rock, limestone, dolomite, sandstone, hard green shale, grey shale with spores, rare black chert. Rock appears to be mainly medium to coarse grained sand of quartz with some igneous grains which are very well rounded, layers of gravel and boulders occur throughout the section. Cuttings of sandstone are usually porous and oil stained.

173' Lower Ramparts.

173' - 190' Limestone - brownish grey, argillaceous, very fine crystalline, rich in fossils - ostracods, brachiopods and gastropods.

190' - 195' Limestone - as above 90%.
Shale - brownish grey, calcareous, rounded fragments of limestone, probably fossils, 10%

195' - 205' Limestone - as above 90%.
Limestone - brown, vitreous, clean, probably coral material 10%.

205' - 220' Limestone - brownish grey, argillaceous, ostracods and brachiopod fragments, brown shaly partings, some with crinoids, traces of clean, fine crystalline limestone (corals?).

220' - 255' (Cavings fairly bad)

Limestone - light brownish grey, very fine, nearly dense, tiny broken fossil debris scattered throughout. Trace of green calcareous shale and greenish grey argillaceous limestone (some of the argillaceous material is up to fine silt size). Pyrite common at top, minor amounts throughout.

 (End of bad cavings)

255' - 300' Limestone - as above but fewer fragments 50%.
Shaly limestone and limy shale - gradational from shale to limestone - greenish, calcareous, soft and flaky to hard, 50%.

300' - 462' Limestone - greenish to brownish grey, the brown limestone is fragmental and fossiliferous, fragments of crinoids, brachiopods and ostracods, greenish limestone is argillaceous, 80%.

300' - 462' (cont'd.)

In places fossils make up to 20% of the limestone.

Shale - green, calcareous, 20%

462' Bear Rock.

462' - 505' Limestone - brown, very fine crystalline to dense, texture often shows pellet like structure, very fine to medium, round, forms in a clear matrix, may be bahamite or algal texture, this texture varies from very faint to pronounced.

505' - 525' Limestone - tan, brown to grey, sub-lithographic, some brown limestone as above, thin partings of hard, dark grey argillaceous material.

525' - 590' Limestone - tan, some grey, sub-lithographic, 50%.
Limestone - brown, very fine crystalline, clear calcite network or inclusions, traces of bahamite or algal texture, 50% ⁺ ₋. Dark argillaceous partings and stylolites, these may be bituminous but have negative CC/4 reaction.

590' - 712' Gradational with above.

Limestone - grey to brown, very fine crystalline to nearly dense, traces of sub-lithographic limestone, algal (?) texture common in upper part, outlined by clear calcite, becomes rare downward; argillaceous partings or stylolites abundant.

630' Trace of clear calcite crystals.

650' Trace of clear calcite crystals.

695' Traces of green shale.

712' - 722' Drilling break, possibly caused by presence of shale. Trace of shale-green, calcareous, disintegrates quickly in water.

Limestone - brown and grey, mostly micro-crystalline to sub-lithographic, practically no change from above. Algal texture very rare.

722' - 900' Limestone - as above.

Traces of shale - dark and bright green, slightly to non-calcareous, hard(disintegrates quickly in water).

722' - 900' (cont'd.)

Some of the shale contains what appears to be rounded limestone grains, also pyrite.

840' Trace of pin point porosity.

Some of the limestone has a slight greenish cast and contains a small amount of very fine silt and argillaceous material.

900' - 937' Limestone - as above, some waxy green shale with rounded limestone grains, algal texture more common.

910' Trace of pin point porosity with oil stain.

937' - 955' Limestone - as above 50%

Dolomite - light brownish grey, very fine crystalline, granular, 50%.

Trace of pin point porosity with oil stain occurs at 940' and below.

965' - 969' Limestone - as below - slight granular texture, brown to grey, micro-crystalline, partings and stylolites of grey and green shale.

CORE #1 969' - 979'

969' - 979' Limestone - light brownish grey, micro-crystalline, very homogeneous, tight. Many tiny stylolites, a few partings up to 1/4" thick of green and grey, laminated, slightly calcareous shale. A few fractures, lined by coarse crystalline calcite - some porosity and oil stain associated with the fractures.

979' - 995' Limestone - as above, no oil stain.

CORE #2 995' - 1005'

995' - 1005' Limestone - light brownish grey, micro-crystalline, some nearly sub-lithographic(lime mud) many dark, thin argillaceous partings. One fracture tightly sealed with calcite. One tiny oil stained vug.

1005' - 1070' Limestone - light grey to brown. micro-crystalline, traces of calcite and green shale.

1070' - 1075' Limestone - brown, micro-crystalline, dark to black shale partings (brown streak).

1075'-1085' Limestone - as above 1070', traces of the dark partings.

1085'-1101' Limestone - as above, some limestone - light grey. very fine crystalline, some pin point and inter-crystalline porosity. Porosity only a trace except below 1095'.

CORE #3 1101' - 1109'

1101'-1109' Limestone - light grey, micro-crystalline, very fine stylolites. Rare fractures lined with medium sized calcite crystals, some very fine limestone associated with the fractures - probably permeable.

1109'-1118' Limestone - light grey, micro-crystalline. (As in core above)

1118'-1125' Limestone - brownish grey, fine crystalline, some porosity. Some limestone as above.

1125'-1150' Limestone - light grey and brownish grey, micro-crystalline, some light and some brownish grey, fine crystalline porous limestone.

1150'-1180' Limestone - light grey and brownish grey, micro-crystalline, mere traces of pin point porosity. Traces of dark green shale, a few very thin stylolites, a few calcite crystals.

1180'-1215' Limestone - as above but no trace of porosity. Trace of darker limestone with pyrite at the base.

1215'-1225' Limestone - brown, fine granular, trace of calcite.

1225'-1235' Limestone - brown, micro-crystalline.

1235'-1270' Limestone - light grey to brown, micro-crystalline, in part has a chalky appearance, a few dark shale partings.

1270' Silurian

1270'-1280' Dolomite - brown, very fine to fine crystalline very slightly silty, tight, pyrite, trace of green waxy shale, some white vein dolomite.

CORE #4 1280' - 1290'

1280'-1290' Rec. 10'

Dolomite - brown, slightly mottled, very fine crystalline, very slightly silty, many fine fractures tightly sealed with clear dolomite, larger fracture shows minor brecciation.

1290'-1337' Dolomite - brown to light brownish grey, traces of small drusy vugs, traces of porosity with oil stain at 1330'.

1337' - 1347' Dolomite - as above, traces of porosity to 1342', below 1342' considerable fine crystalline dolomite with good inter-crystalline porosity.

CORE #5 1347' - 1351'

1347'-1351' Rec. 4'

Dolomite - brown, very fine crystalline, very hard, many small vugs up to 3/8" and irregular fractures. Lining vugs is fine to medium crystalline dolomite with good porosity - excellent permeability. Some mottling and texture which probably represents organisms, possibly a reef or reef breccia.

1351'-1365' Dolomite - as above, considerable amount of good porosity, some limy dolomite.

1365'-1420' Dolomite - brown and light brown, very fine crystalline, some with a lighter and softer appearance, generally tight, trace of porosity as seen above. Small amount of very fine silt.

1420'-1440' Dolomite - as above 70%.
Dolomite - fine crystalline, excellent inter-
crystalline porosity, 30%.

1440'-1455' Dolomite - brown, fine to very fine crystalline, very slightly silty, traces of intercrystalline porosity, white, coarse crystalline dolomite, probably from vug or fracture filling.

1455'-1485' Dolomite - brown to light brownish grey, very fine crystalline, very slightly silty, trace of porosity, signs of drusy vugs, some white dolomite crystals.

1485'-1497' Dolomite - brown, very fine crystalline, rare trace of porosity.

STRATIGRAPHY

GENERAL

In the Rond Lake area, the upper part of the Stratigraphic Section is as follows.

Glacial Deposits

Till and lake sands, up to 200', nearly everywhere present.

Cretaceous

Poorly consolidated quartz sand, thin, random, patchy distribution.

Middle Devonian - Ramparts Formation

Upper Ramparts Limestone - 200'⁺ not present in any of the wells drilled, forms the scarp west of Rond Lake.

Middle Ramparts Shale; also called Hare Indian River Shale - 600' to 700' of green shale, 30' at base contains interbedded dark brown shale.



-47-

Lower Ramparts Limestone - 300 feet minus, fossiliferous limestone.

Bear Rock Formation

800⁺ feet, very fine algal rich limestone, equivalent to the dolomite breccia of the Norman Wells area.

Silurian

Thickness unknown, dolomite with reefs.

PLEISTOCENE AND RECENT

Rond Lake No. 1 encountered 173 feet of glacial deposits - sand and pebbles in a clay matrix. The deposits are chiefly medium to coarse grained quartz sand, with layers of gravel composed of a variety of sedimentary rocks of local derivation as well as a few grains of igneous rock.

LOWER RAMPARTS LIMESTONE

The Lower Ramparts limestone consists of argillaceous, fossiliferous limestone with interbedded green, calcareous shale. Brachiopods, ostracods and cup-corals are common throughout. The upper 82 feet are predominantly limestone, much of which is formed from layers of colonial corals. The lower 207 feet contain more interbedded shale.

- In Rond Lake No. 1, the Lower Ramparts is 289 feet thick, this is 17 feet thicker than in Rond Lake No. 2, the only other well to penetrate the full section. Two hundred eighty nine feet is probably not the full thickness of the Lower Ramparts, as glacial deposits directly overlie the limestone. From a comparison of E-logs in wells No. 1 and No. 2, it can be seen that in well No. 1 the lower part of the section, between 312 feet and 462 feet, thins gradually from 150 feet in No. 1 to 138 feet in No. 2, accounting for 12 of the 17 foot difference.

BEAR ROCK

Rond Lake No. 1 penetrated the full Bear Rock section between 462 and 1270 feet. The formation is 808 feet thick and is composed predominantly of clean, very fine, nearly dense limestone. There are many stylolites and thin partings of brown shale. The texture of the rock indicates that it probably originated as a lime mud bound together by algal material. Ostracods are common throughout the section aside from ostracods and algae, there is no trace of organic material. A characteristic of the Bear Rock formation is the presence, throughout the section of quartz in the form of tiny euhedral crystals.

Traces of pin point porosity occur throughout the lower 430 feet of the formation. Some poor porosity occurs in the layers from 937 to 965 feet and from 1150 to 1180 feet; the layer from 937 to 965 is in part granular dolomite. Better porosity, associated with fractures, occurs from 1095 to 1109 feet and from 1118 to 1125 feet. Good intercrystalline porosity is present between 1125 to 1150 feet.

The oil stained porous layer from 940 to 955 feet was tested by Drill Stem Test No. 2 and by later bailing operations, oil cut sulphur water was obtained. Lower porous layers were not oil stained and were not tested.

SILURIAN

The Silurian was encountered at a depth of 1270 feet and 227 feet were drilled; the total thickness of the Silurian is unknown. The drilled section consists of brown, fine crystalline dolomite, very fine detrital silt is present throughout. Core No. 4, taken near the top of the Silurian shows that the dolomite has a mottled appearance, it is cut by several fractures tightly sealed by crystalline dolomite, minor brecciation is associated with the larger fractures.


Porous layers occur between 1342 and 1365 feet and between 1420 and 1440 feet. In addition traces of porosity are present throughout the section below 1337 feet. Core No. 5 was cut in the upper porous section; good inter-

crystalline porosity is associated with many small vugs and fractures, these vugs and porous patches occur within a body of tight hard, fine dolomite, however the permeability is excellent. The lower porous layer has excellent inter-crystalline porosity.

No recognizable fossils were seen in the cores or samples, however the arrangement and shape of the vugs gives an impression of organic material.

The upper porous zone was tested and contained sulphur water.

DISCUSSION



Rond Lake No. 1 took 42 days to drill 1497 feet. Slow drilling in the hard carbonates, especially reaming to 8 5/8" for surface casing, is one reason for the slow progress but other factors are involved.

The drill pipe became frozen in the hole at 220 feet, a result of not tripping out while making repairs on the mud pump. Although the pipe was rotated and the kelly worked periodically, the hole iced up in twelve hours. This freezing on the wall of the hole happened again during bailing operations, within twenty four hours enough ice formed on the walls of the hole that the bailer could not get down.

Another big time waster was the series of misruns which were a result of running a packer rubber which had been left out in the cold (down to 65 below) between tests. The one successful test of this series was the result of an accident - the packer rubber broke in two and telescoped, fortunately the telescoping occurred with the expanded part of the rubber pointing upwards, otherwise the testing

tool would probably still be in the hole.

The third problem that used a lot of time were the attempts to plug back for a test of the upper porous zone. The permeability in the Silurian was so good that the cement plugs slowly sank, displacing mud into the formation. Actually as it turned out the first drill stem test of this upper zone, which recovered 500 feet of watery mud, effectively evaluated the zone, but the significance was missed because of the complete lack of indications of salt.

Thin zones of porosity with only fair permeability were found low in the Bear Rock formation, cuttings from the upper porous layer had oil stain. Fluid recovered from the zone was oil cut water with a sulphur odour. Thicker, good porosity with excellent permeability was encountered in the Silurian, this layer tested sulphur water. Formation pressures are low, approximately equal to the hydrostatic head of Rond Lake. From results of Rond Lake No. 2 it is evident that there is no permeability barrier between the Silurian and the Bear Rock reservoirs.

Much of the porous rocks, from the upper
porous zone in the Bear Rock was oil stained.

G. K. Williams, P. Eng.

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

Edmonton

Fort St. John

Calgary

WATER ANALYSIS REPORT

Field Well No. Rond Lake #1.

Operator Western Decalta Petroleum Limited Date Received March 21, 1960.

Formation Depths

Other pertinent data Rond Lake drinking water.

Date April 6, 1960

Lab. No. C 2783-4

PARTS PER MILLION (MILLIGRAMS PER LITER)

Na & K	Ca	Mg	Fe	SO ₄	Cl	CO ₃	HCO ₃	OH	H ₂ S
34	35	10		31	14		185		

MILLIGRAM EQUIVALENTS

1.49	1.75	0.82		0.64	0.39		3.03		
------	------	------	--	------	------	--	------	--	--

MILLIGRAM EQUIVALENTS IN PERCENT

18.35	21.55	10.10		7.88	4.80		37.32		
-------	-------	-------	--	------	------	--	-------	--	--

Total Solids in Parts per Million



By evaporation	212
After ignition	142
Calculated	215
Specific Gravity	1.003
Observed pH	8.1
Resistivity	7.42 ohm meters @ 68° F.

Properties of Reaction in Percent

Primary salinity	25.36
Secondary salinity	77
Primary alkalinity	11.34
Secondary alkalinity	63.30
Chloride salinity	37.85
Sulfate salinity	62.15

Remarks and conclusions Organic matter present in total solids.

Milligram equivalents multiplied by 100 on the graph.

LOGARITHMIC PATTERN
MEQ per unit

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

Edmonton

Fort St. John

Calgary

WATER ANALYSIS REPORT

Field Well No. Rond Lake #1

Operator Western Decalta Petroleum Limited Date Received March 21, 1960

Formation Depths 1046'

Other pertinent data Boiling sample March 8, 1960, oil scum.

Date April 6, 1960 Lab. No. C. 2783-1

PARTS PER MILLION (MILLIGRAMS PER LITER)

Na + K	Ca	Mg	Fe	SO ₄	Cl	CO ₂	HCO ₃	OH	HS
1,678	239	175		523	2,900		405		Present

MILLIGRAM EQUIVALENTS

72.98	11.93	14.39		10.88	81.78		6.64		
-------	-------	-------	--	-------	-------	--	------	--	--

MILLIGRAM EQUIVALENTS IN PERCENT

36.75	6.01	7.24		5.48	41.18		3.34		
-------	------	------	--	------	-------	--	------	--	--


Total Solids in Parts per Million

By evaporation 6,760
 After ignition 5,040
 Calculated 5,708
 Specific Gravity 1.008
 Observed pH 8.3
 Resistivity 0.943 ohm meters @ 68° F.

Properties of Reaction in Percent

Primary salinity 73.50
 Secondary salinity 19.82
 Primary alkalinity ---
 Secondary alkalinity 6.68
 Chloride salinity 88.26
 Sulfate salinity 11.74

Remarks and conclusions

LOGARITHMIC PATTERN
MEQ per unit

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

Edmonton

Fort St. John

Calgary

WATER ANALYSIS REPORT

Field **Well No.** **Rond Lake #1**

Operator Western Decalta Petroleum Limited Date Received March 21, 1960.

Formation **Depths**

Other pertinent data. Bond Lake drinking water.

Date April 6, 1960 Lab No C 2783-4

PARTS PER MILLION (MILLIGRAMS PER LITER)

Na & K	Ca	Mg	Fe	SO ₄	Cl	CO ₃	HCO ₃	OH	H ₂ S
34	35	10		31	14		185		

MILLIGRAM EQUIVALENTS

1.49	1.75	0.82		0.64	0.39		3.03		
------	------	------	--	------	------	--	------	--	--

MILLIGRAM EQUIVALENTS IN PERCENT

18.35	21.55	10.10		7.88	4.80		37.32		
-------	-------	-------	--	------	------	--	-------	--	--

Total Solids in Parts per Million

By evaporation	212
After ignition	142
Calculated	215
Specific Gravity	1.003
Observed pH	8.1
Resistivity	7.42 ohm meters @ 68° F


Properties of Reaction in Percent

Primary salinity	25.36
Secondary salinity	777
Primary alkalinity	11.34
Secondary alkalinity	63.30
Chloride salinity	37.85
Sulfate salinity	62.15

Remarks and conclusions. Organic matter present in total solids.

Milligram equivalents multiplied by 100 on the graph.

LOGARITHMIC PATTERN MEO per unit



CHEMICAL & GEOLOGICAL LABORATORIES LTD.

Edmonton

Fort St. John

Calgary

WATER ANALYSIS REPORT

Field Well No. Rond Lake #1

Operator Western Decalta Petroleum Limited Date Received March 21, 1960

Formation Depths 1046'

Other pertinent data Boiling sample March 8, 1960.

Date April 6, 1960 Lab. No. G 2783-2

PARTS PER MILLION (MILLIGRAMS PER LITER)

Na + K	Ca	Mg	Fe	SO ₄	Cl	CO ₃	HCO ₃	OH	H ₂ S
1,471	367	102		685	2,400		535		Present

MILLIGRAM EQUIVALENTS

64.01	18.31	8.38		14.25	67.68		8.77		
-------	-------	------	--	-------	-------	--	------	--	--

MILLIGRAM EQUIVALENTS IN PERCENT

35.29	10.09	4.62		7.86	37.31		4.83		
-------	-------	------	--	------	-------	--	------	--	--



Total Solids in Parts per Million

By evaporation 5,290
 After ignition 4,500
 Calculated 5,288
 Specific Gravity 1.007
 Observed pH 7.8
 Resistivity 1.042 ohm meters @ 68° F.

Properties of Reaction in Percent

Primary salinity 70.58
 Secondary salinity 19.76
 Primary alkalinity 7.76
 Secondary alkalinity 9.66
 Chloride salinity 82.60
 Sulfate salinity 17.40

Remarks and conclusions

LOGARITHMIC PATTERN
MEQ per unit

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

Edmonton - Fort St. John - Calgary

WATER ANALYSIS REPORT

Field Well No. Rond Lake #1

Operator Western Decalta Petroleum Limited Date Received March 21, 1960

Formation Depths Depth of 1046'.

Other pertinent data Boiled by drill pipe, oil scum on top. Boiling trip No. 4, 3 singles from base.

Date April 6, 1960 Lab. No. C 2783-3

PARTS PER MILLION (MILLIGRAMS PER LITER)

Na & K	Ca	Mg	Fe	SO ₄	Cl	CO ₂	HCO ₃	OH	H ₂ S
1,084	4,530	---		91	9,500	72		17	

MILLIGRAM EQUIVALENTS

47.14	226.05			1.89	267.90	2.40		1.00	
-------	--------	--	--	------	--------	------	--	------	--

MILLIGRAM EQUIVALENTS IN PERCENT

8.63	41.37			0.35	49.03	0.44		0.18	
------	-------	--	--	------	-------	------	--	------	--

Total Solids in Parts per Million

By evaporation	19.160
After ignition	13.880
Calculated	15.294
Specific Gravity	1.013
Observed pH	11.2
Resistivity ⁰ .452	ohm meters @ 68° F.

Properties of Reaction in Percent

Primary salinity	17.26
Secondary salinity	81.50
Primary alkalinity	---
Secondary alkalinity	1.24
Chloride salinity	99.29
Sulfate salinity	0.71

Remarks and conclusions

Milligram equivalents multiplied by 10 on the graph.

LOGARITHMIC PATTERN

MEQ per unit

