

GPD NOEL MILLS LAKE
L-41

Drilling Authority No. 305
Date Issued 19-2-68

WELL NAME GPD MOEL MILLS LAKE L-41

FIELD

Area:

LOCATION: Unit L Section 41 Grid 61-50-11 7-00

Latitude 61-40-38.94 Longitude 117-08-58.78 57.77

From Established Reference Marker

UWLR ⁴⁸61.677 ⁵³117.149
UWI 300L16150117000

Rig Release Date: 26/2/68

Status D+R

Information Release Date

CHANGE OF NAME:

DATE RECEIVED	INDEX
19-2-68	Application for a Drilling Authority.
<u>May 14/68</u>	Well Completion Data.
	Well History Report.
<u>May 16/68</u>	Application to Amend a Drilling Authority.
	Application to change a Well Name.
<u>May 17/68</u>	Application to Abandon a Well or Suspend Drilling.
	Application to Alter Condition of a Well.
	Well History Supplement.
	Well Completion Data.
	Work-over Report No.
	Application to Commingle Production before Measurement.
	Data for Back Pressure Test on Natural Gas Wells — Monograph 7 Method.
	Data for Back Pressure Test on Natural Gas Wells — Vitter's Method.
	M.P.R. — Oil — Calculations.
	New Oil Well Report.
	New Gas Well Report.
	Well Inspection Report.
	Rig Inspection Report.
	Battery Inspection Report.
	Equipment Report.
	Well Card.
	New Service Well Report.
	Monthly Water Flood Operations Report
	Monthly Water Receipts and Disposal of Fluids Report
	Logs. Large scale Small scale



File No. 305
Drilling Authority No.

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

Application to Abandon a Well or Suspend Drilling

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to abandon, to suspend drilling—

Name and number of well GFD HOKI, Hills Lake L-41
Location: Unit L Section 41 Grid 61° 30' 117° 00'
Latitude 61° 40' 38.94" Longitude 117° 00' 30.50"
From Established Reference Marker 837' North and 1136 East of SW corner Unit L Sec. 4
Universal Well Location Reference Lat. 61.67788° N, Long 117.14903° W
Permit No. 4497 Lease No.

Northern Oil Explorers Ltd.
(Operator, Licensee, Lessee)

Date of commencement of proposed program February 24, 1968

OIL, GAS, AND WATER ENCOUNTERED
(Depths)

Oil at
Gas at
Water at
Total Depth 1081 Date of last operations February 24, 1968
Present condition of well

CASING RECORD

Casing Size O.D. Inches	Weight	Amount	Set At—	Sacks of Cement and Additives	Amount Palled
1. 7"	200	328.36	324.36	125 sacks + 2% CaCl ₂	
2.					
3.					
4.					
5.					

PROPOSED ABANDONMENT PROGRAM

Plug		Geological Formation	Number of Sacks of Cement	Remarks
No.	Position			
Plug 1	Bottom	Chinichaga	10	
Plug 2	375' - 275'	Hay River Shale	30 sks.	
Plug 3	3' below level	Surface	5 sks.	

The following logs have been run Induction Electrical, Borehole Compensated Sonic Log, Formation Density Log
Other operations proposed Nil

Operations to be carried out by Great Plains Contractor Licence No. A11155
Address 736 - 8th Avenue S.W., Calgary, Alta. Address 6810 - 103rd St., Edmonton, Alta.
Responsible Agent in field G. M. Benter
Dated at Calgary 27 Day of February 68
Signed by S. M. Lehto Company Great Plains Development Company of Canada
Title Drilling Superintendent Operator's Exploratory Licence No. 1049

Note:—The Oil Conservation Engineer's office must be notified before work is commenced.

(For RESOURCE MANAGEMENT DIVISION use only)

APPROVAL

This application has been examined and proposed programme approved, subject to the following conditions:

Confirming oral approval given by Mr. B.H.J. Thoms
on the 25th of February 1968.

Dated 17th May 19 68

B.H.J. Thoms
Oil Conservation Engineer

Forms to be submitted in triplicate to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.

File No.

Drilling Authority No. **305**

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

Application to Amend a Drilling Authority

This application, in triplicate, must be submitted and approved before commencing operations. If the well location is changed, this application must be accompanied where required, with a plan of survey approved by the Surveyor General.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made to amend Drilling Authority No. **305** , concerning

GPD WOEL MILLS LAKE LA1

(Name and Number of Well)

The following amendments are required:

CHANGE OF LOCATION

FROM — Lat. **61° 40' 38.44" N.**

Long. **117° 08' 58.78" W.**

TO — Lat. **61° 40' 38.94" N.**

Long. **117° 08' 59.77" W.**

Reasons for the amendments:

Survey dated the **5th** of **February** **1968** by **Midwest Surveys Co. Ltd.**

Dated at **Calgary** , this **fourteenth** day of **May** , 19 **68**

Signed by

Title **Production Superintendent**

Great Plains Development Company

Company **of Canada, Ltd.**

(For Resource Management Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:

UNIVERSAL WELL LOCATION REFERENCE: Lat. 61.67748° N.

Long. 117.14993° W.


Date **16th May** , 19 **68**

Oil Conservation Engineer

Forms to be submitted to the Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.

FINAL PLAN GPD NOEL MILLS LAKE L4/ 61-50, 117-00

Latitude $61^{\circ}40'38.94''$ Longitude $117^{\circ}08'59.77''$
NORTHWEST TERRITORIES



Scale 1000 feet

CO-ORDINATE TABLE				
UTM Values		Scale Factor 39999		Ref Mer 117°00'
Station	Bearing	Distance	North	East
D24	N 53°39'20" W	1634.0	22,441,274.9	-24,043.4
D24a	S 36°20'40" W	1008.8	22,442,243.3	-25,359.5
D24b	S 36°20'40" W	153.9	22,441,430.7	-25,957.4
Well LOC			22,441,309.9	-26,046.3

Surveyed February 8, 1968
Certified Correct

[Signature]
Alberta Land Surveyor

NOTE:

1. Distances are in feet and decimal and are check chained.
2. Survey Traverse originated from baseline at Fort Providence.

ELEVATION: 701 Ground

DATUM: BM# 66-J-113
Elev. = 684.400

**GREAT PLAINS DEVELOPMENT
COMPANY OF CANADA, LTD.**

[Signature]
D.L. Guiguerick P.Eng.

Prepared by:
MIDWEST SURVEYS CO. LTD.



C34-68

Drilling Authority No. 305

Project No.

File No.



UNIQUE WELL IDENTIFIER - 300L41615011

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

Application for a Drilling Authority

This notice of intention to begin drilling operations, in triplicate, and where required a plan of survey approved by the Surveyor General showing the target area or the site of the well must be submitted and approved before commencing operations.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to drill:—

Name and number of well CPD NOEL MILLS LAKE L-41

Location: Unit L Section 41 Grid 61° 50' : 117° 00'

Latitude 61° 40' 38.44" Longitude 117° 08' 58.78"

From Established Reference Marker 857' North and 1,156 East of S.W. corner Unit L, Sec. 4

Universal Well Location Reference Lat. 61.67734° N., Long. 117.14966° W.

Elevation: Ground 702 K.B. 711 feet above sea-level.

Well is expected to produce from Lonely Bay Formation formation at a depth of about 840 feet. Expected total final depth 1,450

Area assigned to well (for Oil Conservation Engineer's use only)

Permit No. 4497 Lease No. Acreage 60,622

Permittee, licensee, or lessee Northern Oil Explorers Ltd.

Exploratory Licence No. 1088

Surface owned by Crown or Crown

Petroleum and natural-gas rights owned by Northern Oil Explorers Ltd. (If allocated submit name and address of owner and occupant.)

We propose to use the following strings of casing, either cementing or landing them as indicated below:—

Casing Size O.D. (Inches)	Weight (Lb./Ft.)	Grade	New or Used	Estimated Depth	Sacks of Cement
1. 7"	20#	J-55	new	150	60 sacks
2.					
3.					
4.					
5.					

Expected water, gas, and oil horizons and type of control equipment Surface casing will control water or gas in the glacial drift; hydrostatic pressure of the mud column and 6" x 900 series B.O.P.'s to control all formations below surface casing.

Well will be drilled with Rotary Rig No. 1 by Baldwin & Knoll Ltd. (Drilling Contractor or company)

Edmonton, Alberta.

Responsible agent of applicant:— Contractor's Business Licence No. A 11155

At well G. M. Hunter At registered office 6820 - 103rd Street

Address 736 - 8th Ave. S.W., Calgary Address Edmonton, Alberta.

It is understood that if changes become necessary, notice of the change of plan will be submitted.

Dated at Calgary this 16th day of February 19 68.

Signed by M. M. Lehto Company Great Plains Development Company of Canada Ltd.

Title Drilling Superintendent Operator's Licence No. 1098

(For Resource Management Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:—

The Company will submit to this office, on Tuesday of each week, the latest reports received by radio on the progress of the well.

Dated 16th February 19 68

Oil Conservation Engineer

Forms to be submitted to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.



PRELIMINARY PLAN

GPD NOEL MILLS LAKE L-41

Unit L Section 41 Grid Area 61°50'; 117°00'

Latitude 61°40'38.44" Longitude 117°08'58.78"

NORTH WEST TERRITORIES



I certify that this plan is correct to the best of my knowledge and was completed on the 15th day of February, 1968.

Wm Dabbs
Dominion and Alberta Land Surveyor

J. B. Ray
Witness
MIDWEST SURVEYS CO. LTD.

ELEVATION: 702 Ground

CO-ORDS: Well is located 857 N. } of SW cor. Unit L, Sec 41
1156 E. }

GREAT PLAINS DEVELOPMENT
COMPANY OF CANADA, LTD.

M. M. Lento
G. W. Hunter. P. Geo

Scale: 1000' = 1"

Triangulation Station:


Well Location:

Survey Monuments found shown thus:

" " planted " " :

Portions referred to outlined:

Distances are in feet and decimals.



C-34A-68

DRILLING & ABANDONMENT REPORT

OF

GPD NOEL MILLS LAKE L-41

IN

UNIT L SECTION 41 GRID $61^{\circ} 50' 117^{\circ} 00'$

LATITUDE $61^{\circ} 40' 38.74''$

LONGITUDE $117^{\circ} 08' 59.77'$

DRILLING AND ABANDONMENT REPORT


OF

CPD NOEL MILLS LAKE L-41

IN

UNIT L SECTION 41 GRID 61° 50' 117° 00'

LATITUDE 61° 40' 38.94" LONGITUDE 117° 08' 59.77"



Compiled By: George Betts
February, 1968

Signed By:

mm Betts

Date:

May 31, 1968

SECTION I - SUMMARY OF WELL DATA

(a) Well Name and Number

GPD NOEL Mills Lake L-41
Unit L Section 41 Grid 61° 50' 117° 00'

(b) Permittee, Licencee or Lessee

Northern Oil Explorers Ltd.

(c) Name of Operator

Great Plains Development Company of Canada, Ltd.,
736 Eighth Avenue S.W., Calgary 2, Alberta.

(d) Location

Unit L Section 41 Grid 61° 50' 117° 00'
Latitude 61° 40' 38.94" Longitude 117° 08' 59.77"

(e) Co-ordinates

Datum: B.M. #66-T-113
Universal Well Location Reference - Lat. 61.67748° N., Long. 117.14993° W.
Unique Well Identifier - 300L416150117000

(f) Permit

4497

(g) Drilling Contractor

Baldwin and Knoll Ltd., Rig #1

(h) Drilling Authority

February 16, 1968, No. 305

(i) Classification

Wildcat well

(j) Elevations

Ground 701' K.B. 710'

(k) Spudded

February 18, 1968

(l) Completed Drilling

February 24, 1968

(m) Total Depth

1081'

(n) Well Status

Dry hole

(o) Rig Released

February 26, 1968

(p) Hole Size

Surface hole	9 7/8"	-	0' - 347'
Main hole	6 1/4"	-	347' - TD

(q) Casing - Surface

Ran and cemented 328.36' of 7", 20#, J-55 new casing to 324.36'.
Cemented with 125 sacks of cement plus 2% CaCl₂. Plug down at
9:00 P.M. with 500 psi.

GEOLOGY

SECTION II - GEOLOGICAL SUMMARY

(a)	<u>Formation Tops</u>	<u>K.B. Depth</u>	<u>Subsea Elevation</u>
	Hay River	Surface	+ 711'
	Lonely Bay	- 131'	842'
	Chinchaga	- 299'	1010'
(b)	<u>Cored Intervals</u>		
	No cores were cut.		
(c)	<u>Core Descriptions</u>		
	No core descriptions.		
(d)	<u>Sample Description</u>		
	0- 30	<u>Pea gravel</u> , quartz and igneous pebbles and grains with boulders.	
		Quartz - rose & clear, quartzite, etc. well rounded.	
	30- 60	Missing.	
	60- 110	<u>Pea gravel</u> , as above.	
	110- 130	<u>Pea gravel & boulders</u> .	
	130- 200	<u>Shale</u> , light grey to medium, micromicaceous, fairly soft.	
	200- 229	<u>Shale</u> , compact, as above, calcareous. Caving noticeably.	
	229- 245	<u>Limestone</u> , light grey, slightly argillaceous, brittle, angular, non-porous.	
	245- 280	<u>Shale</u> , as above, trace Limestone anhydritic, drilling break, slightly calcareous, micromicaceous.	
	280- 320	<u>Shale</u> , as above.	
	320- 342	<u>Shale</u> , medium grey as above with light green shale.	
	342- 347	Lost circulation, light grey mud developed.	
	347- 400	<u>Shale</u> , as above, grey, micromicaceous, calcareous.	
	400- 450	<u>Shale</u> , as above with traces calcareous argillite.	
	450- 600	<u>Shale</u> , as above, with scattered interbeds calcareous argillite, or argillaceous Limestone.	
	600- 630	<u>Shale</u> , as above, trace limey shale, anhydritic.	
	630- 680	<u>Shale</u> , as above, trace limey shale, anhydritic.	
	680- 730	<u>Shale</u> , dark grey, brittle, micromicaceous, slightly calcareous, slightly bitumen cut.	
	730- 740	<u>Limestone</u> , argillaceous, grey, brittle, trace fossils, slightly bituminous.	
	740- 830	<u>Limestone</u> , argillaceous, medium grey and darker grey, trace pyrite.	
	830- 850	<u>Shale</u> , calcareous, black, fetid odor, fossils.	
	850- 860	<u>Limestone</u> , brown, fine crystalline, argillaceous & buff limestone, trace fossils, tight, fair cut for petrol. Non-porous, fossil pelecypods, etc.	
	860- 870	<u>Limestone</u> , as above, non fossil.	
	870- 880	<u>Limestone</u> , as above, non fossil., non-porous, trace bitumen.	
	880- 900	<u>Limestone</u> , as above, dark brown limestone & buff limestone, non-porous, trace bitumen.	
	900- 940	<u>Limestone</u> , as above.	

(d) Sample Description (Continued)

940- 950	<u>Limestone</u> as above with numerous thin wafers as stylolite infilling?
950- 985	<u>Limestone</u> , as above.
985-1000	<u>Dolomite</u> , light grey-buff, fine crystalline, non-porous.
1000-1010	<u>Dolomite</u> , as above with anhydrite.
1010-1020	<u>Dolomite</u> , buff, trace staining, tight.
1020-1050	<u>Dolomite</u> , buff & brown, tight, trace Anhydrite.
1050-1060	<u>Dolomite</u> , buff & brown, tight. Minor Anhydrite.
1060-1070	<u>Dolomite</u> , as above with Anhydrite more abundant.
1070-1082	<u>Dolomite</u> , as above with Anhydrite more abundant, 10%+.

(e) Deviation Record

120'	-	1/2°
347'	-	1/2°
768'	-	0°
811'	-	3/4°

(f) Abandonment Report

February 26 - Plug #1 - 10 sacks of cement at 1081'. No feel.
Plug #2 - 375'-275'. Cemented with 30 sacks + 2% CaCl₂. Felt at 275'.
Plug #3 - 0' - 3' surface plug, cemented with 5 sacks of cement.

(g) Lost Circulation Zones

342'-347' - Shale formation. Lost circulation due to up hole mud rings.
Corrective measures taken: Pulled out of hole and cleaned to bottom.

Plate welded on top, identification marker installed

CASING and TUBULAR REPORT

CASING INFORMATION

Surface Casing
Intermediate Casing O.D. 7"
Production Casing
Liner

Unit L Section 41 Grid
Well GPD NOEL Mills Lake Location 61° 50' 117° 00' Date February 20, 1968
L-41

Joint on Location	Feet on Location	Casing Weight	Grade	Range	Thread	Threads & Couplings	Male	Joints Run	Depth Landed	Feet Run in Well
16	659.64	20	J-55	3	8Rd			8	324.36	328.36

Shoe: Make Davis Type Guide Length 1.10

Collars: Make Davis Type Float Length 1.40

Landing Joint (when used) Length -----

Overall Length of Casing String ----- 330.86

Feet up from K.B. (Subtract) ----- 6.50

Setting Depth: 324.36 By Driller By Tally 324.36

Shoe Joint: 40.77 Overall (Subtract) 40.77

Float Collar Landed: 283.59 By Driller By Tally 283.59

CENTRALIZERS:

Make B & WNumber 2Positions Middle of Jts. #1 and #3No. of Joints Welded 2 jts. welded.Remarks Surface casing went in easy.

SCRATCHERS:

Make B & W

Number -----

Positions Five feet from the end of Jts. #1 & #3

Operator's Representative -----

RUNNING AND CEMENTING

Surface Casing
Intermediate Casing O.D. 7"
Production Casing
Liner

GENERAL

GPD NOEL Mills Lake Unit L Section 41 Grid
Well L-41 Location 61° 50' 117° 00' Date February 20, 1968
K.B. Elevation 710 K.B. Csg. Range 8.50 Total Depth (Driller) 1081

Hole Size	<u>9 7/8</u>			Casing in Hole	<u>328.36</u>		
Depth	<u>347</u>			Depth Set	<u>324.36</u>		

Mud: Type Gel Wt. 9.0 Visc. 50 W.L. 10

B.O.P.'s _____

RUNNING

Power Tongs _____ Torque: Max. _____ Nom. _____ Min. _____

Time Pipe Started 4:30 P.M. Time on Bottom 6:30 P.M. Time Circ. 1 hour - 6:30-7:30

Fill-up Points _____ Btm. by Casing 324.36' Ft. up from K.B. 6.50'

Remarks _____

CEMENTING

Cement Co. Contractor Operator Baldwin & Knoll Time on Location _____

Types & Quantities of Cement 125 sacks of cement + 2% CaCl₂

Water ahead 1 Bbls. Mix Times: Start 8:00 P.M. Finish 9:00 P.M. Slurry Wt. 15.5

Calc. Disp. _____ Bbls. Est. Disp. time 15 Mins. Start 8:45 Finish 9:00

Max. Pumping Press. 50# Bump. Press. 500 Bumped by Contractor No. times bump. 1

Cement Returns: Yes/No Remarks _____

LANDING

Time Landed 9:00 A.M. Date February 20 Init. Wt. of Cem. String (Less Blks.) _____

Wt. Landed in Slips _____ Make of Bowl _____ Nom. Size _____ Series _____

Slip and Seal Assembly _____ Remarks _____

Operator's Representative _____

BIT

P-5

W-# CPD NOEL Mills Lake L-41

~~Field~~ Mills Lake N.W.T.

[illegible]

DAILY MUD RECORD

DRILLING MUD RECORD

REUD COMPANY Macobar SERVICE ENGINEER Ted Williams

A Gel D Sawdust G Cal. Chloride J Bicarb.

B Caustic E Quickthick H Plaster

C Peltex F Cement I C.M.C.

DAILY DRILLING RECORD

P-1

P-1

P-1

Page 2

[illegible]

Page 2

[illegible]

MISCELLANEOUS

GREAT PLAINS DEVELOPMENT COMPANY OF CANADA, LTD.
736 - 8th Avenue S. W., Calgary, Alberta - Phone 264-0660

DRILLING AND GEOLOGICAL PROGRAM
PART "A"
INSTRUCTIONS TO THE CONTRACTOR

GPD NOEL MILLS LAKE L-41 Lat. $61^{\circ} 40' 38.44''$, Long. $117^{\circ} 08' 58.78''$ W.

Location: Lsd. _____, Sec. _____, Twp. _____, Rge. _____, W. _____ M.

Elevations: Ground - 702 Surv.
K.B. - 710 Est.

- Surface Hole:
- (a) Drill 9-7/8 " surface hole to 200 ' minimum.
 - (b) Take Totco readings at 100' intervals to 200 ' (Maximum deviations 1').
 - (c) Round trip prior to running casing to ensure the hole is clean.
 - (d) Double tally drill pipe on last trip prior to running casing.
 - (e) Measure and record distance from K.B. to Ground and K.B. to casing bowl flange and report with surface casing details.

Surface Casing: To be conducted by Contractor.

- (a) Run and cement 7 ", 20 #, J-55, casing at 200 + ' minimum, using 125 sacks cement plus 2% CaCl_2 . Casing string to be as follows: guide shoe, one joint of casing, float collar and balance of casing to 200 '. One centralizer to be placed in the middle of joints # 1, # _____ and # 3 and a scratcher five feet from each end of the same joints. Weld guide shoe, float collar and two joints of casing. Cement returns to surface must be obtained. Casing must be set so that the casing bowl flange is at ground level or above.
- (b) Land casing after 12 hours, make up bowl and blowout preventors.

Samples: Conservation Board - 10' samples Surface - T.D.
Great Plains - 10' samples _____

<u>Mud Control:</u>	<u>Depth</u>	<u>Viscosity (Sec./Qt.)</u>	<u>Water Loss (cc/30 min.)</u>	<u>Remarks</u>
	Surface Hole			
	0 - 200	Sufficient to clean hole.		Spud in mud. After drilling out guide shoe and jetting cement-cut mud, and S.A.P.P. or Bicarbonate of Soda to treat out residual cement.
				Water
	<u>200 - 1445'</u>	<u>45 - 60</u>	<u>8 - 10</u>	<u>dispersed gyp mud.</u>

Treat mud for salt stringers at 1050'

General Mud Requirements:

- (a) Weight approximately 9.5 /U.S. gallon.
- (b) A complete record of all mud and additives used must be correctly logged in the daily reports by "the contractor."
- (c) Check all mud properties at least twice per tour and note results in tour report.
- (d) Lost circulation - circulation losses may occur during the surface hole and _____

Main Hole Drilling:

- (a) Drill ahead with 6-1/4" bit and follow sample collection.
- (b) Tallies - Drillpipe is to be tallied out every 1000' and prior to:
 - (1) Coring
 - (2) Drillstem testing
 - (3) Logging
 - (4) Running casing

If pipe measurement varies more than three feet from the recorded tally, it must be remeasured and the tally adjusted if necessary. A record of adjustment is to be made in the daily report.

- (c) Hole conditions - Great Plains' Drilling Department is to be notified immediately if poor hole conditions develop, if drillpipe is stuck, or if a fishing job develops.

Abnormal Formation Pressures:

DRILLING AND GEOLOGICAL PROGRAM
PART "B"
INSTRUCTIONS TO GREAT PLAINS PERSONNEL

Samples: Make 1 cuts of samples at wellsite.

Zones of Interest	Approximate Depth	Evaluation Procedure
Lonely Bay	850	Core entire section. Test if warranted.
Chinchaga Dolomite	1000 - 1400	Test if warranted.

Coring

Notes:

- (a) Jars are to be run during coring operations.
- (b) At least two stands of collars are to be left off the coring string.

Drillstem

Tests:

To be conducted in the following manner:

- I.S.I. 60 mins.
- V.O. As required
- F.S.I. 60 minute minimum, or equal to V.O. time.

NOTE:

- (a) Jars, safety joint and pump out sub are to be run on all tests.
- (b) No more than one-half the number of collars in the drilling string are to be run, with a maximum of three stands of collars.
- (c) Gas samples are to be analysed for helium as well as subjected to the conventional analyses. One gas sample per test is to be collected. At least one quart of water should be collected for routine water analysis, and a full sample can of water from each test should be put in small cans supplied and brought to the Production Department of Great Plains Development Company of Canada, Ltd., 6th Floor, Fina Building, 736 - 8th Avenue S.W., Calgary, Alberta.
Attention of: Mr. George Betts

Logging: See attached or below.

Log Type Schlumberger	Scale	Interval
Induction Electric Log	2" - 100'	T.D. - Base surface casing
	5" - 100'	
BHC Sonic GR w/ Caliper	2" - 100'	" " " "
	5" - 100'	" " " "
Formation Density Log	2" - 100'	" " " "
	5" - 100'	" " " "

Production Casing: To be determined.

Cementing Operations: To be determined. State clearly in drilling reports cement mixed and Admix dry volumes and calculate slurry volumes pumped.

Service Companies:	Cementing	Contractor
	Testing	Johnston Testers Ltd.
	Diamond Coring	Johnston Testers Ltd.
	Mud	Magcobar Mud of Canada Ltd.
	Logging	Schlumberger, Canada Ltd.

Sample Lag Time: Samples are to be lagged as directed.

Telephone Numbers:

Office	-	264-0660
G. M. Hunter	-	255-7312
N. M. Lehto	-	289-2029 - 289-4350
L. L. Samoil	-	289-3980
D. L. Gingerick	-	249-4700

Data Requirements:

Company	Samples	Logs		Analyses		DST Charts	Completion Report
		Field	Final	Core	Fluid		
Great Plains	Glass Vials	2	3	2	2	4	2
Conservation Board	N Yes	-	3	2	1	1	-
TOTAL		2	6	4	3	5	2

REVISED GEOLOGICAL PROGNOSIS FOR GPD NOEL MILLS LAKE L-41

Latitude 61° 40' 38.44" N.

Longitude 117° 08' 58.78" N.

Ground Elevation 702' Surveyed

KB Elevation 710' Estimated

<u>Formation Top or Marker</u>	<u>Subsea Elevation</u>	<u>Depth</u>	<u>Interval</u>
Spud In Hay River	+710	Surface	842
Lonely Bay (Limestone)	-140	850	165
Chinchaga	-305	1015	340
Mirage Point	-645	1345	90
Precambrian	-735	1445	

DATE Jul-25-198

[illegible]

DAILY DRILLING REPORT

REPORT NO. 9

DATE FEB 24 1968

OPERATOR G.P.D.	LOCATION 41-8-17-9	SEC 25	TWP. 9	RGE. W	WELL NAME NOEL MILLS LAKE	No. L-41	PROVINCE N.W.T.
CONTRACTOR BALDWIN & KNOLL LIMITED	RIG NO. 1	DRILL PIPE NO. SIZE 2 1/2	TOOL JOINT TYPE THD. 2 1/2	OD 2 1/2	PUMPS NO. MANUFACTURER TYPE STROKE LENGTH 1. GARDNER DENVER F X E 10"	CASING & LINER RECORD	SIZE WT. & GR. DEPTH SET FROM TO PERFORATIONS FROM TO CEMENT USED OTHER
OPERATOR'S REPRESENTATIVE		CONTRACTOR'S TOOL PUSHER					

TIME DISTRIBUTION—HOURS

	MORN	DAY	EVE
DRILLING ACTUAL	6 1/2	6	
REAMING			
CIRCULATING			
TRIPS	1 1/2	1	
DEVIATION SURVEY			
TEST S.O.P			
CUT OFF DRILL LINE			
REPAIR RIG	1/4	1/4	1/4
CORING			
WIRE LINE LOGGING			
OTHER WORK	1/4	3	

FISHING

COMPLETING (A) PERFORATING

(B) RUNNING TUBING

(C) SWABBING

(D) TESTING

(E) ACIDIZING

(F) ADDITIONAL

TOTALS

TIME SUMMARY (OFFICE USE ONLY)

CONTRACTOR'S TIME HRS:

OPERATOR'S TIME:

MRS. W/D.P:

MRS. WO/D.P:

MRS. STANDBY

WIRE LINE RECORD

REEL NO

NO OF LINES SIZE

FEET SLIPPED

FEET CUT OFF

PRESENT LENGTH

TON MI. OF TRIPS SINCE LAST CUT

CUMULATIVE TON MI. OF TRIPS

NO. OF DAYS FROM SPUD

CUMULATIVE ROTATING HRS.

NO.	DRILLING ASSEMBLY	BIT RECORD	HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN	MUD RECORD			
											LINER SIZE	S.P.M.	LINER SIZE	S.P.M.		TIME	WEIGHT	VISC.	W.L.C.C.
21	SNGLS. DP	633.18	SIZE	6 1/4	6 1/4	6 1/4	968	1020	Dolomite.	180	15	200	5	74		3 30	9.3	41	9.1
13	D.C. ID	381.74	MFG.	SEC REED															
	OD	381.74	TYPE	3-4 YMP															
	RMR BODY OD		FT.	NO.	3														
	STB BODY OD		FT.	NOZ.	SIZE	9 1/6													
1	SUBS OD	1.72	SER. NO	41130	AL258		12 10 - 12 30												
	BIT OR C.B.		FT.	DEPTH OUT	970		12 30 - 12 45												
			FT.	CUMULATIVE HOURS RUN	16 1/2	6 1/4	12 15 - 2 15												
	KELLY DOWN	9.41	FT.	COND. OF BIT	DULL	IN	2 15 - 4 00												
	TOTAL	1026.08	FT.	REAMER CUTTER NO.															
	WT. OF STRING		LBS.	TYPE															
	DRILLER	C. H. Hansen																	

NO.	DRILLING ASSEMBLY	BIT RECORD	HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN	MUD RECORD			
											LINER SIZE	S.P.M.	LINER SIZE	S.P.M.		TIME	WEIGHT	VISC.	W.L.C.C.
2	SNGLS. DP	663.18	SIZE	6 1/4	6 1/4	6 1/4	1082	1082	Dolomite.	180	15	200	5	74	5	20	9.4	35	9.1
13	D.C. ID	381.74	MFG.	REED															
	OD	381.74	TYPE	YMP															
	RMR BODY OD		FT.	NO.	4 1/2														
	STB BODY OD		FT.	NOZ.	SIZE	9 1/6													
	SUBS OD	1.72	SER. NO	E AL258			8 00 - 8 30												
	BIT OR C.B.		FT.	DEPTH OUT	1082		8 30 - 8 45												
			FT.	CUMULATIVE HOURS RUN	12 3/4		8 45 - 2 45												
	KELLY DOWN	34.93	FT.	COND. OF BIT	WV		2 45 - 4 00												
	TOTAL	3082	FT.	REAMER CUTTER NO.															
	WT. OF STRING	2609	LBS.	TYPE															
	DRILLER	WELDER NICH																	
		TRUCKING																	
		CAMP																	

NO.	DRILLING ASSEMBLY	BIT RECORD	HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN	MUD RECORD			
											LINER SIZE	S.P.M.	LINER SIZE	S.P.M.		TIME	WEIGHT	VISC.	W.L.C.C.
22	SNGLS. DP	663.61	SIZE	6 1/4	6 1/4	6 1/4										4 00	9.6	35	9.6
13	D.C. ID	381.74	MFG.	YMP															
	OD	381.74	TYPE																
	RMR BODY OD		FT.	NO.	9 1/6														
	STB BODY OD		FT.	NOZ.	SIZE	9 1/6													
1	SUBS OD	1.72	SER. NO	EAL258			4 00 - 4 15												
	BIT OR C.B.		FT.	DEPTH OUT	1082		4 15 - 5 15												
			FT.	CUMULATIVE HOURS RUN	12 3/4		5 15 - 8 30												
	KELLY DOWN	34.93	FT.	COND. OF BIT	Good		8 30 - 9 00												
	TOTAL	1082	FT.	REAMER CUTTER NO.			9 00 - 12 00												
	WT. OF STRING	2609	LBS.	TYPE															
	DRILLER	J. H. Hansen																	

DATE FEB 23 1968

[illegible]

6-4

OPERATOR		G.P.D.		LOCATION		41° 8' 1170		RGE		9' 25" W		WELL NAME		NOEL MILLS LAKE.		No.		L-41		PROVINCE		N.W.T																			
CONTRACTOR		BALDWIN & KNOLL LIMITED		RIG NO.		1		DRILL PIPE STRING NO. SIZE		3 1/2		TOOL JOINT		TYPE THD.		OD		PUMPS		CASING & LINER RECORD		SIZE		WT. & GR.		DEPTH SET		PERFORATIONS		CEMENT USED		OTHER									
OPERATOR'S REPRESENTATIVE				CONTRACTOR'S TOOL PUSHER		D. J. Gendall		NO.		1		MANUFACTURER		GARDNER DENVER		TYPE		FYE		STROKE LENGTH		10'																			
TIME DISTRIBUTION—HOURS		MORN		DAY		EVE		NO.		DRILLING ASSEMBLY		BIT RECORD		HRS. DRLD.		CORE NO.		FROM		TO		FORMATION (SHOW CORE RECOVERY)		ROTA- RY R.P.M.		WT. ON BIT 1000#		PUMP PRESS.		PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN		MUD RECORD					
DRILLING ACTUAL		6		13				3		SNGLS. DP		90.83		SIZE		6 1/4		347		510				700		1500		100		5		74		TIME		5:00		6:00		8:00	
REAMING								13		D.C. 2" ID		381.74		MFG.		SEC																		WEIGHT		9.0		9.0		9.2	
CIRCULATING								13		D.C. 4 3/4 OD		381.74		TYPE		S-3																		VISC		34		35		38	
TRIPS								1		RMR BODY OD		FT.		NOZ.		NO.																		W.L.C.C.		10.5		10.4		10.4	
DEVIATION SURVEY								1		SUBS OD		1.72		SER. NO.		90734																		FLTR. CK.		2/32		2/32		2/32	
TEST B.O.P								1		BIT OR C.B.		FT.		DEPTH OUT																				PH		11.0		11.0		11.0	
CUT OFF DRILL LINE								1		KELLY DOWN		35.80		COND. OF BIT																				SD. CONT.							
REPAIR RIG								1		TOTAL		510.04		REAMER CUTTER NO.																											
CORING								1		WT. OF STRING		LBS.		TYPE																											
WIRE LINE LOGGING								1		DRILLER		P. H. Hansen																													
OTHER								1		NO.		DRILLING ASSEMBLY		BIT RECORD		HRS. DRLD.		CORE NO.		FROM		TO		FORMATION (SHOW CORE RECOVERY)		ROTA- RY R.P.M.		WT. ON BIT 1000#		PUMP PRESS.		PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN		MUD RECORD			
FISHING								10		SNGLS. DP		320.14		SIZE		6 1/4		510		704						200		1500		200		5		74		TIME		11:00		245	
COMPLETING (A) PERFORATING								13		D.C. 2" ID		381.74		MFG.		SEC																		WEIGHT		9.3		9.6			
(B) RUNNING TUBING								13		D.C. 4 3/4 OD		381.74		TYPE		S-3																		VISC		42		49			
(C) SWABBING								1		RMR BODY OD		FT.		NOZ.		NO.																		W.L.C.C.		10.4					
(D) TESTING								1		SUBS OD		1.72		SER. NO.		90734																		FLTR. CK.		2/32		2/32			
(E) ACIDIZING								1		BIT OR C.B.		FT.		DEPTH OUT																				PH		11.0					
(F) ADDITIONAL								1		KELLY DOWN		20		COND. OF BIT		1 1/2																									

DATE FEB 20 1968

LEVENING TOUR

FEB 19 1968

OPERATOR G.P.D.										LOCATION LSD 61° SEC 41'8" TWP. 117° 9'25" W. NOEL DAKLS LAKE.										PROVINCE N.W.T.									
CONTRACTOR BALDWIN & KNOLL LIMITED										PUMPS										CASING & LINER RECORD									
OPERATOR'S REPRESENTATIVE										CONTRACTOR'S TOOL PUSHER										PERFORATIONS									
TIME DISTRIBUTION—HOURS										DRILLING ASSEMBLY										BIT RECORD									
MORNING TOUR										STANDS DP										RUN NO.									
DRILLING ACTUAL										SNGLS. DP										SIZE									
REAMING										D.C. ID										MFG.									
CIRCULATING										RMR BODY OD										NO.									
TRIPS										STB BODY OD										SIZE									
DEVIATION SURVEY										SUBS OD										SER. NO.									
TEST B.O.P										BIT OR C.B.										DEPTH OUT									
CUT OFF DRILL LINE										KELLY DOWN										COND. OF BIT									
REPAIR RIG										TOTAL										REAMER CUTTER NO.									
CORING										WT. OF STRING										LBS.									
WIRE LINE LOGGING										DRILLER										C.H. Hanson									
OTHER										NO. DRILLING ASSEMBLY										BIT RECORD									
FISHING										STANDS DP										RUN NO.									
COMPLETING (A) PERFORATING										SNGLS. DP										SIZE									
(B) RUNNING TUBING										D.C. ID										MFG.									
(C) SWABBING										RMR BODY OD										NO.									
(D) TESTING										STB BODY OD										SIZE									
(E) ACIDIZING										SUBS OD										SER. NO.									
(F) ADDITIONAL										BIT OR C.B.										DEPTH OUT									
TOTALS										KELLY DOWN										COND. OF BIT									
TIME SUMMARY (OFFICE USE ONLY)										TOTAL										REAMER CUTTER NO.									
CONTRACTOR'S TIME HRS.										WT. OF STRING										LBS.									
OPERATOR'S TIME:										DRILLER										C. Blanchette									
MRS. W/D.P.										NO. DRILLING ASSEMBLY										BIT RECORD									
MRS. WO/D.P.										STANDS DP										RUN NO.									
MRS. STANDBY										SNGLS. DP										SIZE									
WIRE LINE RECORD										D.C. ID										MFG.									
REEL NO										RMR BODY OD										NO.									
NO OF LINES										STB BODY OD										SIZE									
SIZE										SUBS OD										SER. NO.									
FEET SLIPPED										BIT OR C.B.										DEPTH OUT									
FEET CUT OFF										KELLY DOWN										COND. OF BIT									
PRESENT LENGTH										TOTAL										REAMER CUTTER NO.									
TON MI. OF TRIPS SINCE LAST CUT										WT. OF STRING										LBS.									
CUMULATIVE										DRILLER										C. Blanchette									
TON MI. OF TRIPS										NO. DRILLING ASSEMBLY										BIT RECORD									
NO. OF DAYS FROM SPUD										STANDS DP										RUN NO.									
CUMULATIVE ROTATING HRS.										SNGLS. DP										SIZE									
										D.C. ID										MFG.									
										RMR BODY OD										NO.									
										STB BODY OD										SIZE									
										SUBS OD										SER. NO.									
										BIT OR C.B.										DEPTH OUT									
										KELLY DOWN										COND. OF BIT									
										TOTAL										REAMER CUTTER NO.									
										WT. OF STRING										LBS.									
										DRILLER										C. Blanchette									

DATE FEB 15

[illegible][illegible][illegible]

WIRE LINE RECORD		LOG																		MUD RECORD						
REEL NO		NO.	DRILLING ASSEMBLY		BIT RECORD			HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1900#	PUMP PRESS	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN	MUD RECORD					
NO OF LINES	SIZE		STANDS	DP	FT.	RUN NO										LINER SIZE	S.P.M.	LINER SIZE	S.P.M.		TIME					
FEET SLIPPED			SNGLS.	DP	FT.	SIZE															WEIGHT					
FEET CUT OFF			ID			MFG.															VISC					
PRESENT LENGTH		2	D.C		59.70	FT.	TYPE														W.L.-C.C.					
TON MI. or TRIPS SINCE LAST CUT			RMR BODY	OD	FT.	NOZ.	NO.			DEPTH	DEV.	DIRECTION	DEPTH	DEV.	DIRECTION	DEPTH	DEV.	DIRECTION			FLTR CK.					
CUMULATIVE TON MI. or TRIPS			STR BODY	OD	FT.	SIZE			RECORD:												PH					
		2	SUBS	OD	283	FT.	SER NO			4 ⁰⁰	4 ¹⁵	REMARKS										SD. CONT				
NO. OF DAYS FROM PUD			BIT OR C.B.		FT.	DEPTH OUT				4 ¹⁵	11 ⁰⁰	DR20 978 HOLE														
CUMULATIVE ROTATING HRS.					FT.	CUMULATIVE HOURS RUN				11 ⁰⁰	11 ¹⁵	WORK ON PUMP														
			KELLY DOWN		35 80	FT.	COND. OF BL.			11 ¹⁵	12 ⁰⁰	DR20 978 HOLE														
			TOTAL		95 00	FT.	REAMER CUTTER NO.															MUD & CHEMICALS ADDED				
			WT OF STRING		LBS.	TYPE																TYPE	AMT.	TYPE	AMT.	
			DRILLER																							
			EVENING TOUR																							
			6 Blanchette																							

7.1.17.168

DATE 7-17-68

1. 2. 3.

[illegible]

DAILY DRILLING REPORT

REPORT NO. 1

DATE

Feb 16/68

OPERATOR <i>C.P.D.</i>	LOCATION 31 60 116° 39 30	SEC 60	TWP. 116°	RGE 39	W. 30	WELL NAME Mills Lake	No. 2 L-41	PROVINCE N.W.T.				
CONTRACTOR BALDWIN & KNOLL LIMITED	RIG NO. 1	DRILL PIPE STRING NO. SIZE	TOOL JOINT	OD	PUMPS	CASING & LINER RECORD	SIZE	WT. & GR.	DEPTH SET FROM TO	PERFORATIONS FROM TO	CEMENT USED	OTHER
OPERATOR'S REPRESENTATIVE	CONTRACTOR'S TOOL PUSHER <i>Samuel</i>											

TIME DISTRIBUTION—HOURS				NO. DRILLING ASSEMBLY		BIT RECORD		HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN	MUD RECORD			
DRILLING ACTUAL	MORN	DAY	EVE	STANDS DP	FT.	KUN NO.													TIME			
REAMING				SNGLS. DP	FT.	SIZE													WEIGHT			
CIRCULATING				D.C. ID		MFG.													VISC			
TRIPS				OD	FT.	TYPE													W.L.C.C.			
DEVIATION SURVEY				RMR BODY OD	FT.	NO. NO.													FLTR. CK.			
TEST B.O.P				STB BODY OD	FT.	NOZ. SIZE													PH			
CUT OFF DRILL LINE				SUBS OD	FT.	SER. NO.													SD. CONT.			
REPAIR RIG				BIT OR C.B.	FT.	DEPTH OUT																
CORING					FT.	CUMULATIVE HOURS RUN																
WIRE LINE LOGGING				KELLY DOWN	FT.	COND. OF BIT																
OTHER				TOTAL	FT.	REAMER CUTTER NO.																
FISHING				WT. OF STRING	LBS.	TYPE																
COMPLETING (A) PERFORATING				DRILLER																		
(B) RUNNING TUBING				<i>1200 - 800 - Move From Lease No 2 To new lease.</i> <i>(MOVING)</i>																		
(C) SWABBING																						
(D) TESTING																						
(E) ACIDIZING																						
(F) ADDITIONAL																						
TOTALS																						
TIME SUMMARY (OFFICE USE ONLY)																						
CONTRACTOR'S TIME HRS:																						
OPERATOR'S TIME:																						
HRS. W/D.P:																						
HRS WO/D.P:																						
HRS STANDBY																						
WIRE LINE RECORD																						

TIME DISTRIBUTION—HOURS				NO. DRILLING ASSEMBLY		BIT RECORD		HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN	MUD RECORD			
DRILLING ACTUAL	MORN	DAY	EVE	STANDS DP	FT.	RUN NO.													TIME			
REAMING				SNGLS. DP	FT.	SIZE													WEIGHT			
CIRCULATING				D.C. ID		MFG.													VISC			
TRIPS				OD	FT.	TYPE													W.L.C.C.			
DEVIATION SURVEY				RMR BODY OD	FT.	NO. NO.													FLTR. CK.			
TEST B.O.P				STB BODY OD	FT.	NOZ. SIZE													PH			
CUT OFF DRILL LINE				SUBS OD	FT.	SER. NO.													SD. CONT.			
REPAIR RIG				BIT OR C.B.	FT.	DEPTH OUT																
CORING					FT.	CUMULATIVE HOURS RUN																
WIRE LINE LOGGING				KELLY DOWN	FT.	COND. OF BIT																
OTHER				TOTAL	FT.	REAMER CUTTER NO.																
FISHING				WT. OF STRING	LBS.	TYPE																
COMPLETING (A) PERFORATING				DRILLER																		
(B) RUNNING TUBING				<i>800 - 400 MOVE FROM LEASE NO 2 TO NEW LEASE</i> <i>(MOVING)</i> <i>MOVED & RIGGED CAMP</i>																		
(C) SWABBING																						
(D) TESTING																						
(E) ACIDIZING																						
(F) ADDITIONAL																						
TOTALS																						
TIME SUMMARY (OFFICE USE ONLY)																						
CONTRACTOR'S TIME HRS:																						
OPERATOR'S TIME:																						
HRS. W/D.P:																						
HRS WO/D.P:																						
HRS STANDBY																						
WIRE LINE RECORD																						

TIME DISTRIBUTION—HOURS				NO. DRILLING ASSEMBLY		BIT RECORD		HRS. DRLD.	CORE NO.	FROM	TO	FORMATION (SHOW CORE RECOVERY)	ROTA- RY R.P.M.	WT. ON BIT 1000#	PUMP PRESS.	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN	MUD RECORD			
DRILLING ACTUAL	MORN	DAY	EVE	STANDS DP	FT.	RUN NO.													TIME			
REAMING				SNGLS. DP	FT.	SIZE													WEIGHT			
CIRCULATING				D.C. ID		MFG.													VISC			
TRIPS				OD	FT.	TYPE													W.L.C.C.			
DEVIATION SURVEY				RMR BODY OD	FT.	NO. NO.													FLTR. CK.			
TEST B.O.P				STB BODY OD	FT.	NOZ. SIZE													PH			
CUT OFF DRILL LINE				SUBS OD	FT.	SER. NO.													SD. CONT.			
REPAIR RIG				BIT OR C.B.	FT.	DEPTH OUT																
CORING					FT.	CUMULATIVE HOURS RUN																
WIRE LINE LOGGING				KELLY DOWN	FT.	COND. OF BIT																
OTHER				TOTAL	FT.	REAMER CUTTER NO.																
FISHING				WT. OF STRING	LBS.	TYPE																
COMPLETING (A) PERFORATING				DRILLER																		
(B) RUNNING TUBING				<i>400 1000 MOVING</i> <i>WATER MECH CAMP</i> <i>TRUCKING BAKER</i>																		
(C) SWABBING																						
(D) TESTING																						
(E) ACIDIZING																						
(F) ADDITIONAL																						
TOTALS																						
TIME SUMMARY (OFFICE USE ONLY)																						
CONTRACTOR'S TIME HRS:																						
OPERATOR'S TIME:																						
HRS. W/D.P:																						
HRS WO/D.P:																						
HRS STANDBY																						
WIRE LINE RECORD																						