

AM HESS GULF REDKNIFE

E-55

Drilling Authority No. 395
Date Issued 31 December 1969

WELL NAME Am Hess Gulf Redknife E-55
FIELD
LOCATION: Unit E Area: 55
Latitude 60-34-23 Section 55 Grid 60-40-119-30
U.W.L.R. 60.57300 -- 119.68986 Longitude 119-41-05.5
U.W.I. 300E556040119300

Rig Release Date:
Status:
Information Release Date:

CHANGE OF NAME:

DATE RECEIVED	INDEX
51/12/69	Application for a Drilling Authority. Well Completion Data. Well History Report.
	Application to Amend a Drilling Authority.
	Application to change a Well Name.
12/2/70	Application to Abandon a Well or Suspend Drilling.
	Application to Alter Condition of a Well.
March 70	Well History Supplement. Well Completion Data. Work-over Report No.
	Application to Commingle Production before Measurement.
	Data for Back Pressure Test on Natural Gas Wells - Monograph 7 Method.
	Data for Back Pressure Test on Natural Gas Wells - Vitter's Method.
	M.P.R. - Oil - Calculations.
	New Oil Well Report.
	New Gas Well Report.
	Well Inspection Report.
	Rig Inspection Report.
	Battery Inspection Report.
	Equipment Report.
	Well Card.
	New Service Well Report.
	Monthly Water Flood Operations Report
	Monthly Water Receipts and Disposal of Fluids Report Logs, Large scale. Small scale.



Drilling Authority No. 395
Date issued December 31, 1969

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

WELL COMPLETION DATA

To be submitted in duplicate within thirty days after the completion, rework, abandonment, recompletion or suspension of every well.

Well name and number Amless Gulf Redknife E-55
Permit No. 3584 Lease No.
Gulf Oil Canada Exploratory Licence No. 1243
(Permittee, Licensee, Lessee)
Amerada Hess Corporation Exploratory Licence No. 1359
(Operator)
Location: Unit E Section 55 Grid 60° 40' N 119° 30' W
Latitude 60 degs. 34' 23" Longitude 119 degs. 41' 5.5"
From Established Reference Marker Shot Point 770 Line 7 x 261
Universal Well Location Reference Lat. 60.57306 Degs 119.68986 Degs. Long.

	DATE	DEPTH	Pool(s)
			Nil
			Interval(s) open to production Nil
Spudded	Jan. 12/70		
Suspended			
Resumed Operations			
Finished Drilling	Jan. 30/70		
Deepened			Elevation: Gr. 1241 K.B. 1258
Complete (gas/oil)			Rig No. 1
Abandoned	Feb. 4/70		Drilling Contractor Can-Tex
Rig released	Feb. 4/70	4807	Contractor's Business Licence No. 652

CASING RECORD

Casing Size (Inches)	Grade	Weight	Amount	Set at -	Sacks of Cement and /additives
1. 9-5/8"	K-55	40.5	643	660	550 sacks with 2% CaCL2
2.					in last 250 sacks
3.					
4.					
5.					
6.					

GEOLOGICAL TOPS	ELEVATION		CORE RECORD					
	Depth	Sub-Sec	From	To	Rec.	From	To	Rec.
Kotcho	865	+393	Nil					
Jean Marie	12308	-1050						
Ft. Simpson	2337	-1079						
Muskwa	3993	-2735						
Slave Point	4039	-2781						
Watt Mtn.	4264	-3006						
Presquille	4291	-3033						
Predevonian	4678	-3420						

GEOLOGICAL TOPS	ELEVATION		LOG RECORD			
	Depth	Sub-Sec	Run No.	Type of Log	From	To
(Quartzite)						
PC (Granite)	4790	-3532				
			1	I.E.S.	659	4808
			1	B.H.C S	659	4802
			1	F.D.C. W/GR	3900	4806
			1	S.N.P. W/GR	3900	4806
			1	Dual Mineral	3900	4806
			1	Porosity Overlay	3900	4806



File No. 395
Drilling Authority No.

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT

OIL AND MINERAL DIVISION

Application to Abandon a Well ~~for Suspension of Drilling~~

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to abandon, to suspend drilling:-

Name and number of well AmHess Gulf Redknife E-55
Location: Unit E Section 55 Grid 60°40' N 119° 30' W
Latitude 60° 34' 23" Longitude 119° 41' 5.5"
From Established Reference Marker Shot point 770 Line 7 x 261
Universal Well Location Reference Lat 60.57306° Long. 119.68986
Permit No. 3584 Lease No.

Gulf Oil Canada

(Permitter, Licensee, Lessee)

Date of commencement of proposed program February 3, 1970

OIL, GAS, AND WATER ENCOUNTERED
(Depths)

Oil at Nil
Gas at Nil
Water at DST No. 1 - 4240-4807
Total Depth 4807 Date of last operations February 4, 1970
Present condition of well Drilled and abandoned
Surface casing cut off 3' below ground level. Dumped 5 sacks cement in 9 5/8" casing and welded steel plate on top. Welded 2" pipe to plate to extend 4' above ground level with well name and location on plate.

CASING RECORD

Casing Size O.D. Inches	Weight	Amount	Set At—	Sacks of Cement and Additives	Amount Pulled
1. 9 5/8"	40.5#	643	660'	500 sacks	Nil
2.				27 CaCl2 in last	
3.				250 sacks	
4.					
5.					

PROPOSED ABANDONMENT PROGRAM

Plug		Geological Formation	Number of Sacks of Cement	Remarks
No.	Position			
1	4807-4400	Granite - Chinchaga	165	
2	4400-4000	Presquile - Watt Mt	165	Located at 3970'
		Slave Point		
3	610-710	Surface	65	Located at 580'

The following logs have been run I.E.S., BHCS, FDC, SNP, GRC

Other operations proposed Nil

Operations to be carried out by Amerada Hess Corporation Contractor Licence No. 652

Address 540 - 5th Avenue S.W., Calgary 1, Alberta Address

Responsible Agent in field P. P. Matkaluk

Dated at Calgary this 11th Day of February 1970

Signed by John E. Jankul Company Amerada Hess Corporation

Title General Superintendent Operator's Exploratory Licence No. 1359

Note:—The Oil Conservation Engineer's office must be notified before work is commenced.

(For RESOURCE MANAGEMENT DIVISION use only)

APPROVAL

This application has been examined and proposed programme approved, subject to the following conditions:

Confirming oral approval given by Mr. B.H.J. Thoms

on the 2nd February 1970

12th February

70

Dated 19

B.H.J. Thoms
Oil Conservation Engineer

Forms to be submitted in triplicate to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.

Drilling Authority No. 395

Project No.

File No.



DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

Application for a Drilling Authority

This notice of intention to begin drilling operations, in triplicate, and where required a plan of survey approved by the Surveyor General showing the target area or the site of the well must be submitted and approved before commencing operations.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to drill—

Name and number of well **Amass Gulf Wellbore E-55**
Location: Unit **E** Section **55** Grid **60° 40' N 119° 30' W**
Latitude **60° 34' 23"** Longitude **119° 41' 5.5"**
From Established Reference Marker **Shot point 770 Line 7 x 161**
Universal Well Location Reference **Lat. 60.57306°, Long. 119.6826°**
Elevation: Ground **1241** **K.B.** feet above sea-level.
Well is expected to produce from **Fort Simpson Reef** formation at a depth of about **2300** feet. Expected total final depth **4700**
Area assigned to well **(Oil Conservation Engineer's use only)**

Permit No. **3584** Lease No. **Oil** Acreage **62,800**
Permitter, licensee, or lessee **Oil**
Exploratory Licence No. **1243**
Surface owned by Crown or **Crown**
Petroleum and natural-gas rights owned by **Crown**
We propose to use the following strings of casing, either cementing or landing them as indicated below:—

Casing Size O.D. (Inches)	Weight (Lb./Ft.)	Grade	New or Used	Estimated Depth	Scale of Cement
1. 9 5/8"	40#	J-55	Used	600	400
2.					
3. Production casing, if required, will be reviewed with the Department					
4. before running.					
5.					

Expected water, gas, and oil horizons and type of control equipment **Adequate and properties**
RGP Equipment: a 10" Ser 900 Hydril and a 10" Ser. 900 Double Shaffer Gate

Well will be drilled with Rotary Rig No. **1** by **Can Tex Drilling & Exploration Ltd.**
(Drilling Contractor or company)

Responsible agent of applicant:— Contractor's business Licence No. **J. E. Newkirk**
At well **F. C. Radwood** At registered office **J. E. Newkirk**
Address **Ed Level, Alberta** Address **540 - 5th Avenue S.W. Calgary 1, Alberta.**
It is understood that if changes become necessary, notice of the change of plan will be submitted.
Dated at **Calgary**, this **30th** day of **December**, 19 **69**
Signed by **J. E. Newkirk** Company **Amass Gulf Corporation**
Title **General Superintendent** Operator's Licence No. **1359**

(For Resource Management Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:—

1. The Company will submit to this office, on Tuesday of each week, the latest reports received by radio on the progress of the well.
2. During well drilling and testing operations, every effort shall be made to ensure

Dated **31st December**, 19 **69**

Forms to be submitted to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.

LAND 52-90-1 (3-67)

UNIQUE WELL IDENTIFIER - **300E556040119300**

(*) Will advise by letter.

that drilling fluids, chemicals and wastes shall be disposed of or contained in a manner that will prevent the contamination of adjacent vegetation and surface or sub-surface waters.

3. We draw your attention to Sections 95 and 96 of the Canada Oil and Gas Land Regulations.
4. Protection and intermediate casing programs shall be approved by the Oil Conservation Engineer.



(for) R.H.J. Thoms, Oil Conservation Engineer

Amecada Hess Corp.

AMHESS GULF REDKNIFE B-55

UNIT E, SEC. 55 GRID 60° 40' N 119° 30' W

1-11-4-27

1-11-4-27

INDEX

Section I	Summary of Well Data
Section II	Geological Summary
Section III	Engineering Summary
Section IV	Logs
Section V	Analysis
Section VI	Completion Summary
Section VII	Well History and Summary



SECTION I

SUMMARY OF WELL DATA

- (a) Complete Well Name and Number
- (b) Permittee, License or Lessee
- (c) Name of Operator
- (d) Location
- (e) Co-ordinates
- (f) Permit or Lease Number
- (g) Drilling Contractor
- (h) Drilling Authority
- (i) Classification
- (j) Elevations
- (k) Spudded
- (l) Complete Drilling
- (m) Total Depth and Plug Back Total Depth
- (n) Well Status
- (o) Rig Released Date
- (p) Hole Sizes to Total Depth
- (q) Casing

SECTION I SUMMARY OF WELL DATA

- (a) Complete Well Name and Number
Amhess Gulf Redknife E-55
- (b) Permittee, License or Lessee
Gulf Oil Canada Limited
- (c) Name of Operator
Amerada Hess Corporation
540 - 5th Avenue S.W.
Calgary 1, Alberta.
- (d) Location
Located in Unit E; Sec. 55,
Grid 60 degs. 40 mins. N;
119 degs. 30 mins. W
Lat: 60 degs. 34 mins. 23 secs.
Long: 119 degs. 41 mins. 5.5 secs.
Shot point 770 Line 7 x 261. Established Reference Marker
Lat. 60.57306 degs, Long. 119.68986 degs. Universal Well Location
Reference - Unique Well Identifier 300 E 556 040 119300
- (e) Co-ordinates
D & A
- (f) Permit Number
3584
- (g) Drilling Contractor
Can-Tex Drilling and Exploration Ltd.
Rig No. 1 - Rotary
- (h) Drilling Authority
No. 395 - Dated at Calgary 31st Day of December 1969
- (i) Classification
Trainer Lake - Wildcat
- (j) Elevations
Ground 1241' K.B. 1258'
- (k) Spudded
5:00 a.m. - January 12, 1970
- (l) Completed Drilling
2:45 a.m. January 30, 1970
- (m) Total Depth and Plug Back Total Depth
Total Depth 4807' Plug back depth 580'

- (n) Well Status
Dry and Abandoned
- (o) Rig Released Date
11:00 p.m. February 4, 1970
- (p) Hole Sizes to Total Depth
13 3/4" 0' to 665'
8 3/4" 665' to 4807'
- (q) Casing
9 5/8" casing cemented at 660' K.B.

SECTION II

- (a) Formation Tops
- (b) Cored Intervals (no coring)
- (c) Core Description (none)
- (d) Sample Description
- (e) Paleontological (none)

AMERADA DIVISION AMERADA HESS CORPORATION

GEOLOGICAL WELL SUMMARY

WELL NAME: AmHess Gulf Redknife E-55

LOCATION: N.W.T. Grid 50° 40' N/
119° 30' W

COORDINATES: 60° 34' 23" / 119° 41' 5.5"

ELEVATIONS: Grd. 1241' K.B. 1258' PARTICIPANTS: Gulf Canada

Spudded: 5:00 a.m. January 12, 1970

Casing Size: 9 5/8" Depth: 660

Released: 11:00 p.m. February 4, 1970

Completed:

F.T.D.: 4807'

In: P E

P.B.D.:

Status: D&A

In:

I.P.:

BOPO

MCF/D

Choke:

Hour Test

Day Test

C.O.R.:

Gravity

BSW

T.P.:

C.P.:

SHP

G/O Int.:

O/W Int.:

Net Pay Thickness: Gas

Oil

Net Pay Thickness: Gas

Oil

FORMATION MARKERS

	Sample	E-Log	Subsea
Kotcho	867	865	+ 393
Jean-Marie	2310	2308	-1050
Ft. Simpson	2337	2337	-1079
Muskwa	4000	3993	-2735
Slave Point	4070	4039	-2781
Watt Mtn.	4320?	4264	-3006
Presquile	4327	4291	-3033
Predevonian	4680	4678	-3420
(Quartzite)			
PE (Granite)	4790	4790?	-3532

CORED INTERVALS

None

Recovery

SAMPLE INTERVALS

600' - T.D.

(10' intervals)

LOGS RUN

Induction Electric
Gamma-Ray-Sonic
FD - Caliper
SNP - Gamma Ray

Geologist.

Let Alvin do it

AMERADA DIVISION
AMERADA HESS CORPORATION
SAMPLE DESCRIPTION

Page 1

Well Amfloss Gulf Redknife 8-25 Location WT Grid 60°40'E; 119°30'W
Province Alberta Logged By A. A. Gross Date Jan. 18/70-Jan. 30/70

Porosity Oil Stain

SAMPLES HEREIN IN CRETACEOUS

600-660 Shale, medium to dark grey, soft to medium hard, fissile. Very slightly calcareous, variably silty. 665' casing shoe.

660?: MISSISSIPPIAN

660-670 Shale, medium grey, calcareous, slightly silty, medium soft.

670-700 Cement from plug obliterates sample.

700-720 Shale, medium grey, calcareous, slightly silty, medium soft.

720-730 No Sample.

730-770 Shale, as above, with stringers of limy siltstone.

770-800 Siltstone, medium grey, calcareous; inter-bedded with shale as above.

800-860 Shale, medium to dark grey, grading to siltstone, slightly calcareous. Traces of mica. Pyrite. Traces of limestone, cream, micro-crystalline.

867: WABAMUN

860-1110 Limestone, cream to grey-brown, micro-crystalline, slightly pyritic, tight. Fossil fragments; Crinoids. Occasional very poor oil staining. v.p.

1110-1200 Limestone as above, with lots of shale cavings.

1200-1280 Shale, medium grey, slightly greenish, variably silty, calcareous.

		<u>Por.</u>	<u>O. Str.</u>
1280-1360	<u>Limestone</u> , cream to light grey, crypto-crystalline to fine crystalline, tight. Crinoids, Gastropods. Glauconite.		
1360-1380	<u>Shale</u> , dark grey to medium grey, silty, calcareous.		
1380-1400	<u>Shale</u> , dark grey, silty.		
1400-1510	<u>Limestone</u> , white to cream to light grey, crypto-crystalline to fine crystalline, tight. Pyrite. Stringers of <u>limestone</u> , light grey, micro-crystalline with traces of chalky and inter-crystalline porosity.	Tr. x, s	
1510-1530	<u>Limestone</u> as above, with interbedded shale, grey, silty, slightly calcareous.		
1530-1760	<u>Limestone</u> , light grey to cream to white, crypto-crystalline to fine crystalline, tight. Fossil fragments. Occasional traces of chalky and inter-crystalline porosity. Stringers of <u>shale</u> , grey, silty, calcareous. Pyrite. Crinoids.		
1760-1780	<u>Shale</u> , grey, silty, slightly calcareous.		
1780-1830	<u>Limestone</u> , white to light grey, micro-crystalline, slightly argillaceous. Traces of inter-crystalline porosity. Occasional very poor dead oil stain. Pyrite.	Tr. x	V.P. dead oil
1830-1860	<u>Limestone</u> as above with some interbeds of <u>siltstone</u> , calcareous, light grey (very fine quartz particles in calcareous cement). Traces of inter-crystalline porosity.	Tr. x	
1860-1880	<u>Limestone</u> , white to light grey, very fine crystalline, silty, partly dolomitized. Crinoid fragments.	Tr. x	
1880-1890	<u>Sandstone</u> , white to light grey, very fine grained, with calcareous cement.	Tr. x	
1890-1910	<u>Siltstone</u> , medium to dark grey, hard, calcareous; interbeds of <u>sandstone</u> and <u>limestone</u> as above.		

		<u>Por.</u>	<u>O. Str.</u>
1910-1950	<u>Limestone</u> , white to cream, crypto-crystalline to very fine crystalline with silty or sandy intervals. Traces of inter-crystalline porosity in sandy intervals. Fossil fragments; Crinoids, Corals.	Tr. x	
1950-1970	<u>Limestone</u> as above, abundant coarse crystalline organic fragments (Possible organic porosity? Not seen).		
1970-1980	<u>Limestone</u> , chalky, white to translucent, micro-crystalline to medium crystalline; Crinoids.		
1980-1990	<u>Limestone</u> , light grey, very fine crystalline, tight.		
1990-2000	<u>Sandstone</u> , grey, very fine grained, calcareous. Poor traces of dead oil.	Tr. x	dead oil
2000-2150	<u>Limestone</u> , white to light grey, or cream, micro-crystalline to very fine crystalline; interbedded with <u>sandstone</u> , white to grey, very fine, grained, calcareous; and <u>siltstone</u> , grey; Crinoid fragments.	Tr. x	dead oil
2150-2230	<u>Shale</u> , medium to light greenish to grey, or dark grey, variably silty, variably calcareous. Some interbeds of <u>limestone</u> , cream to light grey to brown, micro-crystalline to fine crystalline; and <u>siltstone</u> , grey, calcareous.		
2230-2250	<u>Limestone</u> , light grey, very fine crystalline, partly dolomitic. Crinoids.	Tr. x	Tr. of bit
2250-2270	<u>Shale</u> , green and grey, silty, slightly calcareous. Possibly limestone interbeds.		
2270-2300	<u>Limestone</u> , cream to light grey to brown, very fine crystalline, partly dolomitic. Tiny Brachiopods. Stringers of <u>shale</u> , grey.	Tr. x	
2300-2310	<u>Shale</u> , green; and <u>limestone</u> , very fine crystalline, cream to light grey to brown, dolomitic.		

		<u>Por.</u>	<u>O. Str.</u>
<u>2310: JEAN MARIE</u>			
2310-2340	<u>Limestone</u> , light grey to brown, very fine to medium crystalline, partly dolomitic, and <u>shale</u> , greenish grey, slightly silty, calcareous.	Tr. x	Tr. dead oil
<u>2337: FORT SIMPSON</u>			
2340-3930	<u>Shale</u> , green to grey and grey to carmine, variably silty, variably calcareous. Interbeds of <u>siltstone</u> and <u>sandstone</u> as shown below (at first sight the proportion of sandstone in the shales might average 20%):		
2400-2410	Brachiopods		
2410-2420	Interbeds of <u>siltstone</u> and <u>sandstone</u> , grey, very fine grained, slightly calcareous. Pyrite.		
2440-2450	Minor interbeds of <u>sandstone</u> , grey, very fine grained, micaceous, slightly calcareous.		
2470-2480	Interbeds of <u>sandstone</u> , grey, very fine grained, micaceous, slightly calcareous.	Tr. x	
2490-2500	Interbeds of <u>sandstone</u> , grey very fine grained to fine grained, micaceous, slightly calcareous.	Tr. x	
2530-2540	Minor interbeds of <u>sandstone</u> as above.		
2560-2570	Interbeds of <u>sandstone</u> , grey, very fine grained, micaceous; and <u>siltstone</u> , micaceous.	Tr. x	
2600-2610	Interbeds of <u>sandstone</u> , grey, very fine grained, slightly calcareous, micaceous.		
2620-2640	Interbeds of <u>sandstone</u> as above.	Tr. x	
2680-2690	Interbeds of <u>sandstone</u> , light grey, very fine to fine grained, calcareous, micaceous.	Tr. x	
2710-2720	Interbeds of <u>sandstone</u> , light grey, very fine to fine grained, calcareous and dolomitic, micaceous, silty, argillaceous.	Tr. x	

For.O. Stn.

2340-3930

Continued

- 2750-2760 Interbeds of sandstone, very fine to fine grained, light grey, light green to grey, grey to brown, micaceous with variable amounts of calcareous cement (dolomitic in grey to brown sandstone).
- 2770-2780 Interbeds of sandstone as above, siliceous cement; very hard.
- 2860-2870 Interbeds of sandstone, greenish-grey, very fine grained; calcareous cement; micaceous.
- 2890-2910 Traces of limestone, cream, micro-crystalline, fossiliferous; Brachiopods, Crinoids.
- 2960-2970 Interbeds of limestone, cream, micro-crystalline, fossiliferous, tight.
- 2990-2010 Interbeds of sandstone, greenish-grey, very fine grained, calcareous, micaceous.
- 3040-3050 Interbeds of sandstone, grey, very fine grained, very calcareous (almost sandy limestone).
- 3160-3170 Interbeds of sandstone, grey, very fine grained, very calcareous (calcareous cement). Pyrite.
- 3300-3310 Interbeds of sandstone as above, very calcareous.
- 3370-3380 Interbeds of sandstone as above, very calcareous.
- 3410-3420 Interbeds of sandstone, light grey, very fine to fine grained, micaceous, calcareous.
- 3420-3430 Interbeds of sandstone, light grey, very fine to fine grained, micaceous, slightly calcareous.

Por.O. Str.

2340-3930	Continued		
3450-3460	Trace of <u>limestone</u> , light grey, very fine crystalline, sandy.		
3540-3550	Interbeds of <u>sandstone</u> , light grey to translucent, very fine grained, very slightly calcareous.		
3620-3690	Interbeds of <u>sandstone</u> , very fine grained, slightly calcareous, micaceous.		
3770-3780	Traces of <u>limestone</u> , cream, micro-crystalline.		
3800-3810	Interbeds of <u>sandstone</u> as above.		
3860-3930	Traces of <u>limestone</u> , cream, micro-crystalline.		
3930-3950	<u>Limestone</u> , cream, micro-crystalline, chalky cement. Loss of mud (6").	Tr. x,e	
3950-3980	<u>Shale</u> , grey to green, and grey to carmine, silty, variably calcareous.		
3980-4000	<u>Shale</u> as above, micaceous, silty.		
	<u>4000: BITUMINOUS SHALE</u>		
4000-4040	<u>Shale</u> , dark brown to black, bituminous, slightly silty, non calcareous.		
	<u>4040: SLAVE POINT</u>		
4040-4060	<u>Limestone</u> , grey to brown to white, micro-crystalline to medium crystalline. Traces of vuggy porosity.	Tr. v	Bit
4060-4110	<u>Limestone</u> , white, cream to grey to brown, micro-crystalline to medium crystalline, tight. Occasional vuggy or inter-crystalline porosity. The study of coarser chips indicates that the porosity is restricted to some discontinuous patches surrounded by tighter limestone.	Tr. v,x	Tr. Bit
4110-4160	<u>Limestone</u> , medium to dark grey to brown, very fine to medium crystalline. Traces of vuggy or inter-crystalline porosity.	Tr. v,x	Tr. Bit

		<u>Por.</u>	<u>O. Stn.</u>
4160-4255	<u>Limestone</u> , medium to dark grey to brown, very fine to medium crystalline, tight.		
	<u>4255: DOLOMITE</u>		
4255-4270	<u>Dolomite</u> , medium to dark grey to brown, very fine to fine crystalline, tight.		
4270-4320	<u>Dolomite</u> , white to medium to dark grey to brown, fine to medium crystalline, vuggy porosity (geodes).	G,v,x	Tr. Bit
4320-4340	<u>Shale</u> , dark grey to brown, slightly silty, non calcareous. Paper-thin bedded. (cavings?) Interbedded with dolomite as above.		
4340-4350	<u>Dolomite</u> , brownish grey, very fine to medium crystalline. Clear crystals of dolomite (geodes).	G,v	
4350-4460	<u>Dolomite</u> , cream to medium grey to brown, fine to medium crystalline.	G,v	
4460-4480	<u>Dolomite</u> as above.	G,v	Tr. Bit
4480-4490	<u>Dolomite</u> as above. Traces of limestone, light to medium grey to brown, micro-crystalline to fine crystalline.	G,v	
4490-4500	<u>Limestone</u> , light grey to cream, micro-crystalline to very fine crystalline, fossiliferous, tight (cavings?). Also dolomite.		
4500-4520	<u>Dolomite</u> , grey to brown, micro-crystalline to medium crystalline, inter-crystalline and vuggy porosity.	G,x,v	Tr. Bit
4520-4540	Interbeds of <u>dolomite</u> , light brown to grey, crypto to micro-crystalline with vugs filled with clear crystals of dolomite, calcareous. Mostly tight.		Tr. Bit
4540-4550	<u>Dolomite</u> , grey to brown, fine to medium crystalline; vuggy and inter-crystalline porosity.	G,v,x	
4550-4630	<u>Limestone</u> , light tan, white to cream, salt and pepper, crypto-crystalline to micro-crystalline, argillaceous, mostly tight. Possibly trace of chalky porosity.	Tr. c	Tr. Bit

Por.O. Stn.

4630-4638

Dolomite, light grey to brown, micro-crystalline to fine crystalline.
Mostly tight.

4638: RED BEDS

4638-4650

Dolomite as above, and traces of dolomite, green, micro-crystalline, argillaceous; trace of anhvdrite, white to clear crystalline, crypto to micro-crystalline; mixed with dolomite.

4650-4660

Dolomite, green, micro-crystalline, argillaceous, tight; dolomite, cream, micro-crystalline; dolomite, grey to brown, micro-crystalline to medium crystalline.
Pyrite.

4660-4680

Sandstone, red, mottled (red, brown, green, grey, white) (feldspar, dolomite).
Dolomite, argillaceous, fine to coarse grained.

4680-4690

Sandstone, red mottled (red, green, white, grey) (orange-red feldspar) fine to coarse grained.

4690-4700

Quartzite, light green to grey, (translucent), micro-granular, very hard, tight.
Traces of chlorite.

4700-4750

Quartzite, light green to grey (translucent), microgranular with some coarse crystals; very hard, completely tight.

4750-4770

Quartzite, light green, micro-to coarse grained, feldspar (?), chlorite.

4770-4780

Quartzite, light pink and light green, microgranular to coarse granular.
Chlorite. Pyrite.

4780-4790

Weathered granite, coarse crystalline, white, green, pink, grey; quartz feldspar, chlorite.

4790: PRECAMBRIAN

4790-4807

Granite, coarse, pink (red to orange feldspar, quartz, biotite).

4807

TOTAL DEPTH.

SECTION III

ENGINEERING SUMMARY

- (a) Report of Drill Stem Testing
- (b) Casing Record
- (c) Bit Record
- (d) Mud Report
- (e) Deviation Record
- (f) Abandonment Plugs
- (g) Lost Circulation Zones
- (h) Report of Blowouts

(a) Report of Drill Stem Testing

Drill Stem Test No. 1 - 4240-4807 Presquile

Ran in 8 3/4" hole, Johnston Testers on dry 4 1/2" D.P.
with 2 packers, jars, safety joint, hydraulic tool,
pump out sub, 2 recorders and 1/2" bean.

Pre-flow 5 mins. I.S.I. 60 mins. V.O. 60 mins. F.S.I. 60 mins.

Blow: Strong initial puff - good air blow decreasing towards
end of test.

Recovered: 950' muddy salt water - 2700' brackish salt water

Charts: I.H.H.P. 2087#, First flow 1250#, I.S.I.P. 1758#
F.F.P. 1737#, F.S.I.P. 1767#, F.H.H.P. 2087#

Drill Stem Test No. 2 - 4040-4150 Slave Point


Ran in 8 3/4" hole Johnston Testers straddle on 4 1/2" D.P.
with 4 packers, jars, safety joint, shut in tool, pump out
sub, 3 recorders, 1/2" bean.

Pre-flow 5 mins. I.S.I. 60 mins. V.O. 30 mins. F.S.I. 60 mins.

Blow: Good air blow throughout test

Recovered: 220' drilling mud

Charts: I.H.H.P. 1965#, First flow 67#, I.S.I.P. 1523#
F.F.P. 89#, F.S.I.P. 1320#, F.H.H.P. 1926#

[illegible]


A DIVISION OF YORK-BURNINGHAM CANADA LIMITED

D 03695		PRESSURE DATA		FLUID SAMPLE REPORT	
INSTRUMENT No.	AK1-3411	AK1-1935		Sample No.	
CAPACITY - gals	7100	7000		Type	WATER
INSTRUMENT DEPTH FT	4261	4266		Depth	4200 ft.
INSTRUMENT OPENING	OUTSIDE	OUTSIDE		Volume	2500 Cu. Cu.
PRESSURE GRADIENT psi/ft.					
WELL TEMP °F	148				
INITIAL HYDROSTATIC	A 2087#	2097#		Sample Pressure	
FIRST FLOW	B 1250#	1257#		110	psi. at Surface
	B-1 1423#	1454#		Gravity	API 66 °F
INITIAL SHUT-IN	C 1758#	1771#		Gas/Oil Ratio	Cu. Ft./bbl.
SECOND FLOW	D 1461#	1470#			
	D-1 1737#	1752#		Recovery:	
SECOND SHUT-IN	E			Cu. Ft. Gas	
THIRD FLOW	F			cc. Oil	
	F-1			cc. Water	1700
FINAL SHUT-IN	G 1767#	1779#		cc. Mud	
FINAL HYDROSTATIC	H 2087#	2097#		Total Liquid cc.	1700

PRESSURE INCREMENTS

[illegible]

GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z — Special pressure points such as pumping pressures recorded for formation breakdown.




FIELD
REPORT NO.
D 03695


RECORDER NO.
AKI-3411

CAPACITY
7100

REPORTS
REQUESTED
7



GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z - Special pressure points such as pumping pressures recorded for formation breakdown.

FIELD
REPORT NO.

D 03695

RECORDER NO.


AK1-1935

CAPACITY

7000

REPORTS
REQUESTED

7



JOHNSTON TESTERS 211 20TH AVENUE S.E. • CALGARY T6 6M2 • ALBERTA • PH 255-1151


A DIVISION OF SCIENCE AND TECHNOLOGY CANADA 1981/82

D 03596		PRESSURE DATA			FLUID SAMPLE REPORT	
INSTRUMENT NO.	AK1-3411	AK1-1935	AK1-1848		Sample No.	
CAPACITY (mg)	7100	7000	7100		Type	MUD
INSTRUMENT DEPTH	4009	4046	4184		Depth	ft
INSTRUMENT OPENING					Volume	2500 c.c.
PRESSURE GRADIENT psi/ft.						
WELL TEMP °F	146					
INITIAL HYDROSTATIC	A 1965#		2026#		Sample Pressure	10 psig. at Surface
FIRST FLOW	B 67#				Gravity	API Gr. °F
	B-1 67#		A-1 2118#		Gas Oil Ratio	Cu.Ft./bbl.
INITIAL SHUT-IN	C 1523#		A-2 1561#			
SECOND FLOW	D 80#					
	D-1 89#	STYLUS NOT	RAN BELOW		Recovery	
SECOND SHUT-IN	E	ENGAGED	STRADDLE		Cu. Ft. Gas	
THIRD FLOW	F				cc. Oil	
	F-1		A-3 2028#		cc. Water	
FINAL SHUT-IN	G 1320#				cc. Mud	250
FINAL HYDROSTATIC	H 1926#		1987#		Total Liquid cc.	250
REMARKS:						

PRESSURE INCREMENTS

[illegible]

GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z—Special pressure points such as pumping pressures recorded for formation breakdown.



FIELD
REPORT NO.

D 03696

RECORDER NO.


AK1-3411

CAPACITY


7100

REPORTS
REQUESTED

7




GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z - Special pressure points such as pumping pressures recorded for formation breakdown.




FIELD
REPORT NO.
D 03696

RECORDER NO.
AK1-1848

CAPACITY
7100

REPORTS
REQUESTED
7



(b)

Casing Record

9 5/8" casing cemented at 660' K.B.
Ran in 13 3/4" hole, 20 jts. of 40#, K.55 LT&C casing.
Used Guide Shoe on bottom and Float Collar 1 joint
above shoe. Used three centralizers on bottom 3 jts.
and one centralizer one joint below ground level.
Howco cemented casing with 550 sacks of construction
cement with 2% Calcium on last 250 sacks. Used one
rubber plug and water to displace cement. Bumped
plug at 700#. Eled off casing and float held o.k.
Cement in place at 1:00 a.m. January 15, 1970.
Good returns to surface.

(c)

Bit Record

Attached

AMERADA

BIT PERFORMANCE RECORD

L. S. D. _____ SEC. _____ TWP. _____ RGE. _____ S. AREA Trainor Lake
 5:00 a.m. Jan. 12, 1970 COMPLETED 11:00 p.m. Feb. 4, 1970

[illegible]

(d) Mud Report

Gel Ben-ex System

Surface to 2180 Gel Ben-ex and No stik

2180 to 4020' - gel Ben-ex and C.M.C.

4020 to 4807' - gel soda ash Peltex and caustic

Daily mud checks reported in Section VII

Materials Used

Ben-ex	150#
Caustic Soda	1,550#
C.M.C.	750#
DV-68	9 gals.
Hydrogel	80,000#
Peltex	400#
Sawdust	24,500#
Soda Ash	900#
Wt. Material	4,000#
No-stik	45 gals.
Lime	250#

(c) Deviation Record

Totco Surveys

<u>Depth</u>	<u>Degree</u>
100'	1
200'	1/2
290'	1/8
408'	1/2
500'	1/2
600'	3/4
922'	7/8
1240'	1/2
1547'	1/4
1610'	1/8
1920'	1/8
2200'	1/8
2444'	1/8
2535'	1/8
2626'	1/2
2716'	1/2
2897'	1
2958'	1/2
3017'	1/2
3150'	1/2
3241'	1/8
3331'	1/4
3421'	1/2
3512'	1/2
3605'	1/2
3695'	1/2
3783'	1
3843'	1/2
3933'	1/8
4024'	3/4
4106'	1
4620'	1/2

(f)

Abandonment Plugs

Abandonment Plug No. 1 First Stage 4807' to 4401'

Hung 4 1/2" D.P. at 4807'. Howco pumped in and equalized 165 sacks of construction cement, and displaced with 62 bbls. of mud. Plug in place at 11:30 p.m. 2/3/1970

Abandonment Plug No. 2 - Second Stage 4401' to 4000'

Hung 4 1/2" D.P. at 4400'. Howco pumped in and equalized 165 sacks cement and displaced with 55 bbls. mud. Cement in place at 1:00 a.m. 2/4/1970.

Located Plug No. 1 and 2 at 3970' at 9:00 a.m. 2/4/1970

Abandonment Plug No. 3 - 610' to 710'

Hung 4 1/2" D.P. at 710'. Howco pumped in and equalized 65 sacks cement with 2% Calcium. Displaced cement with 9 bbls. water.

Cement in place at 11:30 a.m. 2/4/1970

Located Plug No. 3 at 580' at 8:00 p.m. 2/4/1970

(g) Lost Circulation Zones

Presquile Formation

Last 75 bbls. of mud from 4470' to 4500'

Sealed off with 30 sacks of sawdust.

(h) Report of Blowouts

No blowouts.

SECTION IV

LOGS

Logs

Schlumberger IES Log Run No. 1 - February 1st, 1970

2" scale 659' to 4808'

5" scale 3860' to 4808'

Schlumberger Borehole Compensated Sonic Run No. 1 - February 1st, 1970

2" scale 659' to 4802'

5" scale 3880' to 4802'

Schlumberger Formation Density Gamma Ray and Caliper Run No. 1

February 1st, 1970

5" scale 3900' to 4806'

Schlumberger Sidewall Gamma Ray Neutron Porosity Run No. 1

February 1st, 1970

5" scale 3900' to 4806'

Schlumberger Dual Mineral Log Run No. 1 - February 1st, 1970

3900' to 4806'

Schlumberger Porosity Overlay Run No. 1 - February 1st, 1970

3900' to 4806'

SECTION V

ANALYSIS

(a)	Core Analysis	-	None
(b)	Water Analysis	-	Attached
(c)	Gas Analysis	-	None
(d)	Oil Analysis	-	None

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

WATER ANALYSIS

Lab No. E70-236

Received: Feb. 9, 1970 Reported: Feb. 12, 1970

Well: Location: AMHESS Gulf Redknife

60° 40' N. - 119° 30' W.

Operator: AMERADA HESS CORPORATION

Field or Area:

Elev.: K.B. 1258' Grd.

Zone/Formation: Presquille

Sample Interval: 4240' - 4807'

Method of Production: D.S.T. #1

Sampled from: bottom

Sampled by: Johnston Testers Limited

Date: Feb. 2, 1970

OTHER PERTINENT DATA


Recovered: 3650'

(Signed)

Mg./L	Na	K	Ca	Mg	SO ₄	Cl	CO ₃	HCO ₃	
23305			7347	1337	989	51600		544	
Meq./L									
1013.75			366.63	109.86	20.56	1460.76		8.92	
Meq. %									
34.01			12.30	3.69	0.69	49.01		0.30	

Total Solids Mg/L: By Evaporation 94,417 Fe Very much H₂S Nil
 Calculated 85,322 After Ignition 80,919
 Specific Gravity 1.065 @ 60°F Observed pH 6.8 @ 78°F
 Refractive Index 1.3489 @ 25°C Resistivity 0.123 ohm meters @ 68°F

Pattern Unit Meq./L



Remarks and Conclusions: Sample consisted of colorless water with some black sediment. Some organic matter detected in total evaporated solids.

BENZENE CONTENT: No trace of benzene indicated.

Sample was received in a 1 quart metal container without a foil insert in the screw cap. Container 1/2 full, water was clear.

When taking water samples for benzene analysis, it is recommended that the container be filled as full as possible. Elution of benzene from the water to the vapor space above the sample can appreciably alter the detectable concentration.

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

WATER ANALYSIS

Lab No. E70-237

Received: Feb. 9, 1970 Reported: Feb. 12, 1970

Well: Location:

AMHESSE Gulf Redknife E-55 60° 40' N. - 119° 30' W.

Operator: AMERADA HESS CORPORATION

Field or Area:

Elev.: K.B. 1258' Grd. Zone/Formation: Slave Point

Sample Interval: 4040' - 4150'

Method of Production: D.S.T. #2

Sampled from: bottom

Sampled by: Johnston Testers Limited

Date: Feb. 3, 1970

OTHER PERTINENT DATA


Recovered: 220' fluid.

(Signed)

	Na	K	Ca	Mg		SO ₄	Cl		CO ₂	HCO ₃	
Ng./L	4671		649	187		1668	7340			566	
Meq./L	203.21		32.37	15.38		34.69	206.99			9.28	
Meq. %	40.49		6.45	3.06		6.91	41.24			1.85	

Total Solids Mg/L: By Evaporation 15,309 Fe much Specific Gravity 1.014 @60°F Observed pH 7.8 @ 77°F
 Calculated 15,081 After Ignition 12,036 H₂S nil Refractive Index 1.3356 @25°C Resistivity 0.601 ohm meters @ 68°F

Pattern Unit Meq./L



Remarks and Conclusions: Sample consisted of approximately 45% light brown coloured water and 55% mud. Much organic matter detected in total evaporated solids.

continued.....

CHEMICAL & GEOLOGICAL LABORATORIES LIMITED

OPERATOR: AMERADA HESS CORPORATION REPORT NUMBER: E70-237

DATE SAMPLED: Feb. 3, 1970 DATE RECEIVED: Feb. 9, 1970 DATE REPORTED: Feb. 12, 1970

Kind of Sample: Water Well: AMHESS Gulf Redknife E-55 60° 40' N. - 119° 30' W.

Method of Production: D.S.T. #2 Formation: Slave Point Interval: 4040' - 4150'

Sampled from: bottom Sampled by: Johnston Testers Limited Elevation: K.B. 1258'

Recovered: 220' fluid.

BENZENE CONTENT: Trace

Sample was received in a 1 quart plastic container without a foil insert in the screw cap. Container was full, water was muddy.

The use of plastic containers is not recommended for benzene analysis samples, due to the adsorption and diffusion of benzene through the polyethylene. It has been shown that samples can lose significant quantities of benzene or conversely gain appreciable benzene when kept in proximity to a hydrocarbon source. For this reason, this analysis should not be considered as representative of the benzene content of the water source.

Containers suitable for benzene analysis samples may be obtained from this laboratory.

SECTION VI

COMPLETION RECORD

Dry and Abandoned

SECTION VII

WELL HISTORY & SUMMARY

AMERADA HESS CORPORATION

AMHESSE GULF REDKNIFE E-55

UNIT E SEC. 55 GRID 60° 40' N 119° 30' W

WELL SUMMARY

<u>Field</u>	Trainer Lake - Wildcat
<u>Well Number</u>	AmHess Gulf Redknife E-55
<u>Location</u>	Located in Unit E, Sec. 55, Grid 60 degs. 40 mins. N; 119 degs. 30 mins. W - Lat. 60 degs. 34 mins. 23 secs. Long: 119 degs. 41 mins. 5.5 secs.
<u>Elevation</u>	Ground 1241' K.B. 1258'
<u>Surveyor</u>	No legal survey required
<u>License</u>	Authority #395
<u>Contractor</u>	Can-Tex Drilling & Exploration Ltd. Rig No. 1
<u>Spudded</u>	5:00 a.m. January 12, 1970 T.D. 4807'
<u>Rig Released</u>	11:00 p.m. February 4, 1970
<u>Casing</u>	9 5/8" casing cemented at 660' with 550 sacks
<u>Logs</u>	Schlumberger IES, Borehole Compensated Sonic, Formation Density Gamma Ray & Caliper, Sidewall Gamma Ray Neutron Porosity, Dual Mineral, Porosity Overlay.
<u>Cores</u>	No cores
<u>Tests</u>	D.S.T. No. 1 - 4240-4807 D.S.T. No. 2 - 4040-4150
<u>Plugs</u>	Plug No. 1 - First stage 4807' to 4401' 165 sacks Plug No. 2 - Second stage 4400' to 4000' 165 sacks Plug No. 3 - 610' to 710' 65 sacks
<u>Drilling Time</u>	9 - 8 3/4" bits at 460' per bit 237 1/2 hours at 17.4' per hour
<u>Mud</u>	Drilling Fluids - gel - Ben-ex System Surface to 2180' - gel - Ben-ex and No stick 2180' to 4020' Gel Ben-ex CMC 4020' to 4807' Gel, Soda ash, Peltex and Caustic.

AMERADA HESS CORPORATION

AMERADA HESS GULF REDKNIFE E-55

UNIT E SEC. 55 GRID 60° 40' N 119° 30' W

WELL HISTORY

1970

January 3rd to
January 12th, Incl.

Moved in Can-Tex Rig No. 1. Rigged up to spud.
Waited on part for derrick.
Drilled 13 3/4" hole from 0' to 437'
Wt 9.1, Vis. 50
Spudded in at 5:00 a.m. January 12, 1970

January 13th

Drilled 13 3/4" hole from 437' to 560'
Wt 9.1, Vis. 50
Bit No. 1A 13 3/4" HW OSC-3 (440'/18 1/4 hours)
Spent 14 hours for trip out - measure - built
up mud volume and reaming bridges to bottom.

January 14th

Drilled 13 3/4" hole from 560' to 665'
Wt 9.1, Vis. 60
Bit No. 2A 13 3/4" HW OSC-3 (225'/7 1/2 hours)
Circulated - made a trip - laid down 9" drill
collars. Rigged up and started running 9 5/8"
casing.

January 15th

Depth 665'
9 5/8" casing cemented at 660' K.B.
Ran in 13 3/4" hole, 20 jts. of 40#, K.55 LT&C
used casing. Used Guide Shoe on bottom and float
collar 1 jt. above shoe. Used three centralizers
on bottom and 1 centralizer 1 jt. below ground level.
Howco cemented casing with 550 sacks of construction
cement with 2% Calcium on last 250 sacks. Used one
rubber plug and water to displace cement. Bumped
plug at 700#. Bled off and float held o.k. Cement
in place at 1:00 a.m. January 15, 1970. Drained
and de-iced mud tanks. Dug cellar. Thawed out
mud tanks. Temp. - 40 degs.

January 16th

Depth 665'
Headed up B.O.P.s. Changed head and liners in
pump. Dug mouse hole. Picked up four drill
collars and ran in.

January 17th

Drilled 8 3/4" hole from 660' to 900'
Wt 8.4, Vis. 30
Removed B.O.P.s. Installed new ring gaskets.
Flanged down B.O.P.s Pressured up to 1000#
on blind rams and 1200# on hydril and 4 1/2" rams.
Drilled out and pressured up on cement job to 300# o.k.

January 18th

Drilled 8 3/4" hole from 900' to 1480'
Wt 9.3, Vis. 30

January 19th

Drilled 8 3/4" hole from 1480' to 1876'
Wt 9.1, Vis. 30
Bit No. 1 - 8 3/4" HW XIGJ (945'/34 1/2 hrs.)

January 20th

Drilled 8 3/4" hole from 1876' to 2312'
Wt 9.2, Vis. 34

January 21st

Drilled 8 3/4" hole from 2312' to 2716'
Wt 9.1, Vis. 43
Bit No. 2 - 8 3/4" HW XIG-J (834'/44 hrs.)

January 22nd

Drilled 8 3/4" hole from 2716' to 3060'
Wt 9.3, Vis. 45, W.L. 9.6, Fc. 2/32" pH 8.5
Bit No. 3 - 8 3/4" HW XIG-J (603'/28 hrs.)

January 23rd

Drilled 8 3/4" hole from 3060' to 3578'
Wt 9.3, Vis. 40, W.L. 10, Fc. 2/32" pH 7.2

January 24th

Drilled 8 3/4" hole from 3578' to 3968'
Wt 9.3, Vis. 39, W.L. 10, Fc. 2/32" pH 8.0
Bit No. 4 - 8 3/4" HW XIG (914'/38 3/4 hrs.)

January 25th

Drilled 8 3/4" hole from 3968' to 4144'
Wt 9.3, Vis. 48, W.L. 9.2, pH 8, Fc. 2/32"
Bit No. 5 - 8 3/4" HW XV (145'/14 1/4 hrs.)

January 26th

Drilled 8 3/4" hole from 4144' to 4376'
Wt 9.3, Vis. 70, W.L. 12.2, Fc. 2/32" pH 8.0

January 27th

Drilled 8 3/4" hole from 4376' to 4620'
Wt 9.3, Vis. 50, W.L. 9.4, Fc. 2/32" pH 9.0
Bit No. 6 - 8 3/4" HW X55R (513'/49 hrs.)
Hole tight - 4 stands off bottom

January 28th

Drilled 8 3/4" hole from 4620' to 4697'
Wt 9.1, Vis. 50, W.L. 9.0, Fc. 2/32" pH 9.0
Bit No. 7 HW 8 3/4" ODV (77'/9 hrs.)
Hole tight off bottom. Reamed 20' undergaged
hole to bottom on bit No. 8

January 29th

Drilled 8 3/4" hole from 4697' to 4788'
Wt 9.2, Vis. 65, W.L. 6.8, Fc. 2/32" pH 9.5
Bit No. 8 8 3/4" WDRJ (66'12 3/4 hrs.)
Reamed 40' to bottom on Bit No. 9.

January 30th

Drilled 8 3/4" hole from 4788' to 4807'
Wt 9.2, Vis. 67, W.L. 8.8, Fc. 2/32" pH 8.0
Bit No. 9 - 8 3/4" WD-7 (44'7 1/4 hrs.)
Circulated two hours. Started to make dummy trip to log. Stuck pipe at 4695'. Waited on fishing tools. Ran free point indicator and found pipe stuck at 4400'. Ran Homco string shot and backed pipe off at 4375'. Circulated above fish before pulling out.

January 31st

T.D. 4708'
Pulled out 4 1/2" drill pipe and 7 drill collars. Picked up 6 drill collars off rack. Ran in with Homco jars and bumper sub. Screwed into fish and bumped fish loose. Tried to break circulation, bit plugged. Worked fish loose through tight spot at 4360'. Pulled out of hole and recovered drill collars and bit. Ran in hole with 8 3/4" bit. Circulated hole. Made 10 stand dummy trip to log.

February 1st

T.D. 4807
Pulled out of hole and logged with Schlumberger
Schlumberger IES Log Run No. 1
2" scale 659' to 4808'
5" scale 3860' to 4808'

Schlumberger Borehole Compensated Sonic Run No. 1
2" scale 659' to 4802'
5" scale 3880' to 4802'

Schlumberger Formation Density Gamma Ray and Caliper Run No. 1 - 5" scale 3900' to 4806'

Schlumberger Sidewall Gamma Ray Neutron Porosity Run No. 1
5" scale 3900' to 4806'

Schlumberger Dual Mineral Log Run No. 1 - 3900' to 4806'

Schlumberger Porosity Overlay Run No. 1 - 3900' to 4806'
Started in hole with D.S.T. No. 1

February 2nd

T.D. 4807'
Drill Stem Test No. 1 - 4240-4807 - Ran in 8 3/4" hole
Johnston Testers on dry 4 1/2" D.P. with 2 packers, jars, safety joint, Hydraulic tool, pump out sub, 2 recorders, 1/2" bean. Pre-flow 5 mins. I.S.I. 60 mins. V.O. 60 mins. F.S.I. 60 mins.

Blow: Strong initial puff, good air blow decreasing towards end of test.

Recovered: 3650' of brackish salt water - 69,000 ppm

Charts: I.H.P. 2087#, First flow 1250# - I.S.I.P. 1758#
F.F.P. 1737#, F.S.I.P. 1767# - F.H.H.P. 2087#

Ran in with 8 3/4" bit - circulated hole - pulled out and started in with D.S.T. #2

February 3rd

T.D. 4807'

D.S.T. No. 2 - 4040-4150

Ran in 8 3/4" hole Johnston Testers straddle on 4 1/2" drill pipe, with 4 packers, jars, safety joint, shut in tool, pump out sub, 3 recorders, 1/2" bean. Pre-flow 5 mins. I.S.I. 60 mins. V.O. 30 mins. F.S.I. 60 mins.

Blow: Good air blow throughout test.

Recovered: 220' drilling mud

Charts: I.H.H.P. 1965# First flow 67# I.S.I.P. 1523#
F.F.P. 89#, F.S.I.P. 1320#, F.H.H.P. 1926#

Waited on orders.

Abandonment Plug No. 1 - First Stage 4807' to 4401'

Hung 4 1/2" D.P. at 4807'. Howco pumped in and equalized 165 sacks cement and displaced with 62 bbls. Gel. Plug in place at 11:30 p.m. 2/3/1970

February 4th

Abandonment Plug No. 2 - Second Stage 4401' to 4000'

Hung 4 1/2" D.P. at 4400'. Howco pumped in and equalized 165 sacks cement and displaced with 55 bbls. gel. Cement in place at 1:00 a.m. 2/4/1970

Located Plug No. 1 and 2 at 3970' at 9:00 a.m. 2/4/1970

Abandonment Plug No. 3 - 610' to 710'

Hung 4 1/2" D.P. at 710'. Howco pumped in and equalized 65 sacks cement with 2% Calcium. Cement in place at 11:30 a.m. 2/4/1970

Located Plug No. 3 at 580' at 8:00 p.m. 2/4/1970

Cut casing off 3' below ground level - dumped in 5 sacks cement and welded plate over top. Welded 2" pipe 4' above ground level with well name plate on top.

Rig Released to Contractor at 11:00 p.m. 2/4/1970

SURVEYS

<u>Depth</u>	<u>Degrees</u>
100'	1
200'	1/2
290'	1/8
408'	1/2
500'	1/2
600'	3/4
922'	7/8
1240'	1/2
1547'	1/4
1610'	1/8
1920'	1/8
2200'	1/8
2444'	1/8
2535'	1/8
2626'	1/2
2716'	1/2
2897'	1
2958'	1/2
3017'	1/2
3150'	1/2
3241'	1/8
3331	1/4
3421'	1/2
3512'	1/2
3605'	1/2
3695'	1/2
3783'	1
3843'	1/2
3933'	1/8
4024'	3/4
4106'	1
4620'	1/2

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

WATER ANALYSIS

Lab No. E70-236

Received Feb. 9, 1970 Reported: Feb. 12, 1970 Well location: AMHSS Gulf Redknife 60° 40' N. - 119° 50' W.
 Operator: AMERADA HESS CORPORATION Field or Area: Presquille
 Elev.: K.B. 1258' Grid Zone/Formation: Sample Interval: 4240' - 4807'
 Method of Production: D.S.T. #1 Sampled from: bottom Sampled by: Johnston Testers Date: Feb. 2, 1970
 Limited

OTHER PERTINENT DATA


Recovered: 3550'

(Signed)

Mg./L	Na	K	Ca	Mg	SO ₄	Cl	CO ₃	HCO ₃	
23305			7347	1337	989	51800		544	
1013.75			366.63	109.86	20.56	1460.76		8.92	
Meq. %	34.01		12.30	3.69	0.69	49.01		0.30	

Total Solids Mg./L. By Evaporation 94,417 Fe Very much H₂S N11
 Calculated 85,322 After Ignition 80,919 Refractive Index 1.3489 @25°C Observed pH 6.8 @ 78°F
 Resistivity 0.123 ohm meters @ 68°F

Pattern Unit Meq./L



Remarks and Conclusions: Sample consisted of colourless water with some black sediment. Some organic matter detected in total evaporated solids.

BENZENE CONTENT: No trace of benzene indicated.

Sample was received in a 1 quart metal container without a foil insert in the screw cap. Container was 1/2 full, water was clear.

When taking water samples for benzene analysis, it is recommended that the container be filled as full as possible. Elution of benzene from the water to the vapor space above the sample can appreciably alter the detectable concentration.

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

WATER ANALYSIS

Lab No. E70-231

Received: Feb. 9, 1970 Reported: Feb. 12, 1970 Well: location: AMHSS Gulf Redknife E-55 60° 40' N. - 119° 30' W.
 Operator: AMERADA HESS CORPORATION Field or Area: Sample Interval: 4040' - 4150'
 Elev.: K.B. 1258' Grd. Zone/Formation: Slave Point Sampled by: Johnston Testers Date: Feb. 3, 1970
 Method of Production: D.S.T. #2 Sampled from: bottom Limited

OTHER PERTINENT DATA


Recovered: 220' fluid.

(Signed)

Na	K	Ca	Mg	SO ₄	Cl	CO ₃	HCO ₃
4671		649	187	1668	7340		566
203.21		32.37	15.38	34.69	206.99		9.28
40.49		6.45	3.06	6.91	41.24		1.85

Total Solids Mg/L: By Evaporation 15,309 Fe much Specific Gravity 1.014 @60°F Observed pH 7.8 @ 77°F
 Calculated 15,081 After Ignition 12,036 H₂S nil Refractive Index 1.3356 @75°C Resistivity 0.601 ohm meters @ 68°F

Pattern Unit Meq./L



Remarks and Conclusions: Sample consisted of approximately 45% light brown coloured water and 55% mud. Much organic matter detected in total evaporated solids.

continued.....

CHEMICAL & GEOLOGICAL LABORATORIES LIMITED

OPERATOR: AMERADA HESS CORPORATION REPORT NUMBER: E70-237
DATE SAMPLED: Feb. 3, 1970 DATE RECEIVED: Feb. 9, 1970 DATE REPORTED: Feb. 12, 1970
Kind of Sample: Water Well: AMHES Gulf Redknife E-55 60° 40' N. - 119° 30' W.
Method of Production: D.S.T. #2 Formation: Slave Point Interval: 4040' - 4150'
Sampled from: bottom Sampled by: Johnston Testers Limited Elevation: K.B. 1358'
Recovered: 220' fluid.


BENZENE CONTENT: Trace

Sample was received in a 1 quart plastic container without a foil insert in the screw cap. Container was full, water was muddy.

The use of plastic containers is not recommended for benzene analysis samples, due to the adsorption and diffusion of benzene through the polyethylene. It has been shown that samples can lose significant quantities of benzene or conversely gain appreciable benzene when kept in proximity to a hydrocarbon source. For this reason, this analysis should not be considered as representative of the benzene content of the water source.

Containers suitable for benzene analysis samples may be obtained from this laboratory.

TECHNICAL REPORT

The logo for Johnston is positioned between the words 'REPORT' and 'ART'. It features a stylized 'J' shape formed by two thick, dark arrows. One arrow points downwards from the top of the 'J', and the other points upwards from the bottom of the 'J'. The word 'JOHNSTON' is written in a bold, sans-serif font across the middle of the 'J' shape.

TEST DATA						TOOL SEQUENCE		
Formation	Zone Thickness		Ft	Tool		Length	O.D.	
Interval	4240 To	4807	T.D. 4807	P.C. SUB & SUBS		2.50		
Type of Test	OPEN HOLE, BOTTOM HOLE.			SUB		.60		
Time Started in Hole	2300	Mrs	Tool Opened	0230	Mrs	MFE TOOL	9.00	
First Flow	5	Min	Initial Shut-In	60	Min	BYPASS TOOL	3.00	
Second Flow	60	Min	Second Shut-In		Min	JARS	8.60	
Third Flow		Min	Final Shut-In	60	Min	SAFETY JOINT	1.75	
Pulled Loose Wt	0535	Mrs	Out of Hole	0900	Mrs	S.S. & PACKER	9.35	
Wt Set on Packers	35,000	=	Pulled Loose Wt	10,000	=	T.C. & PACKER	5.40	
Description of Blow During Test				TOTAL		40.20		
STRONG INITIAL PUFF. GOOD AIR BLOW, DECREASING IN 25 MINUTES TO WEAK IN 45 MINS.								
FLUID RECOVERY				Was Test Reverse Circulated Yes ☐ No ☒				
Total Fluid Recovered	3650			Ft				
Description of Fluid Recovered	950' MUDDY, SALT WATER.			RECORDER				
	2700' BRACKISH, SALT WATER.			RECORDER				
				PERF.				
				SUB				
				DRILL PIPE				
				SUB				
				B.N. & PERF.				
				TOTAL INTERVAL				
				567.60				
GAS BLOW MEASUREMENT								
Measured With				I.D. Riser				
Type of Instrument								
Time	Size Choke	Reading per inches	M. Cubic Feet Day					
		NIL						
TOTAL LENGTH 607.80								
Elevation NOT REPORTED.								
Bottom Hole Choke Size 1/2"								
Fluid Cushion Type NIL Amt.								
MUD AND HOLE DATA								
Mud Type GEL & CHEM W.L. 6.0								
Filter Cake 2/32 Visc. 75 Wt. 9.2								
Time Taken								
Contractor CAN-TEX DRLG. Rig No. 1								
Drill Pipe Size 4 1/2 IF - 4 1/2 XH								
Drill Collar Size 2 7/8 ID Length 357.52'								
Main Hole Size 8 3/4"								
Rat Hole Size								
RESISTIVITY				CHLORIDE CONTENT				
Recovery Water	cc	CF	ppm.					
Mud Pit sample filtrate	cc	CF	69,000	ppm.				
District	HIGH LEVEL Ticket No. D 03695		Date		FEBRUARY 2, 1970		Test No. 1 J.T. No. 1	
Company	AMERADA HESS CORPORATION		Address		540-5TH AVENUE S.W.			
Well Name	AMHESS GULF REDKNIFE E-55				CALGARY 1, ALBERTA			
Number	60° 40'N 119° 30'W		Field		WILLOCAT Province NORTH WEST TERRITORIES			
Formation			Co. Rep.		P. MATLOCK			
and Interval	4140 - 4807 DST#1		Technician		H. PALMER			
Distribution of Reports								
6 - CALGARY, 1 - DATA CENTER (ENCLOSED).								




D 03695		PRESSURE DATA		FLUID SAMPLE REPORT	
INSTRUMENT NO.	AK1-3411	AK1-1935		Sample No.	
CAPACITY (gals.)	7100	7000		Type	WATER
INSTRUMENT DEPTH FT.	4261	4266		Depth	4200 ft
INSTRUMENT OPENING	OUTSIDE	OUTSIDE		Volume	2500 c.c.
PRESSURE GRADIENT (psi/ft)					
WELL TEMP. °F	148				
INITIAL HYDROSTATIC	A 2087#	2097#		Sample Pressure:	
FIRST FLOW	B 1250#	1257#		110	psig at Surface
	B-1 1423#	1454#		Gravity	API 68 °F
INITIAL SHUT-IN	C 1758#	1771#		Gas/Oil Ratio	Cu Ft. bbl.
SECOND FLOW	D 1461#	1470#			
	D-1 1737#	1752#			
SECOND SHUT-IN	E			Recovery	
THIRD FLOW	F			Cu Ft. Gas	
	F-1			cc. Oil	
FINAL SHUT-IN	G 1767#	1779#		cc. Water	1700
FINAL HYDROSTATIC	H 2087#	2097#		cc. Mud	
				Total Liquid cc.	1700

PRESSURE INCREMENTS

[illegible]



GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z — Special pressure points such as pumping pressures recorded for formation breakdown.




FIELD
REPORT NO.
D 03695

RECORDER NO.
AK1-3411


CAPACITY
7100

REPORTS
REQUESTED
7





GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z — Special pressure points such as pumping pressures recorded for formation breakdown.



FIELD
REPORT NO.

D 03695

RECORDER NO.


AK1-1935

CAPACITY


7000

REPORTS
REQUESTED

7



TECHNICAL REPORT

The logo for Johnston is positioned between the words 'REPORT' and 'ART'. It features a stylized 'J' composed of two thick, curved arrows: one pointing downwards and to the right, and the other pointing upwards and to the left, creating a circular motion. The word 'JOHNSTON' is printed in a bold, sans-serif font across the middle of the 'J'.

TEST DATA						TOOL SEQUENCE		
Formation	SLAVE POINT	Zone Thickness	Fi	Tool	Length	O.D.		
Interval	4039 To	4150	TD 4807	P.O. SUB	.85			
Type of Test	OPEN HOLE, STRADDLE, CONVENTIONAL.			SUB	.60			
Time Started in Hole	2245	Hrs	Tool Opened	0145	Hrs	MFE TOOL	9.00	
First Flow	5	Min	Initial Shut-In	60	Min	BYPASS TOOL	3.00	
Second Flow	30	Min	Second Shut-In		Min	RECORDER	5.90	
Third Flow		Min	Final Shut-In	60	Min	JARS	8.60	
Pulled Loose ft	0420	Hrs	Out of Hole	0600	Hrs	SAFETY JOINT	1.75	
Wt Set on Packers	35,000	#	Pulled Loose Wt	10,000	#	S.S. & PACKER	9.35	
Description of Blow During Test						T.C. & PACKER	5.40	
GOOD AIR BLOW THROUGHOUT TEST.				TOTAL	44.45			
				STUB.	1.10			
FLUID RECOVERY Was Test Reverse Circulated Yes ☐ No ☒				PERF.	5.00			
Total Fluid Recovered	220		Fi	RECORDER	5.90			
Description of Fluid Recovered	220' DRILLING FLUID.			PERF.	1.50			
				SUB	.80			
				DRILL PIPE	91.88			
				SUB	.80			
				BLANK SUB	.80			
				T.C. & STUB.	3.50			
				TOTAL INTERVAL	111.28			
GAS BLOW MEASUREMENT				PACKER	2.80			
Measured With	I.D. Riser			T.C. & PACKER	6.50			
Type of Instrument				PERF.	24.00			
Time	Size	Choke	Reading psi inches	M	Cubic Feet Day	RECORDER	5.90	
NIL						SUB	.80	
						DRILL PIPE	614.06	
						SUB	.90	
						B.M. & PERF.	2.00	
						TOTAL BELOW INTV.	556.96	
				TOTAL LENGTH	812.69			
				Elevation	NOT REPORTED.			
				Bottom Hole Choke Size	1/2"			
				Fluid Cushion Type	NIL Amt.			
REMARKS TEST SATISFACTORY.				MUD AND HOLE DATA				
RECORDER No. AXI-1935, STYLUS NOT ENGAGED,								
NO PRINTS MADE.								
MFE SAMPLE DRAINED ON LOCATION.								
				Mud Type	W L			
				Filter Cake	Visc	Wt.		
				Time Taken				
				Contractor	CAN-TEX DRLG.	Rig No.	1	
				Drill Pipe Size	4 1/2 IF & 4 1/2 XH			
				Drill Collar Size	2 7/8 ID Length			
				Main Hole Size	8 3/4"			
				Rat Hole Size				
RESISTIVITY				CHLORIDE CONTENT				
Recovery Water	g/l	°F.	ppm.					
Mud Pit sample filtrate	g/l	°F.	ppm.					
District	HIGH LEVEL Ticket No. D 03696			Date	FEBRUARY 3, 1970		Test No. 2 J.T. No. 2	
Company	AMERADA HESS CORPORATION			Address	540-5TH AVENUE S.W.			
Well Name	AMHESS GULF REDKNIFE E-55			CALGARY 1, ALBERTA				
Number	#60° 40'N 119° 30'W			Field	WILDCAT			
Formation	SLAVE POINT			Co. Rep.	P. MATLOCK			
and Interval	4039 - 4150 DST#2			Technician	H. PALMER			
Distribution of Reports								
6 - CALGARY, 1 - DATA CENTER (ENCLOSED).								




D 03696		PRESSURE DATA		FLUID SAMPLE REPORT	
INSTRUMENT NO.	AK1-3411	AK1-1935	AK1-1848	Sample No.	
CAPACITY (cu. ft.)	7100	7000	7100	Type	MUD
INSTRUMENT DEPTH	4009	4046	4184	Depth	ft
INSTRUMENT OPENING				Volume	2500 c.c.
PRESSURE GRADIENT (psi/ft)					
WELL TEMP. °F	145			Sample Pressure	
INITIAL HYDROSTATIC	A 1965#		2026#	10	psi at Surface
FIRST FLOW	B 57#			Gravity	API SG °F
	B-1 67#		A-1 2118#	Gas-Oil Ratio	Cu. Ft. bbl.
INITIAL SHUT-IN	C 1523#		A-2 1561#		
SECOND FLOW	D 80#			Recovery	
	D-1 89#	STYLUS NOT	RAN BELOW	Cu. Ft. Gas	
SECOND SHUT-IN	E	ENGAGED	STRADDLE	cc Oil	
THIRD FLOW	F			cc Water	
	F-1		A-3 2028#	cc Mud	250
FINAL SHUT-IN	G 1320#			Total Liquid cc	250
FINAL HYDROSTATIC	H 1926#		1987#		

PRESSURE INCREMENTS

[illegible]

GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other pecker settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z - Special pressure points such as pumping pressures recorded for formation breakdown.



FIELD
REPORT NO.

D 03696

RECORDER NO.


AKI-3411

CAPACITY


7100

REPORTS
REQUESTED

7



GUIDE TO IDENTIFICATION OF DRILL STEM TEST PRESSURE CHARTS



- A. Initial Hyd. Mud
- B. First Flow
- C. Initial Shut-In
- D. Second Flow
- E. Second Shut-In
- F. Third Flow
- G. Final Shut-In
- H. Final Hyd. Mud

The following points are either fluctuating pressures or points indicating other packer settings (testing different zones).

- A-1, A-2, A-3, etc. Initial Hyd. Pressures
- B, B-1, Initial Flow Pressures
- C, Initial Shut-In
- D-1, D-2, D-3, etc. Second Flow Pressures
- E, Second Shut-In
- F, F-1, F-2, Third Flow Pressures
- G, Final Shut-In
- H, Final Hyd. Pressures
- Z — Special pressure points such as pumping pressures recorded for formation breakdown.




FIELD
REPORT NO.
D 03696

RECORDER NO.
AX1-1848

CAPACITY
7100

REPORTS
REQUESTED
7



CHEMICAL & GEOLOGICAL LABORATORIES LTD.

WATER ANALYSIS

Lab No. E70-236

Received: Feb. 9, 1970 Reported: Feb. 12, 1970

Well: Location:

60° 40' N. - 119° 30' W.

Operator: AMERADA HESS CORPORATION

Field or Area:

Elev.: K.B. 1258' Grd.

Zone/Formation: Presquille

Sample Interval: 4240' - 4807'

Method of Production: D.S.T. #1

Sampled from: bottom

Sampled by: Johnston Testers Limited Date: Feb. 2, 1970

OTHER PERTINENT DATA


Recovered: 3650'

(Signed)

Mg./L	Na	K	Ca	Mg	SO ₄	Cl	CO ₂	HCO ₃	
23305			7347	1337	989	51800		544	
Meq./L									
1013.75			366.63	109.86	20.56	1460.76		8.92	
Meq. %									
34.01			12.30	3.69	0.69	49.01		0.30	

Total Solids Mg/L: by Evaporation 94,417 Fe Very much
 Calculated 85,322 After Ignition 80,919 H₂S Nil
 Specific Gravity 1.065 @60°F Observed pH 6.8 @ 78°F
 Refractive Index 1.3489 @25°C Resistivity 0.123 ohm meters @ 68°F

Pattern Unit Meq./L



Remarks and Conclusions: Sample consisted of colourless water with some black sediment. Some organic matter detected in total evaporated solids.

BENZENE CONTENT: No trace of benzene indicated.

Sample was received in a 1 quart metal container without a foil insert in the screw cap. Container was 1/2 full, water was clear.

When taking water samples for benzene analysis, it is recommended that the container be filled as full as possible. Elution of benzene from the water to the vapor space above the sample can appreciably alter the detectable concentration.

AmHess Gulf Redknife E-55 - Tour
Reports

D.A. 395

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date Feb. 4 1970Rig# 1 Location Amerade 9ders Gulf Reel Knife E-55 Job#

REMARKS															Start	Time	Interval			
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands									
					No.	O.D.	I.D.	Wgt.		FUEL										
										WATER										
TD 4807											RAN PLUG NO 2 SECOND STAGE			12 ⁰⁰						
											4401 To 4000'			1 ⁰⁰	1					
											WOC ON PLUG #1/2			1 ⁰⁰	8 ⁰⁰	7				
Abandonment Plug No 2 Second Stage 4401' to 4000'																				
MUD 12 Mn. 2 a.m. 4 a.m. 6 a.m. Additives											At Surveys Degree			MOTOR HOURS			Next Oil Change			
WEIGHT 7 1/2 D.P. at 4400'. 70000 pumped in and																				
VISCOSITY equalized 165 sacks cement & displaced																				
GEL with 53 bbls bell. cement in place																				
at 1.00 PM 2/4/1970																				
PUMPS No. 1 Pressure S.P.M.																				
Model S.P.M.																				
Liner Size																				
No. 2 Pressure S.P.M.																				
Model S.P.M.																				
Liner Size																				
W.L. F.C. pH.																				
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.)											DRILL COLLARS				FORMATION	OIL	Stands			
											No. O.D. I.D. Wgt.					FUEL				
																WATER				
																CONDITION				
No. Size Type Size Jets Serial No. Weight R.P.M. Ft. Drilled Hrs. Feet Reamed Hrs.																				
BITS																				
D. Collars																				
Other Ft.																				
C.B. Ft.																				
Subs. Ft.																				
Ft. Up On Kelly																				
TOTAL																				
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																				
General																				
W.L. F.C. pH.																				
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.)											DRILL COLLARS				FORMATION	OIL	Stands			
											No. O.D. I.D. Wgt.					FUEL				
																WATER				
																CONDITION				
No. Size Type Size Jets Serial No. Weight R.P.M. Ft. Drilled Hrs. Feet Reamed Hrs.																				
BITS																				
D. Collars																				
Other Ft.																				
C.B. Ft.																				
Subs. Ft.																				
Ft. Up On Kelly																				
TOTAL																				
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																				
General																				
W.L. F.C. pH.																				
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.)											DRILL COLLARS				FORMATION	OIL	Stands			
											No. O.D. I.D. Wgt.					FUEL				
																WATER				
																CONDITION				
No. Size Type Size Jets Serial No. Weight R.P.M. Ft. Drilled Hrs. Feet Reamed Hrs.																				
BITS																				
D. Collars																				
Other Ft.																				
C.B. Ft.																				
Subs. Ft.																				
Ft. Up On Kelly																				
TOTAL																				
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																				
General																				
W.L. F.C. pH.																				
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.)											DRILL COLLARS				FORMATION	OIL	Stands			
											No. O.D. I.D. Wgt.					FUEL				
																WATER				
																CONDITION				
No. Size Type Size Jets Serial No. Weight R.P.M. Ft. Drilled Hrs. Feet Reamed Hrs.																				
BITS																				
D. Collars																				
Other Ft.																				
C.B. Ft.																				
Subs. Ft.																				
Ft. Up On Kelly																				
TOTAL																				
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																				
General																				
W.L. F.C. pH.																				
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.)											DRILL COLLARS				FORMATION	OIL	Stands			
											No. O.D. I.D. Wgt.					FUEL				
																WATER				
																CONDITION				
No. Size Type Size Jets Serial No. Weight R.P.M. Ft. Drilled Hrs. Feet Reamed Hrs.																				
BITS																				
D. Collars																				
Other Ft.																				
C.B. Ft.																				
Subs. Ft.																				
Ft. Up On Kelly																				
TOTAL																				
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																				
General																				
W.L. F.C. pH.																				

Totco Ring on Bit No. _____ D.P. Caliper Date _____ Results _____ Boiler in Operation _____ Toolpusher _____
 B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

DAILY DRILLING REPORT

Date FEB 3 1970

Rig# 1 Location AMERICAN MESS GULF STAL. Red Knife F 55 Job#

REMARKS

[illegible]

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation _____ Toolpusher _____
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

DAILY DRILLING REPORT

Date FEB 3 1970

Rig# 1 Location ANDALUSIA HILLS GOLF. 5TH H. Rd KNIFE EDD Job#

REMARKS

[illegible]

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation _____ Toolpusher _____
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date Feb 2 19 70

Rig# 1 Location ANGADA HILL COLLECTOR ROAD 515 Job#

REMARKS

Rig#		Location		Hess Coll. Ft. H. R. & Knife		Job#		REMARKS		Time																			
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		FUEL		WATER		Stands		Start		Stop		Interval			
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars		Other Ft.		C.B. Ft.	
MUD		12 Mn.		2 a.m.		4 a.m.		4 a.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		Subs. Ft.		Ft. Up On Kelly		TOTAL							
WEIGHT																													
VISCOSITY																													
GEL																													
No. 1		Pres- sure																											
Model		S.P.M.																											
Liner Size																													
No. 2		Pres- sure																											
Model		S.P.M.																											
Liner Size																													
W.L.		F.C.		pH.																									
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		FUEL		WATER		Stands		Company Time		Cont'r Time					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars		Other Ft.		C.B. Ft.	
MUD		8 a.m.		10 a.m.		12 Noon		3 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		Subs. Ft.		Ft. Up On Kelly		TOTAL							
WEIGHT																													
VISCOSITY																													
GEL																													
No. 1		Pres- sure																											
Model		S.P.M.																											
Liner Size																													
No. 2		Pres- sure																											
Model		S.P.M.																											
Liner Size																													
W.L.		F.C.		pH.																									
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		FUEL		WATER		Stands		Company Time		Cont'r Time					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars		Other Ft.		C.B. Ft.	
MUD		4 p.m.		6 p.m.		8 p.m.		10 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		Subs. Ft.		Ft. Up On Kelly		TOTAL							
WEIGHT																													
VISCOSITY																													
GEL																													
No. 1		Pres- sure																											
Model		S.P.M.																											

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher J. W. Long
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date Feb 1 1970Rig# 1 Location AMERINDA HESS GULF FTAL RED KNIFE ESS Job#

REMARKS															Time		
															Start	Stop	Interval
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS			FORMATION		OIL					10:00	10:15	15
					No.	O.D.	I.D.	Wgt.		FUEL	32'						
										WATER							
MUD															10:15	10:30	15
WEIGHT															10:30	10:45	15
VISCOSITY															10:45	11:00	15
GEL															11:00	11:15	15
Additives																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																	
General																	
W.L. F.C. pH.																	
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.) DRILL COLLARS FORMATION OIL FUEL WATER																	
No. O.D. I.D. Wgt.																	
Hrs. Feet Reamed Hrs. CONDITION																	
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
Additives																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																	
General																	
W.L. F.C. pH.																	
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.) DRILL COLLARS FORMATION OIL FUEL WATER																	
No. O.D. I.D. Wgt.																	
Hrs. Feet Reamed Hrs. CONDITION																	
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
Additives																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																	
General																	
W.L. F.C. pH.																	
From Footage To Hrs. on Bottom Wt. Drill String (1000 lbs.) DRILL COLLARS FORMATION OIL FUEL WATER																	
No. O.D. I.D. Wgt.																	
Hrs. Feet Reamed Hrs. CONDITION																	
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
Additives																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
Size TRIPS No. Lines TON MILES TOTAL MILES Slip Feet or Cut Feet Left on Spool Next Slip																	
General																	
W.L. F.C. pH.																	

RIG SERVICE.

CRIC 2.0 100.

HOLE TO LOG

LOCKING

Company Time

Cont'r Time

SCHLUMBERGER LOGGING

Schlumberger logs.

IES 2" scale 659' to 4808'

5" scale 3860' to 4808'

Borehole Compensator Service

2" scale 659' to 4802'

5" scale 3880' to 4802'

Formation Density & Caliper

5" scale 3900' to 4806'

Company Time

Cont'r Time

LOGGING

MAKEUP D.S.T. #1 & RUN TAIL PIPE

Side Wall Neutron Porosity

5" scale 3900' to 4806'

Gamma Ray & Caliper

2" scale 659' to 4806'

Company Time

Cont'r Time

Totco Ring on Bit No. D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by

COPY

DAILY DRILLING REPORT

Date JAN 31 1970

Rig# 1 Location AMERADA MESS GULF REDKNIFE F-55 Job# _____

REMARKS

Rig #		Location		Job #		REMARKS		Time	
								Start	Stop
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)	
No.		Size		Type		Serial No.		Weight	
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S.P.M.							
No. 1		Pressure							
Model		S.P.M.							
No. 2		Pressure							
Model		S							

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher [Signature]
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

DAILY DRILLING REPORT

Date JAN 30 1970

Rig# I Location AMERADA HESS GULF ~~COAST~~ BEDNIKE E-55 Job#

REMARKS

Rig#		Location		Job#		REMARKS		Time																	
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands		Start		Stop		Interval			
4788		194807		2 1/2		82m		18 6 1/4 2 3/4 45						FUEL 76"		46-2 424405		12.00		12.15		1/4			
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
9		8 3/4		WOT		1/2 3/4		19734		45		70		44		79								521.82	
MUD		12 Mn.		2 a.m.		4 a.m.		6 a.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change								C.B. Ft.	
WEIGHT		9.2		9.2		9.2				GEL 3400#		4620 1/2		1										Subs. Ft.	
VISCOSITY		65		65		67								2											
GEL														3										Ft. Up On Kelly 0	
No. 1		Pressure		66										4										TOTAL	
Model		S.P.M.		65										5										4606.87	
Liner Size		6"																						Next Slip	
No. 2		Pressure																							
Model		S.P.M.																							
Liner Size																									
W.L.		8.5		F.C.		1/32		pH.		8.0															
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands									
4407										16 6 1/4 1 1/2 45				FUEL 45		4121405									
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
9		8 3/4		WOT		1/2 3/4		19734		45		70		44		79								521.82	
MUD		8 a.m.		10 a.m.		12 Noon		2 p.m.		A Jilives		At Surveys Degree		MOTOR HOURS		Next Oil Change								C.B. Ft.	
WEIGHT														1										Subs. Ft.	
VISCOSITY														2											
GEL														3										Ft. Up On Kelly 0	
No. 1		Pressure												4										TOTAL	
Model		S.P.M.		6										5										4506.67	
Liner Size		6"																						Next Slip	
No. 2		Pressure																							
Model		S.P.M.																							
Liner Size																									
W.L.		F.C.		pH.																					
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands									
4807										18 6 1/4 1 1/4 45				FUEL		418381									
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
9		8 3/4		WOT		1/2 3/4		19734		45		70		44		7									

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation _____ Toolpusher _____
 B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 26 1970

Rig# I Location AMERDA HESS GULF ETAL RED KNIFE ESS Job#

From		Footage		To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands		REMARKS			Time			
No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	Other Ft.	C.B. Ft.	Subs. Ft.	Ft. Up On Kelly	TOTAL	Start	Stop	Interval	
4144	76	4220	7 1/4	80M	18	6 1/4	2 3/4	45			DRLG	521.28						4220	12.00	12.15	1/4
MUD 12 Mn. 2 a.m. 4 a.m. 6 a.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 8.3 9.3 9.3 9.4 GEL 2000* VISCOSITY 55 43 41 46 BEN-EX 8* GEL PUMPS No. 1 Pressure 650 650 650 650 WATER Model S.P.M. 68 68 68 68 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 75 F.C. 1/32 PH. 8.0																					
B.I.T.S. No. 1 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 190 Hrs. 19 1/2 Feet Reamed 19 1/2 CONDITION DRLG No. 2 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 190 Hrs. 19 1/2 Feet Reamed 19 1/2 CONDITION DRLG MUD 8 a.m. 10 a.m. 12 noon 2 p.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 9.3 9.3 9.3 9.3 1000 VISCOSITY 46 46 47 47 BEN-EX 1000 GEL PUMPS No. 1 Pressure 650 650 650 650 WATER Model S.P.M. 65 65 65 65 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 75 F.C. 1/32 PH. 8.0																					
B.I.T.S. No. 1 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 190 Hrs. 19 1/2 Feet Reamed 19 1/2 CONDITION DRLG No. 2 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 190 Hrs. 19 1/2 Feet Reamed 19 1/2 CONDITION DRLG MUD 8 a.m. 10 a.m. 12 noon 2 p.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 9.3 9.3 9.3 9.3 1000 VISCOSITY 46 46 47 47 BEN-EX 1000 GEL PUMPS No. 1 Pressure 650 650 650 650 WATER Model S.P.M. 65 65 65 65 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 75 F.C. 1/32 PH. 8.0																					
4296	80	4376	7 1/4	80M	18	6 1/4	2 3/4	45			DRLG	521.82						4376	4.00	4.15	1/4
MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 1.4 9.4 9.4 9.3 GEL-900 VISCOSITY 55 50 55 10 BEN-EX 50 GEL PUMPS No. 1 Pressure 700 65 Model S.P.M. 65 65 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 12-2 F.C. 1/32 PH. 8.0																					
B.I.T.S. No. 1 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 270 Hrs. 2 1/2 Feet Reamed 2 1/2 CONDITION DRLG No. 2 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 270 Hrs. 2 1/2 Feet Reamed 2 1/2 CONDITION DRLG MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 1.4 9.4 9.4 9.3 GEL-900 VISCOSITY 55 50 55 10 BEN-EX 50 GEL PUMPS No. 1 Pressure 700 65 Model S.P.M. 65 65 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 12-2 F.C. 1/32 PH. 8.0																					
B.I.T.S. No. 1 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 270 Hrs. 2 1/2 Feet Reamed 2 1/2 CONDITION DRLG No. 2 Size 7 1/4 Type XSSR Serial No. 16828 Weight 45 R.P.M. 35 Ft. Drilled 270 Hrs. 2 1/2 Feet Reamed 2 1/2 CONDITION DRLG MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. Additives At Surveys Degree MOTOR HOURS Next Oil Change WEIGHT 1.4 9.4 9.4 9.3 GEL-900 VISCOSITY 55 50 55 10 BEN-EX 50 GEL PUMPS No. 1 Pressure 700 65 Model S.P.M. 65 65 No. 2 Pressure 1000 1000 Model S.P.M. 1000 1000 W.L. 12-2 F.C. 1/32 PH. 8.0																					

Totco Ring on Bit No. D.P. Calipered Date Results Boiler in Operation Toolpusher
 B.O.P. Test-Operated Time Results Approved by

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 27 1970

Rig# I Location AMERADA HESS GULF ETAL RED KNIFE E-55 Job#

From		Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands	REMARKS				
						No.	O.D.	I.D.	Wgt.				Start	Stop	Interval		
4376		30	4466	7 3/4	80	18	6 1/4	2 3/4	45	SLAVE PT.	FUEL	3912.87	12.00	12.15	1/4		
											WATER	Singles	12.15	8.00	7 3/4		
B I T S		No. 6	Size 8 3/4	Type X55H	Size Jets 3/2	Serial No. 16828	Weight 45	R.P.M. 35	Ft. Drilled 360	Hrs. 34 3/4	Feet Reamed	Hrs.	CONDITION DRLG				
												D. Collars 521.82					
												Other Ft.					
												C.B. Ft.					
												Subs. Ft.					
												Ft. Up On Kelly 10					
												TOTAL 4466					
MUD		12 Mn.	2 a.m.	4 a.m.	6 a.m.	Additives				At Surveys Degree	MOTOR HOURS	Next Oil Change					
WEIGHT		9.3	9.3	9.3	9.3	GEL. 1200#				4106	10	1					
VISCOSITY		57	43	44	48	BENEX-4#						2					
GEL						PECTEX-200#						3					
P U M P S		No. 1	Pressure 700	700	700	700	CAUSTIC. 100#						4				
		Model 33	S.P.M. 70	70	70	70							5				
		Liner Size 6"					Size 1 1/2	TRIPS 59	No. Lines 6	TON MILES	TOTAL MILES 3185	Slip	Feet or	Cut	Feet Left on Spool 2245	Next Slip 3176	
		No. 2	Pressure					General									
		Model 16	S.P.M.														
		Liner Size															
W.L.		8.8 F.C. 1/32 PH 9.0															
4466		37	4553	7 1/4	80	18	6 1/4	2 3/4	45	FORMATION	OIL	4003.27	8.00	8.15	1/4		
											FUEL	Singles	8.15	4.00	7 1/4		
											WATER	DRLG					
B I T S		No. 6	Size 8 3/4	Type X55H	Size Jets 3/2	Serial No. 16828	Weight 45	R.P.M. 35	Ft. Drilled 447	Hrs. 44 1/2	Feet Reamed	Hrs.	CONDITION DRLG				
												D. Collars 521.82					
												Other Ft.					
												C.B. Ft.					
												Subs. Ft.					
												Ft. Up On Kelly 13					
												TOTAL 4553					
MUD		8 a.m.	10 a.m.	12 Noon	2 p.m.	Additives				At Surveys Degree	MOTOR HOURS	Next Oil Change					
WEIGHT		9.3	9.1	9.1	9.1	GEL-3000#						1					
VISCOSITY		18	41	41	50	HINEX-50#						2					
GEL						SANDUST-30 SACKS						3					
P U M P S		No. 1	Pressure 650	650	650	650	HINEX-6#						4				
		Model 300	S.P.M. 65	65	65	65	WATER						5				
		Liner Size 6"					Size 1 1/2	TRIPS 59	No. Lines 6	TON MILES	TOTAL MILES 3185	Slip	Feet or	Cut	Feet Left on Spool 2245	Next Slip 3176	
		No. 2	Pressure					General									
		Model 16	S.P.M.														
		Liner Size															
W.L.		9.2 F.C. 1/32 PH 9.0															
4553		67	4620	6 1/2	82	18	6 1/4	2 3/4	45	FORMATION	OIL	4063.39	4.00	4.15	1/4		
											FUEL	Singles	4.15	10.45	6 1/2		
											WATER	Drill 8 3/4 hole					
B I T S		No. 6	Size 8 3/4	Type X55H	Size Jets 3/2	Serial No. 16828	Weight 45	R.P.M. 35	Ft. Drilled 513	Hrs. 49	Feet Reamed	Hrs.	CONDITION HOLT				
												D. Collars 521.82					
												Other Ft.					
												C.B. Ft.					
												Subs. Ft.					
												Ft. Up On Kelly 631					
												TOTAL 4620					
MUD		4 p.m.	6 p.m.	8 p.m.	10 p.m.	Additives				At Surveys Degree	MOTOR HOURS	Next Oil Change					
WEIGHT		9.3	9.4	9.3	7.3	1000				4620	1 1/2	1					
VISCOSITY		54	60	53	50	BENEX-150						2					
GEL						PECTEX-100						3					
P U M P S		No. 1	Pressure 700					E.M.C. 100#						4			
		Model 300	S.P.M.											5			
		Liner Size 6"					Size 1 1/2	TRIPS 59	No. Lines 6	TON MILES	TOTAL MILES 3185	Slip	Feet or	Cut	Feet Left on Spool 2245	Next Slip 3176	
		No. 2	Pressure					General									
		Model 16	S.P.M.														
		Liner Size															
W.L.		9.4 F.C. 1/32 PH 9.0															

Totco Ring on Bit No.

D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 28 1970

Rig# 1 Location AMERADA DESS GULF BYE RED KNIFE E-55 Job# _____

REMARKS															Start	Time	Interval
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands						
4620	12	4632	1 1/4	82	No.	O.D.	I.D.	Wgt.		FUEL	409353						
										WATER	68"						
Singles															12.00	12.15	1/4
BIG SER.															12.15		
PUMP OUT WORK TIGHT																	
PIPE 4/20 TO 4/100															2.00	1 1/4	
TRIP OUT															2.00	3.30	1 1/2
SLIP LINE															3.30	3.45	1/4
RUN IN BIT #7															3.45	5.45	2
CLEAN 40' TO BTM															5.45	6.15	1/2
DRUG 8 3/4" HOLE															6.15	8.00	1 3/4
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
PUMPS																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
W.L.																	
F.C.																	
pH.																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
C.B. Ft.																	
Subs. Ft.																	
Ft. Up On Kelly																	
TOTAL																	
Slip																	
Feet Left on Spool																	
Next Slip																	
Company Time																	
Cont'r Time																	
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands						
4632	1.5	4697	7 1/4		No.	O.D.	I.D.	Wgt.		FUEL	409353						
										WATER	66"						
Singles															8.00	8.15	1/4
BIG SER.															8.15	8.30	1/4
TRIP OUT															8.30	8.45	1/4
SLIP LINE																	
RUN IN BIT #7																	
CLEAN 40' TO BTM																	
DRUG 8 3/4" HOLE																	
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
PUMPS																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
W.L.																	
F.C.																	
pH.																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
C.B. Ft.																	
Subs. Ft.																	
Ft. Up On Kelly																	
TOTAL																	
Slip																	
Feet Left on Spool																	
Next Slip																	
Company Time																	
Cont'r Time																	
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	Stands						
4697					No.	O.D.	I.D.	Wgt.		FUEL	409353						
										WATER	66"						
Singles															8.45	8.55	1/4
BIG SER.															8.55	9.05	1/4
TRIP OUT															9.05	9.15	1/4
SLIP LINE																	
RUN IN BIT #7																	
CLEAN 40' TO BTM																	
DRUG 8 3/4" HOLE																	
MUD																	
WEIGHT																	
VISCOSITY																	
GEL																	
PUMPS																	
No. 1 Pressure																	
Model S.P.M.																	
Liner Size																	
No. 2 Pressure																	
Model S.P.M.																	
Liner Size																	
W.L.																	
F.C.																	
pH.																	
At Surveys Degree																	
MOTOR HOURS																	
Next Oil Change																	
C.B. Ft.																	
Subs. Ft.																	
Ft. Up On Kelly																	
TOTAL																	
Slip																	
Feet Left on Spool																	
Next Slip																	
Company Time																	
Cont'r Time																	

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher J. M. Kelly
 B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

DAILY DRILLING REPORT

Date JAN 29 19 70

Rig# I Location AMERADA HESS GULF ETAL RED KNIFE E-55 Job#

[illegible]

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher Melroy
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date Jan 23 1970

Rig# 1 Location AMERADA HESS GULF FT. AL. RED KNIFE ESS Job#

Rig# 1 Location AMERADA HESS GULF FT. AL. RED KNIFE ESS Job#															REMARKS		Time						
															Start	Stop	Interval						
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS				FORMATION		OIL		Stands					
2060		158		3218		7 1/2		70M		No. 8		O.D. 6 1/2 I.D. 2 3/8 Wgt. 45						2000					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION	
4		3 1/4		XIG		3-22		17634		30		100		172		8 1/4						dry	
MUD															At Surveys Degree		MOTOR HOURS		Next Oil Change				
WEIGHT															3150		112						
VISCOSITY																							
GEL																							
PUMPS																							
No. 1		Pressure		650																			
Model		S.P.M.		65																			
No. 2		Pressure																					
Model		S.P.M.																					
Liner Size																							
W.L. 11.5 F.C. 2/32 PH.																							
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS				FORMATION		OIL		Stands					
3218		1200		3418		7 1/4		70M		No. 8		O.D. 6 1/2 I.D. 2 3/8 Wgt. 45						2000					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION	
4		3 1/4		XIG		3-22		17634		30		100		372		15 1/2						dry	
MUD															At Surveys Degree		MOTOR HOURS		Next Oil Change				
WEIGHT															3241		110						
VISCOSITY															3331		110						
GEL																							
PUMPS																							
No. 1		Pressure		650																			
Model		S.P.M.		72																			
No. 2		Pressure																					
Model		S.P.M.																					
Liner Size																							
W.L. 11.5 cc. F.C. 2/32 PH. 7.4																							
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS				FORMATION		OIL		Stands					
3418		160		3578		7 1/4		70		No. 8		O.D. 6 1/2 I.D. 2 3/8 Wgt. 45						3009.57					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION	
4		3 1/4		XIG		3-22		17634		30		100		632		37 1/2						DRAG	
MUD															At Surveys Degree		MOTOR HOURS		Next Oil Change				
WEIGHT															3471		110						
VISCOSITY															3512		110						
GEL																							
PUMPS																							
No. 1		Pressure		650																			
Model		S.P.M.		65																			
No. 2		Pressure																					
Model		S.P.M.																					
Liner Size																							
W.L. 11.5 cc. F.C. 2/32 PH. 7.4																							
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS				FORMATION		OIL		Stands					
3418		160		3578		7 1/4		70		No. 8		O.D. 6 1/2 I.D. 2 3/8 Wgt. 45						3009.57					
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION	
4		3 1/4		XIG		3-22		17634		30		100		632		37 1/2						DRAG	
MUD															At Surveys Degree		MOTOR HOURS		Next Oil Change				
WEIGHT															3471		110						
VISCOSITY															3512		110						
GEL																							
PUMPS																							
No. 1		Pressure		650																			
Model		S.P.M.		65																			
No. 2		Pressure																					
Model		S.P.M.																					
Liner Size																							
W.L. 11.5 cc. F.C. 2/32 PH. 7.4																							

Company Time Cont'r Time

RIG SER Y POSS. O.K.
DRAG 8 3/4" HOLE
SURVEY @ 3241 - 1/8"
DRAG 8 3/4" HOLE
SURVEY @ 3331 - 1/8"
DRAG 8 3/4" HOLE
SURVEY @ 3421

Company Time Cont'r Time

RIG SERVICE
SURVEY @ 3421
DRAG
SURVEY @ 3512
DRAG

Company Time Cont'r Time

Boiler in Operation ☒ Toolpusher *J. M. H.*
Approved by *J. M. H.*

Totco Ring on Bit No. D.P. Caliper Date

B.O.P. Test-Operated Time

Results

Results

CONSERVATION BOARD COPY

Date Jan 24 1970

Rig# 1 Location AMERADA HESS GUNF ETAL KAY KNIFE ESS Job#

Rig#		Location		Job#		REMARKS		Time											
								Start	Stop										
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands			
3578		175		3753		7 1/4		70m		18 6 1/4 2 1/8 45						3190.33			
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		CONDITION	
4		8 3/4		XIG		7-20		17634		30		100		706		30		dry	
MUD		12 Mn.		2 a.m.		4 a.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change					
WEIGHT		9.4		1.1		1.3		7.3		GEL-2000 #		3605		1/2		1			
VISCOSITY		40		48		46		40		BENEX-8 #		3695		1/2		2			
GEL										NO STICK 2 gals						3			
No. 1		Pressure		150						DIESEL 40 GAL						4			
Model		S.P.M.		35												5			
No. 2		Pressure								Size		TRIPS		No. Lines		TON MILES		TOTAL MILES	
Model		S.P.M.								1 1/8		57		6		3018		2245	
W.L.		11.8		F.C.		7/32		pH.											
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands			
3753		170		3923		7 1/4		70m		18 6 1/4 2 3/8 45						3370.93			
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		CONDITION	
4		8 3/4		XIG		7-20		17634		30		100		876		37 1/2		dry	
MUD		8 a.m.		10 a.m.		12 Noon		2 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change			
WEIGHT		9.3		9.2		9.2		9.2		GEL-3000 #		3793		10		1			
VISCOSITY		38		45		42		40		BENEX-12 #		3843		30		2			
GEL										NO-STICK 4 gals.						3			
No. 1		Pressure		475		675		675		DIESEL 45 gals.						4			
Model		S.P.M.		72		72		72		Soda Ash 5L #		CINC 100 #				5			
No. 2		Pressure								Size		TRIPS		No. Lines		TON MILES		TOTAL MILES	
Model		S.P.M.								1 1/8		57		6		3018		2245	
W.L.		10.0		F.C.		7/32		pH.											
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands			
3923		45		3968		7 1/2		76m		18 6 1/4 2 3/8 45						3370.73			
No.		Size		Type		Size Jets		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		CONDITION	
4		8 3/4		XIG		7-20		17634		30		100		914		39 1/2		dry	
MUD		4 p.m.		6 p.m.		8 p.m.		10 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change			
WEIGHT		9.2		T		1		4		GEL-1000 #		3933		3		1			
VISCOSITY		110		T		1		4		BENEX-8 #						2			
GEL										WATER 1-1/2 drum						3			
No. 1		Pressure		175				600								4			
Model		S.P.M.		65				65								5			
No. 2		Pressure								Size		TRIPS		No. Lines		TON MILES		TOTAL MILES	
Model		S.P.M.								1 1/8		54		6		81		3099	
W.L.		F.C.																	

Totco Ring on Bit No. _____ D.P. Calipered Date _____

B.O.P. Test-Operated

Time

Results

Results

Boiler in Operation. OK

Toolpusher

Approved

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 25 1970

Rig# 1 Location AMERADA HESS GULF ETAL RED KNIFE Job# E-55

REMARKS															Time					
															Start	Stop	Interval			
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	25760	Stands	RIG SER.					12:00	12:15	1/4
5968	100	4068	7 1/2	78	No.	O.D.	I.D.	Wgt.		FUEL	54"	3521.52	DRUG 8 3/4" HOLE					12:15	4:30	4 1/4
												Singles								
												521.82	SURVEY @ 4024 - 3/4					4:30	4:45	1/4
												Other Ft.	DRUG 8 3/4" HOLE					4:45	8:00	3 1/4
												C.B. Ft.								
												Subs. Ft.								
												Ft. Up On Kelly	1100							
												TOTAL	4068							
												Next Slip								
												Slip								
												Feet or								
												Cut								
												Feet Left on Spool	2245					3176		
												Next Slip								
												General								
												W.L.	9.2					F.C. 1/32		
												pH.	8.0							
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL		Stands	RIG SERVICE / BOP					8:00	8:15	1/4
4068	38	4106	6	78	No.	O.D.	I.D.	Wgt.		FUEL	54"	3551.62	DRUG 8 3/4" HOLE					8:15	2:15	6
												Singles								
												521.82	SURVEY					2:15	2:30	1/4
												Other Ft.	HOLE T.					2:30	4:00	1 1/2
												C.B. Ft.								
												Subs. Ft.								
												Ft. Up On Kelly	8							
												TOTAL	4106							
												Next Slip								
												Slip								
												Feet or								
												Cut								
												Feet Left on Spool	2245					3176		
												Next Slip								
												General								
												W.L.	4.6					F.C. 1/32		
												pH.	8.0							
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL		Stands	RIG SERVICE + CHECK BLIND RAME					4:00	4:15	1/4
4106	38	4144	4 1/4	80	No.	O.D.	I.D.	Wgt.		FUEL		3551.62	WORK ON PUMP					4:15	5:45	1 1/2
												Singles								
												521.82	RUN IN					5:45	7:15	1 1/2
												Other Ft.	CLEAN 40' TO BTM					7:15	7:45	1/2
												C.B. Ft.	DRILL 8 3/4" HOLE					7:45	12:00	4 1/4
												Subs. Ft.								
												Ft. Up On Kelly	30.51							
												TOTAL	4144							
												Next Slip								
												Slip								
												Feet or								
												Cut								
												Feet Left on Spool	2245					3176		
												Next Slip								
												General								
												W.L.	F.C.					pH.		

Totco Ring on Bit No.

D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by

CONSERVATION BOARD COPY

Date JAN 25 19 70

REMARKS

From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	25760	Stands	3521.52	RIG SER.	12:00	12:15	1/4		
3968	100	4068	7 1/2	78	No.	O.D.	I.D.	Wgt.		FUEL	54"	Singles		DRLG 8 3/4" HOLE	12:15	4:30	9 1/4		
										WATER									
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	SURVEY @ 4024- 3/4	4:30	4:45	1/4		
	5	8 3/4	XV	OPEN	18246	30	100	107	8 1/4				Other Ft.	DRLG 8 3/4" HOLE	4:45	8:00	3 1/4		
														C.B. Ft.					
PUMPS	MUD				12 Mm.	2 a.m.	4 a.m.	6 a.m.	Additives	At Surveys Degree		MOTOR HOURS	Next Oil Change	Subs. Ft.					
	WEIGHT				9.3	9.3	9.3	9.3	GEL - 1900*	4024 3/4		1							
	VISCOSITY				40	45	44	48	BEN-IX 8"			2							
	GEL								CHIC 101"			3							
	No. 1	Pres- sure	600	600	600	600								4					
	Model	S.P.M.	72	72	72	72								5					
	Liner Size				6"														
	No. 2	Pres- sure					Size	TRIPS	No. Lines	TON MILES	TOTAL MILES	Slip	Feet Cut	Feet Left on Spool	Next Slip				
	Model	S.P.M.																	
	Liner Size																		
W.L. 7.2 F.C. 7/32 PH. 80																			
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL		Stands	3551.62	RIG SERVICE / BOP	8:00	8:15	1/4		
4068	38	4106	6	78	No.	O.D.	I.D.	Wgt.		FUEL	54"	Singles		DRLG 8 3/4" HOLE	8:15	2:15	1/4		
										WATER									
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	SURVEY	2:15	2:30	1/4		
	5	8 3/4	XV	OPEN	18246	300	100	143	14 1/4				Other Ft.	HAIST.	2:30	4:00	1 1/2		
														C.B. Ft.					
PUMPS	MUD				8 a.m.	10 a.m.	12 Noon	2 p.m.	Additives	At Surveys Degree		MOTOR HOURS	Next Oil Change	Subs. Ft.					
	WEIGHT				9.3	9.3	9.3		WATER - 1/2 stream			1							
	VISCOSITY				50	52	51					2							
	GEL											3							
	No. 1	Pres- sure	600	600	600								4						
	Model	S.P.M.	70	70	70								5						
	Liner Size				6"														
	No. 2	Pres- sure				Size	TRIPS	No. Lines	TON MILES	TOTAL MILES	Slip	Feet Cut	Feet Left on Spool	Next Slip					
	Model	S.P.M.																	
	Liner Size																		
W.L. 2.6 F.C. 3/32 PH. 80																			
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL		Stands	3551.62	RIG SERVICE + CHECK BUMP PUMPS	4:15	4:15	1/4		
4106	38	4144	4 1/4	80	No.	O.D.	I.D.	Wgt.		FUEL		Singles	10.07	WORK ON PUMP	4:15	5:45	1 1/2		
										WATER									
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	RUN IN	5:45	7:15	1 1/2		
	6	8 3/4	XSSR 2-2 1/2		16828	40-45	35	38	4 1/4			only	Other Ft.	CLEAN 40' TO BTM	7:15	7:45	1/2		
														C.B. Ft.	DRILL 8 3/4" HOLE	7:45	12:00	4 1/4	
PUMPS	MUD				4 p.m.	6 p.m.	8 p.m.	10 p.m.	Additives	At Surveys Degree		MOTOR HOURS	Next Oil Change	Subs. Ft.					
	WEIGHT								1.4	4100 10		1							
	VISCOSITY								65			2							
	GEL											3							
	No. 1	Pres- sure	600	600	600								4						
	Model	S.P.M.											5						
	Liner Size				6"														
	No. 2	Pres- sure				Size	TRIPS	No. Lines	TON MILES	TOTAL MILES	Slip	Feet Cut	Feet Left on Spool	Next Slip					
	Model	S.P.M.																	
	Liner Size																		

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher J. M. Elger
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 20 19 70Rig# 1 Location AMERADA HESS GULF ETAL RED KNIFE ESS Job#

From		Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION	OIL	FUEL	WATER	Stands	REMARKS			Time			
						No.	O.D.	I.D.	Wgt.							Start	Stop	Interval			
1816		142	2019	7 1/2	60M	4	6 1/2	2 1/8	42					17	RIG SERVICE			12:00	12:15	1/4	
2		8 3/4	X16	7-16	19727	30M	180		1408	20				1563.53	DRILL 8 3/4" hole			12:15	2:30	2 1/4	
B		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	SURVEY			2:30	2:45	1/4	
I															Other Ft.	DRILL 8 3/4" hole			2:45	2:50	5 1/4
T															C.B. Ft.						
S															Subs. Ft.						
															Ft. Up On Kelly	5:26					
															TOTAL	2018					
MUD		42 Mn.	2 a.m.	4 a.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change								
WEIGHT		30	9.2	30	GEL - BENEX 4100 #				1920		1										
VISCOSITY		30	9.2	30	BENEX 4100 #						2										
GEL		650	70	65							3										
P		No. 1	Pressure	650							4										
U		Model	S.P.M.	65							5										
M		No. 2	Pressure	65																	
P		Model	S.P.M.	65																	
S		No. 2	Pressure	65																	
		Model	S.P.M.	65																	
		Liner Size	6"																		
		General	2915																		
2018		155	2173	7 3/4	60M	4	6 1/2	2 1/8	42					17	RIG SER. 1 B.O.P. C-1 FCK			8:00	8:15	1/4	
2		8 3/4	X16	7-16	19727	30M	100		863	27 3/4				1774.32	DRILL 8 3/4" HOLE			8:15	4:00	7 3/4	
B		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars							
I															Other Ft.						
T															C.B. Ft.						
S															Subs. Ft.						
															Ft. Up On Kelly	0					
															TOTAL	2173.92					
MUD		8 a.m.	10 a.m.	12 Noon	2 p.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change							
WEIGHT		30	9.2	30	9.2	GEL. 2500 #						1									
VISCOSITY		30	9.2	30	9.2	BENEX. 5000 #						2									
GEL		650	70	650	70							3									
P		No. 1	Pressure	650	70							4									
U		Model	S.P.M.	72	72							5									
M		No. 2	Pressure	650	70																
P		Model	S.P.M.	72	72																
S		No. 2	Pressure	650	70																
		Model	S.P.M.	72	72																
		Liner Size	6"																		
		General	Dump 6 CLEAN TANKS																		
2173		136	2173	7 1/2	60M	4	6 1/2	2 1/8	42					17	RIG SERVICE			4:00	4:15	1/4	
2		8 3/4	X16	7-16	19727	30	100		602	34				1924.92	DRILL 8 3/4" HOLE			4:15	5:45	1 3/4	
B		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars	SURVEY @ 2200			5:45	6:00	15	
I															Other Ft.	DRILL			6:00	12:00	6
T															C.B. Ft.						
S															Subs. Ft.						
															Ft. Up On Kelly						
															TOTAL	1217					
MUD		4 p.m.	6 p.m.	8 p.m.	10 p.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change							
WEIGHT		30	9.1	30	9.1	GEL - 4600 #				2200		1									
VISCOSITY		30	31	32	34	BENEX 416 #						2									
GEL		650	650	650	650	WATER - 1 Stream						3									
P		No. 1	Pressure	650	650	NO SICK - 6 GALLONS						4									
U		Model	S.P.M.	65	65							5									
M		No. 2	Pressure	65	65																
P		Model	S.P.M.	65	65																
S		No. 2	Pressure	65	65																
		Model	S.P.M.	65	65																
		Liner Size	6"																		
		General	2915																		

Totco Ring on Bit No. _____ D.P. Celipered Date _____

Results _____

Boiler in Operation YesToolpusher J. Melish

B.O.P. Test-Operated _____ Time _____

Results _____

Approved by _____

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 21 1970

Rig# 1 Location AMERADA HESS GULF ETLA RED KNIFE ESS Job#

REMARKS															Time								
															Start	Stop	Interval						
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION		OIL	Stands		R.C. SERVICE			12 ⁰⁰	12 ¹⁵	1/4				
2312	105	2417	7 1/4	60 m	No.	O.D.	I.D.	Wgt.			FUEL	2015.20											
Singles															30.15	DRILL 8 3/4 hole			12 ¹⁵	8 ⁰⁰	7 3/4		
D. Collars															358.60								
Other Ft.																							
C.B. Ft.																							
Subs. Ft.																							
Ft. Up On Kelly															27.95								
TOTAL															2417								
MUD																							
WEIGHT																							
VISCOSITY																							
GEL																							
PUMPS																							
No. 1 Pressure																							
Model S.P.M.																							
Liner Size																							
No. 2 Pressure																							
Model S.P.M.																							
Liner Size																							
W.L.																							
F.C.																							
pH.																							
From																							
Footage																							
To																							
Hrs. on Bottom																							
Wt. Drill String (1000 lbs.)																							
DRILL COLLARS																							
FORMATION																							
OIL																							
FUEL																							
WATER																							
Stands															213.26			RIG SER & B.O.P.S. & MOTOR SHUT OFF			8.00	8.15	1/4
Singles															358.60			DRILL 8 3/4 HOLE			8.15	9.15	1
D. Collars															358.60			SURVEY @ 2444 - 1/2			9.15	9.30	1/4
Other Ft.																		BOUND TRIP BIT = 2			9.30	12.00	2 1/2
C.B. Ft.																		DRILL 8 3/4 HOLE			12.00	3.30	3 1/2
Subs. Ft.																		SURVEY @ 2535 - 1/2			3.30	3.45	1/4
Ft. Up On Kelly															0			DRILL			3.45	4.00	1/4
TOTAL															2535.8								
MUD																							
WEIGHT																							
VISCOSITY																							
GEL																							
PUMPS																							
No. 1 Pressure																							
Model S.P.M.																							
Liner Size																							
No. 2 Pressure																							
Model S.P.M.																							
Liner Size																							
W.L.																							
F.C.																							
pH.																							
From																							
Footage																							
To																							
Hrs. on Bottom																							
Wt. Drill String (1000 lbs.)																							
DRILL COLLARS																							
FORMATION																							
OIL																							
FUEL																							
WATER																							
Stands															2286.90			RIG SERVICE			4.00	4.15	1/4
Singles															30.94			DRILL 8 3/4 HOLE			4.15	7.15	3
D. Collars															358.60			SURVEY			7.15	7.30	1/4
Other Ft.																		DRILL			7.30	11.45	4 1/4
C.B. Ft.																		SURVEY			11.45	12.00	1/4
Subs. Ft.																							
Ft. Up On Kelly															30.70								
TOTAL															2286.90								
MUD																							
WEIGHT																							
VISCOSITY																							
GEL																							
PUMPS																							
No. 1 Pressure																							
Model S.P.M.																							
Liner Size																							
No. 2 Pressure																							
Model S.P.M.																							
Liner Size																							
W.L.																							
F.C.																							
pH.																							
From																							
Footage																							
To																							
Hrs. on Bottom																							
Wt. Drill String (1000 lbs.)																							
DRILL COLLARS																							
FORMATION																							
OIL																							
FUEL																							
WATER																							
Stands															2286.90								
Singles															30.94								
D. Collars															358.60								
Other Ft.																							
C.B. Ft.																							
Subs. Ft.																							
Ft. Up On Kelly															30.70								
TOTAL															2286.90								
MUD																							
WEIGHT																							
VISCOSITY																							
GEL																							
PUMPS																							
No. 1 Pressure																							
Model S.P.M.																							
Liner Size																							
No. 2 Pressure																							
Model S.P.M.																							
Liner Size																							
W.L.																							
F.C.																							
pH.																							

Totco Ring on Bit No.

D.P. Caliper Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date Jan 22 1970

Rig# 1 Location AMERADA HESS GULF ETAN RED KNIFE ESS Job# 27

From															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															REMARKS															Time																																																																																																																																															
2116															159															2815															7 1/2															62m															No. 4															2 1/2															2 1/2															42																																																																											Start			Stop			Interval																																																																																												
MUD															12 Mn.															2 a.m.															4 a.m.															4 a.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change																																																																																																																																																																													
WEIGHT															9.3															9.3															9.3															9.3															GEL															500*																																																																																																																																																																																																											
VISCOSITY															55															55															55															55															GEL															2																																																																																																																																																																																																											
GEL																																																																																																																																																																																																																																																																																																					
PUMPS															No. 1															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																							
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
No. 2															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																						
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
Liner Size															6"																																																																																																																																																																																																																																																																																						
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							
From															2815															Footage															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															REMARKS															Time																																																																																																																	
2815															60															3060															3															70															12															1 1/2															2 1/2															42																																																																																																																																																																													
MUD															8 a.m.															10 a.m.															12 Noon															2 p.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change																																																																																																																																																																													
WEIGHT															9.3															9.3															9.3															9.3															GEL															500*																																																																																																																																																																																																											
VISCOSITY															42															42															42															42															GEL															2																																																																																																																																																																																																											
GEL																																																																																																																																																																																																																																																																																																					
PUMPS															No. 1															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																							
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
No. 2															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																						
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
Liner Size															6"																																																																																																																																																																																																																																																																																						
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							
From															3000															Footage															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															REMARKS															Time																																																																																																																	
3000															60															3060															3															70															12															1 1/2															2 1/2															42																																																																																																																																																																													
MUD															4 p.m.															6 p.m.															8 p.m.															10 p.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change																																																																																																																																																																													
WEIGHT															9.3															9.3															9.3															9.3															GEL															500*																																																																																																																																																																																																											
VISCOSITY															42															42															42															42															GEL															2																																																																																																																																																																																																											
GEL																																																																																																																																																																																																																																																																																																					
PUMPS															No. 1															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																							
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
No. 2															Size															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																						
Model															S.P.M.															550																																																																																																																																																																																																																																																																							
Liner Size															6"																																																																																																																																																																																																																																																																																						
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							

Totco Ring on Bit No. D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 18 1950

Rig# 1 Location INDIAN HESS GULF AT-HL RD KNIFE 155 Job#

From															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															Stands															Singles															REMARKS															Time																																																																																																																	
Footage															Type															Size Jets															Serial No.															Weight															R.P.M.															Ft. Drilled															Hrs.															Feet Reamed															Hrs.															CONDITION															D. Collars															Other Ft.															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL															Start			Stop			Interval																																
900															170															1070															72															50															17															63															26															119																																													1.10																														646.28															116 SURVEY																														12 ⁰⁰			12 ¹²			2																																															
1															8 1/2															X16															3-15															11610															30															100															405															114																														DRLG															358.60															SURVEY															DRIG																																																																																										12 ¹⁵			12 ⁴⁵			2 1/2		
MUD															12 Mn.															2 a.m.															4 a.m.															6 a.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																																																																																																	
WEIGHT															84															32															34															38															GEL															1000															922															3															1																																																																																																																																																														
VISCOSITY															30															32															34															38															GEL															BICARB 3.00"																																																																																																																																																																																																											
PUMPS															No. 1															Pressure															900															900															900															900															Additives																																																																																																																																																																																												
Model															S.P.M.															60															60															60															60																																																																																																																																																																																																																										
Liner Size															6"															6"															6"															6"																																																																																																																																																																																																																																									
No. 2															Pressure																																																																																																																																																																																																																																																																																						
Model															S.P.M.																																																																																																																																																																																																																																																																																						
Liner Size																																																																																																																																																																																																																																																																																																					
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							
From															Footage															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															Stands															Singles															REMARKS															Time																																																																																																		
1070															225															1295															7 1/2															53m															4															52															2 1/2															42																																													921.28															RIG SERVICE - G.O.P. CHECK																														8 ⁰⁰			8 ¹⁵			1 1/4																																																																													
1															8 1/4															X16															3-15															17678															30															100															630															184																														DRIG															358.60															SURVEY @ 1240 1/2															DRILL 8 3/4 hole																														8 ¹⁵			2 ⁴⁵			6 1/2																																																														
MUD															8 a.m.															10 a.m.															12 Noon															2 p.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																																																																																																	
WEIGHT															7.2															9.1															9.1															9.1																																																																																																																																																																																																																																									
VISCOSITY															32															32															30															31															GEL																																																																																																																																																																																																																										
PUMPS															No. 1															Pressure															900															900															900															900															Additives																																																																																																																																																																																												
Model															S.P.M.															60															60															60															60																																																																																																																																																																																																																										
Liner Size															6"															6"															6"															6"																																																																																																																																																																																																																																									
No. 2															Pressure																																																																																																																																																																																																																																																																																						
Model															S.P.M.																																																																																																																																																																																																																																																																																						
Liner Size																																																																																																																																																																																																																																																																																																					
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							
From															Footage															To															Hrs. on Bottom															Wt. Drill String (1000 lbs.)															DRILL COLLARS															FORMATION															OIL															FUEL															WATER															Stands															Singles															REMARKS															Time																																																																																																		
1295															185															1480															7 3/4															53m															12															64															2 3/8																																													1106.05															RIG SER.																														4 ⁰⁰			4 ¹⁵			3/4																																																																																												
1															8 3/4															X16															3-15															17678															30															100															815															264																														DRLG															358.60															DRILL 8 3/4" HOLE																														4 ¹⁵			12 ⁰⁰			7 3/4																																																																													
MUD															4 p.m.															6 p.m.															8 p.m.															10 p.m.															Additives															At Surveys Degree															MOTOR HOURS															Next Oil Change															C.B. Ft.															Subs. Ft.															Ft. Up On Kelly															TOTAL																																																																																																																	
WEIGHT															9.3															9.3															9.3															9.3															GEL															5 ALK																																																																																																																																																																																																											
VISCOSITY															33															33															30															30															GEL															GEN-EX 2500*																																																																																																																																																																																																											
PUMPS															No. 1															Pressure															400															960															900															900															Additives																																																																																																																																																																																												
Model															S.P.M.															60															60															60															60																																																																																																																																																																																																																										
Liner Size															6"															6"															6"															6"																																																																																																																																																																																																																																									
No. 2															Pressure																																																																																																																																																																																																																																																																																						
Model															S.P.M.																																																																																																																																																																																																																																																																																						
Liner Size																																																																																																																																																																																																																																																																																																					
W.L.															F.C.															pH.																																																																																																																																																																																																																																																																							
Totco Ring on Bit No.															D.P. Calipered Date															Results															Boiler in Operation															Toolpusher															Approved by																																																																																																																																																																																																																										
B.O.P. Test-Operated															Time															Results															Boiler in Operation															Toolpusher															Approved by																																																																																																																																																																																																																										

CONSERVATION BOARD COPY

Date Jan 17 19 70

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 16 1970Rig# 1 Location AMERADA HUES GOLF FT AL RED KNIFE ESS Job#

From		Footage	To	Mrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION		OIL	Stands	REMARKS			Time		
						No.	O.D.	I.D.	Wgt.			FUEL		Start	Stop	Interval			
665						8						WATER	1 45	12:00	1:00	1			
BITS		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION						
MUD		12 Mn.	2 a.m.	4 a.m.	6 a.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change					
WEIGHT														1					
VISCOSITY														2					
GEL														3					
PUMPS		No. 1	Pressure											4					
		Model	S.P.M.											5					
		Liner Size																	
		No. 2	Pressure																
		Model	S.P.M.																
		Liner Size																	
W.L.		F.C.	pH.																
665						44 M						FUEL	W.O.C.	8:00					
BITS		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION						
MUD		8 a.m.	10 a.m.	12 Noon	2 p.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change					
WEIGHT														1					
VISCOSITY														2					
GEL														3					
PUMPS		No. 1	Pressure											4					
		Model	S.P.M.											5					
		Liner Size																	
		No. 2	Pressure																
		Model	S.P.M.																
		Liner Size																	
W.L.		F.C.	pH.																
665						44 M						FUEL	DRILL MOUSE HOLE	4:00	6:00	2			
BITS		No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION						
MUD		4 p.m.	6 p.m.	8 p.m.	10 p.m.	Additives				At Surveys Degree		MOTOR HOURS		Next Oil Change					
WEIGHT														1					
VISCOSITY														2					
GEL														3					
PUMPS		No. 1	Pressure											4					
		Model	S.P.M.											5					
		Liner Size																	
		No. 2	Pressure																
		Model	S.P.M.																
		Liner Size																	
W.L.		F.C.	pH.																

Totco Ring on Bit No.

D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by

CONSERVATION BOARD COPY

CAN-TEX DRILLING & EXPLORATION LTD.

DAILY DRILLING REPORT

Date JAN 15 1970Rig# 1 Location LAKE ARDA HESS GOLF ETAL RED KNIFE 155 Job#

REMARKS															Time									
															Start	Stop	Interval							
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION		OIL	Stands	Displace 2100 WOC			1300	1000	1						
					No.	O.D.	I.D.	Wgt.			FUEL	Singles				100	800	7						
											WATER													
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars											
													775.72											
													Other Ft.											
													C.B. Ft.											
													Subs. Ft.											
MUD			12 Mn.	2 a.m.	4 a.m.	6 a.m.	Additives			At Surveys Degree		MOTOR HOURS		Next Oil Change										
WEIGHT													1											
VISCOSITY													2											
GEL													3											
PUMPS	No. 1	Pressure											4											
	Model	S.P.M.											5											
	Liner Size																							
	No. 2	Pressure																						
	Model	S.P.M.																						
General																								
W.L.			F.C.			pH.													Company Time			Cont'r Time		
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION		OIL	Stands	W.O.C. THAWING OUT MUD TANKS AND CLEAN SAME			800	400	8						
665					No.	O.D.	I.D.	Wgt.			FUEL	Singles												
											WATER													
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars											
													Other Ft.											
													C.B. Ft.											
													Subs. Ft.											
MUD			8 a.m.	10 a.m.	12 Noon	2 p.m.	Additives			At Surveys Degree		MOTOR HOURS		Next Oil Change										
WEIGHT													1											
VISCOSITY													2											
GEL													3											
PUMPS	No. 1	Pressure											4											
	Model	S.P.M.											5											
	Liner Size																							
	No. 2	Pressure																						
	Model	S.P.M.																						
General																								
W.L.			F.C.			pH.													Company Time			Cont'r Time		
From	Footage	To	Hrs. on Bottom	Wt. Drill String (1000 lbs.)	DRILL COLLARS				FORMATION		OIL	Stands	W.O.C. HEAD UP			4.00	8.00	4						
					No.	O.D.	I.D.	Wgt.			FUEL	Singles												
											WATER													
BITS	No.	Size	Type	Size Jets	Serial No.	Weight	R.P.M.	Ft. Drilled	Hrs.	Feet Reamed	Hrs.	CONDITION	D. Collars											
													Other Ft.											
													C.B. Ft.											
													Subs. Ft.											
MUD			4 p.m.	6 p.m.	8 p.m.	10 p.m.	Additives			At Surveys Degree		MOTOR HOURS		Next Oil Change										
WEIGHT													1											
VISCOSITY													2											
GEL													3											
PUMPS	No. 1	Pressure											4											
	Model	S.P.M.											5											
	Liner Size																							
	No. 2	Pressure																						
	Model	S.P.M.																						
General																								
W.L.			F.C.			pH.													Company Time			Cont'r Time		

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher J. M. Methyl
 B.O.P. Test-Operated _____ Time _____ Results _____ Approved by _____

CONSERVATION BOARD COPY.

Date Jan 14 1970

REMARKS

[illegible]

Totco Ring on Bit No. _____ D.P. Calipered Date _____ Results _____ Boiler in Operation Yes Toolpusher J. M. [Signature]
B.O.P. Test-Operated _____ Time _____ Results _____ Approved by [Signature]

CONSERVATION BOARD COPY

DAILY DRILLING REPORT

Date Jan 13 19 70

Rig# 1 Location AMERIND HESS CURS FT AL RED KNIFE LSS Job#

Rig #		Location		Job #		REMARKS		Time															
								Start	Stop														
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands							
No.		Size		Type		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
MUD		12 Mn.		2 a.m.		4 a.m.		6 a.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		C.B. Ft.		Subs. Ft.		Ft. Up On Kelly	
WEIGHT		91		T.		5		50		50 LIME		500		3		1		4		5		TOTAL	
VISCOSITY		40		10		50		50 LIME		500		3		1		4		5		5		560.91	
GEL																							
No. 1		Pressure		400		500		500		500		500		500		500		500		500		500	
Model		S.P.M.		63		65		65		65		65		65		65		65		65		65	
No. 2		Pressure		75		75		75		75		75		75		75		75		75		75	
Model		S.P.M.																					
Liner Size																							
W.L.		F.C.		pH.																			
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands							
No.		Size		Type		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
MUD		8 a.m.		10 a.m.		12 Noon		2 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		C.B. Ft.		Subs. Ft.		Ft. Up On Kelly	
WEIGHT										GEL - 5000				1				4		5		TOTAL	
VISCOSITY										SAND - 70				2				5		5		560.91	
GEL														3									
No. 1		Pressure												4									
Model		S.P.M.												5									
Liner Size																							
No. 2		Pressure																					
Model		S.P.M.																					
Liner Size																							
W.L.		F.C.		pH.																			
From		Footage		To		Hrs. on Bottom		Wt. Drill String (1000 lbs.)		DRILL COLLARS		FORMATION		OIL		Stands							
No.		Size		Type		Serial No.		Weight		R.P.M.		Ft. Drilled		Hrs.		Feet Reamed		Hrs.		CONDITION		D. Collars	
MUD		4 p.m.		6 p.m.		8 p.m.		10 p.m.		Additives		At Surveys Degree		MOTOR HOURS		Next Oil Change		C.B. Ft.		Subs. Ft.		Ft. Up On Kelly	
WEIGHT										GEL 5000				1				4		5		TOTAL	
VISCOSITY										SAND 45				2				5		5		560.91	
GEL														3									
No. 1		Pressure												4									

Totco Ring on Bit No.

D.P. Calipered Date

Results

Boiler in Operation

Toolpusher

B.O.P. Test-Operated

Time

Results

Approved by _____

CONSERVATION BOARD COPY

Date Jan 12 1970

REMARKS

[illegible]

Toolpusher

Approved by _____

CONSERVATION BOARD COPY

Feb 5, 1970

Airtress Gulf Redknife E-55

T.D. 4807

Rig Released

Located plug No 2 3970 9:00 AM. 2-4-70

ABANDON PLUG NO 3 610-710

Hung 4 1/2" drill pipe at 710'. Howled squeezed 65 sacks cement treated with 20% CaCl₂. Cement in place 11:30 AM. 2-4-70

Located plug No 3 580' 8:00 PM 2-4-70

Cut surface casing off 3' below ground level.

Dumped 5 sacks cement in 9 1/8" casing. Welded steel plate on top. Welded 2" pipe to steel plate to extend 4' above ground level and added steel plate with well name and location

RIG RELEASED 11:00 PM Feb 4, 1970

BRKD

1.00 hr Run in & locate Plug No 2

2.00 hrs Pull up to run Plug No 2


1.50 hr Run plug No 3

8.00 hrs W.D.C #3

1.50 hr Locate plug No 3

3.00 hrs Laid down Drill pipe & BOP equipment

9.00 hrs Tear out



Feb 4, 1970

Amherst Gulf Redknife E-55

TD 4807

W.O.C Plug #2

Abandon Plug No 1 4807-4400

Hung 4 1/2" dp @ 4807. Howco equalized 165 sacks
Cement. In place 11:30 P.m 2-3-70

Abandon Plug No 2 4400-4000

Hung 4 1/2" dp @ 4400. Howco equalized 165 sack cement
In place @ 1:00 AM 2-4-70

BRKD

9.00 Wait on orders

1.30 Load out test tools

2.00 laid down drill collars


2.00 Run in to plug - picked up 12 singles

1.00 Run Plug #1

.50 Pulled up for Plug #2

1.00 Run plug #2

7.01 W.O.C



Feb. 3, 1970

Ain Horn Guit Redknife E-55

T.O. 4807

Laying down test tools

DST NO 2 4040 - 4150 Straddle test

Ran in 8 $\frac{3}{4}$ " hole M.O.T. Test Tools on dry 4 $\frac{1}{2}$ " drill pipe
w/ dual packers at 4040 & 4150, Jars. S.T. P.D. Sub.
3 recorders and $\frac{1}{2}$ " bean

Pre flow 5' ISI 60' VO 30' FSI 66'

BLOW: Good air blow through out test.

REC: 200' drilling mud. No evidence of gas or oil

CHARTS I.H.R. 1971# F.H.R. 1935#

IF 72# FF 90#

ISI 1525# FSI 1310# Temp. 146°

Chart below bottom packer shows packers
held ok


BRKD

1.00 laid down P.S.T NO 1 test

7.00 laid down 9" P.E's and ran in with bit to
condition hole for DST NO 2

4.00 Circulated

12.00 Trip & run DST NO 2



February 1, 1970

Amerada Hess Gulf Redknife E-55
TD 4807

Status Schlumberger Logging

Worked fish through tight spot at 4,630' and pulled out wet string. Unable to break circulation--bit plugged. Recovered 11 drill collars and bit. Ran in with 8 3/4" bit and cleaned bridges to bottom from 4,680' to 4,807'. Circulated and conditioned mud. Made a ten stand dummy trip. Circulated and pulled out to log. Schlumberger ran dual induction log to bottom and checked bottom at 4,807'. Logging tool would not work. Pulled out for repairs.

Breakdown

.75 R.S. & B.O.P.
1.75 Worked fish loose.
4.00 Pulled out fish.
1.00 Slip and cut drill line.
6.00 Run in w/bit bumper sub and jars. Clean out 120' to bottom.
4.25 Circulate hole for logging.
.75 Dummy trip.
2.25 Pulled out to log.
3.25 Schlumberger logging.



Jan 31/1970

Amerasia 1 less Gulf Red Knife E-55

Depth 4807

Status Working stuck

pipe. free going down, trying
to get past 4630.

WD-9.2 Wire 67 W.L. 8.0 PH. 8.0 Fr. 1/32

Bit No 9 8 3/4" H.W. WD-7 44' 7 1/4" down.

Worked stuck pipe & waited on fishing equipment.
Bit at 4695. Ran Homer free point indicator
on Schlumberger line & found drill collars stuck
at 4400'-100% Ran 7 Homer string shot & backed
off ~~the~~ stuck collars at 4375'. Pulled out &
recovered 4 1/2" drill pipe & 7 drill collars. Left in hole
11 drill collars & 8 3/4" Bit. Ran in with 7 Homer
bumper sub & jars. Ran 13 drill collars & 4 1/2"
drill pipe. Circulated a bare fish. Screwed into
fish. Bumped fish loose going down. Unable to
bring fish up past 4360'. Free going down. Tried
to break circulation, unable to do so. Trying to
move fish up past tight place. Raining for bit
at all times.

Breakdown

8.00 Working stuck pipe & waiting on tools

7.00 Ran free point indicator & back off shot.

1.50 Circulated

3.50 Trip for bumper sub & jars.

1.00 Picked up 6 drill collars

3.00 Working fish loose.



AMERADA PETROLEUM CORPORATION

REDKNIFE

Daily Drilling Report

Well E-55

Date 1-30-70

Depth 4807 Footage 75 Hours 13 Status Stuck in hole

Mud 9.2 Vis 6.7 WL 8.0 PH 8.0 FC 2 1/2 Sand

Bit No. 8 Make Hw Size 8 3/4 Type WDRT Drilled 6.6 Hours 12 3/4 Comp X Inc

Bit No. 9 Make Hw Size 8 3/4 Type WDRT Drilled 44 Hours 7 1/4 Comp X Inc


Bit No. Make Size Type Drilled Hours Comp Inc

Survey Off Lost Time

BREAKDOWN:

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. R.S. B.O.P. Made dummy to clean hole.
1/2 Hrs. WORK ON PUMP Pulled out to log and stuck
3 1/2 Hrs. TRIP TIME pipe at 4697 no circulation
1 Hrs. Clean 40' to bottom working pipe waiting on fishing
2 Hrs. Circ. to log equipment
3 1/4 Hrs. Stuck pip at 4697
13 Hrs. Drilling
 Hrs.



AMERADA PETROLEUM CORPORATION

Daily Drilling Report

Well E-55 Date 1-29-70

Depth 4732 Footage 100 Hours 14 1/4 Status Drilling

Mud 9.2 Vis 6.4 WL 7 PH 9.5 FC 2/32 Sand

Bit No. 7 Make HW Size 8 3/4 Type DDV Drilled 77 Hours 9 Comp X Inc

Bit No. 8 Make HW Size 8 3/4 Type WOR Drilled 35 Hours 7 Comp Inc X

Bit No. Make Size Type Drilled Hours Comp Inc

Survey Off Lost Time

BREAKDOWN:

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. RS BOP Bit #7 all bearings gone

14 1/4 Hrs. Drilling and out of gauge

1 Hrs. Circulate Sample


1 1/2 Hrs. TIGHT HOLE 4588

4 1/2 Hrs. TRIP TIME

2 Hrs. REAM 10' UNDERGAUGE HOLE

..... Hrs.

..... Hrs.





AMERADA PETROLEUM CORPORATION
Daily Drilling Report

Well Redknife

Date Jan 28

Depth 4632 Footage 166 Hours 16 Status Φ

Mud 93 Vis 50 WL 93 PH 9 FC 7/32 Sand

Bit No. 6 Make H.L. Size 5 3/4 Type XSS Drilled 514 Hours 49 Comp ✓ Inc

Bit No. 7 Make ✓ Size ✓ Type Q²V Drilled 12 Hours 1 3/4 Comp Inc

Bit No. Make Size Type Drilled Hours Comp Inc

Survey 4620 Off 1/2

Lost Time

BREAKDOWN:

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. RS + BOP

1 1/2 Hrs. drill

1/4 Hrs. Survey

1 1/4 Hrs. trip

1/2 Hrs. Clear 40' to bottom

1/4 Hrs. slip Φ line

Hrs.

Hrs.

Pump out singles from 4500 - 4100

TD should be in about 4732

Sch. should be on loc this PM,

AMERADA PETROLEUM CORPORATION

Daily Drilling Report

Well

REDKNIFE E-55

Date

1-27-70

Depth

4466

Footage

246

Hours

23 1/4

Status

Drilling

Mud

9.3

Vis

45

WL

8.8

PH

9.5

FC

2 1/2

Sand

Bit No.

6

Make

HW

Size

8 3/4

Type

X55R

Drilled

360

Hours

35 3/4

Comp

Inc

X

Bit No.

Make

Size

Type

Drilled

Hours

Comp

Inc

Bit No.

Make

Size

Type

Drilled

Hours

Comp

Inc

Survey

Off

Lost Time

BREAKDOWN:

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. RS BOP

23 1/4 Hrs. DRILLING

Hrs.

Hrs.

Hrs.

Hrs.

Hrs.

Hrs.



AMERADA PETROLEUM CORPORATION

Daily Drilling Report

Well E-55

Date 1-26-70

Depth 4220 Footage 152 Hours 18 Status 2

Mud 93 Vis 48 WL 9 PH 8 FC 2 1/2 Sand

Bit No. 5 Make Hw Size 8 3/4 Type XV Drilled 145 Hours 14 1/4 Comp X Inc

Bit No. 6 Make Hw Size 8 3/4 Type XSSR Drilled 114 Hours 12 Comp Inc X

Bit No. Make Size Type Drilled Hours Comp Inc

Survey 4106 Off 1

Lost Time

BREAKDOWN:

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. RSBOP

1 1/2 Hrs. Work over

3 Hrs. TRIP

1 1/2 Hrs. clean 40' to bottom

1/4 Hrs. Survey

18 Hrs. Drilling

Hrs.

Hrs.



AMERADA PETROLEUM CORPORATION

Daily Drilling Report

Well E-55

Date 1-25-70

Depth 4068 Footage 315 Hours 17 1/4 Status 2

Mud 9.3 Vis 48 WL 9.2 PH 8 FC 3/2 Sand

Bit No. 4 Make HW Size 8 3/4 Type XIC Drilled 914 Hours 38 3/4 Comp X Inc

Bit No. 5 Make HW Size 8 3/4 Type XV Drilled 107 Hours 8 1/4 Comp X Inc X

Bit No. Make Size Type Drilled Hours Comp Inc

Survey 3783 Off 1 Lost Time

3840 - 1/2 3933 - 18 4024 - 3/10

BREAKDOWN: REMARKS: (Coring-casing-testing-cement-plug, etc.)

3/4 Hrs. RS BOP

1 Hrs. Survey

3 1/2 Hrs. Trip

1 1/2 Hrs. Clean 120' to bottom

17 1/4 Hrs. Drilling

Hrs.

Hrs.

Hrs.

4070 Slave St

4068

308

Slave Point

AMERADA PETROLEUM CORPORATION

Daily Drilling Report

Well E-55Date 1-24-70Depth 3753 Footage 535 Hours 21 3/4 Status DrillingMud 9.3 Vis 40 WL 11.8 PH FC SandBit No. 4 Make NW Size 8 3/4 Type A16 Drilled 807 Hours 30 Comp Inc X

Bit No. Make Size Type Drilled Hours Comp Inc

Bit No. Make Size Type Drilled Hours Comp Inc

Survey Off

Lost Time

BREAKDOWN:

21 3/4 Hrs. Drilling3/4 Hrs. RSBOP1 1/2 Hrs. Surveys

..... Hrs.

..... Hrs.

..... Hrs.

..... Hrs.

..... Hrs.

REMARKS: (Coring-casing-testing-cement-plug, etc.)

3241 - 1/8

3331 - 1/4

3421 - 1/2

3512 - 1/2

3605 - 1/2

3691 - 1/2



Amerada Division
Amerada Hess Corporation

Calgary, Alberta
CANADA

DAILY DRILLING REPORT

January 23, 1970

NORTHWEST TERRITORIES

Trainor Lake - Wildcat

AmHess Gulf Redknife E-55

January 22, 1970

2875' 458' 19.50 Drilling
Mud 9.3 Vis 55
Surveys: 2444' off 1/8 degree; 2535' off 1/8 degree;
2626' off 1/2 degree; 2716' off 1/2 degree;
2806' off 1/2 degree
Breakdown: 19 1/2 hrs Drilling
2 1/2 hrs Tripping
1 1/4 hrs Surveys
3/4 hr Rig Service and check BOP

January 23, 1970

3218' 343' 17.75 Drilling
Mud 9.5 Vis 45 WL 8.3 pH 8.5 FC 2/32
Surveys: 2897' off 1 degree; 2950' off 1/2 degree;
3150' off 1/2 degree
Breakdown: 3/4 hr Rig Service and check BOP
17 3/4 hrs Drilling
1 hr Pick up six drill collars
1 hr Surveys
3 hrs Trip for bit
1/2 hr Clean 60' to bottom

NOTE: WELL NOW TIGHT HOLE



Amerada Division
Amerada Hess Corporation

Calgary, Alberta
CANADA

DAILY DRILLING REPORT

January 21, 1970

NORTHWEST TERRITORIES

Trainor Lake - Wildcat


AmHess Gulf Redknife E-55

January 20, 1970

2018'	418'	20.50	Drilling
Mud 9.2	Vis 30		
Surveys:	1610' off 1/8 degree;	1920' off 1/8 degree	
<u>Breakdown:</u>	20 1/2 hrs	Drilling	
	3/4 hr	Rig Service and check BOP	
	1/2 hr	Surveys	
	1/4 hr	Slip and cut drilling line	
	2 hrs	Tripping	


January 21, 1970

2417'	399'	23.00	Drilling
Mud 9.2	Vis 45		
Survey:	2200' off 1/8 degree		
<u>Breakdown:</u>	23 hrs	Drilling	
	3/4 hr	Rig Service and check BOP	
	1/4 hr	Survey	



Amerada Division
Amerada Hess Corporation

Calgary, Alberta
CANADA



DAILY DRILLING REPORT

January 19, 1970

NORTHWEST TERRITORIES

Trainor Lake - Wildcat

AmHess Gulf Redknife E-55

Well Particulars: Located in Unit E; Sec 55,
Grid 60 degs 40 mins N;
119 degs 30 mins W
Lat: 60 degs 34 mins 23 secs
Long: 119 degs 41 mins 5.5 secs

Elevation: Ground 1241'

Surveyor: No Legal Survey Required

Contractor: Can-Tex Rig No.1

Drilling License: Authority #395

AmHess Working Interest: 100%

January 2, to 11, 1970

Moving rig from Fina location and rigging up

January 12, 1970

80' 80' 3.00 Drilling

SPUDED IN AT 5:00 AM - JANUARY 12, 1970

ELEVATION: Ground 1241'

KB to ground 14'

1255'

Fill 3'

KB ELEVATION 1258'

Breakdown: 20 hrs Rigging up

1 hr Mix mud

3 hrs Drilling

January 13, 1970

560' 480' 18.50 Drilling

Mud 9.1 Vis 50

Surveys: 100' off 1 degree; 200' off $\frac{1}{2}$ degree;

290' off $\frac{1}{8}$ degree; 408' off $\frac{1}{2}$ degree;

500' off $\frac{1}{2}$ degree

Breakdown: 3/4 hr Rig Service

1 1/4 hrs Surveys

3 1/2 hrs Trip for bit and clean to bottom

18 1/2 hrs Drilling

January 14, 1970

654' 94' 3.50 Drilling

Breakdown: 3/4 hr Rig Service

1/4 hr Circulate

18 1/2 hrs Clean to bottom, mix mud and try
to plug off around conductor pipe

3 1/2 hrs Drilling

1 hr Work on pump

over/

Daily Drilling Report - continued

AmHess Gulf Redknife E-55

January 15, 1970

665' 11' .75 W.O.C

Survey: 600' off 3/4 degree

9-5/8" CASING CEMENTED AT 660"

Ran in 13-3/4" hole with 20 jts of 9-5/8" OD 40.5# K-55 LT&C casing. Used three centralizers on bottom three joints and one centralizer one joint below ground level. Used one guide shoe and one float collar. Howco cemented with 550 sax cement with 2% CaCl₂ on last 250 sax. Pumped plug down with Howco, bumped plug and bled off casing. Float held OK. Good returns. Plug down at 1:00 AM - January 15, 1970.

Breakdown: 1/2 hr Rig Service
3/4 hr Drilling
1/4 hr Survey
1 1/2 hrs Trip
1 hr Circulate and condition mud
2 hrs Lay down 9" drill collars
1 1/2 hrs Rig up to run casing
5 3/4 hrs Run casing
1 3/4 hrs Circulate casing
2 hrs Mix and pump down cement
7 hrs W.O.C

January 16, 1970

665' 0' 0' W.O.C

Breakdown: 24 hrs W.O.C. Thawing out mud tanks, Backed off landing joint, screwed on Cameron casing bowl, install B.O.P's and headed up

January 17, 1970

665' 0' 0' Pulling out

Three flanges in B.O.P leaked. Removed B.O.P and installed new rings

Breakdown: 14 hrs Head up
2 hrs Pick up four drill collars
7 1/2 hrs Pressure test B.O.P
1/2 hr Pull out

January 18, 1970

1070' 410' 11.25 Drilling

Mud 9.1 Vis 38

Survey: 922' off 7/8 degree

Breakdown: 7 1/2 hrs Remove B.O.P Install new rings and test C.S.O to 1000#
1 hr Rig Service
3/4 hr Test DP Rams to 1200# - OK
3 hrs Drill plug and shoe
1/4 hr Test cement job to 300#
11 1/4 hrs Drilling
1/4 hr Survey


January 19, 1970

1600' 530' 22.75 Drilling

Mud 9.1 Vis 32

Surveys: 1240' off 1/2 degree; 1547' off 1/4 degree

Breakdown: 3/4 hr Rig Service and check BOP
22 3/4 hrs Drilling
1/2 hr Surveys



P. 138

**GUIDE
MARGIN**

DATE:

YEAR

1970

A.F.E.

19041

LEASE

Gulf et al Red Knife

WELL No. H-28 NET

CO-ORDINATES

Lat. 61°27'15.67" North; Long. 119°03'51.15" West

Jan. 22

Depth 236, Ftg. 236, Shale and Sandstone, 12½" hole, Drilling
Tri-City Rig #4 from
Edmonton Area

SPUNDED

Days from Spud: 1
Spudded at 7:15 P.M., January 21, 1970

Visc. 42, 95 - $\frac{1}{2}^{\circ}$, 208 - $\frac{1}{2}^{\circ}$. RPM 180, Bit Wt. 12,000, String Wt. 24,000.
Drilling String: 7 - $6\frac{1}{2} \times 2 \frac{7}{8}$ " drill collars (X-hole). Pump No. k,
SPM 75, $5\frac{1}{2} \times 12$, 100 psi. Bit Serial No 87293. Bit No. 1A, S4JR, $12\frac{1}{2}$ ",
In O, Ftg. 236, 10 hours - drilling. Time Breakdown: Drilling 10 hours,
Surveys $\frac{1}{2}$ hour, Rig Service $\frac{1}{2}$ hour, rathole $4\frac{1}{2}$ hours, rig up $6\frac{1}{2}$ hours.
Mud Additives: Gel 1000#, Lime 50#, Caustic 50#.

Temp. -10° Overcast Reported by Hannegan

Jan. 23

Depth 570, Ftg. 334, Simpson Sh., 12 $\frac{1}{2}$ " hole Repairing hand throttle on
draw-works.

Days from Spud: 2 Cost to Date: \$45,494
Drilled from 236 to 291'. Ran low on water. Waited 6 hours for water truck. Trip out. Trip good. Drilled to 570'. Dummy tripped. Straped out okay. Tripped in. Hit fill at 380' to bottom. Balled bit up and had to trip out. Ran in with new bit. Had 20' fill on bottom. Cleaned out to bottom and broke hand throttle.

Mud Wt. 9.1, 43, 320 - $\frac{1}{2}^{\circ}$, 414 - $\frac{1}{2}^{\circ}$, 538 - $7/8^{\circ}$. RPM 180, Bit Wt. 15,000, String Wt. 34,000. Drilling String: 10 - $6\frac{1}{2}$ X $2\frac{7}{8}$ " X H drill collar. Pump No. 1, SPM 75, $5\frac{1}{2}$ X 12, 200 psi. Bit Serial No's 87293 Retip #2 904417 New. Bit No. 1A, S4, $12\frac{1}{2}$ ", 0 - 570, Ftg. 570, 20 $\frac{1}{2}$ hours - 6-6-1. Bit No. 2A, S4, $12\frac{1}{2}$ ", In 570. Time Breakdown: Drilling 10 $\frac{1}{2}$ hours, Trip 2 $\frac{1}{2}$ hours, Surveys $\frac{1}{2}$ hour, Rig Service $\frac{1}{2}$ hour. Waiting on water 6 hours, mix mud $\frac{1}{2}$ hour, clean to bottom $3\frac{1}{2}$ hours, waiting on hand throttle $\frac{1}{2}$ hour.

Temp. 0° Overcast Reported by Hannegan

RECEIVED AT
Edmonton Office

JAN 27 1970



ROUTE TICKET

PLEASE RETAIN ON FILE ☐

PLEASE DESTROY ☐

	NAME	DEPT	DATE	INITIALS
PREPARE COPY FOR MY SIGNATURE				
REPLY DIRECT AND SEND ME COPY				
TAKE CHARGE OF THIS				
RETURN WITH YOUR RECOMMENDATION				
SEE ME ABOUT THIS				
FOR YOUR INFORMATION & FILES	✓ I. H. K. H. T. T. H. S.			
NOTE & RETURN	CIVIL CONSTRUCTION ENGINEER			
FOR YOUR SIGNATURE	DEPT OF INDIAN AFFAIRS			
FOR YOUR APPROVAL	NORTH BRITISH COLUMBIA			
	2300-22 STREET NW			

REMARKS :

CANADIAN H&A

FROM :

DATE