

PLACID-CHEVRON

FOETUS LAKE

C-49

Drilling Authority No. 428
Date Issued 3 March 1970

WELL NAME Placid Chevron Foetus Lake C-49

FIELD
LOCATION: Unit C Area: 49
Latitude 61-08-12 Section 118-38-28 Grid 61-10-118-30
U.W.L.R. 61.13666 --- 118.64111 Longitude 118-38-28
U.W.I. 300C496110118300

Rig Release Date
Status
Information Release Date

CHANGE OF NAME:

DATE RECEIVED	INDEX
3-3-70	Application for a Drilling Authority.
	Well Completion Data.
	Well History Report.
6/3/70	Application to Amend a Drilling Authority.
	Application to change a Well Name.
2-4-70	Application to Abandon a Well or Suspend Drilling.
	Application to Alter Condition of a Well.
8/7/70 Updated	Well History Supplement.
	Well Completion Data.
	Work-over Report No.
	Application to Commingle Production before Measurement.
	Data for Back Pressure Test on Natural Gas Wells - Monograph 7 Method.
	Data for Back Pressure Test on Natural Gas Wells - Vitter's Method.
	M.P.R. - Oil - Calculations.
	New Oil Well Report.
	New Gas Well Report.
	Well Inspection Report.
	Rig Inspection Report.
	Battery Inspection Report.
	Equipment Report.
	Well Card.
	New Service Well Report.
	Monthly Water Flood Operations Report
	Monthly Water Receipts and Disposal of Fluids Report
	Logs. Large scale..... Small scale.....



Drilling Authority No. 428
Date Issued March 3, 1970.

OIL & MINERAL

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

WELL COMPLETION DATA

To be submitted in duplicate within thirty days after the completion, rework, abandonment, recompletion or suspension of every well.

Well name and number **Placid Chevron Postus Lake C-49**
Permit No. **3455** Lease No. **-**
Chevron Standard Ltd. Exploratory Licence No. **1283**
(Permitter, Licensee, Lessee)
Placid Oil Company Exploratory Licence No. **1241**
(Operator)
UNIQUE WELL IDENTIFIER - 300C496110118300
Location: Unit **C** Section **49** Grid **61-10 118° - 30'W**
Latitude **61° 08' 12" N** Longitude **118° 38' 28" W**
From Established Reference Marker
Universal Well Location Reference **Lat. 61.13666° N, Long. 118.64111° W**

	DATE	DEPTH	Pool(s)
Spudded	<i>March 9</i> 11 P.M. 3/9/70		Interwell(s) open to production
Suspended			
Resumed Operations			
Finished Drilling	1:15 3/18/70	2645	
Deepened	PM		Elevation: Gr. 648 K.B. 662
Complete (WATER Dry)			Rig No. 5
Abandoned	3/20/70	2645	Drilling Contractor S & T Drilling
Rig released	2 A.M. 3/20/70		Contractor's Business Licence No. 564
	<i>March 20</i>		

CASING RECORD

Casing Size (Inches)	Grade	Weight	Amount	Set at -	Sacks of Cement and Additives
1. 8 5/8" (7 jts)	J-55	24#	209	204	140 sks. + 3% Cac12
2.					
3.					
4.					
5.					
6.					

GEOLOGICAL TOPS

ELEVATION

CORE RECORD

	Depth	Sub-Sea	From	To	Rec.	From	To	Rec.
Spence River	2006	-1344	NO CORES WERE CUT					
Otter Park	2160	-1498						
Mills Lake	2220	-1550						
Horn River	2302	-1640						
Lonely Bay	2422	-1760						
Chinchaga	2516	-1854	LOG RECORD					
Green Shale	2558	-1896						
Granite Wash	2580	-1918						
Precambrian	2600	-1938						
T.D.	2645	-1983	Run No.	Type of Log		From	To	
			1	Dual Induction Laterolog		2642	204	
			1	B.H.C. Sonic Gamma Ray Caliper		2645	204	
			1	Dipmeter Survey		2645	204	

**** (a Velocity Survey was also run with Century Geophysical)**

ABANDONMENT PLUGS:

THE UNIVERSITY OF CHICAGO LIBRARY
540 EAST 58TH STREET
CHICAGO, ILL. 60637
TEL: 773-936-5000
FAX: 773-936-5001
WWW.CHICAGO.LIBRARY.ORG

DRILL STEM TESTS

[illegible]

ANALYSIS
PRESENT STATUS OF FBI

[illegible]

Lab. No.	Sample	From	To	Source	Remarks
					Oil
					Placid Oil Company
					(General)

NOTED
Signed by R. E. Nawolsky

[illegible][illegible]

Forms to be prepared in duplicate and forwarded to the Oil Conservation Engineer, Calgary, Alberta.



File No. _____
Drilling Authority No. 428

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
OIL & MINERAL DIVISION RESOURCE MANAGEMENT DIVISION

Application to Abandon a Well

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to abandon, to suspend drilling:—

Name and number of well Placid Chevron Foetus Lake C-49
Location: Unit C Section 49 Grid 61-10 118°-30'W
Latitude 61° 08' 12" N Longitude 118° 38' 28" W
From Established Reference Marker
Universal Well Location Reference Lat. 61.13666° N, Long. 118.64111° W
Permit No. 3455 Lease No. -

Chevron Standard Ltd.
(Permitter, Licensee, Lessee)

Date of commencement of proposed program March 20, 1970.

OIL, GAS, AND WATER ENCOUNTERED (Depths)

Oil at -
Gas at -
Water at -
Total Depth 2645 Date of last operations March 20, 1970
Present condition of well Abandoned.

CASING RECORD

Casing Size O.D. Inches	Weight	Amount	Set At—	Series of Cement and Additives	Amount Pulled
1. 8 5/8"	24#	209'	204'	140 sks + 3% Cac12	2 none.
2.					
3.					
4.					
5.					

PROPOSED ABANDONMENT PROGRAM

Flag		Geological Formation	Number of Sacks of Cement	Remarks
No.	Position			
1	2645 - 2370	Lonely Bay	135	
2	255 - 155	49' in surface csg.	75 + 2% Cac12	Felt Plug @ 115'
3	Surface Plug		5	Erect 6' riser & name plate.

The following logs have been run Dual Induction Laterolog, Gamma Ray Sonic Caliper,
Other operations proposed none. Dipmeter and Velocity Survey.

Operations to be carried out by S&T Drilling Contractor Licence No. 564
Address 5825 - 98 Street Address Edmonton, Alberta
Responsible Agent in field Mr. Jack Rosichuk
Dated at Calgary, Alberta, this 26th Day of March, 1970.
Signed by R.E. Nawolsky, Placid Oil Company
Title Drilling & Prod. Supt. Operator's Exploratory Licence No. 1241

Note:—The Oil Conservation Engineer's office must be notified before work is commenced.

(For RESOURCE MANAGEMENT DIVISION use only)

APPROVAL

This application has been examined and proposed programme approved, subject to the following conditions:

Confirming oral approval given by Mr. B.H.J. Thoms
on the 18th March 1970.

Dated 2nd April, 19 70

B.H.J. Thoms
Oil Conservation Engineer

Forms to be submitted in triplicate to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.



DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT

~~XXXXXXXXXXXXXXXXXXXX~~
Oil and Mineral Division

Application to Amend a Drilling Authority

This application, in triplicate, must be submitted and approved before commencing operations. If the well location is changed, this application must be accompanied where required, with a plan of survey approved by the Surveyor General.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made to amend Drilling Authority No. 428, concerning

Placid Chevron Foetus Lake B-49
(Name and Number of Well)

The following amendments are required: Change of location from:

Unit B Section 49 Grid 61-10 118°-30' W Lat. 61° 08' 12" N
Long. 118° 38' 22" W

TO: Unit C Section 49 Grid 61-10 118°-30' W
Latitude 61° 08' 12" N Longitude 118° 38' 28" W

Universal Well Location Reference Lat. 61.13666° N, Long. 118.64111° W.

Unique Well Identifier - 300C496110118300

Reasons for the amendments: error in longitude.

Dated at Calgary, Alberta, this 5th day of March, 1970.

Signed by R. E. Nawolsky

Title Drilling & Production Supt.

Company Placid Oil Company

(For Resource Management Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:

Date 6th March, 1970
Oil Conservation Engineer B. H. Thomas

Forms to be submitted to the Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.



DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

Application for a Drilling Authority

This notice of intention to begin drilling operations, in triplicate, and where required a plan of survey approved by the Surveyor General showing the target area or the site of the well must be submitted and approved before commencing operations.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to drill —

Name and number of well **Placid Chevron Focus Lake 4-49**
Location: Unit **B** Section **49** Grid **61-10 118-30'W**
Latitude **61° 08' 12" N** Longitude **118° 38' 22" W**
From Established Reference Marker

Universal Well Location Reference: Lat. **61.13556° N.**, Long. **118.63944° W.**

Elevation: Ground **648** **Elk Point (Middle Devonian Carbonate)** **660** feet above sea-level.
Well is expected to produce from formation at a depth of about **2130** feet. Expected total final depth **2800**

Area assigned to well

(For Oil Conservation Engineer's use only)

Permit No. **3455** Lease No. **61920**

Permitter, licensee, or lessee **Chevron Standard Limited**

Exploratory Licence No. **1283**

Surface owned by Crown or **Crown**

(If estimated submit name and address of owner and occupant.)

Petroleum and natural gas rights owned by

We propose to use the following strings of casing, either cementing or landing them as indicated below:—

Casing Size O.D. (Inches)	Weight (Lb./Ft.)	Grade	New or Used	Estimated Depth	Backs of Cement
1. 8 5/8"	244	J-55	New	300	180
2. 4 1/2"	9.54	J-55	New	2800	200
3.					
4.					
5.					

Expected water, gas, and oil horizons and type of control equipment **Middle Devonian to be controlled with Drilling Mud and Blow-out Preventers. Hydrel 10" GK 900 Series and Shaeffer 10" Double Gate 900 Series.**

Well will be drilled with Rotary Rig No. **5** by **S & T Drilling (Western) Co. Ltd.**
(Drilling Contractor or company.)

5825 - 98 St., Edmonton 85, Alberta

Responsible agent of applicant:—

At well **Jack Rosichuk**

Address **at Rig**

Contractor's Business Licence No. **564**

At registered office **R. E. Nawolsky**

Address **860 Guinness House, Calgary**

It is understood that if changes become necessary, notice of the change of plan will be submitted.

Dated at **Calgary** this **2nd** day of **March** 19 **70**

Signed by **R. E. Nawolsky** Company **Placid Oil Company**

Title **Drilling & Prod. Supt.** Operator's Licence No. **1241**

(For Resource Management Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:—

1. The Company will submit to this office, on Tuesday of each week, the latest reports received by radio on the progress of the well.
2. During well drilling and testing operations, every effort shall be made to ensure

Dated **3rd March** 19 **70** Please see over page

Oil Conservation Engineer


Forms to be submitted to Oil Conservation Engineer,
Department of Indian Affairs and Northern Development, Calgary, Alberta.

that drilling fluids, chemicals and wastes shall be disposed of or contained in a manner that will prevent the contamination of adjacent vegetation and surface or sub-surface waters.

3. We draw your attention to Sections 95 and 96 of the Canada Oil and Gas Land Regulations.

B.H.J. Thomas

B.H.J. Thomas, Oil Conservation Engineer



331-11 4-19

WELL HISTORY REPORT

Placio Chevron Foetus Lake C-49
61-10 N, 118-30 E.

A.W.T.

WELL HISTORY REPORT

Well Name: Placid Chevron Foetus Lake C-49

I n d e x

Section 1	Summary of Well Data	Page 1
Section 2	Geological Summary Formation Tops, Sample Descriptions.	2
Section 3	Engineering Summary Surface Casing Record, Bit Record, Mud Report, Deviation Record, Abandonment Plugs.	5
Section 4	Logs	7
Section 5	Analysis (nil)	7
Section 6	Completion Summary (nil)	7
Section 7	Daily Chronological Report	7

WELL HISTORY REPORTSECTION 1 SUMMARY OF WELL DATA

Well Name: Placid Chevron Foetus Lake C-49 61°-10'N, 118°-30'W.

Permitter: Chevron Standard Limited

Operator: Placid Oil Company, 860 Guinness House, Calgary.

Location: C-49-61-10-118-30
61°-08'-12"N and 118°-38'-28"W

Universal Well Location Reference: Lat. 61.13666°N
Long. 118.62111°W.

Unique Well Identifier: 300C496110118300

Permit No.: 3455

Drilling Contractor: S&T Drilling (Western) Co. Ltd.
Rig #5 - National 50A

Drilling Authority: #428, March 3, 1970

Classification: Wildcat.

Elevations: Ground Level - 648'
Kelly Bushing - 662'

Spudded: March 9, 1970 at 11.00 P.M.

Completed Drilling: March 12, 1970 at 1:15 P.M.

Total Depth: Driller - 2645'
Schlumberger - 2646'

Well Status: Dry and Abandoned.

Rig Released: March 20, 1970 at 2:00 A.M.

Hole Sizes: Surface - 12½" to 204'
Main hole - 7-7/8" to 2645'

SECTION 2

GEOLOGICAL SUMMARY

2.

<u>Formation Tops:</u>	<u>Formation</u>	<u>Sub-Sea</u>	<u>E-log</u>	<u>Sample</u>
	Spence River	- 1344	2006	2020
	Otter Park	- 1498	2160	2150
	Mills Lake	- 1558	2220	2210
	Horn River	- 1640	2302	
	Lonely Bay	- 1760	2422	2420
	Chinchaga	- 1854	2516	2510
	Green Shale	- 1896	2558	2560
	Granite wash	- 1918	2580	2580
	Precambrian	- 1938	2600	2600
	Total Depth	- 1963	2645	

Cored Intervals: No cores were cut.

Sample Descriptions:

Note: All samples lagged approx. 1 min. per 100' of depth.

0 - 90 Sand	granite wash, quartz, feldspars, biotite, coarse irregular grains, unconsolidated with some sand stone, grey, fine grained, calcareous, tight, and some limestone, brown, cryptocrystalline, dense.
90 - 150 Sandstone	grey, fine grained, quartz, calcareous, with occasional black chert flecks.
150 - 190 Sandstone	as above and becoming silty and shaly in part.
190 - 210 Shale	medium grey and brown, with common white calcite fossil remains and abundant rusty brown staining and fossil remains in a whitish grey limestone, cryptocrystalline, dense.
210 - 280 Sandstone	light grey and greenish, fine grained, calcareous, tight.
280 - 400 Shale	grey green and brown, calcareous, with interbedded sandstone as above. Traces of limey fossil remains.
400 - 590 Shale	green, platy, calcareous.
590 - 620 Limestone	grey, microcrystalline, dense, argillaceous.
620 - 648 Siltstone	light grey and greenish, calcareous.
640 - 690 Shale	dark brown, platy in part, not calcareous, with interbedded limestone and sandstone as above. Common fossil remains.

- 3.
- 690 - 700 Limestone light grey, microcrystalline to fragmental, dense.
 - 700 - 720 Siltstone with limestone and sandstone as above.
 - 720 - 760 Shale brown, light grey and greenish, calcareous, grading to limestone.
 - 770 - 890 Siltstone grey with common limestone as above. Trace of fossils.
 - 890 - 930 Limestone buff and grey, cryptocrystalline to microcrystalline, dense, and as above.
 - 930 - 1160 Shale grey to brownish, silty in part, calcareous, with interbedded limestone as above and sandstone, light grey, fine grained, tight. Abundant green shale - splintery.
 - 1160 - 1170 Sandstone light grey, fine grained, quartz, calcareous infill, tight, with interbedded shale as above.
 - 1170 - 1200 Shale green, brown and grey, silty in part, flaky in part with interbedded sandstone as above.
 - 1200 - 1210 Limestone buff and grey, cryptocrystalline to microcrystalline, dense, argillaceous, and as above.
 - 1210 - 1690 Shale grey and brownish, calcareous, grading to limestone, dense with interbedded sandstone and limestone as above. Traces of fossils.
 - 1690 - 1930 Shale gray brown and grey, with some sandstone and limestone as above.
 - 1930 - 2020 Shale dark grey, silty in part, flaky in part, calcareous, grading to argillaceous limestone with common interbedded sandstone, light grey, fine grained, tight.

SPENCE RIVER - 2006' (-1344)

- 2020 - 2050 Shale dark grey and black, brownish in part, flaky, carbonaceous.
- 2050 - 2080 Limestone light to dark grey brown, argillaceous, cryptocrystalline, dense.
- 2080 - 2160 Shale dark grey and black, flaky in part, carbonaceous.

OTTER PARK - 2160' (-1498)

- 2160 - 2210 Shale as above with interbedded shale - black, carbonaceous and common limestone, light grey, and brownish, cryptocrystalline, dense.

HILLS LAKE - 2220' (-1558)

4.

- 2210 - 2240 Limestone light grey brown, cryptocrystalline, dense, microcrystalline in part, and as above.
- 2240 - 2300 Shale dark grey brown, calcareous, flaky, carbonaceous in part. Limy appearance.

HORN RIVER - 2302' (-1640)

- 2300 - 2320 Shale dark grey brown, as above some carbonaceous bedding.
- 2320 - 2420 Shale brownish black, carbonaceous, slightly calcareous.

LONELY BAY - 2422' (-1760)

- 2420 - 2480 Limestone dark brown to buff, cryptocrystalline to microcrystalline and fine grained, very slightly argillaceous, dense, creamy and chalky in part.
- 2480 - 2485 Limestone as above with common shale, black, flaky, carbonaceous.
- 2485 - 2510 Dolomite buff, microcrystalline to silty, very poor porosity in part with traces of weak oil stain.

CHINCHAGA - 2516' (-1854)

- 2510 - 2540 Dolomite as above, becoming anhydritic with traces of white, silty, crystalline anhydrite.
- 2540 - 2545 Dolomite as above with common shale - grey and grey green, platy.
- 2545 - 2555 Dolomite as above with dolomite - light grey, earthy, dense.

GREEN SHALE - 2558' (-1896)

- 2555 - 2565 Dolomite buff and grey, earthy, anhydritic, dense, traces of silty white anhydrite and light green shale.
- 2565 - 2580 Dolomite as above and grading to limestone with green shale and black carbonaceous shale.

GRANITE WASH - 2580' (-1918)

- 2580 - 2600 Granite wash - unconsolidated grains - quartz, feldspar, biotite, etc.

PRECAMBRIAN - 2600' (-1938)

2600 - 2645 Granite quartz, feldspar, biotite and hornblende, decreasing to mostly quartz and faint feldspars.

SECTION 3 ENGINEERING SUMMARY

Drill Stem Tests: No DSTs were run.

Surface Casing Record:

Ran 7 joints (208.75') of 8-5/8", 24.0 #, J-55, ST&C, new Mannesman casing. Set on bottom at 204.0' and cemented with 140 sac portland cement plus 3% CaCl₂. Good returns to surface (7 bbls.). Plug down at 6:55 P.M., March 11, 1970. Used a Davis guide shoe and float collar.

Tally -

1	14.69
2	29.62
3	28.40
4	28.28
5	25.42
6	40.00
7	39.90

Total 206.31

Total casing	206.31
Guide Shoe	1.07
Float Collar	1.37
	<u>208.75</u>

7 joints left on lease:	25.52
	42.92
	42.65
	42.25
	35.60
	37.42
	<u>35.21</u>
Total	251.57

Bit Record:

No.	Size	Type	Serial No.	Depth Out	Footage	Hours	Condition
1A(RR)	12-1/4	MGJ	551551	50	50	4-3/4	4-2-I
2A(RR)	7-7/8	XIG	18713	140	90	5-1/2	5-2-I
3A	7-7/8	YTIAG-J	78819	327	187	7-1/4	3-2-I
4A(RR)	12-1/4	MG-J	288649	204	154	6-3/4	3-3-I
1	7-7/8	ST3	156799	1640	1313	31	2-6-I
2	7-7/8	XIG	21392	2430	790	54	2-3-I
3	7-7/8	XDV	17608	2645	215	20-1/4	2-2-I
				T.D.			

Rug Report:

Date	Depth	Wt.	Vis.	W.L.	Ph.	Additives
1970						
Mar. 9	10	Spudded at 11:00 P.M.				
	10	295		46		Gel 1500#, Lime 50#
	11	327	Set sfc/csg at 204'			Gel 1500#, Lime 50#
	12	397	Water			
	13	1400	9.5	28		Benex 24#, BiCarb 300#, SAAD 50#
	14	1705	9.0	28		Benex 8#
	15	1970	9.4	34		Gel 7000#, Benex 8#, Caustic 100#
	16	2245	9.4	33	14.0 8.0	Gel 3500#, Benex 8#, Bicarb 100#, Soda Ash 100#
	17	2533	9.5	35	7.8 11.0	Gel 4800#, Bicarb 200#, Caustic 300#, Soda Ash 100#, RD-111 400#.
	18	2645	9.8	90	8.0 10.5	Gel 800#, Caustic 100#, RD-111 200#
	19	2645	Log and abandon			
	20	T.O.	Rig Released at 2:00 A.M.			

Deviation Record:

Depth	Dev.	Depth	Dev.
78	3/4	1845	6-3/4
100	3/4	1876	6-1/2
130	7/8	1908	6-3/4
170	7/8	1939	6-3/4
200	1	1970	6-3/4
265	1/2	2000	6-1/2
327	3/4	2032	6-1/4
550	1/8	2064	6-7/8
768	1/4	2095	6-7/8
984	1/2	2127	6
1172	1/4	2157	6
1393	3/4	2188	6
1508	1-3/4	2220	5-3/4
1611	5	2251	5-1/2
1640	6-1/2	2282	4-3/4
1668	7-1/4	2344	4-1/2
1716	7-1/8	2375	4-1/2
1750	7-1/8	2406	4-1/4
1782	6-3/4	2430	4
1813	6-1/2	2538	3-3/4
		2645	4

(A dipmeter survey was also run.)

Abandonment Plugs:

Plug #1 - 2645' to 2370' - Used 135 sack neat portland cement.
Plug down at 12:30 P.M., March 19, 1970.
Not required to feel.

Plug #2 - 255' to 155' - Used 75 sack portland cement plus 2%
CaCl₂. Plug down at 2:40 P.M., March 19
1970. W.D.C. 8 hours; felt plug #2 at
115'.

Casing cut off 3.0' below ground; 5 sack cement put in top
and a steel plate welded on. A steel riser and well sign
was welded on to casing.

Lost Circulation Zones: nil

Blowouts: nil

SECTION 4 LOGS

Logs by Schlumberger on March 19, 1970.

Dual Induction Laterolog	2642 - 204
BHC Sonic C-R Cal. log	2645 - 204

A dipmeter survey was also run from 2645' to 204'
A velocity survey was run with Century Geophysical.

SECTION 5 ANALYSIS - nilSECTION 6 COMPLETION SUMMARY - nilSECTION 7 DAILY CHRONOLOGICAL REPORT

Date	Day	Depth	Progress	Remarks	
1970					
Mar. 9	1	10	10	Rigged up to spud. Drilled mousehole and rathole with power swivel. Loaded out power swivel. Spudded in with 12 $\frac{1}{4}$ " bit. Drilling surface hole.	
	10	2	295	285	Drilled 12 $\frac{1}{4}$ " hole through surface boulders to 50'. Picked up shock sub and 7-7/8" bit and drilled ahead with 7-7/8" pilot hole.
	11	3	327	32	Drilled pilot hole to 327' K.B. Tripped and picked up 12 $\frac{1}{4}$ " bit and reamed hole to 12 $\frac{1}{4}$ " from 50' to 204'. Picked up 8-5/8" surface casing and ran same to 160' with difficult- ies from boulders which apparently fell in from surface. Could not get casing any deeper. Pulled out casing and reamed from 160' to 204' with 12 $\frac{1}{4}$ " bit. Ran 7 joints (208.74') of 8-5/8", 24.0#, J-55, ST&C,

Date Day Depth Progress Remarks

Mar. 11 cont'd.

new Kinnessman casing. Set on bottom at 204' and cemented with 140 sax portland cement plus 3% CaCl_2 . Good returns (7 bbls.) to surface. Plug down at 6:55 P.M. W.O.C. and start to cut off casing.

12 4 397 70 Finished heading up and pressure tested blind rams; OK. Ran in with bit and felt plug at 180'. Pressure tested pipe rams and Mycrist; OK. Motor shut-offs OK. Drilled out cement plug and shoe and cleaned to bottom of pilot hole. Pulled out and picked up 3 stabilizers and new bit. Drilling ahead in 7-7/8" hole.

13 5 1400 1103 Drilled ahead.

14 6 1735 305 Drilled ahead to 1640'. Found survey to be 6 1/2°. Tripped for new bit and repositioned 2 stabilizers at 60' and 120'. Ran in and fanned hole from 1610' to 1640'. Drilled to 1668'; survey 7 1/2°. Pulled out and laid down shock sub and one stabilizer. Ran in with one spiral stabilizer at 30'. Drilled ahead using 15,000# at 120 RPM.

15 7 1970 265 Drilled ahead with controlled weight and taking surveys every 30'. Deviation staying at approx. 6-3/4°.

16 8 2245 275 Drilled ahead with controlled weight. Deviation gradually came back to 5-3/4°.

17 9 2533 288 Drilled ahead with deviation gradually coming back to 3-3/4°.

18 10 2645 112 Drilled to T.D. of 2645' and circulated to log. Ran DILL and 8HC Sonic logs by Schlumberger.

19 11 2645 T.D. Finished logging. Ran Dipmeter and Velocity Survey. Laid down DCs and ran in open-ended. Ran plug #1 from 2645' to 2370' with 135 sax portland cement. Plug down at 12:30 P.M. Pulled out, laying down drill pipe. Ran in to 255' and ran plug #2 from 255' to 155' with 75 sax portland cement plus 2% CaCl_2 . Plug down at 2:40 P.M. W.O.C. 8 hours. Felt plug #2 at 115'. Laid down BOPs.

20 12 2645 T.D. Cut off casing 3.0' below ground; put 5 sax cement in top and welded on a steel plate with steel well sign. Rig released at 2 AM.

March 23, 1970


 for Placid Oil Company

DAILY DRILLING REPORT

REPORT NO. 7

DATE MARCH 18/70

OPERATOR

PLACID OIL Co.

CONTRACTOR

S & T DRILLING (WESTERN) CO. LTD.

RIG NO. 5

DRILL PIPE STRING

TOOL JOINT 6

O.D.

TYPE THD. F.H.

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

SIGNATURE OF OPERATOR'S REPRESENTATIVE

WELL NO.

FIELD OR DIST.

COUNTY

STATE

N.W.

PUMPS

NO.

MANUFACTURER

TYPE

STROKE LENGTH

LAST CASING TUBING OR LINER

SIZE

MAKE

WT. & GR.

NO. JOINTS

FEET

RKB. TO CSG. HD.

SET AT

REMARKS

TIME DISTRIBUTION-HOURS

MORN DAY EVE

RIG UP & TEAR DOWN

DRILLING ACTUAL

REAMING

CONDITIONING-MUD & CIRCULATING

TRIPS

LUBRICATE RIG

DEVIATION SURVEY

TEST B.O.P.

CUT OFF DRILLING LINE

PAIR RIG

LOGGING

RUNNING CASING & CEMENTING

WAITING ON CEMENT

DRILL STEM TEST

OTHER

FISHING

A. PERFORATING

B. TUBING TRIPS

C. SWABBING

D. TESTING

E. ADDITIONAL

TOTALS

TIME SUMMARY (OFFICE USE ONLY)

DAY WORK

HRS. W/DP

HRS. WO/DP

HRS. STANDBY

TOTAL DAY WORK

WIRE LINE RECORD

REEL NO.

NO. OF LINES

SIZE

FEET SLIPPED

FEET CUT OFF

PRESENT LENGTH

TON MI. OR TRIPS SINCE LAST CUT

CUMULATIVE TON MI. OR TRIPS

NO. OF DAYS FROM SPUD

CUMULATIVE ROTATING HRS.

NO.

DRILLING ASSEMBLY AT END OF TOUR

STANDS D.P.

SINGLES D.P.

D.C.

I.D. O.D.

D.C.

I.D. O.D.

STB. BODY O.D.

STB. BODY O.D.

RMR. BODY O.D.

SUBS O.D.

BIT OR C.B.

KELLY DOWN

TOTAL

WT. OF STRING

LBS.

REAMER NO.

REAMER TYPE

DRILLER

D.R. D. R. CORE-C

CORE NO.

FORMATION (SHOW CORE RECOVERY)

ROTARY RPM

WT. ON BIT 1000#

PUMP PRESS

PUMP NO. 1

PUMP NO. 2

METHOD RUN

SOL-S PART-L-P COM'D-C

LINER SIZE

S.P.M.

LINER SIZE

S.P.M.

DEPTH

DEV.

DIRECTION

DEPTH

DEV.

DIRECTION

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

TIME LOG

FROM

TO

ELAPSED TIME

DETAILS OF OPERATIONS IN SEQUENCE AND REMARKS

DAILY DRILLING REPORT

REPORT NO. 1

DATE MAR 20, 1978

OPERATOR

PLACID OIL CO.

LEASE

PLACID CHEVRON FOETUS LAKE 2-49

WELL NO.

FIELD OR DIST.

61-10 + 118-30

COUNTY

STATE

N. W. T.

CONTRACTOR

S & T DRILLING (WESTERN) CO. LTD.

RIG NO.

5

DRILL PIPE

STRING

NO. 2

SIZE 4 1/2

TYPE THD. F. H.

TOOL JOINT

6" O.D.

PUMPS

NO.

MANUFACTURER

TYPE

STROKE

LENGTH

LAST

CASING

TUBING

OR LINER

SIZE

MAKE

WT. & GR.

NO. JOINTS

FEET

RKB. TO

CSG. HD.

SET AT

REMARKS

SIGNATURE OF OPERATOR'S REPRESENTATIVE

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

TIME DISTRIBUTION-HOURS

MORN DAY EVE

RIG UP & TEAR DOWN

DRILLING ACTUAL

REAMING

CONDITIONING MUD & CIRCULATING

TRIPS

LUBRICATE RIG

DEVIATION SURVEY

TEST B.O.P.

CUT OFF DRILLING LINE

PAIR RIG

CORING

WIRE LINE LOGGING

RUNNING CASING & CEMENTING

WAITING ON CEMENT

DRILL STEM TEST

OTHER

FISHING

A. PERFORATING

B. TUBING TRIPS

C. SWABBING

D. TESTING

E. ADDITIONAL

TOTALS

TIME SUMMARY (OFFICE USE ONLY)

DAY WORK

HRS. W/DP

HRS. WO/DP

HRS. STANDBY

TOTAL DAY WORK

WIRE LINE RECORD

REEL NO.

NO. OF LINES

SIZE

FEET SLIPPED

FEET CUT OFF

PRESENT LENGTH

TON MI. OR TRIPS SINCE LAST CUT

CUMULATIVE TON MI. OR TRIPS

NO. OF DAYS FROM SPUD

CUMULATIVE ROTATING HRS.

MORNING TOUR

DAY TOUR

EVENING TOUR

NO.		DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD		FOOTAGE		FORMATION (SHOW CORE RECOVERY)		ROTARY RPM		WT. ON BIT 1000#		PUMP PRESS		PUMP NO. 1		PUMP NO. 2		METHOD RUN					
NO.		STANDS D.P.		BIT NO.		TIME		FROM		TO		CORE NO.		DEPTH		DEV.		DIRECTION		DEPTH		DEV.		DIRECTION			
16		1475.71 FT.		2		4:00 7:00		1970		2038		D		120		12-15		1075		5 1/2		59		5 1/2		S	
2		SINGLES D.P.		7 1/2		9.5 9.3		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
15		6 1/4 458.45		H.W.		VISC-SEC 34 34		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
RMR. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
SUBS		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
BIT OR C.B.		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
KELLY DOWN		14.98 FT.		COND. OF BIT		RUN		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
TOTAL		2038.00 FT.		REAMER NO.		REAMEX 1.0		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
WT. OF STRING		74 LBS.		REAMER TYPE		DRILLER		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
7		1587.64 FT.		2		10:00 12:00		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
2		SINGLES D.P.		7 1/2		9.3 9.3		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
15		6 1/4 458.45		H.W.		VISC-SEC 34 34		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
RMR. BODY		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
SUBS		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
BIT OR C.B.		O.D.		NO. 3		FLTR. CK.		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
KELLY DOWN		22.96 FT.		COND. OF BIT		RUN		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
TOTAL		2145.00 FT.		REAMER NO.		REAMEX 1.0		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
WT. OF STRING		77 LBS.		REAMER TYPE		DRILLER		2038		2145		D		120		12-15		1075		5 1/2		58		5 1/2		S	
18		1682.64 FT.		2		6:00 8:00		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
2		SINGLES D.P.		7 1/2		9.4 9.4		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
15		6 1/4 458.45		H.W.		VISC-SEC 34 34		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
D.C.		I.D. O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
STB. BODY		O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
RMR. BODY		O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
SUBS		O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
BIT OR C.B.		O.D.		NO. 3		FLTR. CK.		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
KELLY DOWN		34.98 FT.		COND. OF BIT		RUN		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
TOTAL		2245.00 FT.		REAMER NO.		REAMEX 1.0		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	
WT. OF STRING		78 LBS.		REAMER TYPE		DRILLER		2145		2245		D		120		12-15		1075		5 1/2		58		5 1/2		S	

[illegible]

DAILY DRILLING REPORT

REPORT NO. 2

DATE: MARCH 18/70

OPERATOR

PLACID OIL CO.

LEASE

PLACID CHEVRON FOETUS LAKE 6-49

WELL NO.

FIELD OR DIST.

COUNTY

STATE

N. W. T.

CONTRACTOR

S & T DRILLING (WESTERN) CO. LTD.

RIG NO.

5

DRILL PIPE

STRING

NO. 1

SIZE

2 1/2

TYPE THD. F. H.

O.D.

6

TOOL JOINT

6

PUMPS

NO.

1

2

3

MANUFACTURER

NAT.

NAT.

NAT.

TYPE

6-230

8-150

12

STROKE

15

12

12

LAST

CASING

TUBING

OR LINER

SIZE

8 1/2

MAKE

MANN

WT. & GR.

24-353

NO. JOINTS

7

FEET

208

RKB. TO

CSG. HD.

12.70

SET AT

204

REMARKS

SIGNATURE OF OPERATOR'S REPRESENTATIVE

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

TIME DISTRIBUTION-HOURS

	MORNING	AFTERNOON	EVE
RIG UP & TEAR DOWN			
DRILLING ACTUAL	7	2	5 1/2
REAMING		3	
CONDITIONING MUD & CIRCULATING			
TRIPS	1 1/4	2	
LUBRICATE RIG	1/4	1/4	1/4
DEVIATION SURVEY	1/2	1/4	
TEST S.O.P.	1/4		
CUT OFF DRILLING LINE			
PAIR RIG			
WIRE LINE LOGGING			
RUNNING CASING & CEMENTING			
WAITING ON CEMENT			

MORNING TOUR

DAY TOUR

EVENING TOUR

NO.	DRILLING ASSEMBLY AT END OF TOUR	BIT RECORD	MUD RECORD	FOOTAGE	DR. D. RM. R. CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY RPM	WT. ON BIT 1000#	PUMP PRESS	PUMP NO. 1	PUMP NO. 2	METHOD RUN
12	STANDS D.P. 1123.94 FT.	BIT NO. 1	TIME 12:00 2:00 6:00	FROM 1460 TO 1632									
15	SINGLES D.P. 458.45 FT.	SIZE 7 1/2	WEIGHT 7.3 8.9 9.0										
	D.C. 6 1/2	MFG. REED	VISC-SEC										
	I.D. O.D. 458.45 FT.	TYPE STS	W.L.-C.C.										
	D.C.	NOZZLE NO. 2 1	FLTR. CK.										
	I.D. O.D.	SIZE 12 1/2	PH										
	STB. BODY O.D.	SER. NO. 15677	SD. CONT. %										
	STB. BODY O.D.	DEPTH OUT	PRESSURE GRADIENT										
	RMR. BODY O.D.	DEPTH IN 227											
	SUBS O.D. 18.84 FT.	TOTAL FTG. 1305	MUD & CHEMICALS ADDED										
	BIT OR C.B.	TOTAL HR. RUN 50 1/4	TYPE AMT. TYPE AMT.										
	KELLY DOWN 30.77 FT.	COND. OF BIT RUN											
	TOTAL 1632.00 FT.	REAMER NO.											
	WT. OF STRING 68 M LBS.	REAMER TYPE											
		DRILLER Don Boyle											

NO.	DRILLING ASSEMBLY AT END OF TOUR	BIT RECORD	MUD RECORD	FOOTAGE	DR. D. RM. R. CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY RPM	WT. ON BIT 1000#	PUMP PRESS	PUMP NO. 1	PUMP NO. 2	METHOD RUN
12	STANDS D.P. 1123.94 FT.	BIT NO. 1 2	TIME 10:00 12:00 3:00	FROM 1632 TO 1655									
15	SINGLES D.P. 28.37 FT.	SIZE 7 1/2 7 1/2	WEIGHT 8.7 8.4 9.0										
	D.C. 1 1/2	MFG. REED	VISC-SEC 27 27 27										
	I.D. O.D. 458.15 FT.	TYPE STS X 1/2	W.L.-C.C.										
	D.C.	NOZZLE NO. 2 1 3	FLTR. CK.										
	I.D. O.D.	SIZE 12 1/2 12	PH 8.0 8.0 8.0										
	STB. BODY O.D.	SER. NO. 161799 21392	SD. CONT. %										
	STB. BODY O.D.	DEPTH OUT 1160	PRESSURE GRADIENT										
	RMR. BODY O.D.	DEPTH IN 327 1140											
	SUBS O.D. 11.91 FT.	TOTAL FTG. 1313 15	MUD & CHEMICALS ADDED										
	BIT OR C.B.	TOTAL HR. RUN 31 1 1/4	TYPE AMT. TYPE AMT.										
	KELLY DOWN 28.41 FT.	COND. OF BIT RUN											
	TOTAL 1655.00 FT.	REAMER NO.											
	WT. OF STRING 66 M LBS.	REAMER TYPE											
		DRILLER P. O. W. H. H.											

NO.	DRILLING ASSEMBLY AT END OF TOUR	BIT RECORD	MUD RECORD	FOOTAGE	DR. D. RM. R. CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY RPM	WT. ON BIT 1000#	PUMP PRESS	PUMP NO. 1	PUMP NO. 2	METHOD RUN
13	STANDS D.P. 1213.30 FT.	BIT NO. 2	TIME 11:00	FROM 1705 TO 1705									
15	SINGLES D.P. FT.	SIZE 7 1/2	WEIGHT 9.0										
	D.C. 6 1/2	MFG. HW	VISC-SEC 28										
	I.D. O.D. 458.45 FT.	TYPE X 1/2	W.L.-C.C.										
	D.C.	NOZZLE NO. 3	FLTR. CK.										
	I.D. O.D.	SIZE 12	PH 8.0										
	STB. BODY O.D.	SER. NO. 21392	SD. CONT. %										
	STB. BODY O.D.	DEPTH OUT	PRESSURE GRADIENT										
	RMR. BODY O.D.	DEPTH IN 1140											
	SUBS O.D. 14.81 FT.	TOTAL FTG. 15	MUD & CHEMICALS ADDED										
	BIT OR C.B.	TOTAL HR. RUN 6 1/4	TYPE AMT. TYPE AMT.										
	KELLY DOWN 26.97 FT.	COND. OF BIT RUN											
	TOTAL 1705.00 FT.	REAMER NO.											
	WT. OF STRING 68 M LBS.	REAMER TYPE											
		DRILLER P. O. W. H. H.											

TIME SUMMARY (OFFICE USE ONLY)

DAY WORK	
HRS. W/DP	
HRS. WO/DP	
HRS. STANDBY	

TOTAL DAY WORK	
----------------	--

WIRE LINE RECORD

REEL NO.	
NO. OF LINES	SIZE
FEET SLIPPED	
FEET CUT OFF	
PRESENT LENGTH	
TON MI. OR TRIPS SINCE LAST CUT	
CUMULATIVE TON MI. OR TRIPS	
NO. OF DAYS FROM SPUD	
CUMULATIVE ROTATING HRS.	

OPERATOR: Plastic Oil DAILY DRILLING REPORT REPORT NO. 2 DATE: 10/1/10

CONTRACTOR: S & T DRILLING (WESTERN) CO. LTD. RIG NO. 5 LEASE: Plastic Oil Section Lake

WELL NO. 2-119 FIELD OR DIST. N.W. COUNTY STATE

SIGNATURE OF OPERATOR'S REPRESENTATIVE: SIGNATURE OF CONTRACTOR'S TOOL PUSHER

TIME DISTRIBUTION - HOURS: MORNING DAY EVENING

DRILLING ACTUAL: 3:11 6:17

REAMING: 1/2

CONDITIONING MUD & CIRCULATING: 1/4

DEVIATION SURVEY: 1 3/4

TEST S.O.P.:

CUT OFF DRILLING LINE:

PAIR RIG:

WIRE LINE LOGGING:

RUNNING CASING & CEMENTING:

WAITING ON CEMENT:

DRILL STEM TEST:

OTHER:

FISHING:

COMPLETION WORK:

TIME SUMMARY (OFFICE USE ONLY):

DAY WORK:

HRS. W/DP:

HRS. WO/DP:

HRS. STANDBY:

TOTAL DAY WORK:

WIRE LINE RECORD:

REEL NO.:

NO. OF LINES:

SIZE:

FEET SLIPPED:

FEET CUT OFF:

PRESENT LENGTH:

TON MI. OR TRIPS SINCE LAST CUT:

CUMULATIVE TON MI. OR TRIPS:

NO. OF DAYS FROM SPUD:

CUMULATIVE ROTATING HRS.:

NO. DRILLING ASSEMBLY AT END OF TOUR: BIT RECORD: MUD RECORD: FOOTAGE: FORMATION (SHOW CORE RECOVERY):

STANDS D.P. FT. BIT NO. 2A 3A TIME 9:00 11:00

SINGLES D.P. FT. SIZE 7 7/8 WEIGHT 50 46

D.C. 215.96 MFG. HTD VISC-SEC 50 46

I.D. O.D. FT. TYPE YFAC T W.L.-C.C.

I.D. O.D. FT. NOZZLE NO. 2 1 FLTR. CK

STB. BODY O.D. FT. SER. NO. 75519 SD. CONT. %

STB. BODY O.D. FT. DEPTH OUT 140 PH

RMR. BODY O.D. FT. DEPTH IN 140 PRESSURE GRADIENT

SUBS O.D. FT. TOTAL FTG. 150 MUD & CHEMICALS ADDED

BIT OR C.B. FT. TOTAL HR. RUN 5:00 TYPE AMT. TYPE AMT.

KELLY DOWN 11:00 FT. COND. OF BIT 7:11

TOTAL 295 FT. REAMER NO. REAMER TYPE DRILLER

WT. OF STRING 39 LBS.

NO. DRILLING ASSEMBLY AT END OF TOUR: BIT RECORD: MUD RECORD: FOOTAGE: FORMATION (SHOW CORE RECOVERY):

STANDS D.P. FT. BIT NO. 3A TIME 9:00 11:00

SINGLES D.P. FT. SIZE 7 7/8 WEIGHT 50 46

D.C. 215.96 MFG. HTD VISC-SEC 50 46

I.D. O.D. FT. TYPE YFAC T W.L.-C.C.

I.D. O.D. FT. NOZZLE NO. 2 1 FLTR. CK

STB. BODY O.D. FT. SER. NO. 75519 SD. CONT. %

STB. BODY O.D. FT. DEPTH OUT 140 PH

RMR. BODY O.D. FT. DEPTH IN 140 PRESSURE GRADIENT

SUBS O.D. FT. TOTAL FTG. 150 MUD & CHEMICALS ADDED

BIT OR C.B. FT. TOTAL HR. RUN 5:00 TYPE AMT. TYPE AMT.

KELLY DOWN 11:00 FT. COND. OF BIT 7:11

TOTAL 295 FT. REAMER NO. REAMER TYPE DRILLER

WT. OF STRING 39 LBS.

NO. DRILLING ASSEMBLY AT END OF TOUR: BIT RECORD: MUD RECORD: FOOTAGE: FORMATION (SHOW CORE RECOVERY):

STANDS D.P. FT. BIT NO. 3A TIME 9:00 11:00

SINGLES D.P. FT. SIZE 7 7/8 WEIGHT 50 46

D.C. 215.96 MFG. HTD VISC-SEC 50 46

I.D. O.D. FT. TYPE YFAC T W.L.-C.C.

I.D. O.D. FT. NOZZLE NO. 2 1 FLTR. CK

STB. BODY O.D. FT. SER. NO. 75519 SD. CONT. %

STB. BODY O.D. FT. DEPTH OUT 140 PH

RMR. BODY O.D. FT. DEPTH IN 140 PRESSURE GRADIENT

SUBS O.D. FT. TOTAL FTG. 150 MUD & CHEMICALS ADDED

BIT OR C.B. FT. TOTAL HR. RUN 5:00 TYPE AMT. TYPE AMT.

KELLY DOWN 11:00 FT. COND. OF BIT 7:11

TOTAL 295 FT. REAMER NO. REAMER TYPE DRILLER

WT. OF STRING 39 LBS.

DAILY DRILLING REPORT

REPORT NO.

DATE 11/10/64

OPERATOR

CONTRACTOR

S & T DRILLING (WESTERN) CO. LTD.

RIG NO.

DRILL PIPE

STRING

TOOL JOINT

O.P.

PUMPS

WELL NO.

FIELD OR DIST.

COUNTY

NATURE OF OPERATOR'S REPRESENTATIVE

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

TIME DISTRIBUTION—HOURS

MORN DAY EVE

UP & DOWN

DRILLING ACTUAL

CIRCUITING

CONDITIONING MUD

CIRCULATING

S

CRICATE RIG

ATION SURVEY

T.O.P.

OFF

LING LINE

AIR RIG

NG

LINE

ING CASING

MENTING

ING ON

ENT

L STEM TEST

ER

ING

A. PERFORATING

B. TUBING TRIPS

C. SWABBING

D. TESTING

E. ADDITIONAL

ALS

TIME SUMMARY

(OFFICE USE ONLY)

WORK

W/DP

WO/DP

STANDBY

L DAY WORK

WIRE LINE RECORD

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

E LAST CUT

ULATIVE

ML OR TRIPS

OF DAYS

M SPUD

ULATIVE

ATING MCL

NO.

OF LINES

SIZE

SLIPPED

CUT OFF

ENT LENGTH

ML OR TRIPS

