

Shell Arctic Red River

Q - 27.

Drilling Authority No. 476
Date Issued 17 December 1970

WELL NAME Shell Arctic Red River 0-27
FIELD Area:
LOCATION: Unit 0 Section 27 Grid 66-50-132-45
Latitude 66-46-56.032 Longitude 132-49-35.881
U.W.L.R. 66.78223 --- 132.82663
U.W.I. 3000276650132450

Rig Release Date:
Status:
Information Release Date:

CHANGE OF NAME:

DATE RECEIVED	INDEX
17-12-70	Application for a Drilling Authority. Well Completion Data. Well History Report.
	Application to Amend a Drilling Authority.
	Application to change a Well Name.
27-1-71	Application to Abandon a Well or Suspend Drilling.
	Application to Alter Condition of a Well. Well History Supplement.
18-2-71	Well Completion Data. Work-over Report No.
	Application to Commingle Production before Measurement.
	Data for Back Pressure Test on Natural Gas Wells - Monograph 7 Method.
	Data for Back Pressure Test on Natural Gas Wells - Vitter's Method.
	M.P.R. - Oil - Calculations.
	New Oil Well Report.
	New Gas Well Report.
	Well Inspection Report.
	Rig Inspection Report.
	Battery Inspection Report.
	Equipment Report.
	Well Card.
	New Service Well Report.
	Monthly Water Flood Operations Report
	Monthly Water Receipts and Disposal of Fluids Report Logs. Large scale..... Small scale.....




Drilling Authority No.476.....

Date Issued **Dec. 17, 1970**

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
RESOURCE MANAGEMENT DIVISION

WELL COMPLETION DATA

To be submitted in duplicate within thirty days after the completion, rework, abandonment, or suspension of every well.



Well name and number **Shell Arctic Red River 0-27**

Permit No. **6478** Lease No.

Shell Canada Ltd. & Shell Exploratory Licence No. **108 and 116**
(Permittee, Licensee, Lessee) **Explorer Ltd.**

Shell Canada Limited Exploratory Licence No. **108**
(Operator)

Location: Unit **0** Section **27** Grid **66°50'N., 132°45'W.**

Latitude **66°46' 56.032"N.** Longitude **132°49' 35.881"W.**

From Established Reference Marker

Universal Well Location Reference **Lat. 66.78223°N. Long. 132.82663°W.**

	DATE	DEPTH
Spudded	Dec. 26/70	
Suspended		
Resumed Operations		
Finished Drilling	Jan. 18/71	7067
Deepened		
Complete (gas/oil)		
Abandoned	Jan. 23/71	7067
Rig released	Jan. 23/71	7067

Pool(s)

Interval(s) open to production

Elevation: Gr. **432** K.B. **448**

Rig No. **11**

Drilling Contractor **Gustavson Drilling (1964)**

Contractor's Business Licence No. **0832** **Ltd.**

CASING RECORD

Casing Size (Inches)	Grade	Weight	Amount	Set at -	Sacks of Cement and Additives
1. 9 5/8"	K-55	36#	25 its.	812	150 sacks of
2.					permeafrost
3.					280 sacks of
4.					portland cement.
5.					
6. Cond. Pipe: 20"		53#	60'	60'	

GEOLOGICAL TOPS	ELEVATION		CORE RECORD					
	Depths	Sub-Sea	From	To	Rec.	From	To	Rec.
Imperial	400	+48	5188	5217	28.6			
Carol	3246	-2798						
Hume	3518	-3070						
Bear Rock	3852	-3404						
Delorme	5358	-4910						
Mt. Kindle	6292	-5844						

LOG RECORD

Run No.	Type of Log	From	To
1	Dual Induction		
	Laterolog	813	7058
1	Borehole-Sonic	813	7062
1	Microlog-Caliper	813	7063
1	Sidewall Neutron		
	Porosity	813	7063
1	Seismic Reference	813	7062
	Survey		



File No.
Drilling Authority No. 476

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
OIL AND MINERAL DIVISION

Application to Abandon a Well

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to abandon, to suspend drilling:—

Name and number of well Shell Arctic Red River 0-27
Location: Unit 0 Section 27 Grid (66°50'N. 132°45'W)
Latitude 66° 46' 56.032"N. Longitude 132° 49' 35.881"W.
From Established Reference Marker
Universal Well Location Reference Lat. 66.78223°N. Long. 132.82663°W.
Permit No. 6478 Lease No.

Shell Canada Limited
Shell Explorer Ltd.

Date of commencement of proposed program

OIL, GAS, AND WATER ENCOUNTERED
(Depths)

Oil at
Gas at
Water at 5120-5250
Total Depth 7067 Date of last operations January 23, 1971
Present condition of well

CASING RECORD

Casing Size O.D. Inches	Weight	Amount	Set At—	Sacks of Cement and Additives	Amount Pulled
1. <u>9 5/8"</u>	<u>36½</u>	<u>25 jts.</u>	<u>812'</u>	<u>150 sacks of</u>	
2. <u> </u>				<u>permafrost cement</u>	
3. <u> </u>				<u>280 sacks of</u>	
4. <u> </u>				<u>common cement</u>	
5. <u> </u>					

PROPOSED ABANDONMENT PROGRAM

Plug		Geological Formation	Number of Sacks of Cement	Remarks
No.	Position			
<u>1</u>	<u>6200-7067</u>	<u>Mt. Kindle</u>	<u>470</u>	
<u>2</u>	<u>5300-5500</u>	<u>Delorme</u>	<u>200</u>	
<u>3</u>	<u>740-900</u>	<u>Imperial</u>	<u>150</u>	
<u>4</u>	<u>Surface</u>		<u>5</u>	<u>Permanently marked pipe.</u>

The following logs have been run SNP, BHCS-GR-C, MLC, DILL
Other operations proposed

Operations to be carried out by Gustavson Contractor Licence No. 0832
Address 9825-60th Ave. Edmonton, Alberta Address Box 186, Edmonton, Alta
Responsible Agent in field D. Brown
Dated at Edmonton, Alberta, this 26th Day of January 1971
Signed by [Signature] Company Shell Canada Limited
Title Manager, Edmonton Div. Prod. Operator's Exploratory Licence No. 108

Note:—The Oil Conservation Engineer's office must be notified before work is commenced.

(For OIL AND MINERAL DIVISION use only)

APPROVAL

This application has been examined and proposed programme approved, subject to the following conditions:

Confirming oral approval given by Mr. B.H.J. Thom
on the 22nd January 1971.

Dated 27th January, 19 71

[Signature]
Oil Conservation Engineer

Drilling Authority No. 476

Project No.

File No.



CANADA

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
OIL AND MINERAL DIVISION

Application for a Drilling Authority

This notice of intention to begin drilling operations, in triplicate, and where required a plan of survey approved by the Surveyor General showing the target area or the site of the well must be submitted and approved before commencing operations.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to drill:—

Name and number of well **Shell Arctic Red River 0-27**
 Location: Unit **0** Section **27** Grid **(66°50'N. 132°45'W)**
 Latitude **66° 46' 56.032"N.** Longitude **132° 49' 35.881"W.**
 Unique Well Identifier **3000276650132450**
 Universal Well Location Reference **Lat. 66.78223°N. Long. 132.82663°W.**
 Elevation: Ground **432.4** K.B. **449 (Est.)** feet above sea-level.
 Well is expected to produce from **Bear Rock** formation at a depth
 of about **5,000** feet. Expected total final depth **7,000**
 Area assigned to well. (for Oil Conservation Engineer's use only)

Permit No. **6478** Lease No. **50,604 acres**
 Permittee, licensee, or lessee **Shell Canada Limited & Shell Explorer Ltd.**
 Exploratory Licence No. **108** **116**
 Surface owned by **Crown** or (If alienated, submit name and address of owner and occupant.)

Petroleum and natural-gas rights owned by **Crown**

We propose to use the following strings of casing, either cementing or landing them as indicated below:—

Casing Size O.D. (Inches)	Weight (Lb./Ft.)	Grade	New or Used	Estimated Depth	Sacks of Cement
1. 9 5/8"	36#	K-55	New	800	500 sxs.
2.					
3.					
4.					
5.					

Expected water, gas, and oil horizons and type of control equipment **Unknown**

10" Hydril, Double Ram (10") SOP's

Well will be drilled with Rotary Rig No. **11** by **Gustavson**
 (Drilling Contractor or company)

Responsible agent of applicant:— Contractor's Business Licence No. **0832**
 At well **D. Brown** At registered office **D.S. Fleming**
 Address **Box 186, Edmonton** Address **Box 186, Edmonton, Alberta**
 It is understood that if changes become necessary, notice of the change of plan will be submitted.
 Dated at **Edmonton, Alberta** this **11th** day of **December** 19 **70**
 Signed by **P. J. Berra** Company **Shell Canada Limited**
 Title **Manager, Edmtn. Div. Prod. Operator's Licence No. 108**

(For Oil and Mineral Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:—

1. Copies of this Drilling Authority shall be exhibited at the Drilling Rig in both the Doghouse and Drilling Foreman's Office between spud and rig release dates.
2. The Company will submit to this office, on Tuesday of each week, the latest reports

Dated **17th December** 19 **70** Please see over page
 Oil Conservation Engineer

Forms to be submitted to Oil Conservation Engineer,
 Department of Indian Affairs and Northern Development, Calgary, Alberta.

received by radio on the progress of the well.

3. During well drilling and testing operations, every effort shall be made to ensure that drilling fluids, chemicals and wastes shall be disposed of or contained in a manner that will prevent the contamination of adjacent vegetation and surface or sub-surface waters.
4. We draw your attention to Sections 95 and 96 of the Canada Oil and Gas Land Regulations.
5. Any additional strings of casing are to receive the approval of the Oil Conservation Engineer prior to running.

B.H.J. Thoms


B.H.J. Thoms, Oil Conservation Engineer

WELL PROGNOSIS

TIGHT HOLE

EXPLORATION PROGRAM - WEST GLACIER BLOCK N.W.T., WINTER 1971

WELL: Shell Arctic Red River 0-27
LOCATION: Lat. 66° 46' 56.03" N.
Long. 132° 49' 35.881" W.
ELEVATION: G.L. + 432' (Act.)
K.B. + 448' (Est.)
TOTAL DEPTH: 7,000'



A. Summary of Drilling Program

(Refer to Drilling Operations Program for details)

(i) Hole and Casing Program:

- (a) Auger drill 24" conductor hole to 60'
- (b) Set 60' of 20" 53# conductor pipe
- (c) Install 10" casing bowl and 10" Series 900 Hydril
- (d) Drill 8 3/4" hole to 800', ream to 13 3/4"
- (e) Set 9 5/8" 36# K-55 casing
- (f) Install 10" Series 900 casing bowl and 10" Series 900 BOP stack
- (g) Drill 8 3/4" hole to T.D.

(ii) Deviation:

- (a) Target area for all objective zones (see attachment)
- (b) Surveys must be taken at least every 250'

(iii) Mud Properties:

Ensure that mud properties are such that the following criteria are satisfied.

- (a) Mud is capable of forming good quality mud cake for definition of permeable zones.
- (b) Representative and good quality samples are obtained.
- (c) Hole conditions are maintained such that there is negligible fill to accomodate "behind the bit" evaluation procedures (i.e. coring, testing and logging)
- (d) Below 3000' maintain a maximum 8.0 cc water loss to eliminate excessive invasion which is detrimental to good reservoir evaluation by electric logs.

B. Evaluation Program

(i)	<u>Formation Tops</u>	<u>Symbol</u>	<u>Lithology</u>	<u>Depth</u>
	Imperial	Dim	Shale, silt and sand	150'
	Canol	Dca	Chert and shale	3350'
	Hume	Dh	Limestone and shale	3600'
	Bear Rock	Dbr	Upper Limestone-, and basal dolomite interval	4000'
	Delorme	D/S	Upper-, and basal shale sand member	5500'
			Middle dolomite member	6500'
	Mount Kindle	S-Ok	Dolomite and chert	7000'
	T.D.			

(ii) Samples:

- (a) One large (8" x 12") unwashed, Plastic Lined bag every 10' from surface to T.D.
- (b) One small (4" x 6") semi-washed, Non Lined bag every 10' from surface to T.D.
- (c) Two washed and dried plastic vial cuts every 10' from surface to T.D.
- (d) One semi-washed canned sample every 30' from surface to T.D. for the Geological Survey of Canada.

(iii) Cores:

- (a) A 30' core will be cut whenever reservoir quality rock is encountered.
- (b) Be prepared to cut approximately 100' of core at unspecified intervals for paleontological and/or lithological purposes. Instructions will be obtained from General Section.

(iv) Drill Stem Tests:

- (a) After obtaining a core containing reservoir quality rock a conventional off-bottom drill stem test will be run before drilling ahead.
- (b) Additional tests will be carried out where warranted after reaching final total depth and logs have been run.

NOTE:

Lynes United will provide testing tools and personnel from their base at Kaps Transport's camp in Inuvik.

(v) Logs:

<u>Tool</u>	<u>Interval</u>	<u>Remarks</u>
DILL	T.D. to surface casing	2" and 5" scales
BHCS-GR-C <u>(integrated)</u>	T.D. to surface casing	2" and 5" scales 40-70-100 sensitivity to top of carbonate 40-60-80 sensitivity below top of carbonate
FDC-GR	T.D. to surface casing	2" and 5" scales
SNP	T.D. to surface casing	2" and 5" scales
MLC	T.D. to surface casing	2" and 5" scales

A seismic reference survey will be shot at T.D. after the above logs have been run.

NOTE:

Obtain 6 field prints of each log and have them flown to Edmonton as soon as possible.

RECOMMENDED

P. S. B. 10 Dec 70

APPROVED

[Signature]

RECOMMENDED

[Signature] Dec 10/70

DATE

Dec 11, 1970

RECOMMENDED

[Signature] Dec 11/70

APPROVED

P. O. Brady Jr. RSM

RECOMMENDED

P. O. Brady Dec. 15/70

DATE

Dec. 15/70

*297
K.R. [Signature]*

67° 00'

ATTACHMENT # 1
WEST GLACIER AREA
N.W.T.

Scale - 1" = 16000'

SHELL
Arctic Red River


66° 45'


WEST GLACIER

132° 40'

133° 00'

20'





ENCLOSURE # 2

WEST GLACIER AREA

LOCATION: SHELL - Arctic
Red River I-20

Scale: 1" = 1000'

IMP 26-9

PREFERRED LOCATION


Target Area

2-90

2-91

2-89

SHELL ARCTIC
WELL RED RIVER 0-27 DATE Dec. 15/70 CONTRACTOR Gustafson



NOTES:

1. KELLY COCK MUST BE USED - MIN. W.P. 3000 PSI.
2. SELF SEALING RING GASKETS MUST BE USED.
3. IF BOP HAS FLANGED SIDE OUTLET, IT MUST BE EQUIPPED WITH A SERIES 900 STEEL GATE VALVE OR COMPANION BLIND FLANGE. BOP'S WITH SCREWED SIDE OUTLETS NOT ACCEPTABLE.
4. PRESSURE ACCUMULATOR UNIT AND TWO NITROGEN CYLINDERS FOR EMERGENCY TO BE LOCATED 100 FEET FROM WELL IN HEATED HOUSE. PRESSURE IN NITROGEN CYLINDERS SHALL BE MAINTAINED AT 1500 PSI OR MORE.
5. BOP CONTROLS MUST BE PROVIDED ON THE FLOOR AND AT THE ACCUMULATOR.
6. CHOKE MANIFOLD VALVES MUST BE EASILY ACCESSIBLE.
7. NO THREADED OR WELDED CONNECTIONS TO BE USED FROM DRILLING SPOOL OUT TO CHOKES.
8. A SINGLE CHOKE MANIFOLD IS ACCEPTABLE FOR COMPLETION WORK.
9. BOP'S AND ASSOCIATED EQUIPMENT MUST BE TESTED IN ACCORDANCE WITH THE FOLLOWING PROCEDURES PRIOR TO DRILLING OUT CASING - PRESSURE TEST ALL BLOWOUT CONTROL EQUIPMENT (INCLUDING KELLY COCK) WITH WATER TO 77% OF RATED BURST RESISTANCE OF CASING STRING (2400 PSI MAX.). DAILY TESTS - CHECK CLOSING AND OPENING OF BOP'S WITH ACCUMULATOR AND WORK KELLY COCK. 15 DAY TESTS - PRESSURE TEST KELLY COCK FROM BELOW WITH WATER TO 2400 PSI. - CLOSE HYDRIL WITHOUT PIPE IN HOLE. - RETIGHTEN ALL FLANGES IN BOP STACK AND CHOKE MANIFOLD. SUBSEQUENT TESTS - APPROXIMATELY EVERY 45 DAYS, AND AS DIRECTED BY SHELL, PRESSURE TEST CASING AND ALL BLOWOUT EQUIPMENT WITH WATER TO 67 PER CENT OF RATED BURST RESISTANCE OF CASING STRING (MAX. 2400 PSI) FOR A MINIMUM OF 15 MINUTES USING A DEMCO TESTER OR OTHER PACKER ABOVE THE SHOE.

SHELL CANADA LIMITED CALGARY E. & P. PRODUCTION DEPT-MECHANICAL ENG. SECTION		
B.O.P. CLASSIFICATION NO.3. SERIES 900 DRILLING TO 15,000 FT. COMPLETION TO 12,000 FT.		
DESIGNED -	SCALE - N.T.S.	
DRAWN	CHKD. - <i>W83</i>	DATE - 10/63
APPR <i>BBB</i>	A-XX-D15-3642	



File No.....
Drilling Authority No.....476.....

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT

OIL AND MINERAL DIVISION

WELL-SITE INSPECTION REPORT

FROM: Field Office or Area: INUUVIK Date: 10th July 1971

TO: The Oil Conservation Engineer:

RE: SHELL ARCTIC RED RIVER 0-27 66-50-132-K5

Location: 66.78223°N., 132.82663°W. Status: D&A 1971

This location was inspected by the undersigned on 10th July 1971

The location is in satisfactory/unsatisfactory condition. TD 7067'


The following items require attention:

1. Remove lumber around cellar and backfill.
2. Bury plastic sheeting.
3. Paint identifier pipe and plate fluorescent orange.
4. _____
5. _____
6. _____

Other comments and recommendations: (Include Map, if necessary for clarity)

Good cleanup but polyethylene sheeting left lying around.

Lease level but very soft and muddy.



Inspected by M. D. Thomas


M. D. Thomas
District 2

WELL HISTORY REPORT

SHELL ARCTIC RED RIVER 0-27

37-11-6-104

37-11-6-104



WELL HISTORY REPORT

SHELL ARCTIC RED RIVER 0-27

SHELL CANADA LIMITED

WELL HISTORY REPORT

SHELL ARCTIC RED RIVER 0-27

TABLE OF CONTENTS

		<u>Page</u>
SECTION I	<u>SUMMARY OF WELL DATA</u>	1
SECTION II	<u>GEOLOGICAL SUMMARY</u>	3
	(a) Formation Tops	
	(b) Core Intervals	
	(c) Core Description	
	(d) Sample Description	
	(e) Paleontological Determinations	
SECTION III	<u>ENGINEERING SUMMARY</u>	6
	(a) Drill Stem Tests	
	(b) Casing Record	
	(c) Bit Record	
	(d) Mud Report	
	(e) Deviation Record	
	(f) Abandonment Plugs	
	(g) Lost Circulation Zones	
	(h) Blowouts	
SECTION IV	<u>LOGS</u>	8
SECTION V	<u>ANALYSIS</u>	9
	(a) Core	
	(b) Water	
	(c) Gas	
	(d) Oil	
SECTION VI	<u>COMPLETION SUMMARY</u>	10
	(a) Tubing Record	
	(b) Perforation Record	
	(c) Cementation	
	(d) Acidization and Fracturing	
	(e) Back Pressure and Production	
APPENDIX "A"		11
APPENDIX "B"		12

SECTION I - SUMMARY OF WELL DATA(a) Well Name and Number

Shell Arctic Red River 0-27

(b) Permittee

Shell Canada Limited
P.O. Box 186
Edmonton, Alberta
and
Shell Explorer Limited

(c) Name of Operator

Shell Canada Limited

(d) Location

Unit 0, Section 27, Grid 66°50'N., 132°45'W.
Latitude: 66° 46' 56.032" N.
Longitude: 132° 49' 35.891" W.
Universal Well Location Reference:
Lat. 66.78223°N.
Long. 132.82663°W.
Unique Well Identifier: 3000276650132450

(e) Permit Number

6478

(f) Drilling Contractor

Gustavson Drilling (1964) Ltd. No. 11

(g) Drilling Authority Number

Drilling Authority No. 476
Issued December 17, 1970

(h) Classification

Wildcat

(i) Elevation

Ground Level 432'
Kelly Bushing 448'

(j) Date Spudded

December 26, 1970, 12:01 A.M.

(k) Date Completed Drilling

January 18, 1971

(l) Total Depth

F.T.D. 7067'

(m) Well Status

Abandoned

(n) Rig Released

January 23, 1971, 11:59 P.M.

(o) Hole Sizes

24" to 60' K.B.
13 3/4" to 813' K.B.
8 3/4" to 7067' K.B.

(p) Casing

20" 53# set at 60'
9 5/8", New K-55, 36#
Surface casing landed at 812' K.B.
Cemented with 150 sacks of permeafrost
cement and 280 sacks of portland cement.

SECTION II - GEOLOGICAL SUMMARY(a) Formation Tops

<u>Formation</u>	<u>Sample Tops</u>	<u>Log Top</u>
Imperial	-	400'
Canol	3240'	3246'
Hume	3546'	3518'
Bear Rock	3880'	3852'
Delorme	5420'	5358'
Mt. Kindle	6310'	6292'

(b) Cored Intervals

Core No. 1:
5188-5217, Basal Bear Rock, Rec. 28.6'

(c) Core Description

Core No. 1: Dolomite, fine to medium, microfractures
closed with calcite.

<u>Coring Times</u>	
<u>Depth</u>	<u>Min./Ft.</u>
5188	
89	17
90	5
91	3
92	4
93	5
94	5
95	4
96	4
97	5
98	5
99	7
5200	7
1	5
2	7
3	6
4	7
5	6
6	5
7	5
8	3
9	5
5210	5

Coring Times

<u>Depth</u>	<u>Min./Ft.</u>
5211	4
12	5
13	5
14	5
15	7
16	6
5217	7

(d) Sample Description

0'-100'	Glacial Till	Shale with sandstone stringers
100'-3540'	Shale-Sandstone-Siltstone	Traces of pyrite calcite, dolomite and chert
3540'-3940'	Shale-Limestone	Traces of pyrite with calcareous siltstone
3940'-4140'	Limestone	Clean limestone with minor amounts of slightly argillaceous limestone. Interbedded shale.
4140'-4590'	Limestone	Clean to slightly argillaceous limestone.
4590'-4690'	Limestone-Dolomite	Clear to slightly argillaceous limestone and dolomite with interbedded shale
4690'-4900'	Dolomite	Clean dolomite with minor amounts of limestone and shale, traces of calcite
4900'-5000'	Dolomite	Clean dolomite with minor amounts of clean limestone
5000'-5020'	Dolomite	Minor amounts of slightly argillaceous limestone
5020'-5120'	Dolomite	Clean dolomite and minor amounts of clean limestone, trace of calcite.
5120'-5250'	Dolomite	Clean dolomite with calcite infilling

5250'-5400'	Dolomite	Slight to moderately argillaceous dolomite. Minor amounts of shale, calcite infilling and siltstone
5400'-5600'	Dolomite	Clean limey dolomite with trace of siltstone, calcite and pyrite. minor amount of shale
5600'-5950'	Dolomite	Clean dolomite with traces of calcite and pyrite
5950'-6350'	Dolomite	Clean to slightly argillaceous dolomite. Traces of calcite
6350'-6520'	Dolomite	Slightly argillaceous dolomite. Traces of pyrite, calcite and chert
6520'-6970'	Dolomite	Slight to moderately argillaceous dolomite. Traces of calcite, pyrite
6970'-7067'	Dolomite	Clean to slightly argillaceous dolomite. Traces of calcite, pyrite and chert

(e) Paleontological Determinations

Nil

SECTION III - ENGINEERING SUMMARY

(a) Drill Stem Tests

<u>No.</u>	<u>Interval</u>	<u>Flow Rate & Recovery</u>	<u>IFP</u>	<u>FFP/ Time</u>	<u>ISIP/ Time</u>	<u>FSIP/ Time</u>
1	5120-5250	2900' mud cut salt water	434	1244/ 60 min.	2239/ 60 min.	2101/ 60 min.
				IHP: 2431.	FHP: 2420.	

(b) Casing Record

<u>Date</u>	<u>Size</u>	<u>Grade</u>	<u>Weight</u>	<u>Amount</u>	<u>Set At</u>
Dec. 26	20"		53#		60'
Dec. 30	9 5/8	K-55	36#	25 jts.	812'

Cemented with 150 sacks of permafrost cement and
280 sacks of portland cement

(c) Bit Record

<u>No.</u>	<u>Size</u>	<u>Type</u>	<u>Depth Out</u>	<u>Footage</u>	<u>Time/Hours on Bottom</u>
1A	8 3/4	DTJ	678'	678	15 3/4
2A	8 3/4	DTJ	816'	138	3 1/4
1B	13 3/4	Reamer	369'	369	14
2B	13 3/4	Reamer	647'	278	13 1/4
3B	13 3/4	Reamer	813'	170	13
1	8 3/4	DTJ	1919'	1106	18 1/4
2	8 3/4	XIG	3009'	1090	19 1/2
3	8 3/4	XIG	3358'	352	11 1/4
4	8 3/4	XDU	3687'	329	19
5	8 3/4	M88	4412'	725	44 3/4
6	8 3/4	X55R	5188'	776	48 1/2
6A	6 7/32	Diamond	5217'	29	3
7	8 3/4	X55R	5679'	462	33 1/2
8	8 3/4	X55R	6050'	371	35
9	8 3/4	M88	6405'	355	35
10	8 3/4	M88	6825'	420	34
11	8 3/4	SCM5	7067'	242	22 1/4

(d) Mud Record

	<u>Pounds</u>
Gel	82,500
Benex	284
Caustic	2,100
CMC	1,750
Peltex	200
Bicarb	100

(e) Deviation Record

<u>Depth</u>	<u>Deviation</u>	<u>Depth</u>	<u>Deviation</u>
100'	1/8°	2606'	1 1/2°
224'	1/4°	2822'	1 1/4°
		3006'	1°
317'	1/2°	3254'	1 1/8°
415'	1/2°	3358'	3/4°
480'	3/4°	3687'	0°
570'	1/4°	3934'	1/4°
678'	1 1/2°	4194'	1/4°
755'	1 1/4°	4420'	1/4°
1051'	1°	4678'	1/2°
1290'	1°	5160'	3/4°
1535'	1°	5679'	1 1/8°
1794'	1 3/4°	6050'	1 1/4°
1919'	1 1/2°	6405'	2°
2160'	1°	6800'	2 7/8°
2420'	2 3/4°	7067'	3°

(f) Abandonment Plugs

<u>Plug Number</u>	<u>Interval</u>	<u>Sacks of Cement</u>
1.	6200-7067'	470
2	5300-5500'	200
3	740-900'	150
4	Surface	10

Plug #2 was felt at 5280'. Plug #3 was felt at 681'. A 1/2" plate was welded on top of the casing and a riser with identification marker was installed.

(g) Lost Circulation Zones

<u>Depth when Circulation Lost</u>	<u>Fluid Lost</u>
5170'	20 bbls. of mud.

(h) Blowouts

Nil

SECTION IV - Logs

<u>Type</u>	<u>Interval</u>	<u>Date</u>
DILL	813'-7058'	January 19, 1971
BHCS-GR-C	813'-7062'	January 19, 1971
MLC	813'-7063'	January 19, 1971
SNP	813'-7063'	January 19, 1971
SRS	813'-7062'	January 20, 1971

SECTION V - ANALYSIS(a) Core Analysis

See Appendix A

(b) Water Analysis

See Appendix B

(c) Gas Analysis

Nil

(d) Oil Analysis

Nil

SECTION VI - COMPLETION SUMMARY(a) Tubing Record

Nil

(b) Perforation Record

Nil

(c) Cementation

<u>Plug no.</u>	<u>Date</u>	<u>Plug Interval</u>	<u>Porous Interval</u>	<u>Sacks of Cement</u>	<u>Depth Felt</u>
1	1/22/71	6200-7067	6250-6700	470	-
2	1/22/71	5300-5500	5450-6100	200	5280
			4485-5350		
3	1/23/71	740-900		150	681
4	1/23/71	Surface		10	


A 1/2" plate was welded on top of the casing and
a riser with identification marker was installed.

(d) Acidization and Fracturing

Nil

(e) Back Pressure and Production

Nil


D.S. Fleming, Manager
Edmonton Division Production

APPENDIX "A"
CORE ANALYSES

SHELL CANADA LIMITED PRODUCTION LABORATORY
CORE ANALYSIS REPORT

Page _____ of _____
Date: January, 1971.

WELL: Shell Arctic Red River 0-27				KB 449		FIELD Wildcat		CORED INTERVAL 5188.0 - 5217.0 RECOVERY 28.6				FORMATION Bear Rock				
Lab. No. SMALL CORE SAMPLES 'S' Suffix	SECTION REPRESENTED		Interval	Ft.	Lithological Description	ORIENTATION	Whole Core Samples - G.D. calc. Small Core Samples - G.D. measured				Oil Sat'n % P.V.	Water Sat'n % P.V.	Fluor Cut	Remarks		
	Interval						Poro %	Kmax md	K90 md	Kvert md					G.D. gm/cc	
Core #1	5188.0 - 5217.0	28.6	Recovery													
A-1	5188.0-5217.0	1.0			DO, CA, III/I, F, B, C		13.7	271. f*	14.7		2.850			N		
A-2	89.0 - 90.0	1.0			DO, CA, III/I, F, B, C		12.7	14.1 f*	12.4 f		2.856			N		
A-3	90.0 - 90.7	0.7			DO, CA, III/I, F, B, C		11.3	6.13 f	6.08f*		2.838			N		
A-4	90.7 - 92.0	1.3			DO, CA, III/I, F, B,		9.5	3.92f*	3.81f		2.838			N		
A-5	92.0 - 93.0	1.0			Similar to A-4									N		
A-6	93.0 - 93.8	0.8			DO, CA, III/I, F, B		8.8	3.20f*	2.43		2.853			N		
A-7	93.8 - 94.5	0.7			DO, CA, III/I, F, B-D		12.8	17.3 f	15.9 f*		2.849			N		
A-8	94.5 - 95.5	1.0			DO, CA, III/I, F, B-D		13.4	18.6 f	17.6 f*		2.856			N		
A-9	95.5 - 96.5	1.0			DO, CA, AN, III/I, F,		10.9	7.73 f	7.61f*		2.844			N		
A-10	96.5 - 98.0	1.5			B-D		7.9	2.20f*	.84		2.843			N		
A-11	99.0-5200.0	1.0			DO, CA, AN I/III, F, B		6.9	.77	.72 *		2.815			N		
A-12	5200.0-5201.0	1.0			DO, CA, AN, tr PY, I/III		4.6	1.24f*	.42		2.796			N		
A-13	01.0 - 02.0	1.0			F, B		9.3	1.33 *	1.13		2.855			N		
A-14	02.0 - 03.0	1.0			DO, CA, AN, III/I, F, tr B		10.7	2.4. *	2.45		2.849			N		
A-15	03.0 - 04.0	1.0			DO, CA, AN, III/I, F,		11.4	5.78 f	4.66f*		2.853			N		
A-16	04.0 - 05.0	1.0			B-D		12.0	5.91f*	5.37f		2.857			N		
A-17	05.0 - 06.0	1.0			DO, AN, III/I, F, B-D		12.0	11.4 f*	10. f		2.859			N		
A-18	06.0 - 07.0	1.0			DO, AN, III/I, F, B-D		12.8	7.17 *	7.09		2.862			N		
A-19	07.0 - 07.8	0.8			DO, AN, III/I, F, B-D		15.8	33.7 f*	32.7 f		2.851			N		
A-20	07.8 - 08.5	0.7			DO, AN, III/I, FM, B-D		15.6	29.5 f	29. f*		2.852			N		
A-21	08.5 - 09.0	0.5			DO, AN, III/I, FM, B-D		15.1	33.2 f	32.8 f*		2.863			N		
A-22	09.0 - 09.7	0.7			DO, AN, I/III, FM, B-D		10.6	13.9 f*	6.83f		2.827			N		
A-23	09.7 - 10.4	0.7			DO, AN, III/I, FM, B-D		11.3	10.7 f*	6.73f		2.848			N		
A-24	10.4 - 10.8	0.4			DO, AN, III/I, FM, B-D		16.5	49.2 f*	38.6 f		2.853			N		
A-25	10.8 - 11.3	0.5			DO, AN, I/III, FM, CD		16.8	50.9 f	44.0 f*		2.854			N		
					DO, AN, I/III, FM, C-D		18.1	74.8 f	50.4 f*		2.842			N		

Badly broken

Missing

APPENDIX "B"
WATER ANALYSIS

SHELL CANADA LIMITED

PRODUCTION LABORATORY ANALYSIS REPORT CALGARY, ALBERTA

 Laboratory Number 20
WATER

 Sample Received FEBRUARY 2, 1971
 Sample Analyzed FEBRUARY 4, 1971
 Results Reported FEBRUARY 5, 1971

66° 40' 56.032"N


Well SHELL ARCTIC RED RIVER Q-27 132° 49' 35.881" W WEST GLACIER BLK.
 Well K.B. 448.25' G.L. 432'
 T.D. P.B.T.D.
Lsd Sec Twg Rge W FormationMethod of production DST #1 5120-5250'DST Recovery MUD CUT SALT WATERSample obtained from SAMPLE CHAMBER FIELD #5Perforator O.H.Sampled by F. BUDDADate JAN. 21, 1971 Time
 Specific Gravity at 60°F 1.0455 pH 6.5 Resistivity 0.161 ohm-m at 60°F H₂S NONE Calculated Total Solids 53,972 Mg/L

	Calc. Na+K	Ca	Mg	Fe	CO ₃	HCO ₃	SO ₄	Cl
Mg./L	19,145	1490	264	MUCH	0	275	126	32,672

MEQ./L	832.42	74.35	21.71		0	4.51	2.62	921.35
--------	--------	-------	-------	--	---	------	------	--------

MEQ. %	44.83	4.00	1.17		0	0.24	0.14	49.62
--------	-------	------	------	--	---	------	------	-------

Milliequivalents per Litre

Remarks: SO₄ POSSIBLY HIGH
 File Code No. 15-1100
 Production Department, Calgary Area 1
 Division Office N. Div. Explor. 5
 Production Laboratory, Calgary Area 2
Chemist N.L. Johnson

NOMENCLATURE (Definition of Symbols)

Q	= average production rate during test, bbls./day
Q_g	= measured gas production rate during test, MCF/day
k	= permeability, md
h	= net pay thickness, ft. (when unknown, test interval is chosen)
μ	= fluid viscosity, centipoise
Z	= compressibility factor
T_r	= reservoir temperature, ° Rankine
m	= slope of final SIP buildup plot, psig/cycle (psig ² /cycle for gas)
b	= approximate radius of investigation, feet
r_w	= wellbore radius, feet
t_o	= total flowing time, minutes
P_o	= Extrapolated maximum reservoir pressure, psig
P_f	= final flowing pressure, psig
$P.I.$	= productivity index, bbls./day/psi
$P.I._t$	= theoretical productivity index with damage removed, bbl./day/psi
$D.R.$	= damage ratio
$E.D.R.$	= estimated damage ratio
AOF	= absolute open flow potential, MCF/D
AOF_t	= theoretical absolute open flow if damage were removed
Z	= subsea depth
W	= water gradient based on salinity
H_w	= potentiometric surface

In making any interpretation, our employees will give Customer the benefit of their best judgment as to the correct interpretation. Nevertheless, since all interpretations are opinions based on inferences from electrical, mechanical or other measurements, we cannot, and do not, guarantee the accuracy or correctness of any interpretations, and we shall not be liable or responsible, except in the case of gross or wilful negligence on our part, for any loss, costs, damages or expenses incurred or sustained by Customer resulting from any interpretation made by any of our agents or employees.

DEFINITION OF SYMBOLS

Recorder Depth 5125 ft. Subsea depth 4677 ft. Ticket No. 1537 Hour Recorder No. 4379

Recorder Depth $t_o = 5$ Mins. Initial Shut-In Pressure				Second Flow Pressure		t _o = 65 Mins. Final Shut-In Pressure			
Time, Min. ϕ	$\frac{t_o + \phi}{\phi}$	PSIG	PSIG ² +100 (Gas)	Time Dufl. .000"	PSIG	Time, Min. ϕ	$\frac{t_o + \phi}{\phi}$	PSIG	PSIG ² +100 (Gas)
0	----	506				0	----	1341	
5	2.000	2151				5	14.000	1932	
10	1.500	2177				10	7.500	1976	
15	1.333	2194				15	5.333	2004	
20	1.250	2205				20	4.250	2022	
25	1.200	2212				25	3.600	2038	
30	1.167	2218				30	3.167	2054	
35	1.143	2223				35	2.857	2065	
40	1.125	2229				40	2.625	2076	
45	1.111	2232				45	2.444	2085	
50	1.100	2235				50	2.300	2094	
55	1.091	2237				55	2.182	2100	
60	1.083	2239				60	2.083	2106	

Recorder Depth ft. Subsoil depth ft. Ticket No. Hour Recorder No.

[illegible]

Interval of Pressure Readings (Mins.)	ISIP	5	2nd Flow Press.	FSIP	5
---------------------------------------	------	---	-----------------	------	---

Remarks: DST # 1

PRESSURE DATA

$t_o + \phi$

50

40

30

20

Rec. No. 4379

Depth 5125 ft.

P_o^2 (Gas) _____ psig²

P_o 2195 psig

m 282 psig/cycle

Initial SIP $\square$ 2254 psig.

2nd SIP $\triangle$

Final SIP $\odot$ 2195 psig.

10

9

8

7

6

5

4

3

2

1.5

1

1700

1800

1900

2000

2100

2200

2300

PSIG (OIL OR WATER)

DST # 1

PRESSURE EXTRAPOLATION PLOT

/ Shell Canada Ltd.

Company

Shell Arctic Red River 0-27 660 46
Well Name and Description 320 49

#1
Test No.

January 21/71
Date of Test

- 1 - INITIAL HYDROSTATIC
- 2 - PRE-FLOW
- 3 - INITIAL SHUT-IN
- 4a - 2nd INITIAL FLOW
- 4b - 2nd FINAL FLOW
- 4c - 2nd SHUT-IN
- 5 - 3rd INITIAL FLOW
- 6 - FINAL FLOW
- 7 - FINAL SHUT-IN
- 8 - FINAL HYDROSTATIC

2431
507
2239

434
1344
2101
2420


2431
506
2239
431
1341
2106
2427

2451
399
2236
437
1327
2100
2446

recorder
malfunctioned

GUIDE TO INTERPRETATION AND IDENTIFICATION OF LYNES DRILL STEM TEST PRESSURE CHARTS

AK-1 recorders. Read from right to left.




K-3 recorders. Read from left to right.

1. INITIAL HYDROSTATIC MUD PRESSURE
2. PRE-FLOW
3. INITIAL SHUT-IN
- 4a. 2nd INITIAL FLOW
- 4b. 2nd FINAL FLOW
- 4c. 2nd SHUT-IN
5. 3rd INITIAL FLOW
6. FINAL FLOW
7. FINAL SHUT-IN
8. FINAL HYDROSTATIC MUD PRESSURE

N.B. When only two shut-in and flow periods are run, 4a, 4b and 4c are omitted.

Typical charts for visual field analysis ranging from very low to high permeability.




Very low permeability. Usually only mud recovered from interval tested. Virtually no permeability.

Slightly higher permeability. Again usually mud recovered.

Slightly higher permeability. Small recovery, less than 200' ft).

Average permeability. Final and initial shut-ins differ by 50 psi.

Average permeability. Strong damage effect. High shut-in pressure, low flow pressure.



Excellent permeability where final flow final shut-in pressure.

High permeability where ISIP and FSIP are within 10 psi.

Deep well bore invasion or damage. Final shut-in higher than the initial shut-in.

Tight hole chamber tester. Permeability very difficult to interpret unless the recovery is less than chamber length. Flow pressure builds up rapidly if recovery is large, similar to a shut-in.

OPERATOR Shell Canada Limited						CONTRACTOR GUSTAFSON				RIG NO. 11	DEPTH AT START OF MORNING TOUR	DEPTH AT END OF EVENING TOUR	DAILY PROGRESS	CUMULATIVE ROTATING HOURS	DAYS FROM SPUD MONTH DAY YEAR 1 23 71		DATE	
SIGNATURE OF OPERATOR'S REPRESENTATIVE <i>[Signature]</i>						SIGNATURE OF CONTRACTOR'S TOOL PUSHER <i>[Signature]</i>				7067				(29)				
DP./DC. SIZE	WT./FT.	GRADE	MIN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER	TYPE	STROKE LENGTH	LAST CASING TUBING OR LINER	SIZE	WT. AND GR.	NO. OF JOINTS	FEET	KB TO CSG HEAD	BCT AT USED (SACKS)	REMARKS	
4"	1.4	E	2 7/8	5 1/4	4FH.	1	NATIONAL	SPFO	8 1/2'									
						2	NATIONAL	SPFO	8 1/2'									

[illegible]

WELL NAME	SHELL ARCTIC RED RIVER	
LOCATION	0-27	PROVINCE
		N.W.T.

OPERATOR	Shell Canada Limited	CONTRACTOR	GUSTAUSON DRILLING
SIGNATURE OF OPERATOR REPRESENTATIVE		SIGNATURE OF CONTRACTOR'S TOOL PUSHER	

DP / DC SIZE	WT. LBS	GRADE	MIN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER
4	14#	E	2 13/16	5 1/4	F.H.	1	NAT.
6 1/4	10 1/2		2 3/8		5 H.90	2	NAT.

TIME DISTRIBUTION - HOURS						DRILLING ASSEMBLY NO CODE AT END OF TOUR		BIT RECORD				MUD RECORD						
CODE NO.	OPERATION	MORN.	DAY	EVE.	TOTAL	NO	CODE	BIT	FT	BIT NO.				TIME				
1	RIG UP TEAR DOWN							ID OD X	FT.	SIZE				WEIGHT				
2	DRILLING ACTUAL							ID OD X	FT.	MFG.				VIS.-SEC				
3	REAMING							ID OD X	FT.	TYPE				PV / YP	/	/	/	
4	CORING							ID OD X	FT.	JETS 1/32"				GELS	/	/	/	
5	CLEAN TO BOTTOM AND CIRCULATING							ID OD X	FT.	SERIAL NO				W.L.-C.C.				
6	TRIPS			1/4				ID OD X	FT.	DEPTH OUT				PH				
7	RIG SERVICE							ID OD X	FT.	DEPTH IN				% SOLIDS				
8	RIG REPAIR							DP STANDS	FT	TOTAL FTG.				% SAND				
9	CUT AND/OR SLIP LINE							DP SINGLES	FT	TOTAL HRS. RUN				MUD MATERIALS ADDED				
10	DEVIATION SURVEY							KELLY DOWN	FT.	BIT CONDITION 1/8" T/B/GAGE				TYPE	AMOUNT	TYPE	AMOUNT	
11	WIRE LINE LOG	8	8	7/4				TOTAL	FT.									
12	RUN CASING AND CEMENT							WT OF DC IN AIR	LBS.	REAMER CUTTER NO.								
13	WAIT ON CEMENT							WT. OF STRING	LBS.	REAMER TYPE								

NIPPLE UP B.O.P.				DRILLING ASSEMBLY				BIT RECORD				MUD RECORD			
				NO	CODE	END OF TOUR									
14	TEST B.O.P.			BIT		FT		BIT NO.				TIME			
15	DRILL STEM TEST			ID	OD	FT.		SIZE				WEIGHT			
16	PLUG BACK			ID	OD	FT.		MFG.				VIS. SEC.			
17	SQUEEZE CEMENT			ID	OD	FT.		TYPE				PV / YP			
18	STUCK OR FISHING			ID	OD	FT.		JETS 1/32"				GELS			
19	HANDLE TOOLS			ID	OD	FT.		SERIAL NO.				W L - C C			
20	CONDITION MUD			ID	OD	FT.		DEPTH OUT				PH			
21	LOST CIRCULATION			ID	OD	FT.		DEPTH IN				% SOLIDS			
22				DP	STANDS	FT.		TOTAL FTG.				% SAND			
23				DP	SINGLES	FT.		TOTAL HRS. RUN				MUD MATERIALS ADDED			
24												TYPE			
25												AMOUNT			
26												TYPE			
27												AMOUNT			
28															
29															
30															
31															
32															
33															
34															
35															
36															
37															
38															
39															
40	PERFORATE			KELLY DOWN				FT.				BIT CONDITION			
41	TUBING TRIPS			TOTAL				FT.				1/8" T/B/GAGE			
42	TREATING			WT. OF DC IN AIR				LBS.				REAMER CUTTER NO.			
43	SWABBING			WT. OF STRING				LBS.				REAMER TYPE			

I O N	44	TESTING				DRILLING ASSEMBLY		BIT RECORD						MUD RECORD			
						NO.	CODE	AT END OF TOUR									
	45						BIT	FT.	BIT NO.	RA 11			TIME				
60	ABANDON					1 BS	ID X CD	3.96 FT.	SIZE	8 3/4			WEIGHT				
70	STANDBY						ID OD X	FT.	MFG.	Reed			VIS.-SEC				
TOTALS		8	8	8			ID OD X	FT.	TYPE	SAM 5			PV / YP	/	/	/	
HOURS FOR SHELL ACCOUNT		8	8	8	24		ID OD X	FT.	JETS 1/32"	16/16 1/4			GELS	/	/	/	
BOILER		8	8	8	24		ID OD X	FT.	SERIAL NO.	625985			W L - C C				
Code E 250							ID OD X	FT.	DEPTH OUT				PH				
						6 DC 3 7/8 1/2	ID OD	180.00 FT.	DEPTH IN				% SOLIDS				
							DP STANDS	FT.	TOTAL FTG.				% SAND				
							DP SINGLES	FT.	TOTAL HRS. RUN				MUD MATERIALS ADDED				
													TYPE	AMOUNT	TYPE	AMOUNT	
1	HOLE DRAG (1000#)					KELLY DOWN		FT.	BIT CONDITION	1/8" T/B/GAGE							
2	TORQUE ON BOTTOM (DP TURNS)					TOTAL		FT.									
3	FILL ON BOTTOM (FEET)					WT. OF DC IN AIR		LBS.	REAMER CUTTER NO.								
						WT. OF STRING		LBS.	REAMER TYPE								

RIG NO.	DEPTH AT START OF MORNING TOUR	DEPTH AT END OF EVENING TOUR	DAILY PROGRESS	CUMULATIVE ROTATING HOURS	DAYS FROM SPUD	DATE		
						MONTH	DAY	YEAR
11					26	1	20	1971

STROKE LENGTH	LAST CASING TUBING OR LINER	SIZE	WT. AND GR.	NO. OF JOINTS	FEET	KB. TO CSG. HEAD	SET AT	CEMENT USED (SACKS)	REMARKS
80	8 1/2	9 5/8	35# K55	25	813		813	430	
80	8 1/2								

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT. ON BIT (1000 #)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN
FROM	TO									LINER SIZE	S P M	LINER SIZE	S P M	
1122	1123													
1123	1124													
1124	1125													
1125	1126													
1126	1127													
1127	1128													
1128	1129													
1129	1130													
1130	1131													
1131	1132													
1132	1133													
1133	1134													
1134	1135													
1135	1136													
1136	1137													
1137	1138													
1138	1139													
1139	1140													
1140	1141													
1141	1142													
1142	1143													
1143	1144													
1144	1145													
1145	1146													
1146	1147													
1147	1148													
1148	1149													
1149	1150													
1150	1151													
1151	1152													
1152	1153													
1153	1154													
1154	1155													
1155	1156													
1156	1157													
1157	1158													
1158	1159													
1159	1160													
1160	1161													
1161	1162													
1162	1163													
1163	1164													

[illegible][illegible][illegible][illegible]

TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS
FROM	TO			
8.00	4.00			LOGGING
				RAN OIL 7064 - 813 2" x 5" SCALES
				BHC-GR 7064 - 813 2" x 5" SCALES
				MLC 7064 - 813 2" x 5" SCALES
				SNP 7064 - 813 2" x 5" SCALES
				HAD TOOL PROBLEMS WITH FDC JKB.
				COULD NOT OBTAIN A RUN DRILLER 11:00

[illegible][illegible][illegible]

DAILY DRILLING REPORT

WELL NAME

WELL NAME SHELL ARCTIC RED RIVER

LOCATION 0-27

PROVINCE	N. W. T.
----------	----------

OPERATOR **Shell Canada Limited**

CONTRACTOR
GUSTAVSON DRILLING

RIG NO.

DEPTH AT START
OF MORNING TOUR

DEPTH AT END
OF EVENING TOUR

DAILY
PROGRESS

CUMULATIVE
ROTATING HOURS:

DAYS FROM
SPUD

MONTH

DATE _____
DAY _____

YEAR

SIGNATURE OF OPERATOR'S REPRESENTATIVE

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

6670

6872

202'

23

1

17

71

DI. NO. SIZE	WT. / FT	GRADE	MIN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER
4	14#	E	2 1/16	5 1/4	F.H.	1	NAT.
13 1/2	10 1/2		2 3/8		5H90	2	NAT.

TYPE	STROKE LENGTH
8-P-80	8 1/2
8-P-80	8 1/2

**LAST
CASING
TUBING
OR
LINER**

SIZE	WT. AND GR.
9 3/8	35# K5.

NO. OF JOINTS	FEET
25	813

KB. TO CSG. HEAD	SET AT	CEMENT USED (SACKS)
	813	430

REMARKS	

TIME DISTRIBUTION - HOURS						DRILLING ASSEMBLY AT END OF TOUR				BIT RECORD				MUD RECORD			
CODE NO.	OPERATION	MORN.	DAY	EVE	TOTAL	BIT		FT		BIT NO.		TIME					
1	RIG UP TEAR DOWN					1	BS	23	63	3.96	FT.	SIZE	10				
2	DRILLING ACTUAL	7 3/4	4 1/2	1 3/4		1	SS	2	63	8.50	FT.	MFG.	834				
3	REAMING			1		1	SI	23	63	4.50	FT.	TYPE	SEC				
4	CORING					1	CO	23	63	2.10	FT.	JETS 1/32"	M88				
5	CLEAN TO BOTTOM AND CIRCULATING										FT.	SERIAL NO.	11 11 11				
6	TRIPS		3	1 3/4							FT.	DEPTH OUT	236823				
7	RIG SERVICE	1/4	1/4	1/4		21	DC	23	63	650-10	FT.	DEPTH IN	6405				
8	RIG REPAIR					65	DP				FT.	TOTAL FTG.	360				
9	CUT AND/OR SLIP LINE			1/4		1	DP				FT.	TOTAL HRS. RUN	29 1/2				
10	DEVIATION SURVEY										FT.	BIT CONDITION 1/8" T/B/GAGE	DRAG				
11	WIRE LINE LOG										FT.						
12	RUN CASING AND CEMENT										FT.						
13	WAIT ON CEMENT										FT.						

MORNING TOUR

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT ON BIT (1000 #)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO 1	PUMP NO 2	METHOD PUMPS	
FROM	TO											LINER SIZE	S P M
6670	6765	7 3/4	95			50	50	2150		6"	120		
DEVIATION RECORD		DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION			
TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS									
FROM	TO												
12.00	1.45	1 3/4		DRLG									
1.45	2.00	1/4		RIG SERV & HYDRIL.									
2.00	8.00	6		DRLG.									
		8											
				(HELD BLOW OUT DRILL & USE OF AIR PACKS)									
				(OPERATION & SPEED OF APPLYING SAME)									
				DRILLER D. Cwasink									

[illegible]

DAY TOUR

FOOTAGE		ROT HOURS	DR-D	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY	WT ON	PUMP	AIR	PUMP NO 1	PUMP NO 2	METHOD	
FROM	TO		RM-R CORE-C			RPM	BIT (1000#)	(AIR) PRESS	VOL (CFM)	LINER SIZE	SPM	LINER SIZE	SPM
6765	6725	4 1/2	60			50	50	2150		6	120	6	
								750		6	60		
DEVIATION RECORD		DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION			
		6800	2 1/8										
TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS									
FROM	TO												
8.00	9.30	1 1/2		DRILL									
9.30	9.45	1/4		CHECK B.O.P SER. RIG.									
9.45	12.45	3		DRILL									
12.45	3.00	2 1/4		DROP SURVEY PULL OUT									
3.00	3.15	1/4		CHECK BLIND RAMS CHANGE BIT									
3.15	4.10	3/4		RUN IN D.C.S									
				DRILLER J. Hunsell									

T O N	44	TESTING	DRILLING ASSEMBLY				BIT RECORD				MUD RECORD					
			NO.	CODE	AT END OF TOUR		BIT NO.				TIME					
	45		BIT				FT	BIT NO.	11			TIME	8:20 11:00			
60	ABANDON		1	BS	2 1/2" x 6 3/4"	3.96	FT.	SIZE	8 3/4			WEIGHT	9.1 9.1			
70	STANDBY		1	SS	2 1/2" x 6 3/4"	8.50	FT.	MFG.	Reed			VIS-SEC	48 47			
TOTALS		8 8 8	1	ST	2 1/2" x 6 3/4"	4.50	FT.	TYPE	SCM5			PV/YP	28/50			
HOURS FOR SHELL ACCOUNT			24	1	CL	2 1/2" x 6 3/4"	2.10	FT.	JETS 1/32"	11 11 12			GELS.	4/6		
NO. OF BOILER FEET	BOILER #1	8 8 8			X		FT.	SERIAL NO.	683985			W.L-C-C	1.9			
	Boiler #2	8 8 8			X		FT.	DEPTH OUT				PH	9.5			
	Code 232		21	QC	2 1/2" x 6 3/4"	650.10	FT.	DEPTH IN	6825			% SOLIDS				
			46	DP	STANDS		FT.	TOTAL FTG.				% SAND				
	HOLE CONDITION		1	DP	SINGLES	6169.78	FT.	TOTAL HRS. RUN	4 3/4			MUD MATERIALS ADDED				
1.	HOLE DRAG (1000#)	5	KELLY DOWN				33.30	FT.	BIT CONDITION	1/8" T/B/GAGE			BEL 2400#			
2.	TORQUE ON BOTTOM (DP TURNS)		TOTAL				6872.24					BENEX 10#				
3.	FILL ON BOTTOM (FEET)	Nil	WT. OF DC IN AIR				65M	LBS.	REAMER CUTTER NO.			CMC 50#				
			WT. OF STRING				146M	.BS.	REAMER TYPE							

1	E
	V
	E
	N
	I
	N
	G
	C
	T
COUNT	
	C
	U
	I

FOOTAGE		ROT HOURS	DR-D	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY	WT ON	PUMP	AIR	PUMP NO. 1	PUMP NO. 2		METH
FROM	TO		RM-R CORE-C			RPM	BIT (1000 #)	WATER PRESS.	VOL (CFM)	LINER SIZE	S P M	LINER SIZE	S P M
6825'	6872'	4 ³ / ₄	47'			50	50	2100		6"	120	6"	120

DEVIATION RECORD	DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION	DEPTH	DEVIATION °	DIRECTION

TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS
FROM	TO			
4 ⁰⁰	4 ²⁵	$\frac{1}{4}$		Set Rig Held Blow out Dslg while -
4 ¹⁵	4 ³⁰	$\frac{1}{4}$		Slip Dslg line Tripping.
4 ³⁰	6 ¹⁵	1 ³ / ₄		Run in
6 ¹⁵	7 ¹⁵	1		Ream to Bottom 27'
7 ¹⁵	12 ⁰⁰	4 ³ / ₄		Dslg

DRILLED BY Bo Johnson

DAILY DRILLING REPORT

WELL NAME	SHELL ARCTIC RIVER	
LOCATION	0-27	PROVINCE N.W.S.

OPERATOR	Shell Canada Limited	CONTRACTOR	AUSTINSON DRLS	RIG NO.	11	DEPTH AT START OF MORNING TOUR	6050	DEPTH AT END OF EVENING TOUR	6249	DAILY PROGRESS	199	CUMULATIVE ROTATING HOURS	20	DAYS FROM SPUD	20	MONTH	1	DAY	14	YEAR	71
SIGNATURE OF OPERATOR'S REPRESENTATIVE	<i>[Signature]</i>	SIGNATURE OF CONTRACTOR'S TOOLPUSHER	<i>[Signature]</i>																		
DP / DC SIZE	WT. / FT.	GRADE	MIN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER	TYPE	STROKE LENGTH	LAST CASING TUBING OR LINER	SIZE	WT. AND GR.	NO. OF JOINTS	FEET	KB TO CSG. HEAD	SET AT	CEMENT USED (SACKS)	REMARKS			
4"	14"	E	2 1/16	5 1/4	FH	1	NAT.	8-2 80	8 1/2		9 3/8	35 K	25			813					
6 3/4"	10 1/2"		2 1/8	5 1/2	5 1/2	2	NAT.	8-2 80	8 1/2												

TIME DISTRIBUTION - HOURS				DRILLING ASSEMBLY		BIT RECORD		MUD RECORD		FOOTAGE		ROTARY		FORMATION		PUMP NO. 1		PUMP NO. 2		METHOD				
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	NO.	CODE	AT END OF TOUR	BIT NO.	TIME	FROM	TO	ELAPSED TIME	CODE	(SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	LINER SIZE	S.P.M.	LINER SIZE	S.P.M.	PUMPS RUN
1	RIG UP					1	BS	2 1/2 x 6 3/4	3.96	FT.	SIZE	8 3/4	9.1	9.1										
2	DRILLING ACTUAL	4 1/2	7 3/4	7 1/4	20	1	SS	2 x 6 3/4	9.50	FT.	MFG.	SEC	53	51										
3	REAMING					1	SI	2 1/2 x 6 3/4	4.50	FT.	TYPE	M88	25	20										
4	CORING					1	90	2 1/2 x 5 1/4	2.10	FT.	JETS 1/32"	11 11 11												
5	CLEAN TO BOTTOM AND CIRCULATING	1/4		1/4						FT.	SERIAL NO.	911905												
6	TRIPS	2 1/2		2 1/2						FT.	DEPTH OUT													
7	RIG SERVICE	1/4	1/4	1/2	21	20	2 1/2 x 6 3/4	650.10	FT.	DEPTH IN	6050													
8	RIG REPAIR					58	DP	STANDS		FT.	TOTAL FTG.	40												
9	CUT AND/OR SLIP LINE	1/2		1/2			DP	SINGLES	5393.08	FT.	TOTAL HRS. RUN	4 1/2												
10	DEVIATION SURVEY																							
11	WIRE LINE LOG																							
12	RUN CASING AND CEMENT																							
13	WAIT ON CEMENT																							
14	NIPPLE UP B.O.P.																							
DETAILS OF OPERATION IN SEQUENCE AND REMARKS																								
PULL OUT B.T. #8																								
RIG SER. / BLIND RAMS																								
RUN IN DCs																								
SLIP 33' of Dalg LINE																								
RUN IN W/B.T. #9																								
BREAK CIR & CLEAN 15 FEET TO BOTTOM																								
Dalg 8 3/4 HOLE																								
DRILLER: D. Jendall																								

TIME DISTRIBUTION - HOURS				DRILLING ASSEMBLY		BIT RECORD		MUD RECORD		FOOTAGE		ROTARY		FORMATION		PUMP NO. 1		PUMP NO. 2		METHOD				
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	NO.	CODE	AT END OF TOUR	BIT NO.	TIME	FROM	TO	ELAPSED TIME	CODE	(SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	LINER SIZE	S.P.M.	LINER SIZE	S.P.M.	PUMPS RUN
15	TEST B.O.P.	1/4	1/4																					
16	DRILL STEM TEST					1	BS	2 1/2 x 6 3/4	3.96	FT.	SIZE	8 3/4	9.1	9.1										
17	PLUG BACK					1	SS	2 x 6 3/4	8.50	FT.	MFG.	SEC	50	58										
18	SQUEEZE CEMENT					1	SI	2 1/2 x 6 3/4	4.50	FT.	TYPE	M88	21	23										
19	STUCK OR FISHING					1	CD	2 1/2 x 5 1/4	2.10	FT.	JETS 1/32"	11 11 11												
20	HANDLE TOOLS									FT.	SERIAL NO.	911905												
21	CONDITION MUD																							
22	LOST CIRCULATION					21	DCS	2 1/2 x 6 3/4	650.10	FT.	DEPTH IN	6050												
23						59	DP	STANDS		FT.	TOTAL FTG.	120												
24							DP	SINGLES	5486.51	FT.	TOTAL HRS. RUN	13 1/4												
DETAILS OF OPERATION IN SEQUENCE AND REMARKS																								
RIG SERV. / B.O.P.S.																								
DRLG.																								
17-11-71																								
DRILLER: A. Ciesinski																								

TIME DISTRIBUTION - HOURS				DRILLING ASSEMBLY		BIT RECORD		MUD RECORD		FOOTAGE		ROTARY		FORMATION		PUMP NO. 1		PUMP NO. 2		METHOD				
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	NO.	CODE	AT END OF TOUR	BIT NO.	TIME	FROM	TO	ELAPSED TIME	CODE	(SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	LINER SIZE	S.P.M.	LINER SIZE	S.P.M.	PUMPS RUN
40	PERFORATE																							
41	TUBING TRIPS																							
42	TREATING																							
43	SWABBING																							
44	TESTING																							
45																								
60	ABANDON					1	BS	2 1/2 x 6 3/4	3.96	FT.	SIZE	8 3/4	9.1	9.1										
70	STANDBY					1	SS	2 x 6 3/4	8.50	FT.	MFG.	SEC	60	55										
TOTALS																								
8 8 8 24 1/2																								
HOURS FOR SHELL ACCOUNT																								
24 1/2																								
BOILER																								
8 8 8 24																								
CWO 24320																								
232 B																								
HOLE CONDITION																								
2 DP SINGLES																								
TOTAL F.S. RUN																								
20																								
BIT CONDITION 1/8" T/B/GAGE																								
1/2																								
GEL 1500 lbs.																								
CMC 100 lbs.																								
CAUSTIC - 100 lbs.																								
BEN-EX - 6 lbs.																								
DRILLER: J. H. H. H.																								

[illegible][illegible][illegible][illegible][illegible]

N	45				NO. CODE	BIT	FT.	BIT NO.	8	TIME	4.00	8.00		RODAGE		ROT. HOURS	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY RPM	WT. ON BIT (1000#)	PUMP (AIR) PRESS	VOL (CFM)	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN
														FROM	TO								LINER SIZE	S.P.M.	LINER SIZE	S.P.M.	
60	ABANDON				1 BS	10 ³ 58x64	3.96	SIZE	8 3/4	WEIGHT	9.1	9.1		5198	5329	74	141			55	50	2000	6	150	6		
70	STANDBY				1 SS	10 ³ 2x4	8.50	MFG.	H.W	VIS-SEC	67	58															
TOTALS		8	8	8	241	10 ³ 58x64	4.50	TYPE	55R	PV, YP	/	/	/														
HOURS FOR SHELL ACCOUNT		8	8	8	241	10 ³ 58x64	2.10	JETS 1/32"	11/11/11	GELS	/	/	/	DEVIATION: DEPTH DEVIATION ° DIRECTION DEPTH DEVIATION ° DIRECTION DEPTH DEVIATION ° DIRECTION													

BOILER #1	8	8	24	10	0.0	FT.	SERIAL NO.	23412	W.L.-C.C.	8.
Boiler #2	8	8	24	10	0.0	FT.	DEPTH, OUT		PH	9.1 ⁿ
17 HRS	Code 252	2100	2864	650.10			DEPTH IN	5190	% SOLIDS	
7 HRS	Code 232	50	DP	STANDS	4649.63	FT.	TOTAL FTG.	141	% SAND	
HOLE CONDITION		DP	SINGLES		FT.		TOTAL HRS. RUN	7	MUD MATERIALS ADDED	
							RPT. CONDITION		TYPE	AMOUNT
									TYPE	AMOUNT

N
G
T

TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS
FROM	TO			
4.00	4.15	1/4		REAM RAT HOPE TO 8 3/4
4.15	4.30	1/4		CHECK B.O.P SER. RLG
4.30	5.00	1/2		REAM

1	HOLE DRAG (1000#)	KELLY DOWN	12	FT.	8 1/8" O.D. / 1" T/GAGE	100 lbs.	5.00	12.00	7	DRILL 8 3/4 HOLE
2	TORQUE ON BOTTOM (DP TURNS)	TOTAL	5329.89			75 lbs.				
3	FILL ON BOTTOM (FEET)	WT. OF DC IN AIR	56	LBS.	REAMER CUTTER NO.	1700				
		WT. OF STRING	125	LBS.	REAMER TYPE	BENEX				

[illegible]

DAILY DRILLING REPORT

WELL NAME		LOCATION		PROVINCE		OPERATOR		CONTRACTOR		RIG NO.		DEPTH AT START OF MORNING TOUR		DEPTH AT END OF EVENING TOUR		DAILY PROGRESS		CUMULATIVE ROTATING HOURS		DAYS FROM SPUD		DATE															
SHELL Arctic Red River		0-27		N.W.T		Shell Canada Limited		Gustavson D/Lg		11		3934'		4268'		334'		12		1		6 71															
SIGNATURE OF OPERATOR'S REPRESENTATIVE		SIGNATURE OF CONTRACTOR'S TOOL PUSHER		PUMP NO.		PUMP MANUFACTURER		TYPE		STROKE LENGTH		LAST CASING TUBING OR LINER		SIZE		WT. AND GR.		NO. OF JOINTS		FEET		KB. TO CSG. HEAD		SET AT		CEMENT USED (SACKS)		REMARKS									
D.P. / DC. SIZE		WT. / FT.		GRADE		MIN. I.D.		TOOL JT. O.D.		TYPE THREAD		PUMP NO.		PUMP MANUFACTURER		TYPE		STROKE LENGTH		LAST CASING TUBING OR LINER		SIZE		WT. AND GR.		NO. OF JOINTS		FEET		KB. TO CSG. HEAD		SET AT		CEMENT USED (SACKS)		REMARKS	
4" 14"		14"		5		3 1/4"		5 1/4"		F.H.		1		Nat.		8P80		8 1/2"		LAST CASING TUBING OR LINER		9 5/8"		36" 155		25		16.25		8'13"		430					
6 7/8"		101"				2 7/8"		6 3/4"		5" 11/16"		2		Nat.		8P80		8 1/2"																			
TIME DISTRIBUTION - HOURS																																					
DRILLING ASSEMBLY AT END OF TOUR																																					
BIT RECORD																																					
MUD RECORD																																					
FOOTAGE																																					
FORMATION (SHOW CORE RECOVERY)																																					
ROTARY R.P.M.																																					
WT. ON BIT (1000#)																																					
PUMP (AIR) PRESS.																																					
AIR VOL (CFM)																																					
PUMP NO. 1 LINER SIZE S.P.M.																																					
PUMP NO. 2 LINER SIZE S.P.M.																																					
METHOD PUMPS RUN																																					
DEVIATION RECORD																																					
TIME LOG																																					
ELAPSED TIME																																					
CODE																																					
DETAILS OF OPERATION IN SEQUENCE AND REMARKS																																					
1 RIG UP																																					
2 RIG DOWN																																					
3 DRILLING ACTUAL																																					
4 REAMING																																					
5 CORING																																					
6 CLEAN TO BOTTOM AND CIRCULATING																																					
7 TRIPS																																					
8 RIG SERVICE																																					
9 RIG REPAIR																																					
10 CUT AND/OR SLIP LINE																																					
11 DEVIATION SURVEY																																					
12 WIRE LINE LOG																																					
13 RUN CASING AND CEMENT																																					
14 WAIT ON CEMENT																																					
15 NIPPLE UP B.O.P.																																					
16 TEST B.O.P.																																					
17 DRILL STEM TEST																																					
18 PLUG BACK																																					
19 SQUEEZE CEMENT																																					
20 STUCK OR FISHING																																					
21 HANDLE TOOLS																																					
22 CONDITION MUD																																					
23 LOST CIRCULATION																																					
24																																					
40 PERFORATE																																					
41 TUBING TRIPS																																					
42 TREATING																																					
43 SWABBING																																					
44 TESTING																																					
45																																					
60 ABANDON																																					
70 STANDBY																																					
TOTALS																																					
HOURS FOR SHELL ACCOUNT																																					
BOILER #1																																					
Boiler #2																																					
Code 232																																					
HOLE CONDITION																																					
1 HOLE DRAG (1000#)																																					
2 TORQUE ON BOTTOM (DP TURNS)																																					
3 FILL ON BOTTOM (FEET)																																					

DRILLER: *G. Johnson*

DRILLER: *N. Lindall*

DRILLER: *A. Brown*

[illegible]

Sketch Arctic Red River.

LOCATION Office 1100
P-27

PROVINCE	N. W. T.
----------	----------

OPERATOR **Shell Canada Limited**

CONTRACTOR
Custerson, R. L.

RIG NO.

DEPTH AT START
OF MORNING TOUR

DEPTH AT END
OF EVENING TOUR

DAILY
PROGRESS

CUMULATIVE
ROTATING HOURS

DAYS FROM
SPUD

MONTH

DATE
DAY

YEAR

SIGNATURE OF OPERATOR'S REPRESENTATIVE

SIGNATURE OF CONTRACTOR'S TOOL PUSHER

100

1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024, 2025, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033, 2034, 2035, 2036, 2037, 2038, 2039, 2040, 2041, 2042, 2043, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2054, 2055, 2056, 2057, 2058, 2059, 2060, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2068, 2069, 2070, 2071, 2072, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2080, 2081, 2082, 2083, 2084, 2085, 2086, 2087, 2088, 2089, 2090, 2091, 2092, 2093, 2094, 2095, 2096, 2097, 2098, 2099, 2100, 2101, 2102, 2103, 2104, 2105, 2106, 2107, 2108, 2109, 2110, 2111, 2112, 2113, 2114, 2115, 2116, 2117, 2118, 2119, 2120, 2121, 2122, 2123, 2124, 2125, 2126, 2127, 2128, 2129, 2130, 2131, 2132, 2133, 2134, 2135, 2136, 2137, 2138, 2139, 2140, 2141, 2142, 2143, 2144, 2145, 2146, 2147, 2148, 2149, 2150, 2151, 2152, 2153, 2154, 2155, 2156, 2157, 2158, 2159, 2160, 2161, 2162, 2163, 2164, 2165, 2166, 2167, 2168, 2169, 2170, 2171, 2172, 2173, 2174, 2175, 2176, 2177, 2178, 2179, 2180, 2181, 2182, 2183, 2184, 2185, 2186, 2187, 2188, 2189, 2190, 2191, 2192, 2193, 2194, 2195, 2196, 2197, 2198, 2199, 2200, 2201, 2202, 2203, 2204, 2205, 2206, 2207, 2208, 2209, 2210, 2211, 2212, 2213, 2214, 2215, 2216, 2217, 2218, 2219, 2220, 2221, 2222, 2223, 2224, 2225, 2226, 2227, 2228, 2229, 2230, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2239, 2240, 2241, 2242, 2243, 2244, 2245, 2246, 2247, 2248, 2249, 2250, 2251, 2252, 2253, 2254, 2255, 2256, 2257, 2258, 2259, 2260, 2261, 2262, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2272, 2273, 2274, 2275, 2276, 2277, 2278, 2279, 2280, 2281, 2282, 2283, 2284, 2285, 2286, 2287, 2288, 2289, 2290, 2291, 2292, 2293, 2294, 2295, 2296, 2297, 2298, 2299, 2300, 2301, 2302, 2303, 2304, 2305, 2306, 2307, 2308, 2309, 2310, 2311, 2312, 2313, 2314, 2315, 2316, 2317, 2318, 2319, 2320, 2321, 2322, 2323, 2324, 2325, 2326, 2327, 2328, 2329, 2330, 2331, 2332, 2333, 2334, 2335, 2336, 2337, 2338, 2339, 2340, 2341, 2342, 2343, 2344, 2345, 2346, 2347, 2348, 2349, 2350, 2351, 2352, 2353, 2354, 2355, 2356, 2357, 2358, 2359, 2360, 2361, 2362, 2363, 2364, 2365, 2366, 2367, 2368, 2369, 2370, 2371, 2372, 2373, 2374, 2375, 2376, 2377, 2378, 2379, 2380, 2381, 2382, 2383, 2384, 2385, 2386, 2387, 2388, 2389, 2390, 2391, 2392, 2393, 2394, 2395, 2396, 2397, 2398, 2399, 2400, 2401, 2402, 2403, 2404, 2405, 2406, 2407, 2408, 2409, 2410, 2411, 2412, 2413, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2421, 2422, 2423, 2424, 2425, 2426, 2427, 2428, 2429, 2430, 2431, 2432, 2433, 2434, 2435, 2436, 2437, 2438, 2439, 2440, 2441, 2442, 2443, 2444, 2445, 2446, 2447, 2448, 2449, 2450, 2451, 2452, 2453, 2454, 2455, 2456, 2457, 2458, 2459, 2460, 2461, 2462, 2463, 2464, 2465, 2466, 2467, 2468, 2469, 2470, 2471, 2472, 2473, 2474, 2475, 2476, 2477, 2478, 2479, 2480, 2481, 2482, 2483, 2484, 2485, 2486, 2487, 2488, 2489, 2490, 2491, 2492, 2493, 2494, 2495, 2496, 2497, 2498, 2499, 2500, 2501, 2502, 2503, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 2511, 2512, 2513, 2514, 2515, 2516, 2517, 2518, 2519, 2520, 2521, 2522, 2523, 2524, 2525, 2526, 2527, 2528, 2529, 2530, 2531, 2532, 2533, 2534, 2535, 2536, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544, 2545, 2546, 2547, 2548, 2549, 2550, 2551, 2552, 2553, 2554, 2555, 2556, 2557, 2558, 2559, 2560, 2561, 2562, 2563, 2564, 2565, 2566, 2567, 2568, 2569, 2570, 2571, 2572, 2573, 2574, 2575, 2576, 2577, 2578, 2579, 2580, 2581, 2582, 2583, 2584, 2585, 2586, 2587, 2588, 2589, 2590, 2591, 2592, 2593, 2594, 2595, 2596, 2597, 2598, 2599, 2600, 2601, 2602, 2603, 2604, 2605, 2606, 2607, 2608, 2609, 2610, 2611, 2612, 2613, 2614, 2615, 2616, 2617, 2618, 2619, 2620, 2621, 2622, 2623, 2624, 2625, 2626, 2627, 2628, 2629, 2630, 2631, 2632, 2633, 2634, 2635, 2636, 2637, 2638, 2639, 2640, 2641, 2642, 2643, 2644, 2645, 2646, 2647, 2648, 2649, 2650, 2651, 2652, 2653, 2654, 2655, 2656, 2657, 2658, 2659, 2660, 2661, 2662, 2663, 2664, 2665, 2666, 2667, 2668, 2669, 2670, 2671, 2672, 2673, 2674, 2675, 2676, 2677, 2678, 26

1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024, 2025, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033, 2034, 2035, 2036, 2037, 2038, 2039, 2040, 2041, 2042, 2043, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2054, 2055, 2056, 2057, 2058, 2059, 2060, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2068, 2069, 2070, 2071, 2072, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2080, 2081, 2082, 2083, 2084, 2085, 2086, 2087, 2088, 2089, 2090, 2091, 2092, 2093, 2094, 2095, 2096, 2097, 2098, 2099, 2100, 2101, 2102, 2103, 2104, 2105, 2106, 2107, 2108, 2109, 2110, 2111, 2112, 2113, 2114, 2115, 2116, 2117, 2118, 2119, 2120, 2121, 2122, 2123, 2124, 2125, 2126, 2127, 2128, 2129, 2130, 2131, 2132, 2133, 2134, 2135, 2136, 2137, 2138, 2139, 2140, 2141, 2142, 2143, 2144, 2145, 2146, 2147, 2148, 2149, 2150, 2151, 2152, 2153, 2154, 2155, 2156, 2157, 2158, 2159, 2160, 2161, 2162, 2163, 2164, 2165, 2166, 2167, 2168, 2169, 2170, 2171, 2172, 2173, 2174, 2175, 2176, 2177, 2178, 2179, 2180, 2181, 2182, 2183, 2184, 2185, 2186, 2187, 2188, 2189, 2190, 2191, 2192, 2193, 2194, 2195, 2196, 2197, 2198, 2199, 2200, 2201, 2202, 2203, 2204, 2205, 2206, 2207, 2208, 2209, 2210, 2211, 2212, 2213, 2214, 2215, 2216, 2217, 2218, 2219, 2220, 2221, 2222, 2223, 2224, 2225, 2226, 2227, 2228, 2229, 2230, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2239, 2240, 2241, 2242, 2243, 2244, 2245, 2246, 2247, 2248, 2249, 2250, 2251, 2252, 2253, 2254, 2255, 2256, 2257, 2258, 2259, 2260, 2261, 2262, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2272, 2273, 2274, 2275, 2276, 2277, 2278, 2279, 2280, 2281, 2282, 2283, 2284, 2285, 2286, 2287, 2288, 2289, 2290, 2291, 2292, 2293, 2294, 2295, 2296, 2297, 2298, 2299, 2300, 2301, 2302, 2303, 2304, 2305, 2306, 2307, 2308, 2309, 2310, 2311, 2312, 2313, 2314, 2315, 2316, 2317, 2318, 2319, 2320, 2321, 2322, 2323, 2324, 2325, 2326, 2327, 2328, 2329, 2330, 2331, 2332, 2333, 2334, 2335, 2336, 2337, 2338, 2339, 2340, 2341, 2342, 2343, 2344, 2345, 2346, 2347, 2348, 2349, 2350, 2351, 2352, 2353, 2354, 2355, 2356, 2357, 2358, 2359, 2360, 2361, 2362, 2363, 2364, 2365, 2366, 2367, 2368, 2369, 2370, 2371, 2372, 2373, 2374, 2375, 2376, 2377, 2378, 2379, 2380, 2381, 2382, 2383, 2384, 2385, 2386, 2387, 2388, 2389, 2390, 2391, 2392, 2393, 2394, 2395, 2396, 2397, 2398, 2399, 2400, 2401, 2402, 2403, 2404, 2405, 2406, 2407, 2408, 2409, 2410, 2411, 2412, 2413, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2421, 2422, 2423, 2424, 2425, 2426, 2427, 2428, 2429, 2430, 2431, 2432, 2433, 2434, 2435, 2436, 2437, 2438, 2439, 2440, 2441, 2442, 2443, 2444, 2445, 2446, 2447, 2448, 2449, 2450, 2451, 2452, 2453, 2454, 2455, 2456, 2457, 2458, 2459, 2460, 2461, 2462, 2463, 2464, 2465, 2466, 2467, 2468, 2469, 2470, 2471, 2472, 2473, 2474, 2475, 2476, 2477, 2478, 2479, 2480, 2481, 2482, 2483, 2484, 2485, 2486, 2487, 2488, 2489, 2490, 2491, 2492, 2493, 2494, 2495, 2496, 2497, 2498, 2499, 2500, 2501, 2502, 2503, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 2511, 2512, 2513, 2514, 2515, 2516, 2517, 2518, 2519, 2520, 2521, 2522, 2523, 2524, 2525, 2526, 2527, 2528, 2529, 2530, 2531, 2532, 2533, 2534, 2535, 2536, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544, 2545, 2546, 2547, 2548, 2549, 2550, 2551, 2552, 2553, 2554, 2555, 2556, 2557, 2558, 2559, 2560, 2561, 2562, 2563, 2564, 2565, 2566, 2567, 2568, 2569, 2570, 2571, 2572, 2573, 2574, 2575, 2576, 2577, 2578, 2579, 2580, 2581, 2582, 2583, 2584, 2585, 2586, 2587, 2588, 2589, 2590, 2591, 2592, 2593, 2594, 2595, 2596, 2597, 2598, 2599, 2600, 2601, 2602, 2603, 2604, 2605, 2606, 2607, 2608, 2609, 2610, 2611, 2612, 2613, 2614, 2615, 2616, 2617, 2618, 2619, 2620, 2621, 2622, 2623, 2624, 2625, 2626, 2627, 2628, 2629, 2630, 2631, 2632, 2633, 2634, 2635, 2636, 2637, 2638, 2639, 2640, 2641, 2642, 2643, 2644, 2645, 2646, 2647, 2648, 2649, 2650, 2651, 2652, 2653, 2654, 2655, 2656, 2657, 2658, 2659, 2660, 2661, 2662, 2663, 2664, 2665, 2666, 2667, 2668, 2669, 2670, 2671, 2672, 2673, 2674, 2675, 2676, 2677, 2678, 2679, 26

100

100

100

100

DP. / OC. SIZE	WT. / FT	GRADE	MIN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER
4" / 11	114	E		5 1/4"	FH	1	National
6 3/4" / 110			2 1/4"	6 3/4"	5" NPT	2	"

TYPE	STROKE LENGTH
8P80	8½"
8P80	8½"

LAST
CASING
TUBING
OR
LINER

	WT. AND GR.
1	36 th K55

OF	FE

KB. TO CSG. HEAD	
16.25	

	CEMENT USED (SACK
	430

REMARK

1

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY		BIT RECORD		MUD RECORD					
CODE NO.	OPERATION	MORH.	DAY	EVE	TOTAL	NO	CODE	AT END OF TOUR	BIT NO.		TIME			
1	RIG UP TEAR DOWN					1	BS	278.63	3.96	FT.	SIZE	2		
2	DRILLING ACTUAL	7	53	54	18	1	SS	1" x 1/4"	8.50	FT.	MFG.	NW		
3	REAMING					1	CL	278.63	2.10	FT.	TYPE	XIG		
4	CORING					1	FO	278.63	2.20	FT.	JETS 1/32"	10/10/11		
5	CLEAN TO BOTTOM AND CIRCULATING					1	NW	278.63	2.14	FT.	SERIAL NO	22747		
6	TRIPS	1 1/2	2 1/2		4	1	ST	278.63	4.50	FT.	DEPTH OUT			
7	RIG SERVICE	1/4	1/4	1/4	3/4	18	DC	278.63	556.41	FT.	DEPTH IN	1919		
8	RIG REPAIR					21	DP	STANDS		FT	TOTAL FTG.	796		
9	CUT AND/OR SLIP LINE					2	DP	SINGLES	2108.64	FT	TOTAL HRS. RUN	13 1/4		
10	DEVIATION SURVEY	3/4	1/2		1 1/4			KELLY DOWN	36.00	FT	BIT CONDITION 1/8" T/B/GAGE	IN		
11	WIRE LINE LOG							TOTAL	2715.55					
12	RUN CASING AND CEMENT							WT. OF DC IN AIR	53 M.	LBS.	REAMER CUTTER NO.			
13	WAIT ON CEMENT							WT. OF STRING	84 M.	LBS.	REAMER TYPE			

FOOTAGE		ROT HOURS	DR-R RM-R CORE-C	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT ON BIT (1000 #)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO 1		PUMP NO 2		METHOD PUMPS RUN
FROM	TO									LINER SIZE	S P M	LINER SIZE	S P M	
2327'	2715'	7	388			80	35m.w.t			6"	120	6"		
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION				
		2420'	2 1/2		2606'	1 1/2								
TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS										
FROM	TO													
1200	1215	1/4		Set Rtg & Swivel & Checked R.O.P										
1215	130	1 3/4		Dolg										
130	145	1/4		Survey										
145	515	3 1/2		Dolg 35m.w.t 120 R.P.M.										
515	545	1/2		Survey										
545	800	2 3/4		Dolg										
DRILLER <i>E. Johnson</i>														

14	NIPPLE UP B.O.P.				DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD			MUD RECORD				
					NO.	CODE	BIT	FT.	BIT NO.			TIME		
15	TEST B.O.P.					BIT	FT.	BIT NO.	2	3	TIME	8 ⁰⁰	12 ⁰⁰	2 ⁰⁰
16	DRILL STEM TEST				1	AS 2 1/2 X 3 1/2	396	SIZE	8 3/4	8 3/4	WEIGHT	9.2	9.2	9.2
17	PLUG BACK				1	SS 2 X 1 1/2	8.50	MFG.	H.W	H.W	VIS-SEC	35	36	40
18	SQUEEZE CEMENT				1	90 2 1/2 X 3 1/2	2.10	TYPE	XIG	XIG	PV/YP	/	/	/
19	STUCK OR FISHING				1	90 2 1/2 X 3 1/2	2.20	JETS 1/32"	10/10/11	10/10/10	GELS	/	/	/
20	HANDLE TOOLS				1	KV 2 1/2 X 3 1/2	2.14	SERIAL NO.	22749	22639	W L - C C			
21	CONDITION MUD				1	SI 2 1/2 X 3 1/2	4.50	DEPTH OUT	3009		PH	9.0	9.0	9.5
22	LOST CIRCULATION				1	DCS 2 1/2 X 3 1/2	556.41	DEPTH IN	1919	3009	% SOLIDS			
23					25	DP STANDS	FT.	TOTAL FTG.	1090		% SAND			
24					2	DP SINGLES	2388.10	TOTAL HRS. RUN	19 1/2		MUD MATERIALS ADDED			
											TYPE	AMOUNT	TYPE	AMOUNT
C O M P L E T	40	PERFORATE				KELLY DOWN	40.80	BIT CONDITION 1/8" T/B/GAGE	2 4 0			GEL	2400	
	41	TUBING TRIPS				TOTAL	3009.31					RENEGY	10 th	
	42	TREATING				WT. OF DC IN AIR	55m	REAMER CUTTER NO.				CAUSSIC	100 th	
	43	SWABBING				WT. OF STRING	86m	REAMER TYPE						

FOOTAGE		ROT HOURS	DR D RM-R CORE-C	CORE NO	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT ON BIT (1000 #)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO. 1		PUMP NO. 2		METHOD PUMPS RUN
FROM	TO									LINER SIZE	S P M	LINER SIZE	S P M	
2715	3009	53		274		100	35	2000		6	120			
DAY TOUR														
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION				
2922		114												
TIME LOG		ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS										
FROM	TO													
800	815	1/4		Rig Set V BOPs.										
815	1000	134		DRLg 8 3/4 Hole. Tally 3009.31										
1000	1015	14		SURVY. Strap 3006.14										
1015	215	4		DRLg 8 3/4 Hole 3.17 DIFF										
215	230	14		SURVY.										
230	400	1 1/2		Trip out B.T #2										
				DRILLER D. Lindall										

I O N	44 TESTING				DRILLING ASSEMBLY				BIT RECORD				MUD RECORD						
					NO.	CODE	AT. END OF TOUR												
45					BIT				FT		BIT NO.		3		TIME		7:00 8:00 12:00		
60	ABANDON				1	BS	2 1/2	10 00	3.96	FT.	SIZE	8 3/4			WEIGHT	9.3	9.3	9.6	
70	STANDBY				1	SS	2	10 00	8.50	FT.	MFG.	H.W.			VIS - SEC	43	40	45	
TOTALS		8	8	8	24	1	90	2 1/2	10 00	2.10	TYPE		XIG			PV / YP	/	/	/
HOURS FOR SHELL ACCOUNT		8	8	8	24	1	90	2 1/2	10 00	2.20	JETS 1/32"		10/10/11			GELS	/	/	/
BOILER #1		8	8	8	24	1	KV	2 1/2	10 00	2.14	SERIAL NO.		22627			W.L.-C.C.			
Boiler #2		8	8	8	24	1	ST	2 1/2	10 00	4.50	DEPTH OUT		3192			PH	9.0	9.0	9.0
Code 232						18	DC	2 1/2	10 00	556.41	DEPTH IN		3000			% SOLIDS			
						27	DP	STANDS		FT.	TOTAL FTG.		786			% SAND			
HOLE CONDITION					2	DP	SINGLES		2571.29	FT.	TOTAL HRS. RUN		5 1/2			MUD MATERIALS ADDED			
1	HOLE DRAG (1000#)				KELLY DOWN				40.98	FT.	BIT CONDITION 1/8" T/B/GAGE					TYPE	AMOUNT	TYPE	AMOUNT
2	TORQUE ON BITCH (DP TURNS)				TOTAL				3742.03	FT.					GE 4	1800	ph		
3	FILL ON BOTTOM (FEET)				WT. OF DC IN AIR					LBS.	REAMER CUTTER NO.				BEN-EX	7#			
					WT. OF STRING				88M	LBS.	REAMER TYPE								

[illegible]

DAILY DRILLING REPORT

WELL NAME SHELL ARCTIC RED RIVER D-27	
LOCATION D-27	PROVINCE N. W. T.

OPERATOR Shell Canada Limited		CONTRACTOR GUSTAFSON		RIG NO. 11	DEPTH AT START OF MORNING TOUR 1250	DEPTH AT END OF EVENING TOUR 2327	DAILY PROGRESS 1077	CUMULATIVE ROTATING HOURS 25	DAYS FROM SPUD 7	DATE MONTH 1 DAY 2 YEAR 71																							
SIGNATURE OF OPERATOR'S REPRESENTATIVE <i>J. Brown</i>		SIGNATURE OF CONTRACTOR'S TOOL PUSHER <i>J. Gustafson</i>																															
DP / DC SIZE 4" / 6 3/4"	WT. / FT. 14	GRADE E	MIN. I.D. 5 1/4"	TOOL JT. O.D. 4" FH.	TYPE THREAD 1	PUMP NO. 1	PUMP MANUFACTURER NATIONAL	TYPE 8P90	STROKE LENGTH 8 1/2"	LAST CASING TUBING OR LINER 9 5/8 36"	NO. OF JOINTS 25	FEET 813	CEMENT USED (SACKS) 430	REMARKS																			
TIME DISTRIBUTION - HOURS		DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD		FOOTAGE		FORMATION (SHOW CORE RECOVERY)					ROTARY R.P.M.		WT. ON BIT (1000#)		PUMP (AIR) PRESS		AIR VOL (CFM)		PUMP NO. 1 LINER SIZE S.P.M.		PUMP NO. 2 LINER SIZE S.P.M.		METHOD PUMPS RUN						
CODE NO.	OPERATION	MORN.	DAY	EVE	TOTAL	BIT NO.	FT.	SIZE	TIME	WEIGHT	VIS-SEC	PV/YP	GELS	W.L.C.C.	PH	% SOLIDS	% SAND	MUD MATERIALS ADDED TYPE AMOUNT TYPE AMOUNT	FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS										
1	RIG UP TEAR DOWN					1	5 1/4	3.96	8 3/4	8.6	8.6	9.7								1250	1731	7 1/2	481	80-180 20322000 6 120 6									
2	DRILLING ACTUAL	7 1/2	4 1/2	6 3/4	18 3/4	5	5 1/4	8.50	SMITH	3.0	3.1	3.4																					
3	REAMING					1	5 1/4	2.10	DTJ																								
4	CORING					1	5 1/4	2.20	JETS 1/32"	10/10/10																							
5	CLEAN TO BOTTOM AND CIRCULATING								SERIAL NO.	AP063																							
6	TRIPS	2 3/4	3/4	3 1/2					DEPTH OUT																								
7	RIG SERVICE	1/4	1/4	1/2	18 0	12	DP	556.41	DEPTH IN	813																							
8	RIG REPAIR								TOTAL FTG.	918																							
9	CUT AND/OR SLIP LINE					1	DP	1148.14	TOTAL HRS. RUN	13 1/4																							
10	DEVIATION SURVEY	1/2	1/2	1/4	1 1/4			10.00	BIT CONDITION 1/8" T/B/GAGE	1N																							
11	WIRE LINE LOG								TOTAL	1731.31																							
12	RUN CASING AND CEMENT							55" LBS.	REAMER CUTTER NO.																								
13	WAIT ON CEMENT							70" LBS.	REAMER TYPE																								
14	NIPPLE UP B.O.P.																																
15	TEST B.O.P.								BIT NO.	1	2																						
16	DRILL STEM TEST					1	5 1/4	3.96	SIZE	8 3/4	8 3/4																						
17	PLUG BACK					1	5 1/4	8.60	MFG.	Smith HW																							
18	SQUEEZE CEMENT					1	5 1/4	2.10	TYPE	DTJ X16																							
19	STUCK OR FISHING					1	5 1/4	2.20	JETS 1/32"	10/10/10																							
20	HANDLE TOOLS					1	5 1/4	2.14	SERIAL NO.	AP063 22747																							
21	CONDITION MUD					1	5 1/4	4.60	DEPTH OUT	1919'																							
22	LOST CIRCULATION					1	5 1/4	556.41	DEPTH IN	813' 1919'																							
23						14	DP	1303.02	TOTAL FTG.	1106'																							
24						-	DP		TOTAL HRS. RUN	18 1/4																							
40	PERFORATE							737.00	BIT CONDITION 1/8" T/B/GAGE	66L																							
41	TUBING TRIPS							1919.83																									
42	TREATING								REAMER CUTTER NO.																								
43	SWABBING							72" LBS.	REAMER TYPE																								
44	TESTING																																
45																																	
60	ABANDON					1	5 1/4	3.96	SIZE	8 3/4																							
70	STANDBY					1	5 1/4	8.50	MFG.	HW																							
TOTALS		8	8	8	24	1	5 1/4	2.10	TYPE	X16																							
HOURS FOR SHELL ACCOUNT		8	8	8	24	1	5 1/4	2.20	JETS 1/32"	10/10/11																							
BOILER #1		8	8	8	24	1	5 1/4	2.14	SERIAL NO.	22747																							
Boiler #2		8	8	8	24	1	5 1/4	4.20	DEPTH OUT																								
Code 232						18	DP	556.41	DEPTH IN	1919																							
HOLE CONDITION						1	DP	1706.83	TOTAL FTG.	408																							
1 HOLE DRAG (1000#)								4080	BIT CONDITION 1/8" T/B/GAGE																								
2 TORQUE ON BOTTOM (DP TURNS)								2327.44																									
3 FILL ON BOTTOM (FEET)								55" LBS.	REAMER CUTTER NO.																								
									REAMER TYPE																								

DRILLER
D. J. DUNDALL

[illegible][illegible]

[illegible][illegible]

DAILY DRILLING REPORT

WELL NAME SHELL ARCTIC RED RIVER	
LOCATION 0-27	PROVINCE N.W.T.

OPERATOR Shell Canada Limited	CONTRACTOR GUSTADSON DRILLING
SIGNATURE OF OPERATOR'S REPRESENTATIVE <i>[Signature]</i>	SIGNATURE OF CONTRACTOR'S TOOL PUSHER <i>[Signature]</i>

Merry Christmas

DP / DC SIZE	WT. / FT.	GRADE	MIN. I.D.	TOOL X O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER	TYPE	STROKE LENGTH

DEPTH AT START OF MORNING TOUR	DEPTH AT END OF EVENING TOUR	DAILY PROGRESS	CUMULATIVE ROTATING HOURS	DAYS FROM SPUD	DATE MONTH DAY YEAR 12 25 70

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE NO.	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT NO.	FT.	TIME	WEIGHT	
1	RIG UP TEAR DOWN									
2	DRILLING ACTUAL									
3	REAMING									
4	CORING									
5	CLEAN TO BOTTOM AND CIRCULATING									
6	TRIPS									
7	RIG SERVICE									
8	RIG REPAIR									
9	CUT AND/OR SLIP LINE									
10	DEVIATION SURVEY									
11	WIRE LINE LOG									
12	RUN CASING AND CEMENT									
13	WAIT ON CEMENT									
14	NIPPLE UP B.O.P.									

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT. ON BIT (1000#)	PUMP (AIR) PRESS.	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
1200		800				CEMENT CRIBBING IN CELLAR W/ 160 SLS CEMENT						

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE NO.	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT NO.	FT.	TIME	WEIGHT	
15	TEST B.O.P.									
16	DRILL STEM TEST									
17	PLUG BACK									
18	SQUEEZE CEMENT									
19	STUCK OR FISHING									
20	HANDLE TOOLS									
21	CONDITION MUD									
22	LOST CIRCULATION									
23										
24										
40	PERFORATE									
41	TUBING TRIPS									
42	TREATING									
43	SWABBING									
44	TESTING									
45										

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT. ON BIT (1000#)	PUMP (AIR) PRESS.	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
8:00						RIG UP TO SPUD.						
2 HRS. RIG UP						J. HONISH, A. F. W. ASLUND, E. HENNER BICKLER J. MAGSON, 8 HRS. OVER TIME RUNNING CAT.						

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE NO.	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT NO.	FT.	TIME	WEIGHT	
60	ABANDON									
70	STANDBY									
TOTALS										
HOURS FOR SHELL ACCOUNT		24								
BOILER		1	8	8	8					
Boiler #2		8	8	8						
HOLE CONDITION										
1	HOLE DRAG (1000#)									
2	TORQUE ON BOTTOM (DP TURNS)									
3	FILL ON BOTTOM (FEET)									

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R P M	WT. ON BIT (1000#)	PUMP (AIR) PRESS.	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
1200		1200	12			Hooked up Sample Box Rig up to Spud & mix mud Serv. Rig Swivel & Table 4 HRS over time E. Johnson A. Lundle A. Skjensberg C. Greff H. Haydon						

DAILY DRILLING REPORT

WELL NAME SHELL ARCTIC RED RIVER		PROVINCE N.W.T.
LOCATION D-27		

OPERATOR Shell Canada Limited		CONTRACTOR Gustafson Drilling		RIG NO. 11	DEPTH AT START OF MORNING TOUR	DEPTH AT END OF EVENING TOUR	DAILY PROGRESS	CUMULATIVE ROTATING HOURS	DAYS FROM SPUD	DATE MONTH DAY YEAR 12 24 70																
SIGNATURE OF OPERATOR'S REPRESENTATIVE <i>[Signature]</i>		SIGNATURE OF CONTRACTOR'S TOOL PUSHER <i>[Signature]</i>																								
DP / DC SIZE	WT. / FT	GRADE	MIN. I.D.	TOOL JT O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER	TYPE	STROKE LENGTH	LAST CASING TUBING OR LINER	SIZE	WT. AND GR.	NO. OF JOINTS	FEET	KB TO CSG. HEAD	SET AT	CEMENT USED (SACKS)	REMARKS								
TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD		FOOTAGE		ROTARY		WT. ON BIT (1000#)		PUMP (AIR) PRESS		AIR VOL (CFM)		PUMP NO. 1 LINER SIZE S.P.M.		PUMP NO. 2 LINER SIZE S.P.M.		METHOD PUMPS RUN	
CODE NO.	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT	FT.	BIT NO.	TIME	WEIGHT	VIS-SEC.	PV / YP	GELS	W.L.-C.C.	PH	% SOLIDS	% SAND	DETAILS OF OPERATION IN SEQUENCE AND REMARKS								
1	RIG UP TEAR DOWN					X	FT.	SIZE																		
2	DRILLING ACTUAL					X	FT.	MFG.																		
3	REAMING					X	FT.	TYPE																		
4	CORING					X	FT.	JETS 1/32"																		
5	CLEAN TO BOTTOM AND CIRCULATING					X	FT.	SERIAL NO.																		
6	TRIPS					X	FT.	DEPTH OUT																		
7	RIG SERVICE					X	FT.	DEPTH IN																		
8	RIG REPAIR						FT.	TOTAL FTG.																		
9	CUT AND/OR SLIP LINE						FT.	TOTAL HRS. RUN																		
10	DEVIATION SURVEY						FT.	BIT CONDITION 1/8" T/B/GAGE																		
11	WIRE LINE LOG						FT.	TOTAL																		
12	RUN CASING AND CEMENT						LBS.	REAMER CUTTER NO.																		
13	WAIT ON CEMENT						LBS.	REAMER TYPE																		
14	NIPPLE UP B.O.P.																									
15	TEST B.O.P.						FT.	BIT NO.																		
16	DRILL STEM TEST					X	FT.	SIZE																		
17	PLUG BACK					X	FT.	MFG.																		
18	SQUEEZE CEMENT					X	FT.	TYPE																		
19	STUCK OR FISHING					X	FT.	JETS 1/32"																		
20	HANDLE TOOLS					X	FT.	SERIAL NO.																		
21	CONDITION MUD					X	FT.	DEPTH OUT																		
22	LOST CIRCULATION					X	FT.	DEPTH IN																		
23							FT.	TOTAL FTG.																		
24							FT.	TOTAL HRS. RUN																		
40	PERFORATE						FT.	BIT CONDITION 1/8" T/B/GAGE																		
41	TUBING TRIPS						FT.	TOTAL																		
42	TREATING						LBS.	REAMER CUTTER NO.																		
43	SWABBING						LBS.	REAMER TYPE																		
44	TESTING																									
45							FT.	BIT NO.																		
60	ABANDON					X	FT.	SIZE																		
70	STANDBY					X	FT.	MFG.																		
TOTALS						X	FT.	TYPE																		
HOURS FOR SHELL ACCOUNT					24	X	FT.	JETS 1/32"																		
BOILER						X	FT.	SERIAL NO.																		
CODE 230						X	FT.	DEPTH OUT																		
BT 208						X	FT.	DEPTH IN																		
HOLE CONDITION							FT.	TOTAL FTG.																		
							FT.	TOTAL HRS. RUN																		
1 HOLE DRAG (1000#)							FT.	BIT CONDITION 1/8" T/B/GAGE																		
2 TORQUE ON BOTTOM (DP TURNS)							FT.	TOTAL																		
3 FILL ON BOTTOM (FEET)							LBS.	REAMER CUTTER NO.																		
							LBS.	REAMER TYPE																		

MORNING TOUR

1200 1200 1200

RIG UP. LEVEL MUD TANK. HOOR UP SUCTION ON MUD PUMP UNLOAD MUD OFF TRUCKS.

4 HRS. OVERTIME W. SHUPRA L. SCOTT R. BERG R. LANGLOIS L. BRALLER.

DAY TOUR

RIG UP WELD ON CON PIPE & PUT ON HYDRIL W/04" FLARE LINES WELD KELLY SOCK.

OVERTIME 4 Hrs. J. Housh A. Eversh B. Spers. C. Housh J. Magnuson.

EVENING TOUR

1200 1200 1200

Head up Hydril lay Flare lines & set line Crib Cellar

4 HRS overtime E. Johnson A. Hurdle R. Skjorsberg C. Greff H. Haydon

DRILLER *[Signature]*

DAILY DRILLING REPORT

WELL NAME SHELL ARCTIC RED RIVER	
LOCATION D-27	PROVINCE N.W.T.

OPERATOR Shell Canada Limited	CONTRACTOR GUSTAFSON DRILLING
SIGNATURE OF OPERATOR'S REPRESENTATIVE <i>[Signature]</i>	SIGNATURE OF CONTRACTOR'S TOOL PUSHER <i>[Signature]</i>

DP / DC SIZE	WT. / FT.	GRADE	MUN. I.D.	TOOL JT. O.D.	TYPE THREAD	PUMP NO.	PUMP MANUFACTURER	TYPE	STROKE LENGTH

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT	FT.	BIT NO.	TIME	
1	RIG UP TEAR DOWN					10	OD	FT.	SIZE	
2	DRILLING ACTUAL					10	OD	FT.	MFG.	
3	REAMING					10	OD	FT.	TYPE	
4	CORING					10	OD	FT.	JETS 1/32"	
5	CLEAN TO BOTTOM AND CIRCULATING					10	OD	FT.	SERIAL NO.	
6	TRIPS					10	OD	FT.	DEPTH OUT	
7	RIG SERVICE					10	OD	FT.	DEPTH IN	
8	RIG REPAIR					DP	STANDS	FT.	TOTAL FTG.	
9	CUT AND/OR SLIP LINE					DP	SINGLES	FT.	TOTAL HRS. RUN	
10	DEVIATION SURVEY					KELLY DOWN		FT.	BIT CONDITION 1/8" T/B/GAGE	
11	WIRE LINE LOG					TOTAL		FT.		
12	RUN CASING AND CEMENT					WT. OF DC IN AIR	LBS.	REAMER CUTTER NO.		
13	WAIT ON CEMENT					WT. OF STRING	LBS.	REAMER TYPE		
14	NIPPLE UP B.O.P.					DRILLING ASSEMBLY AT END OF TOUR				

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT	FT.	BIT NO.	TIME	
15	TEST B.O.P.					10	OD	FT.	SIZE	
16	DRILL STEM TEST					10	OD	FT.	MFG.	
17	PLUG BACK					10	OD	FT.	TYPE	
18	SQUEEZE CEMENT					10	OD	FT.	JETS 1/32"	
19	STUCK OR FISHING					10	OD	FT.	SERIAL NO.	
20	HANDLE TOOLS					10	OD	FT.	DEPTH OUT	
21	CONDITION MUD					10	OD	FT.	DEPTH IN	
22	LOST CIRCULATION					10	OD	FT.	TOTAL FTG.	
23						DP	STANDS	FT.	TOTAL HRS. RUN	
24						DP	SINGLES	FT.	TOTAL HRS. RUN	
40	PERFORATE					KELLY DOWN		FT.	BIT CONDITION 1/8" T/B/GAGE	
41	TUBING TRIPS					TOTAL		FT.		
42	TREATING					WT. OF DC IN AIR	LBS.	REAMER CUTTER NO.		
43	SWABBING					WT. OF STRING	LBS.	REAMER TYPE		
44	TESTING					DRILLING ASSEMBLY AT END OF TOUR				

TIME DISTRIBUTION - HOURS					DRILLING ASSEMBLY AT END OF TOUR		BIT RECORD		MUD RECORD	
CODE	OPERATION	MORN.	DAY	EVE.	TOTAL	BIT	FT.	BIT NO.	TIME	
60	ABANDON					10	OD	FT.	SIZE	
70	STANDBY					10	OD	FT.	MFG.	
TOTALS						10	OD	FT.	TYPE	
HOURS FOR SHELL ACCOUNT					24	10	OD	FT.	JETS 1/32"	
BOILER						10	OD	FT.	SERIAL NO.	
Code 230						10	OD	FT.	DEPTH OUT	
OT 20800						10	OD	FT.	DEPTH IN	
HOLE CONDITION						DP	STANDS	FT.	TOTAL FTG.	
1	HOLE DRAG (1000#)					DP	SINGLES	FT.	TOTAL HRS. RUN	
2	TORQUE ON BOTTOM (DP TURNS)					TOTAL		FT.		
3	FILL ON BOTTOM (FEET)					WT. OF DC IN AIR	LBS.	REAMER CUTTER NO.		
						WT. OF STRING	LBS.	REAMER TYPE		

RIG NO. 11	DEPTH AT START OF MORNING TOUR	DEPTH AT END OF EVENING TOUR	DAILY PROGRESS	CUMULATIVE ROTATING HOURS	DAYS FROM SPUD	MONTH 12	DAY 25	YEAR 70
----------------------	--------------------------------	------------------------------	----------------	---------------------------	----------------	--------------------	------------------	-------------------

LAST CASING TUBING OR LINER	SIZE	WT. AND GR.	NO. OF JOINTS	FEET	RB. TO CSG. HEAD	SET AT	CEMENT USED (SACKS)	REMARKS

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
1200		1200				PUT UP PREFABS. INSULATE. BUILDING. RIG UP.						
						4 HRS OVERTIME W. SHUDRA I. SCOTT R. BERG. R. LANGLOIS L. BRAZEL.						

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
8.00		8.00				RIG UP W/O PREFABS PUT COLLARS & CSG ON RACKS						
						OVERTIME 4 HRS. J. Hunk A. Lamm B. Speers E. Hunschiller J. Magano.						

FOOTAGE		ROT HOURS	DR-D RM-R CORE-C	CORE NO.	FORMATION (SHOW CORE RECOVERY)	ROTARY R.P.M.	WT. ON BIT (1000#)	PUMP (AIR) PRESS	AIR VOL (CFM)	PUMP NO. 1 LINER SIZE S.P.M.	PUMP NO. 2 LINER SIZE S.P.M.	METHOD PUMPS RUN
FROM	TO											
DEVIATION RECORD		DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION	DEPTH	DEVIATION°	DIRECTION		
TIME LOG		FROM	TO	ELAPSED TIME	CODE	DETAILS OF OPERATION IN SEQUENCE AND REMARKS						
1200		1200		12		Line up pumps. Hook up mud lines & suction. Fire up #2 Boiler Put Cap on Building & Plug all Holes w/ Insulating.						
						4 Hrs overtime E. Johnson A. Lundell H. Skjorsberg C. Greff H. Haydon						

8-10/69) DAILY DRILLING REPORT

WELL NAME SHELL ARCTIC RED RIVER 0-27 LOCATION 0-27 PROVINCE N.W.T.

OPERATOR Shell Canada Limited CONTRACTOR Gustafson Drilling RIG NO 11

SIGNATURE OF OPERATOR'S REPRESENTATIVE SIGNATURE OF CONTRACTOR'S TOOL PUSHER

DEPTH AT START OF MORNING TOUR DEPTH AT END OF EVENING TOUR DAILY PROGRESS CUMULATIVE ROTATING HOURS DAYS FROM SPUD MONTH DAY YEAR 12 21 70

DP / DC SIZE WT / FT GRADE MIN. I.D. TOOL JT O.D. TYPE THREAD PUMP NO. PUMP MANUFACTURER TYPE STROKE LENGTH LAST CASING TUBING OR LINER SIZE WT. AND GR. NO. OF JOINTS FEET KB TO CSE. HEAD SET AT CEMENT USED (SACKS) REMARKS

TIME DISTRIBUTION - HOURS DRILLING ASSEMBLY AT END OF TOUR BIT RECORD MUD RECORD FOOTAGE

CODE NO. OPERATION MORN. DAY EVE. TOTAL BIT NO. TIME WEIGHT VIS - SEC PV / YP GELS W L - C C PH % SOLIDS % SAND MUD MATERIALS ADDED TYPE AMOUNT TYPE AMOUNT

1 RIG UP TEAR DOWN 10 00 X FT. SIZE WEIGHT

2 DRILLING ACTUAL 10 00 X FT. MFG. VIS - SEC

3 REAMING 10 00 X FT. TYPE PV / YP

4 CORING 10 00 X FT. JETS 1/32" GELS

5 CLEAN TO BOTTOM AND CIRCULATING 10 00 X FT. SERIAL NO. W L - C C

6 TRIPS 10 00 X FT. DEPTH OUT PH

7 RIG SERVICE 10 00 X FT. DEPTH IN % SOLIDS

8 RIG REPAIR DP STANDS FT. TOTAL FTG. % SAND

9 CUT AND/OR SLIP LINE DP SINGLES FT. TOTAL HRS. RUN

10 DEVIATION SURVEY KELLY DOWN FT. BIT CONDITION 1/8" T/B/GAGE

11 WIRE LINE LOG TOTAL FT.

12 RUN CASING AND CEMENT WT. OF DC IN AIR LBS. REAMER CUTTER NO.

13 WAIT ON CEMENT WT. OF STRING LBS. REAMER TYPE

14 NIPPLE UP B.O.P. DRILLING ASSEMBLY AT END OF TOUR BIT RECORD MUD RECORD FOOTAGE

15 TEST B.O.P. BIT NO. TIME WEIGHT VIS - SEC PV / YP GELS W L - C C PH % SOLIDS % SAND MUD MATERIALS ADDED TYPE AMOUNT TYPE AMOUNT

16 DRILL STEM TEST 10 00 X FT. SIZE WEIGHT

17 PLUG BACK 10 00 X FT. MFG. VIS - SEC

18 SQUEEZE CEMENT 10 00 X FT. TYPE PV / YP

19 STUCK OR FISHING 10 00 X FT. JETS 1/32" GELS

20 HANDLE TOOLS 10 00 X FT. SERIAL NO. W L - C C

21 CONDITION MUD 10 00 X FT. DEPTH OUT PH

22 LOST CIRCULATION 10 00 X FT. DEPTH IN % SOLIDS

23 DP STANDS FT. TOTAL FTG. % SAND

24 DP SINGLES FT. TOTAL HRS. RUN MUD MATERIALS ADDED TYPE AMOUNT TYPE AMOUNT

C 40 PERFORATE KELLY DOWN FT. BIT CONDITION 1/8" T/B/GAGE

O 41 TUBING TRIPS TOTAL FT.

M 42 TREATING WT. OF DC IN AIR LBS. REAMER CUTTER NO.

P 43 SWABBING WT. OF STRING LBS. REAMER TYPE

E 44 TESTING DRILLING ASSEMBLY AT END OF TOUR BIT RECORD MUD RECORD FOOTAGE

I 45 BIT NO. TIME WEIGHT VIS - SEC PV / YP GELS W L - C C PH % SOLIDS % SAND MUD MATERIALS ADDED TYPE AMOUNT TYPE AMOUNT

N 60 ABANDON 10 00 X FT. SIZE WEIGHT

70 STANDBY 10 00 X FT. MFG. VIS - SEC

TOTALS 10 00 X FT. TYPE PV / YP

HOURS FOR SHELL ACCOUNT 24 10 00 X FT. JETS 1/32" GELS

BOILER 10 00 X FT. SERIAL NO. W L - C C

12 HRS TO 2080 10 00 X FT. DEPTH OUT PH

HOLE CONDITION 10 00 X FT. DEPTH IN % SOLIDS

1 HOLE DRAG (1000#) KELLY DOWN FT. BIT CONDITION 1/8" T/B/GAGE

2 TORQUE ON BOTTOM (DP TURNS) TOTAL FT.

3 FILL ON BOTTOM (FEET) WT. OF DC IN AIR LBS. REAMER CUTTER NO.

WT. OF STRING LBS. REAMER TYPE

FOOTAGE FROM TO ROT HOURS DR-D RM-R CORE-C CORE NO FORMATION (SHOW CORE RECOVERY) ROTARY R P M WT ON BIT (1000#) PUMP (AIR) PRESS AIR VOL (CFM) PUMP NO 1 LINER SIZE S P M PUMP NO 2 LINER SIZE S P M METHOD PUMPS RUN

DEVIATION RECORD DEPTH DEVIATION° DIRECTION DEPTH DEVIATION° DIRECTION DEPTH DEVIATION° DIRECTION

TIME LOG FROM TO ELAPSED TIME CODE DETAILS OF OPERATION IN SEQUENCE AND REMARKS

1200 1200 PUT UP MUD TANK PREFABS. RIG UP. DAWLER 1200 1200 4 HRS OVER TIME RIG UP W. SHUPAA. R. LANGLOIS. A. SCOTT L. BAZEL. CARHEAD F. DORMAN

8.00 8.00 W/O PREFABS PUT UP PREFABS RIG UP DVERTIME 4 HRS J. HOWISH A. ELIASIUK E. HENNERBICHLER J. MAGNUSON

1200 1200 12 PUT UP Prefabs Hook up Steam Water & Fuel Lines 4 Hrs over time F. Johnson A. Lynde A. Skjonsberg G. Greff H. Haydon