



Well Name Nom du puits		Miami Amoco Kakisa River I-52		Drilling Authority No. Autorisation de forage n°		741	
Field/Area Gisement/Région				Date Issued Date d'émission		14-01-74	
Location Emplacement		Unit Unité I-52-60-10-117-45		Section		Permit or Lease 3876	

Latitude 60°01'34"N

Longitude 117°54'42"W

U.W.L.R.
N.R.U.E.P. 60.02611 - 117.91167U.W.I. No.
N.I.P. No. 300I526010117450

File Microfilmed

Rig. Release Date
Date de transfert de
la tour de forage

Feb. 27, 1974

Tour Sheets, Microfilmed

Status
Statut

D. + R.

Information Release Date
Date de publication autorisée
des informations

Feb. 27, 1976

CHANGE OF NAME:
CHANGEMENT DE NOM:Change of Location
Changement de emplacement

INDEX	DATE RECEIVED RECU LE	INDEX
Application for a Drilling Authority		Demande d'autorisation de forage
Well Completion Data	May 28/74	Renseignements sur le forage d'un puits
Well History Report		Données chronologiques sur le puits
Application to Amend a Drilling Authority		Demande de modification d'une autorisation de forage
Application to Change a Well Name		Demande de changement du nom d'un puits
Application to Abandon a Well or Suspend Drilling		Demande d'abandon d'un puits ou de suspension du forage
Application to Alter Condition of a Well		Demande d'autorisation de modifier l'état d'un puits
Well History Supplement		Supplément aux données chronologiques sur le puits
Well Completion Data		Renseignements sur le forage d'un puits
Work-Over Report No.		Rapport de reconditionnement n°
Application to Commingle Production before Measurement		Demande d'autorisation de mélanger la production avant jaugeage
Data for Back Pressure Test on Natural Gas Wells		Données de calcul de la capacité de production d'un puits de gaz naturel — Méthode graphique n° 7
Data for Back Pressure Test on Natural Gas Wells		Données de calcul de la capacité de production d'un puits de gaz naturel — Méthode de Vitter
M.P.R. — Oil — Calculations		Calcul du T.M.P. (Taux maximal de production) de pétrole
New Oil Well Report		Rapport sur un nouveau puits de pétrole
New Gas Well Report		Rapport sur un nouveau puits de gaz naturel
Well Inspection Report		Rapport d'inspection de l'emplacement d'un puits
Rig Inspection Report		Rapport d'inspection d'une tour de forage
Battery Inspection Report		Rapport d'inspection d'une batterie de puits
Equipment Report		Rapport d'inspection des compteurs
Well Card		Fiche de puits
New Service Well Report		Rapport sur un nouveau puits de service
Strat Service Logs		Rapport mensuel des injections d'eau
Logs — Large scale		Diagrammes: Grande échelle
Logs — Small scale		Diagrammes: Petite échelle




Drilling Authority No. 741
Date Issued January 14, 1974

LAND 52-90 (2) (3-70)

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
OIL AND MINERAL DIVISION

WELL COMPLETION DATA

To be submitted in duplicate within thirty days after the completion, rework, abandonment, or suspension of every well.



Well name and number MIAMI AMOCO KAKISA RIVER I-52
Permit No. 3876 Lease No.
Amoco Canada Petroleum Company Ltd Exploratory Licence No. 2266
(Permitter, Licensee, Lessee)
Miami Oil Producers, Inc. Exploratory Licence No. 2132
(Operator)
Location: Unit I Section 52 Grid 60-10-117-45
Latitude 60° 01' 34" N Longitude 117° 54' 42" W
Unique well identifier 300I526010117450
Universal Well Location Reference Lat. 60.02611° N, Long. 117.91167° W

	DATE	DEPTH	Pool(s)
Spudded	Feb. 1/74		Interval(s) open to production
Suspended			
Resumed Operations			
Finished Drilling	Feb. 22/74	5651'	
Deepened			Elevation: Gr. 2384' K.B. 2397.5'
Complete (gas/oil)			Rig No. 19
Abandoned	Feb. 26/74	598'	Drilling Contractor Westburne - G.P.
Rig released	Feb. 27/74		Contractor's Business Licence No.

CASING RECORD

Casing Size (Inches)	Grade	Weight	Amount	Set at -	Sacks of Cement and Additives
1. 9-5/8"	H-40	32.3#	16 jts.	635' KB	500 sacks cement
2.					plus 2% CaCl ₂
3.					plus 25% gel flake.
4.					Recemented with
5.					90 sacks of Port-
6.					land cement plus
					3% CaCl ₂ .

GEOLOGICAL TOPS	ELEVATION		CORE RECORD					
	Depths	Sub-Sea	From	To	Rec.	From	To	Rec.
Wabamun	1680'	+ 718'	NO CORES CUT.					
Hay River Shale	2550'	- 152'						
BHL Shale	4300'	-1902'						
Slave Point	4620'	-2222'						
Ft. Vermillion	4766'	-2368'						
Watt Mountain	4795'	-2397'						
Sulphur Point	4805'	-2407'						

	Run No.	Type of Log	LOG RECORD	
			From	To
Muskeg				
Keg River Plat.	1	Dual Induction		
Chinchaga		Laterolog	638'	5645'
Red Beds	1	Borehole Compen-	638'	5641'
Granite Wash		sated Sonic Log		
Basement	1	Compensated Neu-		
		tron Formation	4250'	5636'
		Density Log		
		Sample Description		
		Log	1600	TD (5651')



Drilling Authority No. 741

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT
OIL AND MINERAL DIVISION

Application to Abandon a Well or Suspend Drilling

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to abandon, to suspend drilling:—

Name and number of well MIAMI AMOCO KAKISA RIVER I-52
Location: Unit I Section 52 Grid 60-10-117-45
Latitude 60°01'34"N Longitude 117°54'42"W
From Established Reference Marker 300I526010117450
Universal Well Location Reference Lat. 60.02611°N, Long. 117.91167°W
Permit No. 3876 Lease No.

Amoco Canada Petroleum Company Ltd.
(Permittee, Licencee, Lessee)

Date of commencement of proposed program February 26, 1974

OIL, GAS, AND WATER ENCOUNTERED
(Depths)

Oil at Nil
Gas at Nil
Water at 5180' - 5290'
Total Depth 5651' Date of last operations February 27, 1974
Present condition of well Dry and Abandoned

CASING RECORD

Casing Size O.D. Inches	Weight	Amount	Set At—	Sacks of Cement and Additives	Amount Pulled
1. 9-5/8"	32.3#	16 jts.	635' KB	500 sacks cement	
2.				plus 2% CaCl ₂ plus	
3.				25% gel flake. Re-	
4.				cemented with 90	
5.				sxs Portland cement	
				plus 3% CaCl ₂ .	

PROPOSED ABANDONMENT PROGRAM

Plug		Geological Formation	Number of Sacks of Cement	Remarks
No.	Position			
1	5651'-5460'	Granite Wash	90 sacks	
2	5360'-5150'	Keg River	100 sacks	Felt @ 5142'.
3	660'- 610'	Devonian	65 sacks	Felt @ 598'.

The following logs have been run. Dual Induction, BHC Sonic, Compensated Neutron
Other operations proposed.

Operations to be carried out by Westburne - G.P. Contractor Licence No.
Address 550 - 6th Avenue S.W., Calgary Address
Responsible Agent in field Helton Engineering Ltd. 625 - 4th Avenue S.W., Calgary.
Dated at Calgary, this 28th Day of May 1974
Signed by [Signature] Company Miami Oil Producers, Inc.
Title Agent for Miami Oil Prod. Operator's Exploratory Licence No. 2132

Note:—The District Conservation Engineer's office must be notified before work is commenced.

(For OIL AND MINERAL DIVISION use only)

APPROVAL

This application has been examined and proposed programme approved, subject to the following conditions:

Confirming oral approval given by G. E. Blue on February 24, 1974. Approval included cutting casing off 3 feet below ground level with a 5-sack surface plug plus welded plate and well marker.

Dated June 4, 1974

[Signature]
District Conservation Engineer



CANADA

DEPARTMENT OF INDIAN AFFAIRS AND NORTHERN DEVELOPMENT

OIL AND MINERAL DIVISION

Application for a Drilling Authority

This notice of intention to begin drilling operations, in triplicate, and where required a plan of survey approved by the Surveyor General showing the target area or the site of the well must be submitted and approved before commencing operations.

In compliance with the "Canada Oil and Gas Land Regulations", application is hereby made for approval to drill:-

Name and number of well . . . MIAMI AMOCO KAKISA RIVER . . . I-52 . . .

Location: Unit . . . I . . . Section . . . 52 . . . Grid . . . 60 -10 - 117 - 45

Latitude . . . 60° 01' 34" N . . . Longitude . . . 117° 54' 42" W . . .

Unique Well Identifier . . . 300I526010117450 . . .

Universal Well Location Reference . . . Lat. 60.02611° N., Long. 117.91167° W. . .

Elevation: Ground . . . 2384.0' . . . K.B. . . . 2397.5' . . . feet above sea-level.

Well is expected to produce from . . . Sulphur Point or Keg River . . . formation at a depth of about 4800 & 4900 resp. feet. Expected total final depth . . . 5600'

Area assigned to well . . . Exploratory . . .

(for District Conservation Engineer's use only)

Permit No. . . 3876 . . . Lease No. . . . Acreage . . . 63,854 acres . . .

Permittee, licensee, or lessee . . . Amoco Canada Petroleum Company Ltd. . . .

Exploratory Licence No. . . . 2266 . . .

Surface owned by Crown or . . . Crown . . .

(If alienated submit name and address of owner and occupant.)

Petroleum and natural gas rights owned by . . . Crown . . .

We propose to use the following strings of casing, either cementing or landing them as indicated below:-

Casing Size O.D. (Inches)	Weight (Lb./Ft.)	Grade	New or Used	Estimated Depth	Sacks of Cement
1. . . 9-5/8" . . .	32.3# . . .	H . . .	New . . .	560' . . .	500 sacks . . .
2. . . 4-1/2" . . .	9.5# . . .	J . . .	New . . .	5600' . . .	As required. . .
3. . .					
4. . . (In the event that 9-5/8" casing is not available, we propose					
5. . . to use 10-3/4", 32.75#, H casing.) . . .					

Expected water, gas, and oil horizons and type of control equipment. Sulphur Point, Keg River, . . .

Slave Point and Beaverhill Lake. . . Control Equipment - 10" . . .

900 Series Hydril and Double Hydraulic Ram Preventers. . .

Well will be drilled with Rotary Rig No. . . 19 . . . by . . . Westburne - G.P. Drilling Ltd. . .

(Drilling Contractor or company)

#932, 550 - 6th Avenue S.W., Calgary, Alberta

Responsible agent of applicant:- Contractor's Business Licence No. . . Applied For

At well. Helton Engineering Ltd. At registered office. . . Helton Engineering Ltd.

Address 625 . . 4th Ave. . S.W. Address 625 . . 4th Ave. . S.W. . Calgary, Alberta

It is understood that if changes become necessary, notice of the change of plan will be submitted.

Dated at . . . Calgary . . . this . . . 7th . . . day of . . . January . . . 19 74

Signed by . . . [Signature] . . . Company . . . Miami Oil Producers, Inc.

Title Agent for Miami Oil . . . Operator's Licence No. . . 2132 . . .

(For Oil and Mineral Division use only)

APPROVED

This application has been examined and approved subject to the following conditions:

Please see Conditions of Approval on the attached sheet.

Dated. . . January 14 . . . 19 74 . . .


[Signature]
District Conservation Engineer

Forms to be submitted to District Conservation Engineer,
Department of Indian Affairs and Northern Development.

TO BE ATTACHED TO AND MADE A PART OF DRILLING AUTHORITY NO. 741
FOR Miami Amoco Kakisa River I-52 APPROVED January 14, 1974.

CONDITIONS OF APPROVAL:

1. Copies of this Drilling Authority or Amendments to a Drilling Authority shall be exhibited at the drilling rig in both the Doghouse and the Drilling Foreman's office between spud and rig release dates.
2. The Company shall submit to this office, on Tuesday of each week/daily, the latest reports received on the progress of the well.
3. During well drilling and testing operations, every effort shall be made to ensure that drilling fluids, chemicals and wastes shall be disposed of or contained in a manner that will prevent contamination of adjacent areas, or sub-surface waters.
4. We draw your attention to Sections 95 and 96 of the Canada Oil and Gas Land Regulations.
5. Approval must be obtained from the District Conservation Engineer to run any casing or liners not approved on the Drilling Authority.
6. All shows of oil and/or gas, and water flows, or any unusual events shall be reported to the District Conservation Engineer immediately.
7. Should a fatal accident occur, drilling operations are to be suspended and the District Conservation Engineer notified immediately. Permission to resume drilling must be obtained from the District Conservation Engineer.
8. Two field print copies of all well logs and three copies of the core analyses and fluid analyses must be forwarded to the District Conservation Engineer as soon as they are available.
9. Formation tops (samples or logs) of the section penetrated each week are to be reported with the weekly drilling reports.
10. The District Conservation Engineer must be notified at least 24 hours before spudding the well.
11. Permission to drill beyond the approved final total depth MUST be obtained from the District Conservation Engineer.
12. All Tool-pushers and all back-up Supervisory Personnel who are engaged in Northern operations are required to hold a valid PITS Well-Control Training Course Certificate (or its equivalent as rated by a committee representative of industry interests, to be established by APOA).
13. All such northern locations require at least one of the certified persons mentioned under item (12) above to be on-site at all times during drilling operations.
14. Pre-spud drilling safety Supervisory meetings shall be held on-site between Operator/Contractor(s) personnel, followed by regular blow-out control procedures drills. These meetings and drills shall be noted on the daily tour sheets.




G.E. Blue,
District Conservation Engineer,
District 2.

WESTBURNE DRILLING RIG No. 19

- 10" - 3000' B.O.P. STACK,

- 3" x 2" 3000' MANIFOLD,




Well No. 109

MIAMI AMOCO CAMERON HILLS I 52

Unit I Section 52 Grid Area $60^{\circ}10' - 117^{\circ}45'$

Latitude $60^{\circ}01'34''$ Longitude $117^{\circ}54'42''$

NORTHWEST TERRITORIES



HELTON ENGINEERING LTD.
for
MIAMI OIL PRODUCERS, INC.

Elevation: 2384 (copied from Seismic Notes)
Horizontal Information scaled from seismic maps.

R. Russell Vice President
M. A. Helton President

Prepared by
MIDWEST SURVEYS CO. LTD.



Date: January 7, 1974

C-960-73-1

Form 46 12-71



SUGGESTED MUD PROGRAM

Miami Oil Producers Inc.,
P.O. Box 2040,
Abilene, Texas.

Miami Cameron Hills 1-52 60° 10'N 117° 45'W #109

We are pleased to submit herewith mud summary and cost estimate for the above captioned wells. We estimate 20 contract days, 5 days daywork and 2 days surface casing and w.o.c.

SURFACE HOLE:

Drill surface with a conventional spud mud, using bentonite and small amounts of lime and/or caustic soda to raise the viscosity as required to maintain good hole conditions. If loss circulation occurs, raise viscosity as described and add sawdust until returns are regained.

TOP HOLE to 500' ABOVE SLAVE POINT:

Drill out cement and dump cement cut returns. Treat out excess cement contamination with 200# Bicarbonate of Soda. Drill ahead with water. Add 10# S.A.P.P. each 200 feet of hole drilled to disperse mud ring build up.

500' ABOVE SLAVE POINT to TOTAL DEPTH:

Estimated formation tops:	#109	#110.
Slave Point	4608'	4393'
Watt Mtn	4798'	4553'
Nuskeg	4913'	4703'
Keg River	4973'	4753'
Chinchaga	5393'	5213'
PreCambrian	5533'	5363'
Total Depth	5583'	5401'
Mud up	4100'	3900'



SUGGESTED MUD PROGRAM

2.

Mud up with gel chemical mud system. Hole is to be kept full at all times and in shape for evaluation of various formations.

Suggested Properties:

Weight	.944-9.6 #/gal. Let weight build up to 10.5 #/gal for penetration of Slave Point and balance of hole.
Viscosity	
Drilling	45-55 sec/qt
Coring	60-65 sec/qt
Testing	70-80 sec/qt
Plastic viscosity	15-30
Yield point	15-40
Gels 0 min	10-15
Gels 10 min	15-30
pH	9.0
Water loss	8 c.c.

Raise viscosity prior to reaching total depth for logging operations allowing sufficient time for gel to yield.

The cost of the above program is estimated at \$7,000.00 per well plus trucking of \$1,500.00 per well from High Level stock point.

SERVICE ENGINEER: Mr. Rick Michalski, who will be stationed at the well site.

PROGRAM BY: Arthur L. Hazle

November 28, 1973.



Westburne - G.P. Drilling Ltd. **Forage Westburne - G.P. Ltée.**

R I G # 1 9

MAJOR COMPONENTS

- | | |
|----------------------|--|
| Mast | - 126' Lee C. Moore, capacity 370,000#. |
| Substructure | - 10' steel. |
| Drawworks | - National T32 double drum, torque converter driven. |
| Engines | - GM Twin 6 "N" Series on hoist, 310 HP. |
| | - Caterpillar D379 on K500A pump, 520 HP. |
| Slush Pump | - National K500A (7 3/4 x 15) unitized in building. |
| Mud Mixer Pump | - 5 x 6 Mission, centrifugal mounted in pump building, driven from Cat motor. |
| Drill Pipe | - 4" Grade E, 14#, 3 1/2" IF connections w/5" OD tool jts. |
| Drill Collars | - 18 - 5" x 31' x 2 1/4", 3 1/2" IF connections. |
| | - 7 - 6 3/4" x 31' x 2 7/8" bore, 5" H90 connections. |
| | - 19 - 6 1/4" x 31' x 2 7/8" bore, 4 1/2" H90 connections. |
| | - Oilwell 17 1/2". |
| Rotary Table | - 6 sheave - integral part of mast. |
| Crown | |
| Travelling Block | - Baash Ross Model DBM - 430 - 150 Ton combination. |
| Hook | |
| Swivel | - Oilwell SA 150. |
| Drilling Line | - 1". |
| Light Plant | - D 315 Caterpillar 30 KW - AC. |
| Boiler | - 50 HP Napanee type diesel fired, automatic. |
| Shale Shaker | - Link Belt NRM 145, single. |
| Mud Tanks | - 1 - 4' x 12' x 45', capacity 385 Bbls. with low and high pressure mud mixing system. |
| Deviation Equipment | - Totco, double recorder. 80 |
| B.O.P.'s | - 10 - 900 Hydril GK |
| | - 10 - 900 Hydraulic Double Shaffer. |
| | - Hydril Model 80 Accumulator - remote controls and standby nitrogen bottles. |
| | - Manifold - outside subbase. |
| Buildings | - 8' x 43' steel light plant, change house and accumulator house. |
| | - 8' x 23' steel oil house and tool house. |
| | - 8' x 15' steel drillers' doghouse. |
| Water & Fuel Storage | - 300 Bbls. - water; 5000 Gals. - fuel, combined in one load. |
| Special Equipment | - Martin Decker hydro-mech rotary torque gauge. |
| | - Foster tong torque gauge. |
| | - Eastman drilling time recorder. |
| | - Satellite automatic driller. |
| | - Hydromatic brake. |
| Unitized Lines | - Suitcase type. |

MIAMI OIL PRODUCERS, INC.


MIAMI AMOCO KAKISA RIVER I-52

60° 1' 34" N - 117° 54' 42" W

WELL HISTORY REPORT

Prepared by: HELTON ENGINEERING LTD.

April, 1974


R. J. Russell, P. Eng.

MIAMI AMOCO KAKISA RIVER I-52

TABLE OF CONTENTS

SECTION I - SUMMARY OF WELL DATA

- (a) Well Name
- (b) Permittee
- (c) Name of Operator
- (d) Location
- (e) Co-ordinates
- (f) Permit Number
- (g) Drilling Contractor
- (h) Drilling Authority
- (i) Classification
- (j) Elevations
- (k) Date Spudded
- (l) Date Completed Drilling
- (m) Total Depth and Plugged Back Total Depth
- (n) Well Status
- (o) Rig Release Date
- (p) Hole Sizes
- (q) Casing Size and Setting Depth

SECTION II - GEOLOGICAL SUMMARY

- (a) Electric Log Tops
- (b) Sample Tops
- (c) Sample Description (In pocket)

SECTION III - ENGINEERING SUMMARY

- (a) Drill Stem Test No. 1
- (b) Casing Summary
- (c) Mud Report
- (d) Deviation Record
- (e) Bit Record
- (f) Abandonment Plugs

SECTION IV - LOGS

- (a) Log Information

POCKET

Dual Induction Laterolog (Final Print)
Borehole Compensated Sonic Log (Final Print)
Compensated Neutron Formation Density Log (Final Print)
Sample Description

MIAMI AMOCO KAKISA RIVER I-52

WELL HISTORY REPORT

SECTION I - SUMMARY OF WELL DATA

MIAMI AMOCO KAKISA RIVER I-52

WELL HISTORY REPORT

SECTION I - SUMMARY OF WELL DATA

(a) Miami Amoco Kakisa River I-52

(b) Permittee

Amoco Canada Petroleum Company Ltd.

(c) Name of Operator

Miami Oil Producers, Inc.
P.O. Drawer 2040
Abilene, Texas 79604

(d) Location

I-52-60-10-117-45

(e) Co-Ordinates

Latitude: 60°01'34"N Longitude: 117°54'42"W

Unique Well Identifier: 300I526010117450

Universal Well Location Reference: Lat. 60.02611°N
Long. 117.91167°W

(f) Permit Number

3876

(g) Drilling Contractor

Westburne - G.P. Drilling Ltd.
Rig #19 - National T32

(h) Drilling Authority

Drilling Authority No. 741 - January 14, 1974

(i) Classification

New Field Wildcat

Page 2
Summary of Well Data

(j) Elevations

Ground 2384' Kelly Bushing 2397.5' Casing Flange 2384'

(k) Date Spudded

February 1, 1974

(l) Date Completed Drilling

February 22, 1974

(m) Total Depth and Plugged Back Total Depth

Total Depth: 5651' Plugged Back Total Depth: 598'

(n) Well Status

Dry and Abandoned

(o) Rig Release Date

February 27, 1974

(p) Hole Sizes

13-3/4" 0 - 598', 13 1/2" 598' - 640', 8-3/4" 640' - 5651'

(q) Casing Size and Setting Depth

Surface Casing: 9-5/8", 32.3#, H-40 casing.
Landed at 635' K.B.

MIAMI AMOCO KAKISA RIVER I-52

WELL HISTORY REPORT

SECTION II - GEOLOGICAL SUMMARY

MIAMI AMOCO KAKISA RIVER I-52

ELECTRIC LOG TOPS

K.B. Elevation: 2397.5

<u>Formation</u>	<u>Depth</u>	<u>Subsea</u>
Wabamun	1691'	+ 707'
Hay River Shale	2553'	- 155'
Beaverhill Lake Shale	4301'	-1903'
Slave Point	4618'	-2220'
Fort Vermillion Member	4766'	-2368'
Watt Mountain	4680'	-2382'
Sulphur Point	4794'	-2396'
Muskeg	4870'	-2472'
Keg River Platform	5174'	-2776'
Chinchaga	5432'	-3034'
Red Beds	5494'	-3096'
Granite Wash	5581'	-3183'
Granite	5623'	-3225'
Total Depth	5651'	-3253'

MIAMI AMOCO KAKISA RIVER I-52

SAMPLE TOPS

K.B. Elevation: 2379.5

<u>Formation</u>	<u>Depth</u>	<u>Subsea</u>
Wabamun	1680'	+ 718'
Hay River Shale	2550'	- 152'
Beaverhill Lake Shale	4300'	-1902'
Slave Point	4620'	-2222'
Fort Vermillion Member	4766'	-2368'
Watt Mountain	4795'	-2397'
Sulphur Point	4805'	-2407'
Muskeg	4876'	-2478'
Keg River Platform	5215'	-2817'
Chinchaga	5436'	-3038'
Red Beds	5533'	-3135'
Granite Wash	5581'	-3183'
Basement	5610'	-3212'

MIAMI AMOCO KAKISA RIVER I-52

CORED INTERVALS

There were no cores cut on Miami Amoco Kakisa River I-52.

SAMPLE DESCRIPTION

The sample description for Miami Amoco Kakisa River I-52 is enclosed in the pocket at the end of this report.

MIAMI AMOCO KAKISA RIVER I-52

WELL HISTORY REPORT

SECTION III - ENGINEERING SUMMARY

LYNES UNITED SERVICES LTD.

TEST DATA				GENERAL INFORMATION	
Test No.	1		Lynes Test	1	
Formation	Keg River		T.D.	5651	
Interval Tested	5180	Fl. to	5290	Company	Miami Oil Producers Inc.
Interval Tested	110	Fl.	Net Pay Tested	Address	c/o Helton Engineering Ltd.
Type of Test	Dual Conventional Straddle				
Pushion	Amount		Fr.	Well Name	Miami Amoco Kakisa River
Started in Hole at	4:30	Hrs.	Tool Open at	9:35	Hrs.
Pre-Flow	3	Mins.	Initial Shut-in	30	Mins.
2nd Flow		Mins.	Second Shut-in		Mins.
Final Flow	30	Mins.	Final Shut-in	60	Mins.
Remarks:					
Blow: Weak air blow on preflow. Weak blow on valve open dead in 55 mins.					
GAS BLOW MEASUREMENTS					
Measured with					
MUD AND HOLE DATA					
Mud Type Gel Chem					
Weight 9.8 Viscosity 55 Water Loss 9.8					
Filter Cake 2/32 Bottom Hole Temperature					
Drill Pipe Size 4" (3 1/2 IF) Weight 13.30					
Drill Collars 6 3/4 I.D. 2 7/8 Feet Run 258					
Main Hole or Casing Size 8 1/2					
Pothole or Liner Size No. of Feet					
Bottom Hole Choke Size 5/8					
Surface Choke Size 1"					
Packer Rubber Size 7 1/2					
REMARKS					
Shut-in pressures suggest relatively high permeability within the interval tested.					
RECOVERY					
TOTAL FLUID RECOVERED 3252 Ft. Consisting of:					
3252 Ft. of Black muddy water & water					
Ft. of					
Ft. of					
Ft. of					
Test was/was not Reverse Circulated was not					
Oil Recovery A.P.I. Water Specific Gravity					
Salinity 109,600 PPM					
PRESSURE READINGS					
Inside X Outside		Inside Outside X		Inside Outside X	
Recorder No. 8855		Recorder No. 2816		Recorder No. 2080	
Capacity 4300		Capacity 4600		Capacity 4100	
Depth 5162		Depth 5326		Depth 5196	
NUMBER KEY:					
1 - INITIAL HYDROSTATIC		2560		2553	
2 - PRE-FLOW		380		778	
3 - INITIAL SHUT-IN		1657		1646	
4a - 2nd INITIAL FLOW					
4b - 2nd FINAL FLOW		Below			
4c - 2nd SHUT-IN		Straddle			
5 - 3rd INITIAL FLOW		447		781	
6 - FINAL FLOW		1578		1585	
7 - FINAL SHUT-IN		1657		1657	
8 - FINAL HYDROSTATIC		2558		2530	

Miami Oil Producers Inc.

Miami Amoco Kakisa River I-52

1

February 25, 1974

LYNES UNITED SERVICES LTD.

WELL NAME - MIAMI AMOCO KAKISARIVER

LOCATION - I-52

DST NUMBER - 1

INTERVAL TESTED - 5180 TO 5290

RECORDER NO. - 2080

DEPTH - 5196

INITIAL SHUT IN PRESSURE

TIME(MIN) ϕ	$\frac{T + \phi}{\phi}$	PSIG
0	0.0000	778
3	2.0000	1626
6	1.5000	1630
9	1.3333	1633
12	1.2500	1637
15	1.2000	1639
18	1.1667	1641
21	1.1429	1642
24	1.1250	1644
27	1.1111	1645
30	1.1000	1646

EXTRAPOLATION OF INITIAL SHUT-IN = 1653.28

LYNES UNITED SERVICES LTD.

WELL NAME - MIAMI AMOCO KAKISARIVER

LOCATION - I-52

DST NUMBER - 1

INTERVAL TESTED - 5180 TO 5290

RECORDER NO. - 2080

DEPTH - 5196

SECOND SHUT IN PRESSURE

TIME(MIN) ϕ	$\frac{T + \phi}{\phi}$	PSIG
0	0.0000	1585
5	7.6000	1621
10	4.3000	1629
15	3.2000	1637
20	2.6500	1641
25	2.3200	1645
30	2.1000	1649
35	1.9429	1652
40	1.8250	1653
45	1.7333	1655
50	1.6600	1656
55	1.6000	1657
60	1.5500	1657

EQU. FITTED LINE IS $\log((T_0 + \phi)/\phi) = -0.01641 \text{ PSIG} + 27.38292$

EXTRAPOLATION OF SECOND SHUT-IN = 1668.60 M= 60.94


LYNES UNITED SERVICES LTD.

DST NO. 1

REC. NO. 2080

DEPTH 5196

$$\frac{T0+\phi}{\phi}$$



PRESSURE EXTRAPOLATION PLOT

MIAMI AMOCO KAKISA RIVER

1 52 8855-1

⑧

①

⑦

③

⑥

⑤

②


⑧

BELOW STRADDLE

MIAMI AMALO KAKISA RIVER

I-52

2080-1



MIAMI AMOCO KAKISA RIVER I-52

CASING SUMMARY

Surface Casing: Ran 16 joints (total of 659.65')
of 9-5/8", 32.3#, H-40 casing.
Landed at 635' K.B. Cemented with
500 sacks cement plus 2% CaCl_2 plus
25# gel flake. Plug down at 5:00 a.m.,
February 4, 1974 with fair returns.

Recemented outside top of casing
with 90 sacks of Portland cement
plus 3% CaCl_2 .

MIAMI AMOCO KAKISA RIVER I-52

MUD REPORT

<u>TYPE</u>	<u>UNIT</u>	<u>AMOUNT</u>
Acegel	100#	511 sacks
Caustic Soda	50#	25 sacks
Lime	50#	10 sacks
Sawdust	50#	113 sacks
Bicarbonate of Soda	100#	1 sack
Ace Bar Sparton	100#	80 sacks
Soda Ash	100#	35 sacks
Petro Lig	50#	1 sack
Kwik Seal	50#	8 sacks
CMC LoVis	50#	25 sacks
Benex	50#	75 sacks
Ace Tan	50#	10 sacks
Barium Carbonate	100#	10 sacks

MIAMI AMOCO KAKISA RIVER I-52

DEVIATION RECORD

<u>Depth Feet</u>	<u>Deviation Degrees</u>	<u>Change Degrees</u>	<u>Interval Feet</u>	<u>Hole Size Inches</u>
135	1-1/16	0	135	13-3/4
164	1	1/16	29	13-3/4
191	1/2	1/2	27	13-3/4
248	1/2	0	57	13-3/4
335	1/2	0	87	13-3/4
394	5/8	1/8	59	13-3/4
480	1/2	1/8	86	13-3/4
570	5/8	1/8	90	13-3/4
640	7/8	1/4	70	13-1/2
1200	1/4	3/8	560	8-3/4
1700	1/2	1/4	500	8-3/4
2025	1/2	0	325	8-3/4
2500	1/2	0	475	8-3/4
2731	1/2	0	231	8-3/4
3230	0	1/2	499	8-3/4
3480	1/2	1/2	250	8-3/4
3972	1	1/2	492	8-3/4
4161	1-1/4	1/4	189	8-3/4
4351	3	1-3/4	190	8-3/4
4414	3	0	63	8-3/4
4500	2-1/2	1/2	86	8-3/4
4601	3	1/2	101	8-3/4
4665	2-1/2	1/2	64	8-3/4
4760	Misrun			
4885	2-3/4	1/4	220	8-3/4
5230	1-3/4	1	345	8-3/4
5651	1	3/4	421	8-3/4

MIAMI AMOCO KAKISA RIVER I-52

BIT RECORD

Bit No.	Depth		Size	Make and Type	Hours Run	Footage
	From	To				
1A	0	598	13-3/4"	Hughes Western OSC3	50	598
2A	598	640	13-1/2"	Reed YHT	2	42
1	640	2026	8-3/4"	Hughes Western X1G	26-3/4	1386
2	2026	2731	8-3/4"	Hughes Western X1G	24½	705
3	2731	3482	8-3/4"	Hughes Western X1G	30½	751
4	3482	4500	8-3/4"	Hughes Western J33	83½	1019
5	4500	5238	8-3/4"	Smith F4	60-3/4	738
6	5238	5651	8-3/4"	Security	40½	413

MIAMI AMOCO KAKISA RIVER I-52

ABANDONMENT PLUGS

- Plug #1: 5651' - 5460' Cemented with 90 sacks of neat construction cement. Plug down at 9:20 a.m., February 26, 1974.
- Plug #2: 5360' - 5150' Cemented with 100 sacks of construction cement plus 2% CaCl_2 . Plug down at 10:00 a.m., February 26, 1974. Felt plug #2 at 5142' at 5:15 p.m.
- Plug #3: 660' - 610' Cemented with 65 sacks of construction cement plus 3% CaCl_2 . Plug down at 11:50 p.m., February 26, 1974. Felt plug #3 at 598' at 7:00 a.m., February 27, 1974.

MIAMI AMOCO KAKISA RIVER I-52

WELL HISTORY REPORT

SECTION IV - LOGS

MIAMI AMOCO KAKISA RIVER I-52

LOGS

<u>Date Run</u>	<u>Interval</u>	<u>Type of Log</u>
February 23, 1974	638' - 5645'	Dual Induction- Laterolog
February 23, 1974	638' - 5641'	Borehole Compensated Sonic Log
February 23, 1974	4250' - 5636'	Compensated Neutron- Formation Density

A final print of each log is enclosed in the pocket at the end of this report.

WESTBURNE

WARDEN DRILLING COMPANY LIMITED

DAILY DRILLING LOG

DIRECTIONS TO

WELL

RIG NO. 19

LOCATION

Miami, Amoco KAKISAR 152

SEC.

TWP.

RGC.

W.

DATE

FEB 28

1974

54 mi. NW STEEN RIVER

MAILING

POINT STEEN RIVER

SHIPPING

POINT STEEN RIVER

MILES

MOVED 270

ROAD

CONDITIONS Rough

DAYS FROM

SPUD

TOUR MIDNIGHT TO 8 AM TO 4 PM TO MIDNIGHT

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly			
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
MUD	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change		
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1 188	250		
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2 188	250		
GEL						LINE SIZE					LINE SIZE				3 888	1000		
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4 888	250				5 178	250		
ADDITIVES:	GENERAL:																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool					
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly			
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
MUD	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change		
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1			
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2			
GEL						LINE SIZE					LINE SIZE				3			
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4					5			
ADDITIVES:	GENERAL:																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool					
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly			
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
MUD	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change		
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1			
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2			
GEL						LINE SIZE					LINE SIZE				3			
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4					5			
ADDITIVES:	GENERAL:																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool					

REMARKS		TIME	
START	STOP	INTVL	
WASH FLOOR & MATTING			B 00
CHANGE CLUTCH ON PUMP K500A			
GENERAL RIGGING OUT			4 00
FIRES			
DRILLER'S SIGNATURE			
TAKE DOWN PREFABS			8 00
LAY DOWN BOP'S			
RIG OUT			
LAY DOWN DERRICK			
DRESS DERRICK FOR			
MOVING TO NEXT			
LOCATION			4 00 8
FIRES			
DRILLER'S SIGNATURE			
Finish cleaning mud Tanks			8 00
General rigging out.			4 00 8
FIRES			
DRILLER'S SIGNATURE			
FIRES			
DRILLER'S SIGNATURE			

B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	1570 gals.	CASING REPORT	RAN	ITS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #
Hydril					Rig Savers Chk'd.	Fuel Rec'd Today (and)							
Pipe Rams.					Kelly Cock Chk'd.	TOTAL							
Blind Rams.						Fuel on Hand 11.59 p.m. (deduct)							
TOTCO RING ON BIT #					Boiler Operated: 18 Hrs.	FIRE EQUIP. Chk'd.							
						FUEL USED							
						CEMENT RETURNS - (YES/NO)							
						EQUIPMENT CHANGES							
						TOTAL COMPANY TIME - HRS.							
						TOTAL CONTRACTOR'S TIME - HRS.							
						Approved by Operator							
						Approved by Representative							
						Approved by Toolpusher							

CONSERVATION BOARD COPY

W 6392

JESTBURNIE

WARDEN DRILLING COMPANY LIMITED

DAILY DRILLING LOG

DIRECTIONS TO WELL 5.4 mi. NW STEEN RIVER

RIG NO. 19 LOCATION Miami Amoco Kakisar 1-52 LSD. SEC. TWP. RGE. W. DATE FEB 27 1974

MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER

MILES MOVED 270

ROAD CONDITIONS

DAYS FROM SPUD 24

TOUR MIDNIGHT TO 8 AM TOUR 8 AM TO 4 PM TOUR 4 PM TO MIDNIGHT

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	
1	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1	250
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2	250
GEL					LINER SIZE					LINER SIZE					3	1000
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4	250	Weather		Water	Temp.	Bbls.
ADDITIVES: GENERAL:																
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool			
1	W.R. CHZ	1-860	8			16074				18392		15792	220			

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly		
1	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change	
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1	172	250
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2	172	250
GEL					LINER SIZE					LINER SIZE					3	872	1000
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4	872	250	Weather		Water	Temp.	Bbls.
ADDITIVES: GENERAL:																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1	W.R. CHZ	1-860	8			16074				18392		15792	220				

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly		
1	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change	
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1	180	250
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2	180	250
GEL					LINER SIZE					LINER SIZE					3	880	1000
W.L.	F.C.	pH.	DESILTER: Hours Op.	U. Flow:	O. Flow:	SURVEYS		At Feet	Degrees	4	880	250	Weather		Water	Temp.	Bbls.
ADDITIVES: GENERAL:																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1	W.R. CHZ	1-860	8			16074				18392		15792	220				

REMARKS	START	STOP	INTVL
W.O.P. Pull to stds circulate hole.	12	12:30	1/2
Wash down Matting + BOPs	12:30		
Remove Bop lines + Bop Valves			
START CLEANING Mud Tank			
Run Two stds in + tag Plug +	7:00	7:00	6 1/2
Lay down Pipe			8:00
Fuel for plug #3 launch top @ 598' had all O.P. @ 7:00 AM 2/27/74			
M. Surais			
DRILLER'S SIGNATURE			
WASH DOWN RIG FLOOR + BOPs	8:00		
TAKE VALVES OFF BOPs			
PULL MOUSE HOLE			4:00
Rig released @ 2:00 PM 2/27/74			
JP			
C. Durand			
DRILLER'S SIGNATURE			
clean muds tanks.	12:00 noon		
Change heads + liners in pump			
Lay down Kelly			
Wash matting			
Restack + cement mud			
finish taking off valves + B.O.A. bolts.			10:00
FIRES N:1			
JP Buell			
DRILLER'S SIGNATURE			

B.O.P.	Tested	Elapsed Time	Pres. sure	Packing & Seal Inspected Date	Crown-o-matic Chk'd.	Fuel on Hand 12.01 a.m.	506 gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #
Hydril					Rig Savers Chk'd.	Fuel Rec'd Today (add)	1305 gals.	TO	KB. USED	SAX	CEM		
Pipe Rams.					Kelly Cock Chk'd.	TOTAL	1711 gals.	PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD:	
Blind Rams.					Fire Equip. Chk'd.	Fuel on Hand 11.59 p.m. (deduct)	1570 gals.	CEMENT RETURNS - (YES/NO)					
TOTCO RING ON BIT #					Boiler Operated: 24 Hrs.	FUEL USED	241 gals.	EQUIPMENT CHANGES					
APPROVED BY OPERATOR REPRESENTATIVE													
APPROVED BY TOOLPUSHER													

CONSERVATION BOARD COPY

W 6391

WESTBURN

WARDEN DRILLING COMPANY LIMITED

DAILY DRILLING LOG
DIRECTIONS TO WELL

RIG NO. 19

LOCATION

Miami Amoco KAKISAA 1-52

L.S.D.

SEC.

TWP.

RGE.

W.

DATE FEB. 26

1974

54 miles NW STEEN RIVER

MAILING POINT STEEN RIVER

SHIPPING POINT STEEN RIVER

MILES MOVED 270

ROAD CONDITIONS Rough & Snow

DAYS FROM SPUD 5

TOUR MIDNIGHT TO 8 AM
TOUR 8 AM TO 4 PM
TOUR 4 PM TO MIDNIGHT

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. on Kelly		
5651				5cm 69	2										24		
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
OPEN END																	
MUD	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change	
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				148	250	
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2148	250	
GEL						LINEAR SIZE					LINEAR SIZE				3848	1000	
W.L.	F.C.	pH	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		498	250	
ADDITIVES: GENERAL: 5138 250																	
Weather Windy Temp. - 28°																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1" Weight	1-960	8	5	75	160	74	65	65	15292	2-17-74	15192	220					
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly		
MUD 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. MOTOR HOURS																	
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1		
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2		
GEL						LINEAR SIZE					LINEAR SIZE				3		
W.L.	F.C.	pH	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4		
ADDITIVES: GENERAL: Ran plug #1, 5651-5460 by Howe																	
w/ 90 say class & cement plug 2 1/2 placed @ 9:30 AM 2/26/74																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. MOTOR HOURS																	
WEIGHT					No. 1	PRES. SURE				No. 2	PRES. SURE				1		
VISCOSITY					MODEL	S.P.M.				MODEL	S.P.M.				2		
GEL						LINEAR SIZE					LINEAR SIZE				3		
W.L.	F.C.	pH	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4		
ADDITIVES: GENERAL: Ran plug #3 by Howe w/ 65 say class & cement w/ 2% sand 2 added plug displaced 11:50 PM, 2/26/74																	
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				

REMARKS		TIME		
		START	STOP	INTVL
Finish loading out TESTER		12:00	12:30	1/2
Rig Up to Lay down Collars		12:30		
+ Lay down SAME			2:30	2
CLEAN up FLOOR + Run in		2:30		
Hole OPEN END. #			7:30	5
TAD Bottom 24' in on Kelly				
Circ. & W.O. Howe		7:30	8:00	1/2
FIRES M. Hovais: DRILLER'S SIGNATURE				
THAW MUD LINES, RIG UP TO RUN		8		
PLUG RAN PLUG #1 + "2 W.O.C.			10:00	2
PULL 8 STDS WET W.O.C.		10:00		
ROLL DC. ON MAKE ROOM FOR		11		
D.P.			12	1
CLEAN ICE OFF MATTING		12	2	2
THAW OUT MUD ROLLS		2	4	2
Ran plug #2. 5360-5150 by Howe w/ 100 say class				
A cement w/ 2% sand 2 added plug in place @ 10:00				
FIRES DRILLER'S SIGNATURE				
THAW out mud rolls		4	5	1
Feel for plug #2		5	5:30	1/2
Laid down D.P.		5:30	11:00	5 1/2
Rig & run plug #3 & RUN		11:00	12	1
660-610				
Feel for plug # to @ 5:00 PM to top				
to 5142 w/ 5000 lbs				
FIRES N.1 H. Buehler: DRILLER'S SIGNATURE				

B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-o-matic Chk'd.	Fuel on Hand 12.01 a.m.	1101	gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #
Hydri					Rig Savers Chk'd.	Fuel Rec'd Today (add)		gals.	TO	KB. USED	SAX	CEM		
Pipe Rams.					Kelly Cock Chk'd.	TOTAL		gals.	PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD:	TOTAL COMPANY TIME HRS.
Blind Rams.						Fuel on Hand 11.59 p.m. (deduct)		gals.	CEMENT RETURNS - (YES/NO)					Approved by Operator's Representative
TOTCO RING ON BIT		Boiler Operated: 24	Hrs.		Fire Equip. Chk'd.	FUEL USED		gals.	EQUIPMENT CHANGES					Approved by Toolpusher

CONSERVATION BOARD COPY

W 6390

W 6389

WEST BURN

WIDEAN-DRILLING COMPANY LIMITED

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19

LOCATION: Miami Amoco

Block 109

KAKISAR 1-52

LSD. SEC. TWP. RGE. W.

DATE FEB 24

74

MAILING POINT: STEEN RIVER

SHIPPING POINT: STEEN RIVER

MILES MOVED 270

ROAD CONDITIONS Rough

DAYS FROM SPUD 23

From		Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS			TIME		
No.		Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INTVL	
5651																			Finish lay Down COLLAR	12 ⁰⁰	3 ³⁰	3 1/2
																			Trip in w/PIPE OPEN END	3 ³⁰		
																			pick up pipe to replace		8 ⁰⁰	4 1/2
MUD		12 mn.	2 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.	2 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS		Next Oil Change		
WEIGHT						No. 1	PRES. SURE				No. 2	PRES. SURE						1	800	250		
VISCOSITY						MODEL	S.P.M.				MODEL	S.P.M.						2	100	250		
GEL						MODEL	LINER SIZE				MODEL	LINER SIZE						3	800	1000		
W.L.		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	800	250		
ADDITIVES:		GENERAL:																5	900	250		
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool									
1" WRIGHT		1-960	9				15772	65	65	15292	2-17-74	15792	220									
From		Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly						
@ 5651						54	59	2														
MUD		8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP		8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP		8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS		Next Oil Change		
WEIGHT		9.6				No. 1	PRES. SURE				No. 2	PRES. SURE						1	108	250		
VISCOSITY		12				MODEL	S.P.M.				MODEL	S.P.M.						2	108	250		
GEL						MODEL	LINER SIZE				MODEL	LINER SIZE						3	808	1000		
W.L.		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	808	250		
ADDITIVES:		GENERAL:																5	98	250		
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool									
1" WRIGHT		1-960	8				15774	65	65	15292	2-17-74	15792	320									
From		Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly						
@ 5651						59	2	9	63 1/4													
MUD		4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP		4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP		4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS		Next Oil Change		
WEIGHT						No. 1	PRES. SURE				No. 2	PRES. SURE						1	116	250		
VISCOSITY						MODEL	S.P.M.				MODEL	S.P.M.						2	116	250		
GEL						MODEL	LINER SIZE				MODEL	LINER SIZE						3	806	1000		
W.L.		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	816	250		
ADDITIVES:		GENERAL:																5	106	250		
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool									
1" WRIGHT		1-960	9	1/2			75	15547	65	65	15292	2-17-74	15792	220								
From		Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly						
@ 5651																						
B.O.P.		Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-o-matic Chk'd.	Fuel on Hand 12.01 a.m.	18 98	gals.	CASING REPORT		RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND		TRANSFER #					
Hydri		✓				Rig Savers Chk'd.	Fuel Rec'd Today (add)		gals.													
Pipe Rams.		✓				Kelly Cock Chk'd.	TOTAL		gals.			TO	KB. USED	SAX	CEM							
Blind Rams.		✓					Fuel on Hand 11.59 p.m. (deduct)	1570	gals.			PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD: 23						
TOTCO RING ON BIT			Boiler Operated: 24	Hrs.	Fire Equip. Chk'd.		FUEL USED	328	gals.	CEMENT RETURNS (YES/NO)		EQUIPMENT CHANGES										
																		TOTAL COMPANY TIME		TOTAL CONTRACTOR'S TIME		
																		Approved by Operator's Representative		Approved by Toolpusher		

CONSERVATION BOARD COPY

W 6388

From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS			TIME				
No.		Size		Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INTVL			
5651						88	53													Blow Kelly & Trip 186th.			1200		
																				Dumpy Trip			300	3	
																				Circ. & Condition Mud			300	530	2 1/2
																				DROPPED SURVEY			530	545	1/4
																				Blow Kelly & BREAK Kelly hose off & Hosit to Log			545	800	2 1/4
M.U.D.		12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change								
WEIGHT						No. 1					No. 2					1 76		250							
VISCOSITY						MODEL					MODEL					2 76		250							
GEL						LINE SIZE					LINE SIZE					3 776		1000							
W.L.		9.6 F.C. 2/22 pH 9.5				DESILTER: Hours Op:				U. Flow:				O. Flow:				SURVEYS							
ADDITIVES:		GEL - 1500 #				GENERAL:								At Feet				Degrees							
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool											
5651		1" WRIGHT	1-960	8	1/2	104	15672	65	65	15792	2-17-74	15792	220												
																				FINIS TRIP OUT TO LOG			8.00	10.30	2 1/2
																				RIG TO LOG & LOG			10.30	4.00	5 1/2
M.U.D.		8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change								
WEIGHT						No. 1					No. 2					1 84		250							
VISCOSITY		2099119				MODEL	Logging				MODEL					2 84		250							
GEL						LINE SIZE					LINE SIZE					3 784		1000							
W.L.		F.C.				pH.				DESILTER: Hours Op:				U. Flow:				O. Flow:				SURVEYS			
ADDITIVES:						GENERAL:								At Feet				Degrees							
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool											
5651		1" WRIGHT	1-960	8	1/2	104	15672	65	65	15792	2-17-74	15792	220												
																				Disiliter shut off & disconnected also shock sub. <i>[Signature]</i>					
M.U.D.		4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change								
WEIGHT						No. 1					No. 2					1 92		250							
VISCOSITY						MODEL					MODEL					2 92		250							
GEL						LINE SIZE					LINE SIZE					3 792		1000							
W.L.		F.C.				pH.				DESILTER: Hours Op:				U. Flow:				O. Flow:				SURVEYS			
ADDITIVES:						GENERAL:				1/2 gal. 2-17-74				At Feet				Degrees							
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool											
5651		1" WRIGHT	1-960	8	1/2	104	15672	65	65	15792	2-17-74	15792	220												
																				LOGGING			4.00	8.30	4 1/2
																				TEAR out Logging Equipment			9.30	9.00	1/2
																				Run in w/ Drill Collars & Lay down 3-4 3/4" 3-6 1/4"			9.00		
																				3-6 3/4" B.C. S.V. 635-5651			1200	3	
																				245" D.L.L. 635-5651, 3" & 5" CNFD & FDL 4180-5651 both 5" scale by Seltumberger.					
M.U.D.		4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change								
WEIGHT						No. 1					No. 2					1 92		250							
VISCOSITY						MODEL					MODEL					2 92		250							
GEL						LINE SIZE					LINE SIZE					3 792		1000							
W.L.		F.C.				pH.				DESILTER: Hours Op:				U. Flow:				O. Flow:				SURVEYS			
ADDITIVES:						GENERAL:				1/2 gal. 2-17-74				At Feet				Degrees							
Drilling Line Record		Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool											
5651		1" WRIGHT	1-960	8	1/2	104	15672	65	65	15792	2-17-74	15792	220												
																				FIRE					
																				M. Germain					
B.O.P.		Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crownomatic Chk'd.	Fuel on Hand 12.01 a.m.	2349 gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #											
Hydril		✓				Rig Savers Chk'd.	Fuel Rec'd Today (add)	1898 gals.																	
Pipe Rams.		✓				Kelly Cock Chk'd.	TOTAL																		
Blind Rams.						Fuel on Hand 11.59 p.m. (deduct)																			
TOTCO RING ON BIT #		6	Boiler Operated:	24 Hrs.	Fire Equip. Chk'd.	FUEL USED	451 gals.	CEMENT RETURNS - (YES/NO)					EQUIPMENT CHANGES												
													SAMPLE BOY NOT IN USE FROM 1201 AM Feb 23/74												

WESTBURN
WARREN DRILLING COMPANY LIMITED
DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MARIAMPOKA KAKISAR 1-52 L50 SEC. TWP. RGE. W. DATE FEB 22 74
54 mi. NW STAN RIVER MAILING POINT STAN RIVER SHIPPING POINT STAN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 21

TOUR MINIGHT TO 8 AM TOUR															8 AM TO 4 PM TOUR															4 PM TO MIDNIGHT														
From 5440 To 665506 7 3/4 Hrs. on Bottom 90 51 1 DRILL COLLARS 13 3 1/4 609.03															REMARKS															TIME														
																														START STOP INTVL														
B No. 6 Size 8 3/4 Type M88 Jets/W.C. 1/2 3/4 Serial No. 460624 Wgt. 40 R.P.M. 50 Drilled or Cored 268 Hrs. 26 1/4 Reamed 1100 Pump No. 1100 Pump Pressure 60 S.P.M. 60 Table Torque T. B. G.															Rig Service DRLG 8 3/4 Hole															12:00 12:15 1/4 12:15 8 73/4														
M.U.D. 12 m. 2 a.m. 4 a.m. 6 a.m. PUMP 12 m. 2 a.m. 4 a.m. 6 a.m. PUMP 12 m. 2 a.m. 4 a.m. 6 a.m. MOTOR HOURS																																												
WEIGHT 9.5 9.5 9.5 9.5 No. 1 1100 1100 1100 1100 No. 2 1100 1100 1100 1100																																												
VISCOSITY 36 38 43 39 No. 1 60 60 60 60 No. 2 60 60 60 60																																												
GEL 1500 5 1/2 x 15 1500 5 1/2 x 15 1500 5 1/2 x 15 1500 5 1/2 x 15																																												
W.L. 10 F.C. 3/32 pH 9.5 DESILTER: Hours Op: 8 U. Flow: 10.1 O. Flow: 9.4 SURVEYS																																												
ADDITIVES: 100 CAUSTIC SODA GENERAL: DUMP TANK: SORBELS																																												
1000# GEL 100# BARIUM CARBONATE 1" STREAM WATER																																												
400# SODA ASH 50# FELTEX 1# BENEX LOCAL D.F. 50 CMC																																												
Drilling Line Record 1" WRIGHT 1-960 8 15568 65 65 15292 2-17-74 15792 220																																												
From 50690 To 55867 3/4 Hrs. on Bottom 88 52 1 DRILL COLLARS 13 3 1/4 609.03															FIRE nil															B. Huber DRILLER'S SIGNATURE 8														
B No. 6 Size 8 3/4 Type M88 Jets/W.C. 1/2 3/4 Serial No. 460624 Wgt. 20-40 46-60 354 34															DRLG 8 3/4 Hole															8:00 9:15 1 1/4														
															Rig Serv. & V Bops															9:15 9:30 1/4														
															DRLG 8 3/4 Hole															9:30 4:00 6 1/2														
M.U.D. 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. MOTOR HOURS																																												
WEIGHT 9.5 9.5 9.5 9.5 No. 1 1100 1100 1100 1100 No. 2 1100 1100 1100 1100																																												
VISCOSITY 39 40 42 48 No. 1 60 60 60 60 No. 2 60 60 60 60																																												
GEL 1500 5 1/2 x 15 1500 5 1/2 x 15 1500 5 1/2 x 15 1500 5 1/2 x 15																																												
W.L. 12.2 F.C. 3/32 pH 9.0 DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS																																												
ADDITIVES: GE 1-3000# GENERAL: DAKOLITE-50#																																												
Soda Ash-100# Caustic-100# CMC-100#																																												
Drilling Line Record 1" WRIGHT 1-960 8 15568 65 65 15292 2-17-74 15792 220																																												
From 5586 To 55651 6 1/4 Hrs. on Bottom 88 53 DRILL COLLARS 13 3 1/4 2 1/2 609.03															FIRE															M. S. Lewis DRILLER'S SIGNATURE														
B No. 6 Size 8 3/4 Type M88 Jets/W.C. 1/2 3/4 Serial No. 460624 Wgt. 30 50 413 40 1/2															DRILL 8 3/4 HOLE															4:00 5:45 1 1/4														
															RIG SERVICE															5:45 6:00 1/4														
															DRILL 8 3/4 HOLE															6:00 10:30 4 1/2														
															CIRC COND. HOLE															10:30 12 1 1/2														
M.U.D. 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. MOTOR HOURS																																												
WEIGHT 9.6 9.5 9.6 9.6 No. 1 1100 1100 1100 1200 No. 2 1100 1100 1100 1200																																												
VISCOSITY 54 56 55 54 No. 1 60 60 60 60 No. 2 60 60 60 60																																												
GEL 500 5 1/2 x 15 500 5 1/2 x 15 500 5 1/2 x 15 500 5 1/2 x 15																																												
W.L. 9.4 F.C. 3/32 pH 9.5 DESILTER: Hours Op: 8 U. Flow: 10.6 O. Flow: 9.4 SURVEYS																																												
ADDITIVES: Water 1" stream GENERAL: GEL = 1200 lbs Barium Carb = 90 lbs.																																												
Soda Ash = 100 C.M.C. = 50 lbs.																																												
Drilling Line Record 1" WRIGHT 1-960 8 15568 65 65 15292 2-17-74 15792 220																																												
B.O.P. Tested Elapsed Time Pressure Packing & Seal Inspected Date Crown-a-matic Chk'd.															FUEL ON HAND 12.01 a.m. 3089 gals.															CASING REPORT														
Hydril															Fuel Rec'd Today (add) 7349 gals.															RAN														
Pipe Rams.															TOTAL 740 gals.															JTS														
Blind Rams.															Fuel on Hand 11.59 p.m. (deduct) gals.															CSG														
TOTCO RING ON BIT # 6 Boiler Operated: 24 Hrs. Fire Equip. Chk'd.															FUEL USED 740 gals.															TO														
															CEMENT RETURNS - (YES/NO)															SAX														
															EQUIPMENT CHANGES															CEM														
															DAYS FROM SPUD: 21															PLUG DOWN														
															TOTAL COMPANY TIME															A.M. P.M.														
															HRS.															MRS.														
															Approved by Operator's Representative															TRANSFER #														
															Approved by Toolpusher																													

WESTBURN
 DEAN DRILLING COMPANY LIMITED
 DAILY DRILLING LOG
 DIRECTIONS TO WELL

HIG NO 19 LOCATION MIAMI AREA, KAKISAR, 1-52 LSD. SEC. TWP. RGE. W. DATE FEB 21 1974
 MAILING POINT STERN RIVER SHIPPING POINT STERN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 20

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME	START	STOP	INTVL													
5238	5275	3	80m	119				13	6.71	2.78	609.03					HOIST BIT #5	12:00	1:00	1														
5	8 3/4	F4	42 3/4	RF525		738	64 3/4		1	1000	60		34	1	1	REGULAR SURVEY BBL + MARK UP B. #6	1:00	1:15	1/4														
6	8 3/4	M88	42 3/4	460624	20m	50		3								RIG SERVICE CHECK BLOW DOWNS	1:15	1:30	1/4														
MUD																12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change		
WEIGHT																9.6	9.7	9.6	9.7	No. 1	1000	1000	1100	1100	No. 2	1000	1000	1100	1100	1	28	250	
VISCOSITY																39	38	39	40	MODEL	60	60	60	60	MODEL	60	60	60	60	2	28	250	
GEL																													3	628	1000		
W.L.																9.8	F.C.	3/32	pH.	9.5	DESILTER: Hours Op.	8	U. Flow:	10.2	O. Flow:	9.4	SURVEYS	At Feet	Degrees	4	728	250	
ADDITIVES:																														5	18	250	
GENERAL:																																	
Drilling Line Record																1"	WRIGHT	1-960	8	72	15568	65	65	15292	2-17-74	15792	220	FIRE	nil	DRILLER'S SIGNATURE			8
5275	85	5360	8	80m	50			13	6.71	2.78	609.03					DRILL 8 3/4" HOLE	8:00	4:00	8														
6	8 3/4	M88	42 3/4	460624	20-40	50	122	11				1	1100	60																			
MUD																8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change		
WEIGHT																9.6	9.7	9.6	9.7	No. 1	1000	1000	1100	1100	No. 2	1000	1000	1100	1100	1	36	250	
VISCOSITY																39	38	39	40	MODEL	60	60	60	60	MODEL	60	60	60	60	2	36	250	
GEL																														3	636	1000	
W.L.																9.8	F.C.	3/32	pH.	9.5	DESILTER: Hours Op.	8	U. Flow:	10.2	O. Flow:	9.4	SURVEYS	At Feet	Degrees	4	736	250	
ADDITIVES:																														5	26	250	
GENERAL:																																	
Drilling Line Record																1"	WRIGHT	1-960	8	72	15568	65	65	15292	2-17-74	15792	220	FIRE	nil	DRILLER'S SIGNATURE			8
5360	80	5440	7 1/2	90	50	2		15	6.71	2.78	609.03					DRILL 8 3/4 HOLE	4:00	6:30	2 1/2														
6	8 3/4	M88	42 3/4	460624	30-40	50	202	18 1/2				1	1100	60																			
MUD																4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change		
WEIGHT																9.6	9.6	9.5	9.5	No. 1	1100	1100	1100	1100	No. 2	1100	1100	1100	1100	1	44	250	
VISCOSITY																39	39	38	38	MODEL	60	60	60	60	MODEL	60	60	60	60	2	44	250	
GEL																														3	644	1000	
W.L.																9.8	F.C.	3/32	pH.	9.5	DESILTER: Hours Op.	8	U. Flow:	10.2	O. Flow:	9.4	SURVEYS	At Feet	Degrees	4	744	250	
ADDITIVES:																														5	34	250	
GENERAL:																																	
Drilling Line Record																1"	WRIGHT	1-960	8	72	15568	65	65	15292	2-17-74	15792	220	FIRE	nil	DRILLER'S SIGNATURE			8
B.O.P.																Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	3757	gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #				
Hvdrill																				Rig Savers Chk'd.	Fuel Rec'd Today (add)		gals.										
Pipe Rams.																				Kelly Cock Chk'd.	TOTAL		gals.	TO	KB. USED	SAX	CEM						
Blind Rams.																					Fuel on Hand 11.59 p.m. (deduct)	3089	gals.	PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD: 20	TOTAL COMPANY TIME	TOTAL CONTRACTOR'S TIME			
TOTCO RING ON BIT #																6	Boiler Operated: 24	Hrs.	Fire Equip. Chk'd.	FUEL USED	668	gals.	CEMENT RETURNS - (YES/NO)		EQUIPMENT CHANGES								
Approved by Operator's Representative																Approved by Toolpusher																	

CONSERVATION BOARD COPY

WESTBURN
WARDEAN DRILLING COMPANY LIMITED
DAILY DRILLING LOG
DIRECTIONS TO
WELL

BLOCK 109
RIG NO. 19 LOCATION MIAMI ARLAND KENISE A 1-52 LSD. SEC. TWP. RGE. W. DATE FEB 19 1974
MAILING POINT STERN RIVER SHIPPING POINT STERN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 18

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME
4760	85	4845	7 1/2	78	44	1	15	3	6 3/4	2 3/4	609.03						
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
5	8 3/4	F4	1/2 3/10	RF525	38-40	50	340	30			1	900	60				
M.U.D.	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change	
WEIGHT	9.8	9.7	9.7	9.8	No. 1	900	900	900	900	No. 2					1 700	500	
VISCOSITY	42	57	42	38	MODEL	59	60	59	60	MODEL					2 700	350	
GEL					5500	5 1/2	15								3 580	1000	
W.L.	9.5	F.C.	2 1/2	pH.	9.5	DESILTER: Hours Op.	8	U. Flow:		O. Flow:					4 680	350	
ADDITIVES:	600# SODA ASH	GENERAL:													5 718	350	
Drilling Line Record	1" WRIGHT	1-960	8												Temp.	107	110 Bbls.
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME
4845	80	4925	7 1/2	78	45	1	15	3	6 3/4	2 3/4	609.03						
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
5	8 3/4	F4	1/2 3/10	RF525	38-40	50	420	37 1/2			1	1000	60				
M.U.D.	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change	
WEIGHT	9.8	9.9			No. 1	1000	1000	1000	1000	No. 2					1 708	500	
VISCOSITY	38	37			MODEL	60	60	60	60	MODEL					2 708	350	
GEL															3 588	1000	
W.L.	10	F.C.	2	pH.	9.5	DESILTER: Hours Op.	8	U. Flow:		O. Flow:					4 688	350	
ADDITIVES:	Soda ash 600#	GENERAL:													5 726	350	
Drilling Line Record	1" WRIGHT	1-960	8												Temp.		Bbls.
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME
4925	86	5011	7 3/4	78	46		15	3	6 3/4	2 3/4	609.03						
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
5	8	F4	1/2 3/10	RF525	38-40	50	500	45			1	1100	60				
M.U.D.	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change	
WEIGHT	9.9	9.8	9.7	9.6	No. 1	1000	1000	1100	1100	No. 2					1 716	500	
VISCOSITY	Gelled			48	MODEL	60	60	60	60	MODEL					2 716	350	
GEL					500	5 1/2	15								3 596	1000	
W.L.	11.2	F.C.	4 3/2	pH.	9.0	DESILTER: Hours Op.	8	U. Flow:	10.2	O. Flow:	9.6				4 696	350	
ADDITIVES:	Water 1" stream	GENERAL:													5 734	350	
Drilling Line Record	1" WRIGHT	1-960	8												Temp.		Bbls.
B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	1954 gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #				
Hydri	✓				Rig Savers Chk'd.	Fuel Rec'd Today (add)		TO	KB. USED	SAX	CEM						
Pipe Rams.	✓				Kelly Cock Chk'd.	TOTAL		PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD: 18	TOTAL COMPANY TIME				
Blind Rams.					Fire Equip. Chk'd.	Fuel on Hand 11.59 p.m. (deduct)	1052 gals.	CEMENT RETURNS - (YES/NO)									
TOTCO RING ON BIT = 5	Boiler Operated: 24	Hrs.				FUEL USED	902 gals.	EQUIPMENT CHANGES									
APPROVED BY OPERATOR'S REPRESENTATIVE: [Signature]																	
APPROVED BY TOOLPUSHER: [Signature]																	

WESTBURN
WARDEAN DRILLING COMPANY LIMITED
DAILY DRILLING LOG
DIRECTIONS TO WELL

BLOCK 109
RIG NO 19 LOCATION MIAMI HENRICH 1-52 LSD SEC TWP RGE W DATE FEB 17 1974
MAILING POINT STERN RIVER SHIPPING POINT STERN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 16

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	
44146	54	4500	3 3/4	724	40	2	15	3	6 3/4	2 3/4	609.03				8	
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	
1	4	8 3/4	T33	1/2 3/4	46610	50	70	1019	33 1/4				520	60	1	
MUD	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	
WEIGHT	9.85	9.85			No. 1	850	850			No. 2					1 652	
VISCOSITY	38				MODEL	60	60			MODEL					2 652	
GEL	38				K59	5 1/2 x 15				MODEL					3 532	
W.L.	F.C.	pH.	DESILTER: Hours Op:	U. Flow:	O. Flow:	SURVEYS		At Feet		Degrees		Weather		Temp.		
ADDITIVES: GENERAL:																
Total casing to H.B. Hydril & pipe rammed up 1500 PSI for 15'																
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1	1/2	WRIG	1-960	8	1/2	93	15292	65	65	14789	1-24-74	15283	285			
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	
4500					40	2	15	3	6 3/4	2 3/4	609.03				8	
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	
1	5	8 3/4	F4	1/2 3/4	RF525											
MUD	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	
WEIGHT					No. 1					No. 2					1 660	
VISCOSITY					MODEL					MODEL					2 660	
GEL															3 540	
W.L.	F.C.	pH.	DESILTER: Hours Op:	U. Flow:	O. Flow:	SURVEYS		At Feet		Degrees		Weather		Temp.		
ADDITIVES: GENERAL:																
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1	1/2	WRIG	1-960	8	1/2	93	15292	65	65	14789	1-24-74	15283	285			
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	
4500					75	40	2	15	3	6 3/4	2 3/4	609.03			8	
B	No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	
1	5	8 3/4	F4	1/2 3/4	RF525											
MUD	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	
WEIGHT					No. 1					No. 2					1 668	
VISCOSITY					MODEL					MODEL					2 668	
GEL															3 548	
W.L.	F.C.	pH.	DESILTER: Hours Op:	U. Flow:	O. Flow:	SURVEYS		At Feet		Degrees		Weather		Temp.		
ADDITIVES: GENERAL:																
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				
1	1/2	WRIG	1-960	8	1/2	60	15352	65	65	15292	2-17-74	15292	285			

REMARKS	START	STOP	INTVL
DELEG 8 3/4 Hole	12 00	3 45	3 3/4
CIRCUMFERENCE SPOON	3 45	4 05	1/2
DRILL SURVEY Borehole & Holes	4 15	4 30	1/4
out w/ Bit #4 increased	4 30	8 00	3 3/4
FIRES			
Hosif Bit #4 & SLM out.	8 00	9 00	1
Pick Up 2 singles & Rig Up	9 00		
Csg. Testing Plug & Rig kill line to Csg. Bowl			
PRESSURE Up Hydril to 1600 # Held O.K.			
PRESSURE Up Pipe Rams to 1500 # Held O.K.			
Check Motor shut off			
Lay down Singles & Test Plug	3 30	6 00	1/2
Make Up Bit #5 Smith F4	3 30	4 00	1/2
FIRES			
RUN COLLARS IN	4 00	5 00	1
SLIP & CUT 65' O/LINE	5 00	6 00	1
RIG SERVICE	6 00	6 15	1/4
TRIP IN	6 15	8 00	1 3/4
HOOK UP HEATERS IN SUB	8 00	10 00	2
FINISH IN	10 00	11 00	1
CLEAN 80' TO BOTTOM	11 00	12 00	1
FIRES			

TOUR	MIDNIGHT TO 8 A.M.	8 A.M. TO 4 P.M.	4 P.M. TO MIDNIGHT	From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS			TIME												
				No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INT											
				4200	96	4296	8	71m	38	2		15	6 1/4	2 1/8	60903				23	DRILL 8 3/4" Hole			12 00	8 00	8										
B				71	8 3/4	T33	1/4 3/4	46610	20-30	70	815	144			1	850	60			12															
I																																			
T																																			
S																																			
				MUD				12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP				12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP				12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS				Next Oil Change			
				WEIGHT				9.9	9.15	9.8	9.9	No. 1	800	800	400	850	No. 2				1	622	500												
				VISCOSITY				36	37	37	36	MODEL	60	60	60		MODEL	S.P.M.		2	622	250													
				GEL								K509	5 1/2	X 15						3	588	1000													
				W.L.				9.4	F.C.	3.2	pH.	9.5	DESILTER: Hours Op:				8	U. Flow:				10.2	O. Flow:				9.8								
				ADDITIVES				6	LENER			GENERAL:				DUMP TANK - 60 BBLs																			
								1700 GEL																											
								11.5 M WATER																											
				Drilling Line Record				1"	WRIGHT	1-960	8					15200	65	65	14789	1-24-74	15283	285	FIRES			M. Huber			DRILLER'S SIGNATURE						
				From				Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	DRILL 8 3/4" Hole			8 00	12 45	4 3/4							
B				4296	110	4406	7 3/4	71m	39	2		15	6 1/4	2 1/8	60903				8	DRILL 8 3/4" Hole			8 00	12 45	4 3/4										
I				4	8 3/4	T33	1/4 3/4	46610	30	70	925	72			1	850	60					SURVEY @ 4351-30			12 45	1 00									
T																					DRILL 8 3/4" Hole			1 00	4 00	3									
S																																			
				MUD				8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP				8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP				8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS				Next Oil Change			
				WEIGHT				9.9	9.8	9.9	9.8	No. 1	800	850	450	850	No. 2				1	636	500												
				VISCOSITY				40	37	40	38	MODEL	60	60	60	60	MODEL	S.P.M.		2	636	250													
				GEL								K509	5 1/2	X 15						3	516	1000													
				W.L.				7.3	F.C.	3.2	pH.	9.5	DESILTER: Hours Op:					U. Flow:					O. Flow:												
				ADDITIVES				2	REFLEX			GENERAL:								4351 30															
								1700 GEL																											
								2 REFLEX																											
								1700 GEL																											
				Drilling Line Record				1"	WRIGHT	1-960	8					15200	65	65	14789	1-24-74	15283	285	FIRES			M. Huber			DRILLER'S SIGNATURE						
				From				Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	DRILL 8 3/4" Hole			4 00	4 30	1 1/2							
B				4406	40	4446	7 1/2	71m	40	1		15	6 1/4	2 1/8	60903					DRILL 8 3/4" Hole			4 00	4 30	1 1/2										
I				4	8 3/4	T33	1/4 3/4	46610	5-30	5-80	965	74			1	850	60					SURVEY @ 4414			4 30	4 45	1 1/2								
T																					Rig SERV. y BOPs			4 45	5 00										
S																					DRILL 8 3/4" Hole			5 00	12 00	7									
				MUD				4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP				4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP				4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS				Next Oil Change			
				WEIGHT				9.7	9.7	9.8	9.8	No. 1	550	850	850	550	No. 2				1	644	500												
				VISCOSITY				37	37	38	39	MODEL	60	60	60	60	MODEL	S.P.M.		2	644	250													
				GEL																	3	524	1000												
				W.L.					F.C.		pH.		DESILTER: Hours Op:					U. Flow:					O. Flow:												
				ADDITIVES				del	1700			GENERAL:								4414 30															
								1700 GEL																											
								1700 GEL																											
				Drilling Line Record				1"	WRIGHT	1-960	8					15200	65	65	14789	1-24-74	15283	285	FIRES			M. Lewis			DRILLER'S SIGNATURE						

B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	gals.	CASING REPORT	RAN	JTS	CSC	RENTAL EQUIPMENT ON HAND	TRANSFER #
Hydril	✓				Rig Savers Chk'd.	Fuel Rec'd Today (add)	gals.						
Pipe Rams.	✓				Kelly Cock Chk'd.	TOTAL	gals.	TO	KB. USED	SAX	CEM		
Blind Rams.					Fire Equip. Chk'd.	Fuel on Hand 11.59 p.m. (deduct)	23.15 gals.	PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD: 15	
TOTCO RING ON BIT =		Boiler Operated: 24 Hrs.				FUEL USED	gals.	CEMENT RETURNS - (YES/NO)				EQUIPMENT CHANGES	
													TOTAL COMPANY TIME HRS.
													TOTAL CONTRACTOR'S TIME HRS.
													Approved by Operator's Representative
													Approved by Toolpusher

WARDEN DRILLING COMPANY LIMITED
DAILY DRILLING LOG
DIRECTIONS TO WELL

RIG NO 19 LOCATION MIAMI AMOCO KAKISA R-152 BLOCK 109 SEC W TWP W RGE W DATE FEB. 15 1974
MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 14

TOUR	MIDNIGHT	8 AM	TOUR	4 PM	MIDNIGHT	From		Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Fr. up on Kelly	REMARKS	TIME			
						START	STOP																	INTVL			
						3903	100	4003	6 3/4	70	35	1												DRILL 8 3/4 HOLE	12.00	12.15	1/4
						4	8 3/4	133	1/4 3/4	46610	30	60/70	521	41 1/2										RIG SERVICE	12.15	12.30	1/4
																							CLEAN RAD & CHANGE	12.30			
																							FAN BELT ON LIGHT PLANT		1.30	1	
																							DRILL 8 3/4 HOLE	1.30	9.00	1 1/2	
						4003	104	4107	7 1/2	70m	36	2												DRILL 8 3/4 HOLE	8.00	8.30	1/2
						4	8 3/4	133	1/4 3/4	46610	30	60/70	625	49										SURVEY @ 3000	8.30	9.00	1/2
																							DRILL 8 3/4 HOLE	9.00	4.00	7	
						4107	93	4200	7 1/4	70m	37	2												DRILL 8 3/4 HOLE	4.00	5.30	1 1/2
						4	8 3/4	133	1/4 3/4	46610	30	60/70	719	56 1/2										Rig SER. & BOPS	5.30	5.45	1/4
																							DRILL 8 3/4 HOLE	5.45	10.15	4 1/2	
																							SURVEY @ 4161	10.15	10.25	1/2	
																							DRILL 8 3/4 HOLE	10.25	12.00	1 1/4	
						4200	93	4300	7 1/4	70m	37	2												DRILL 8 3/4 HOLE	12.00		
						4	8 3/4	133	1/4 3/4	46610	30	60/70	719	56 1/2										Rig SER. & BOPS			
																							DRILL 8 3/4 HOLE				
																							SURVEY @ 4161				
																							DRILL 8 3/4 HOLE				

WESTBURNIE
WARDEN DRILLING COMPANY LIMITED
DAILY DRILLING LOG
DIRECTIONS TO WELL 54 N.W. STEEN RIVER

RIG NO 19

LOCATION MIAMI AMOCO KAKISA R-152

BLOCK 109

DATE FEB. 14.

1974

MAILING POINT STEEN RIVER

SHIPPING POINT STEEN RIVER

MILES MOVED 270

ROAD CONDITIONS ROUGH

DAYS FROM SPUD 13

From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	It up on Kelly	REMARKS			TIME						
No.		Size		Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INTVL					
3630		68				3699	512	70	32	1							21.76	22		DRILL 8 3/4" HOLE	12.00	1.15	1 1/4				
4		8 3/4		J33	4 3/10	46610	30	60	214	194			1	800	60		IN			START LIGHT PLANT	1.15	3.45	2 1/2				
																				DRILL 8 3/4" HOLE	3.45	8.00	4 1/4				
MUD		12 mn.		7 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.		2 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.		2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS		Next Oil Change				
WEIGHT		9.8		9.8	9.8	9.8	No. 1	800	800	800	No. 2	800	800	1	580	500											
VISCOSITY		39		38	38	38	MODEL	60	60	60	MODEL	60	60	2	580	250											
GEL							KSP	5 1/2 x 15						3	460	1000											
W.L.		10.1		F.C. 2/152	pH. 9.0	DESILTER: Hours Op: 8	U. Flow: 10.7		O. Flow: 9.8	SURVEYS		At Feet		Degrees		4	540	250									
ADDITIVES		Water 1" screen		GENERAL:										5	600	250											
Drilling Line Record		1		WRIGHT	1-960	8	15200		65	65	14789	1-24-74	15283	285	FIRES		C. D. Darnold		DRILLER'S SIGNATURE								
From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	It up on Kelly	REMARKS			TIME						
3698		105				3803	73 1/4	70m	33	1								12		DRILL 8 3/4" HOLE	8.00	10.00	2				
4		8 3/4		J33	4 3/10	46610	30-35	56-70	421	27			1	800	60		IN			CRACKED POWER DISC & BOLTS	10.00	10.15	1 1/4				
																				DRILL 8 3/4" HOLE	10.15	4.00	5 3/4				
MUD		8 a.m.		10 a.m.	12 noon	2 p.m.	PUMP		8 a.m.		10 a.m.	12 noon	2 p.m.	PUMP		8 a.m.		10 a.m.	12 noon	2 p.m.	MOTOR HOURS		Next Oil Change				
WEIGHT		9.8		9.8	9.8	9.8	No. 1	800	800	800	No. 2	800	800	1	588	500											
VISCOSITY		58		36	38	37	MODEL	60	60	60	MODEL	60	60	2	588	250											
GEL							KSP	5 1/2 x 15						3	460	1000											
W.L.		10.00		F.C. 2/12	pH. 9.5	DESILTER: Hours Op: 8	U. Flow: 10.4		O. Flow: 9.7	SURVEYS		At Feet		Degrees		4	548	250									
ADDITIVES		100 CAUSTIC SODA		GENERAL:										5	108	250											
Drilling Line Record		1		WRIGHT	1-960	8	15200		65	65	14789	1-24-74	15283	285	FIRES		B. D. Darnold		DRILLER'S SIGNATURE								
From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	It up on Kelly	REMARKS			TIME						
3803		100				3903	73 1/4	70m	34	1								5		DRILL 8 3/4" HOLE	4.20	11.30	1 1/2				
4		8 3/4		J33	4 3/10	46610	30-35	56-70	421	24 1/2			1	800	60					Big SEAL & BOLTS	4.30	4.45	1 1/4				
																				DRILL 8 3/4" HOLE	4.45	12.00	7 1/4				
MUD		4 p.m.		6 p.m.	8 p.m.	10 p.m.	PUMP		4 p.m.		6 p.m.	8 p.m.	10 p.m.	PUMP		4 p.m.		6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS		Next Oil Change				
WEIGHT		33		32	35	34	No. 1	800	800	800	No. 2	800	800	1	590	500											
VISCOSITY		9.9		9.4	9.8	9.8	MODEL	60	60	60	MODEL	60	60	2	596	250											
GEL							KSP	5 1/2 x 15						3	476	1000											
W.L.		10.1		F.C. 4/12	pH. 9.5	DESILTER: Hours Op: 8	U. Flow: 10.4		O. Flow: 9.7	SURVEYS		At Feet		Degrees		4	556	250									
ADDITIVES		C-1 2000"		GENERAL:										5	616	250											
Drilling Line Record		1		WRIGHT	1-960	8	15200		65	65	14789	1-24-74	15283	285	FIRES		M. J. Germain		DRILLER'S SIGNATURE								
B.O.P.		Tested		Elapsed Time		Pressure		Packing & Seal Inspected Date		Crown & Motor Chk'd.		Fuel on Hand 12:01 a.m.		2690 gals.		CASING REPORT		RAN		JTS		CSG		RENTAL EQUIPMENT ON HAND		TRANSFER #	
Hydril										Rig Savers Chk'd.		Fuel Rec'd Today (add)				gals.		TO		KB. USED		SAX		CEM			
Pipe Rams.										Kelly Cock Chk'd.		TOTAL				gals.		PLUS		%		PLUG DOWN		A.M. P.M.			
Blind Rams.										Fire Equip. Chk'd.		Fuel on Hand 11:59 p.m. (deduct)		1943		gals.		CEMENT RETURNS - (YES/NO)				EQUIPMENT CHANGES					
TOTCO RING ON BIT				Boiler Operated: 24		Hrs.				FUEL USED		953		gals.										TOTAL COMPANY TIME		TOTAL CONTRACTOR'S TIME	
																								Approved by Operator's Representative		Approved by Toolpusher	

DAILY DRILLING LOG
DIRECTIONS TO
WELL

54 N.W. STEEN RIVER MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER

MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD

1974

CONSERVATION BOARD COPY

W 6376

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG
DIRECTIONS TO
WELLRIG NO. 19 LOCATION MIAMI AMOCO KAKISA R-152 SEC. TWP. RGE. W. DATE FEB. 11 1974
MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 10

From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Fl. up on Kelly	REMARKS			TIME														
No.		Size		Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INTVL.													
2633		98				2731	3	62	22								5.97	27	RIG SERVICE			12.00	12.15	1/4											
2		8 3/4		X16	3/4	49032	40	80	705	244			1	1150	54		5	8	1	DRILL 8 3/4 HOLE			12.15	3.15	3										
																				BLOW KELLY & SURVEY			3.15	3.45	1/2										
																				TRIP OUT			3.45	8.00	4 1/2										
MUD		12 mn.		2 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.		2 a.m.	4 a.m.	6 a.m.	PUMP		12 mn.		2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS		Next Oil Change												
WEIGHT		9.2		9.2			No. 1	PRES. SURE	1150		1150		No. 2	PRES. SURE	408		500																		
VISCOSITY		30		31	TRIP		MODEL	S.P.M.	54		54		MODEL	S.P.M.	408		250																		
GEL							MODEL	S.P.M.	54		54		MODEL	S.P.M.	398		1000																		
W.L.		F.C. 2/32		pH. 8.5	DESILTER: Hours Op: 5		U. Flow: 10.4		O. Flow: 9.2		SURVEYS		At Feet		Degrees		4.468		250																
ADDITIVES		Water - 1" stream		GENERAL:																															
Drilling Line Record		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip or Cut		At Miles		Date Slip or Cut		Next Slip		Fl. Left on Spool											
1		WAKHT		1-960		8		1/2		93		15023		65		65		14784		124.74		15283		285											
From		Footage		To		Hrs. on Bottom		Wt. Drill Pipe (1000 lbs.)		Stands		Singles		DRILL COLLARS		No.		O.D.		I.D.		Length		Air Wt.		Sub. Wt.		C.B. Ft.		Fl. up on Kelly					
31		185		2916		3		6-1		24																									
No.		Size		Type		Jets/W.C.		Serial No.		Wgt.		R.P.M.		Drilled or Cored		Hrs.		Reamed		Hrs.		Pump No.		Pump Pressure		S.P.M.		Table Torque		T.		B.		G.	
3		8 3/4		X16		3/4		63993		50-40		70		195		3						1													
MUD		8 a.m.		10 a.m.		12 noon		2 p.m.		PUMP		8 a.m.		10 a.m.		12 noon		2 p.m.		PUMP		8 a.m.		10 a.m.		12 noon		2 p.m.		MOTOR HOURS		Next Oil Change			
WEIGHT		9.4		9.4				No. 1		PRES. SURE				No. 2		PRES. SURE						1		416		500									
VISCOSITY		TRIP		32				MODEL		S.P.M.				MODEL		S.P.M.						2		416		250									
GEL		TRIP		K5				MODEL		S.P.M.				MODEL		S.P.M.						3		396		1000									
W.L.		F.C. 1/32		pH. 8.7		DESILTER: Hours Op: 7		U. Flow: 10.2		O. Flow: 9.3		SURVEYS		At Feet		Degrees		4.476		250															
ADDITIVES		100% G.M.C.		GENERAL:																															
Drilling Line Record		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip or Cut		At Miles		Date Slip or Cut		Next Slip		Fl. Left on Spool											
1		WAKHT		1-960		8		1/2		93		15023		65		65		14784		124.74		15283		285											
From		Footage		To		Hrs. on Bottom		Wt. Drill Pipe (1000 lbs.)		Stands		Singles		DRILL COLLARS		No.		O.D.		I.D.		Length		Air Wt.		Sub. Wt.		C.B. Ft.		Fl. up on Kelly					
2916		209		3125		8		65		26																									
No.		Size		Type		Jets/W.C.		Serial No.		Wgt.		R.P.M.		Drilled or Cored		Hrs.		Reamed		Hrs.		Pump No.		Pump Pressure		S.P.M.		Table Torque		T.		B.		G.	
3		8 3/4		X16		3/4		63993		50-40		80		394		11						1		800		60		TR							
MUD		4 p.m.		6 p.m.		8 p.m.		10 p.m.		PUMP		4 p.m.		6 p.m.		8 p.m.		10 p.m.		PUMP		4 p.m.		6 p.m.		8 p.m.		10 p.m.		MOTOR HOURS		Next Oil Change			
WEIGHT		9.4		9.6				No. 1		PRES. SURE		1150		200		200		200		No. 2		PRES. SURE		1080				1		424		500			
VISCOSITY		33		32				MODEL		S.P.M.		70		60		60		60		MODEL		S.P.M.		1080				2		424		250			
GEL								MODEL		S.P.M.										MODEL		S.P.M.		1080				3		404		1000			
W.L.		F.C. 1/32		pH. 8		DESILTER: Hours Op: 8		U. Flow: 10.5		O. Flow: 9.5		SURVEYS		At Feet		Degrees		4.484		250															
ADDITIVES		Gel 15% & 2%		GENERAL:		Hump + 2% water																													
Drilling Line Record		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip or Cut		At Miles		Date Slip or Cut		Next Slip		Fl. Left on Spool											
1		WAKHT		1-960		8		1/2		93		15023		65		65		14784		124.74		15283		285											
B.O.P.		Tested		Elapsed Time		Pressure		Packing & Seal Inspected Date		Crown-o-matic Chk'd.		Fuel on Hand 12.01 a.m.		452.2 gals.		CASING REPORT		RAN		JTS		CSG		RENTAL EQUIPMENT ON HAND		TRANSFER #									
Hyaril										Rig Savers Chk'd.		Fuel Rec'd Today (add)				TO		KB. USED		SAX		CEM													
Pine Rams										Kelly Cock Chk'd.		TOTAL				PLUS		% PLUG DOWN		A.M. P.M.		DAYS FROM SPUD: 10		TOTAL COMPANY TIME		TOTAL CONTRACTOR'S TIME									
Blind Rams		2								Fire Equip. Chk'd.		Fuel on Hand 11.59 p.m. (deduct)		397.1 gals.		CEMENT RETURNS - (YES/NO)						EQUIPMENT CHANGES		Approved by Operator's Representative		Approved by Toolpusher									
TOTCO RING ON BIT = 2				Boiler Operated: 24 Hrs.						FUEL USED		551 gals.												8925											

CONSERVATION BOARD COPY

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MIAMI AMOCO KAKISA R-1-52 LSD. SEC. TWP. RGE. W. DATE FEB. 10 19 74
 EN RIVER MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 9

[illegible]

CONSERVATION BOARD COPY

8924

DAILY DRILLING LOG
DIRECTIONS TO
WELL 54

RIG. NO. 19 LOCATION MIAMI AMOCO KAKISAR 1-52 USD. BLOCK 109 SEC. TWP. RGE. W. DATE FEB. 9 19 74
MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD 8

[illegible]

8923

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MIAMI AMOCO KAKISA R 1-52 LSD. SEC. TWP. RGE. W. DATE FEB. 8 1974
MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD

From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS			TIME				
No.		Size		Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T	B	G	START	STOP	INTVL.			
640										10	6 3/4	2 7/8								THAW OUT KELLY			1200	200	2
1		8 3/4		XIG	3-10	62927	10-15	50	CEMENT				1	800	46					DRILL OUT CEMENT & SHOE			200	800	6
640		40		680	1 1/2	45				16	6 3/4	2 7/8	14784	1-24-74	15283	285				DUMP & CLEAN TANKS			8.00		
1		8 3/4		XIG	3-10	62927	5-15	50	40	1 1/2			1	800	46		10			DISPLACE HOLE					
																				THAW & REPAIR MUD					
																				MIXING SYSTEM PREMIX					
																				MUD TO DRILL			2.30	1 1/2	
																				DRILL 8 3/4 HOLE			2.30	4.00	1 1/2
680		441		1121	7 1/2	50M	4	2		16	6 3/4	2 7/8	14784	1-24-74	15283	285				FIRE					
1		8 3/4		XIG	3-10	62927	5-15	50	481	9			1	800	45					DRILL 8 3/4 HOLE			4.00	10.00	6
																				NO VOLUME			10.00	10.30	1/2
																				DRILL 8 3/4 HOLE			10.30	12.00	1 1/2
680		441		1121	7 1/2	50M	4	2		16	6 3/4	2 7/8	14784	1-24-74	15283	285				FIRE					
1		8 3/4		XIG	3-10	62927	5-15	50	481	9			1	800	45					DRILL 8 3/4 HOLE			4.00	10.00	6
																				NO VOLUME			10.00	10.30	1/2
																				DRILL 8 3/4 HOLE			10.30	12.00	1 1/2
680		441		1121	7 1/2	50M	4	2		16	6 3/4	2 7/8	14784	1-24-74	15283	285				FIRE					
1		8 3/4		XIG	3-10	62927	5-15	50	481	9			1	800	45					DRILL 8 3/4 HOLE			4.00	10.00	6
																				NO VOLUME			10.00	10.30	1/2
																				DRILL 8 3/4 HOLE			10.30	12.00	1 1/2

CONSERVATION BOARD COPY

8922

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MIAMI AMOCO KAKISAR. 1-52 LSD. _____ SEC. _____ TWP. _____ RGE. _____ W. _____ DATE FEB 7 19 74
 MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD _____

[illegible]

CONSERVATION BOARD COPY

8921

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO 19 LOCATION Miami AMSCO KAKISA RT-52

BLOCK 109

SEC. _____ TWP. _____ RGE. _____ W. _____ DATE FEB. 6 1924

MAILING POINT STEEN RIVER

SHIPPING
POINT

MILES MOVED 270

ROAD CONDITIONS Good

DAYS FROM
SPIN

[illegible]

CONSERVATION BOARD COPY

8920

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MIAMI AMOCO KARISA R 7-52 LSD. BLUCK 109 SEC. TWP. RGE. W. DATE FEB. 5 19 74
MAILING POINT STEEN RIVER SHIPPING POINT STEEN RIVER MILES MOVED 270 ROAD CONDITIONS ROUGH DAYS FROM SPUD

	From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME START STOP INTVL.		
B	640								180	9 3/4	2 7/8	633.53		5.97			NIPPLE UP - CLEAN MUD	1200		
T																	TANKS CHANGE HEADS			
S																	P LINES		800	8
M U D	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change				
WEIGHT					No. 1 PRES-SURE				No. 2 PRES-SURE						1 280	250				
VISCOSITY					MODEL S.P.M.				MODEL S.P.M.						2 280	250				
GEL					LINER SIZE				LINER SIZE						3 260	1000				
W.L.	F.C.	pH.	DESILTER:	Hours Op:	U. Flow:	O. Flow:	SURVEYS													
ADDITIVES: GENERAL:																				
Weather																	Water			
Temp.																	Bbls.			
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool							
1	WRIGHT	1-960	8			14813	14813	65	65	14784	-24-74	15283	265							
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly					
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.			
M U D	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change				
WEIGHT					No. 1 PRES-SURE				No. 2 PRES-SURE						1 288					
VISCOSITY					MODEL S.P.M.				MODEL S.P.M.						2 288					
GEL					LINER SIZE				LINER SIZE						3 268					
W.L.	F.C.	pH.	DESILTER:	Hours Op:	U. Flow:	O. Flow:	SURVEYS													
ADDITIVES: GENERAL:																				
Weather																	Water			
Temp.																	Bbls.			
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool							
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly					
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.			
M U D	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change				
WEIGHT					No. 1 PRES-SURE				No. 2 PRES-SURE						1 296	250				
VISCOSITY					MODEL S.P.M.				MODEL S.P.M.						2 296	250				
GEL					LINER SIZE				LINER SIZE						3 326	1000				
W.L.	F.C.	pH.	DESILTER:	Hours Op:	U. Flow:	O. Flow:	SURVEYS													
ADDITIVES: GENERAL:																				
Weather																	Water			
Temp.																	Bbls.			
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool							
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly					
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.			
M U D	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change				
WEIGHT					No. 1 PRES-SURE				No. 2 PRES-SURE						1 296	250				
VISCOSITY					MODEL S.P.M.				MODEL S.P.M.						2 296	250				
GEL					LINER SIZE				LINER SIZE						3 326	1000				

8919

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19 LOCATION MIAMI AMOCO KAKISA R-1-52 Block 109 DATE Feb 4 74
MAILING POINT STEEN RIVER SHIPPING POINT _____ MILES MOVED 770 ROAD CONDITIONS ROUGH DAYS FROM SPUD _____

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.
640																	
MUD 12 mn. 2 a.m. 4 a.m. 6 a.m. PUMP 12 mn. 2 a.m. 4 a.m. 6 a.m. PUMP 12 mn. 2 a.m. 4 a.m. 6 a.m. MOTOR HOURS WEIGHT No. 1 PRES. SURE No. 2 PRES. SURE VISCOSITY MODEL S.P.M. MODEL S.P.M. GEL LINER SIZE LINER SIZE W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees ADDITIVES: GENERAL: VISUALLY INSPECT 9 3/4 CASING - NO DEFECTS BY VISUAL INSPECTION @ 1100 Drilling Line Record Size Make Serial No. No. Lines Trips Ton Miles Total Miles Slip or Cut At Miles Date Slip or Cut Next Slip Ft. Left on Spool 1" WRIGHT 1-960 8 14083 15 65 14053 1-24-74 15283 285																	
640																	
MUD 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. MOTOR HOURS WEIGHT No. 1 PRES. SURE No. 2 PRES. SURE VISCOSITY MODEL S.P.M. MODEL S.P.M. GEL LINER SIZE LINER SIZE W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees ADDITIVES: GENERAL: Drilling Line Record Size Make Serial No. No. Lines Trips Ton Miles Total Miles Slip or Cut At Miles Date Slip or Cut Next Slip Ft. Left on Spool 1" WRIGHT 1-960 8 14083 15 65 14053 1-24-74 15283 285																	
640																	
MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. MOTOR HOURS WEIGHT No. 1 PRES. SURE No. 2 PRES. SURE VISCOSITY MODEL S.P.M. MODEL S.P.M. GEL LINER SIZE LINER SIZE W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees ADDITIVES: GENERAL: Drilling Line Record Size Make Serial No. No. Lines Trips Ton Miles Total Miles Slip or Cut At Miles Date Slip or Cut Next Slip Ft. Left on Spool 1" WRIGHT 1-960 8 14083 15 65 14053 1-24-74 15283 285																	

B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #
Hydril													
Pipe Rams.													
Blind Rams.													
TOTCO RING ON BIT = Boiler Operated: 221 Hrs. Fire Equip. Chk'd. FUEL USED gals. CEMENT RETURNS (YES/NO) EQUIPMENT CHANGES Approved by Operator's Representative <i>[Signature]</i> Approved by Toolpusher <i>[Signature]</i>													

CONSERVATION BOARD COPY

8918

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG
DIRECTIONS TO
WELL

RIG NO. 19

LOCATION MIAMI AMOCO KAKISA R I-52

BLOCK 109

SEC.

TWP.

RGE.

W.

DATE FEB 3

1974

MAILING
POINT

STEEN RIVER

SHIPPING
POINT

STEEN RIVER

MILES
MOVED

270

ROAD
CONDITIONS

ROUGH

DAYS FROM
SPUD

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME																																		
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Corod	Hrs.	Roomed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	B.	G.	START	STOP	INTVL.																															
485	113	598	8	40				13	6 3/4	2 3/8	520.19		9.08		0																																				
1A	13 3/4	OSC 3	3-18	61338	5-10	160-80	598	50			1	800	72																																						
M U D																		PUMP		MOTOR HOURS		Next Oil Change																													
WEIGHT																		9.1		96																															
VISCOSITY																		1.9		44																															
GEL																																																			
W.L.																		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS																							
ADDITIVES: 3200 GEL																		GENERAL:																																	
110 Lime																																																			
1-1/2 WATER																																																			
Drilling Line Record																		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip		Feet or Cut		At Miles		Date Slip or Cut		Next Slip		Ft. Left on Spool									
1" WRIGHT																		1-960		8																															
597	8	606	1/2					13	6 3/4	2 3/8	575.61																																								
1A	13 3/4	OSC 3	3-18	61338																																															
2A	13 3/4	OSC 3	3-18	8087	10	180	1/2				1	800	72																																						
M U D																		PUMP		PUMP		MOTOR HOURS		Next Oil Change																											
WEIGHT																		9.3																																	
VISCOSITY																		54																																	
GEL																																																			
W.L.																		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS																							
ADDITIVES:																		GENERAL:																																	
Drilling Line Record																		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip		Feet or Cut		At Miles		Date Slip or Cut		Next Slip		Ft. Left on Spool									
1" WRIGHT																		1-960		8		1		20		14803		65		65		14783		1-24-74		15283		275													
606	34	640	1					15	6 3/4	2 3/8	605.06																																								
2A	13 3/4	YH 3	3-18	8088	10	185	42	1 1/2			1	800	72																																						
M U D																		PUMP		PUMP		MOTOR HOURS		Next Oil Change																											
WEIGHT																																																			
VISCOSITY																		68																																	
GEL																																																			
W.L.																		F.C.		pH.		DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS																							
ADDITIVES: 900 GEL																		GENERAL:																																	
40 Lime																																																			
Drilling Line Record																		Size		Make		Serial No.		No. Lines		Trips		Ton Miles		Total Miles		Slip		Feet or Cut		At Miles		Date Slip or Cut		Next Slip		Ft. Left on Spool									
1" WRIGHT																		1-960		8		1/2		10		14813		64		64		14783		1-24-74		15283		235													
B.O.P.																		Tested		Elapsed Time		Pres. sure		Packing & Seal Inspected Date		Crown-o-matic Chk'd.		Fuel on Hand 12.01 a.m.		547		gals.		CASING REPORT		RAN		JTS		CSG		RENTAL EQUIPMENT ON HAND		TRANSFER #							
Hydril																										Rig Savers Chk'd.		Fuel Rec'd Today (add)																							
Pipe Rams.																										Kelly Cock Chk'd.		TOTAL																							
Blind Rams.																												Fuel on Hand 11.59 p.m. (deduct)		506		gals.		P:US		%		PLUG DOWN		A.M. P.M.		DAYS FROM SPUD:		TOTAL COMPANY TIME		HRS.		TOTAL CONTRACTOR'S TIME		HRS.	
TOTCO RING ON BIT #																		Boiler Operated: 24		Hrs.		Fire Equip. Chk'd.		FUEL USED																											
CONSERVATION BOARD COPY																																																			

CONSERVATION BOARD COPY

8917

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG
DIRECTIONS TO
WELLRIG NO. 19 LOCATION Miami Dade County KARIKA River I-52 BLOCK 109 TWP. SEC. 13 RGE. W. DATE FEBRUARY 2nd 1974
MAILING POINT STEVEN RIVER SHIPPING POINT STEVEN RIVER MILES MOVED 220 ROAD CONDITIONS ROUGH DAYS FROM SPUD

From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS	TIME						
																START	STOP	INTVL.					
180	98	278	8	28			8	6 3/4	2 1/2		227.98												
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.						
1A	13 3/4	OSC-3	3/18	61338	5-10	120	278	28			1	750	77										
MUD 12 mn. 2 a.m. 4 a.m. 6 a.m. PUMP 12 mn. 2 a.m. 4 a.m. 6 a.m. MOTOR HOURS Next Oil Change																							
WEIGHT 9.2 No. 1 PRES. SURE 750 750 750 750 No. 2 PRES. SURE 1 208 250																							
VISCOSITY 42.50 42.40 MODEL 72 72 72 72 MODEL 72 72 72 72 2 208 250																							
GEL 50 50 50 50 3 196 1000																							
W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees 4 276 250																							
ADDITIVES: 900 GEL 50 LIME GENERAL: 191 1/2 5 334 250																							
Weather: -20 Water: Bbls.																							
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool										
1" WRIGHT	1-960	8				14783	65	65	14783	1-24-74	15283	285	FIRES 112 B.W. Huber DRILLER'S SIGNATURE										
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly								
278	116	394	6	30 m			12	6 3/4	2 1/2		344.05			9.08									
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.						
1A	13 3/4	OSC-3	3/18	61338	5-10	180	394	34			1	800	72										
MUD 8 a.m. 10 a.m. 12 noon 2 p.m. PUMP 8 a.m. 10 a.m. 12 noon 2 p.m. MOTOR HOURS Next Oil Change																							
WEIGHT 8.9 No. 1 PRES. SURE 750 750 800 800 No. 2 PRES. SURE 1 216 250																							
VISCOSITY 5 No. 1 PRES. SURE 750 750 800 800 No. 2 PRES. SURE 1 216 250																							
GEL 40 MODEL 72 72 72 72 MODEL 72 72 72 72 3 208 1000																							
W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees 4 284 250																							
ADDITIVES: GENERAL: 335 1/2 5 344 250																							
Weather: 394 2/3 Water: Bbls.																							
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool										
1" WRIGHT	1-960	8				14783	65	65	14783	1-24-74	15283	285	FIRES 112 Mike Karpinski DRILLER'S SIGNATURE										
From	Footage	To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly								
394	91	485	8	36			15	6 3/4	2 1/2		574.30												
No.	Size	Type	Jets/W.C.	Serial No.	Wgt.	R.P.M.	Drilled or Cored	Hrs.	Reamed	Hrs.	Pump No.	Pump Pressure	S.P.M.	Table Torque	T.	S.	G.						
1A	13 3/4	OSC-3	3-18	61338	5-10	180-90	485	42			1	800											
MUD 4 p.m. 6 p.m. 8 p.m. 10 p.m. PUMP 4 p.m. 6 p.m. 8 p.m. 10 p.m. MOTOR HOURS Next Oil Change																							
WEIGHT 9.393 9.4 9.5 No. 1 PRES. SURE 700 800 800 800 No. 2 PRES. SURE 1 224 250																							
VISCOSITY 43 42 59 52 MODEL 72 72 72 72 MODEL 72 72 72 72 2 224 250																							
GEL 25 25 50 50 3 212 1000																							
W.L. F.C. pH. DESILTER: Hours Op: U. Flow: O. Flow: SURVEYS At Feet Degrees 4 292 250																							
ADDITIVES: GEL 400 LIME 10 GENERAL: 480 1/2 5 352 250																							
Weather: Temp. Water: Bbls.																							
Drilling Line Record	Size	Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool										
1" WRIGHT	1-960	8				14783	65	65	14783	1-24-74	15283	285	FIRES 112 Frank Karpinski DRILLER'S SIGNATURE										
B.O.P.	Tested	Elapsed Time	Pressure	Packing & Seal Inspected Date	Crown-a-matic Chk'd.	Fuel on Hand 12.01 a.m.	1202 gals.	CASING REPORT	RAN	JTS	CSG	RENTAL EQUIPMENT ON HAND	TRANSFER #										
Hydril					Rig Savers Chk'd.	Fuel Rec'd Today (add)		TC	KB. USED	SAX	CEM												
Pipe Rams.					Kelly Cock Chk'd.	TOTAL	1202 gals.	PLUS	%	PLUG DOWN	A.M. P.M.	DAYS FROM SPUD:	TOTAL COMPANY TIME	TOTAL CONTRACTOR'S TIME	HRS.								
Blind Rams.					Fire Equip. Chk'd.	Fuel on Hand 11.59 p.m. (deduct)	547 gals.	CEMENT RETURNS - (YES/NO)	EQUIPMENT CHANGES														
TOTCO RING ON BIT #																Boiler Operated: 24 Hrs.		FUEL USED 655 gals.		Approved by Operator's Representative		Approved by Toolpusher	

CONSERVATION BOARD COPY

8916

WESTBURNE DRILLING LTD.

DAILY DRILLING LOG

DIRECTIONS TO WELL

RIG NO. 19

LOCATION MIAMI BLOCK 109

LSD. SEC. TWP. RGE. W.

DATE Feb 1

1974

4N 54 N x W STEEN RIVER

MAILING POINT STEEN RIVER

SHIPPING POINT STEEN RIVER

MILES MOVED 270

ROAD CONDITIONS Rough

DAYS FROM SPUD

From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly	REMARKS			TIME						
																			START	STOP	INTVL.						
78		78		4					1	63/4			28.76				DOWN		SRL RAT HOLE			1200	200	2			
1A 13740553		3/4		61338															Rig To SPUD			200	400	2			
																			SRL			400	800	4			
M U D		12 m.		2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	PUMP	12 m.	2 a.m.	4 a.m.	6 a.m.	MOTOR HOURS	Next Oil Change									
WEIGHT							No. 1	PRES. SURE				No. 2	PRES. SURE				1	184	250								
VISCOSITY							MODEL	S.P.M.				MODEL	S.P.M.				2	184	250								
GEL							LINER SIZE					LINER SIZE					3	172	1000								
W.L.		F.C.		pH.	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	252	250								
ADDITIVES:		GENERAL:																5	310	250							
2400 GEL																		Weather	Water								
Temp.																		Bbls.									
Drilling Line Record		Size		Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				FIRES			DRILLER'S SIGNATURE					
1" 13740553		1-960		8					14783	15	15	14783	1-24-74	15783	255							8					
From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly										
78		37		115	8				3	63/4			85.72				20				DRLG 13 3/4 HOLE			800	400	8	
1A 13740553		3/4		61338																							
M U D		8 a.m.		10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	PUMP	8 a.m.	10 a.m.	12 noon	2 p.m.	MOTOR HOURS	Next Oil Change									
WEIGHT							No. 1	PRES. SURE	750	750	750	750	No. 2	PRES. SURE			1	192	250								
VISCOSITY		40		42	31	38	MODEL	S.P.M.	72	72	72	72	MODEL	S.P.M.			2	192	250								
GEL							LINER SIZE		7	7	7	7	LINER SIZE				3	180	1000								
W.L.		F.C.		pH.	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	260	250								
ADDITIVES:		GENERAL:																5	218	250							
GEL 1500																		Weather	Water								
Temp.																		Bbls.									
Drilling Line Record		Size		Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				FIRES			DRILLER'S SIGNATURE					
1" 13740553		1-960		8					14783	15	15	14783	1-24-74	15783	285							8					
From		Footage		To	Hrs. on Bottom	Wt. Drill Pipe (1000 lbs.)	Stands	Singles	DRILL COLLARS	No.	O.D.	I.D.	Length	Air Wt.	Sub. Wt.	C.B. Ft.	Ft. up on Kelly										
115		65		180	8	12			5	1 3/4			141.64				11				DRLG 13 3/4 DRILLER ON ROADERS 4 00 12 00			4 00	12 00	8	
1A 13740553		3/4		61338																							
M U D		4 p.m.		6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	PUMP	4 p.m.	6 p.m.	8 p.m.	10 p.m.	MOTOR HOURS	Next Oil Change									
WEIGHT		2.1		2.2	2.2	2.3	No. 1	PRES. SURE	750	750	750	No. 2	PRES. SURE				1	200	250								
VISCOSITY		39		38	37	39	MODEL	S.P.M.	72	72	72	MODEL	S.P.M.				2	200	250								
GEL							LINER SIZE		7	7	7	LINER SIZE					3	188	1000								
W.L.		F.C.		pH.	DESILTER: Hours Op:		U. Flow:		O. Flow:		SURVEYS		At Feet		Degrees		4	268	250								
ADDITIVES:		GENERAL:																5	326	250							
GEL 1000																		Weather	Water								
Temp.																		Bbls.									
Drilling Line Record		Size		Make	Serial No.	No. Lines	Trips	Ton Miles	Total Miles	Slip	Feet or Cut	At Miles	Date Slip or Cut	Next Slip	Ft. Left on Spool				FIRES			DRILLER'S SIGNATURE					
1" 13740553		1-960		8					14783	15	15	14783	1-24-74	15783	275							8					
B.O.P.		Tested		Elapsed Time		Pres. sure		Packing & Seal Inspected Date		Crown-o-matic Chk'd.		Fuel on Hand 12.01 a.m.		1733 gals.		CASING REPORT		RAN		JTS		CSG		RENTAL EQUIPMENT ON HAND		TRANSFER #	
Hydril										Ria Savers Chk'd.		Fuel Rec'd Today (add)				TO		KB. USED		SAX		CEM					
Pipe Rams.										Kelly Cock Chk'd.		TOTAL															
Blind Rams.												Fuel on Hand 11.59 p.m. (deduct)		1302 gals.		PLUS		%		PLUG DOWN		A.M. P.M.		DAYS FROM SPUD:			
TOTCO RING ON BIT										Fire Equip. Chk'd.		FUEL USED		521 gals.		CEMENT RETURNS - (YES/NO)				EQUIPMENT CHANGES							
Boiler Operated:		24		Hrs.																							
Approved by Operator's Representative																											
Approved by Toolpusher																											

CONSERVATION BOARD COPY 16421 71989

8915