



Nova Scotia	☐	West Coast	☐	Well Status	
Newfoundland	☐	Northern	☒	Suspended	☐
Gulf of St. Lawrence	☐	Hudson Bay	☐	Completed	☒
				Abandoned	☐

WELL TERMINATION RECORD

This record is submitted in triplicate in compliance with Section 184 of the Canada Oil and Gas Drilling Regulations.

WELL DATA

Well Name: Paramount et al Cameron N-28 Area: Cameron Hills, N.W.T.
Grid Area: 60-10-117-30 Field/Pool: N/A
Permit or Lease No.: N89A227 Final Coordinates: Lat.: 60° 07' 59.23"N Long: 117° 35' 07.63"W
Drilling Unit: Sierra Rig #5 Elevations-RT/KB: 764.1 m FWR 3F/GL: 760.1 m FWR
Spud Date: 1990-02-26 Rig Released: 1990-03-19 Total Depth: 1591.8 m
Re-entered: 1990-03-26 Rig Released: 1990-03-27 Flint Service Rig #706
UWI: 300N286010117300 CASING AND CEMENTING 28

O.D.:	Weight:	Grade:	Depth Set:	Cement and Additives:
298.5 mm	62.5 kg/m	H-40	203.30 m	28 T 0:1:0 'G' + 2% CaCl ₂ .
219.1 mm	35.72 kg/m	IK55	834.29 m	18.01 T 0:1:8 + 0.75% T10 Tailed In with 14.26 T 0:1:0 + 0.8% NFL + 0.10% SPC 12000.
139.7 mm	23.09 kg/m	IK55	1590.5 m To 732.0 m (Liner)	35.6 T 0:1:4 'G' + 0.75% T10, 29.0 T 0:1:0 'G' + 0.8% NFL 3 + 0.10% SPC 12000.

PLUGGING PROGRAM

Approval of the following program was obtained by (person) from
(person) of the Canada Oil and Gas Lands Administration by means of
on 19

Type of Plug:	Interval:	Felt:	Cement and Additives:
Cement	1590.5 - 1576.00	Est.	

Lost Circulation/Overpressure Zones: N/A
Equipment left on Seafloor (Describe): N/A
Provision for Re-entry (Describe and attach sketch): N/A
Cores: Type: Intervals: Not Run
Other Downhole Completion/Suspension Equipment: To be completed in 1990-1991 Season.

CERTIFICATION

I certify on the basis of personal knowledge of operations undertaken at the above named well that the above information is accurate.

Signed: P. G. Besler P. Eng. Title: Assistant Drilling Manager
Name: P. G. Besler Date: November 5, 1990

Acknowledged by: Engineering Branch
Date: 90-11-19
File: 9211-P33-5-2