



# WELL TERMINATION RECORD

This record is submitted in triplicate in compliance with Section 184 of the Canada Oil and Gas Drilling Regulations.

## WELL DATA

Well Name: Paramount et al Bovie C-76 (Re-entry) Area: Fort Liard, N.W.T.  
Grid Area: 60° 20' 122° 45' Field/Pool: N/A  
Permit or Lease No.: EL 369 Final Coordinates: Lat: 60° 15' 14.83" Long: 122° 59' 22.34"  
Drilling Unit: Alberta Gold #30 Elevations-RT/KB: 433.32 m SF/GL: 426.80 m  
SPM Date: 18-Dec-97 Rig Released: 19-Feb-98 Total Depth: 3220 m  
Re-entry

## CASING AND CEMENTING

| O.D.: | Weight: | Grade:                   | Depth Set: | Cement and Additives:                                                                                                              |
|-------|---------|--------------------------|------------|------------------------------------------------------------------------------------------------------------------------------------|
| 339.7 | 81.1    | K-55                     | 453 m      | 70 t 0:1:0 G + 1% CaCl <sub>2</sub>                                                                                                |
| 244.5 | 69.9    | L-80                     | 1713 m     | 5 t 0:1:0 G + 1% CaCl <sub>2</sub> + 0.5% T-10 + 0.5% D-24                                                                         |
| 177.8 | 43.2    | L-80                     | 2897 m     | 60 t 1:1:2 G + 0.5% T-10                                                                                                           |
| 114.3 | 17.3    | 183 m K-55<br>296 m L-80 | 3220 m     | 36 t 0:1:0 G + 1.1% NFL-3<br>19.5 t 1:1:2 + 0.5% T-10 + 0.2% R-6*<br>9.0 t Thermal 40F + 0.4% D-24 + 0.5% T- + 0.3% R-6 + 0.5% Gel |

## PLUGGING PROGRAM

\*See Attached Diagram

Approval of the following program was obtained by (person) ..... from  
(person) ..... by means of  
..... on ..... 19 ..

| Type of Plug: | Interval: | Felt: | Cement and Additives: |
|---------------|-----------|-------|-----------------------|
| BP            | 3113.5    |       |                       |
| BP            | 2934.0    |       | w/175m cmt on top     |
| BP            | 2720.0    |       | w/10m cmt on top      |
| BP            | 2495.0    |       |                       |

Lost Circulation/Overpressure Zones: Lost circulation at 140 m, 463 m, 680 m, Gas cutting at 1543 m - mud weight 1150.

Equipment left on Seafloor (Describe): N/A

Provision for Re-entry (Describe and attach sketch): .....

Cores: Type: None Intervals: .....

Other Downhole Completion/Suspension Equipment: Cut window from 2658.0-2675 mKB.

## CERTIFICATION

I certify on the basis of personal knowledge of operations undertaken at the above named well that the above information is accurate.

Signed: Shirley Maaskant  
Name: Shirley Maaskant

Title: Drilling Consultant  
Date: March 31, 1998

Acknowledged by: Jenny Baker  
Engineering Branch

Date: Oct 27/98

File: WID.1817.9211-P33-8-1RE  
UWI 300C766020122451

Well Status  
Suspended ☐  
Completed ☐  
Abandoned ☒

Canada