

Well Name: Chevron et al Liard K-29		Onshore		
	RT (m)	4.50		
	Water Depth (m)	0.00		
	Total Depth (TVD, (m))	3000.00		
	Mud Weight (kg/cu. m)	1550.00		
Line # in Casing Database	245	201	102	
Type	Surface	Intermediate	Liner	
Mud Weight (kg/cu. m)	1120.00	1550.00	1150.00	
Next Casing Mud Weight	1550.00	1150.00	1150.00	
Top Depth (m RT)	4.50	4.50	2490.00	
Bottom Depth (TVD, (m RT))	700.00	2615.00	3000.00	
Next Casing Depth (m RT)	2615.00	3000.00	3000.00	
Grade	K-55	L-80	L-80	
Casing Size, O.D. (mm)	339.70	244.50	177.80	
Casing Weight (kg/m)	90.78	69.94	38.69	
Collapse (kPa)	10600	32800	37300	
Burst (kPa)	21300	47400	49900	
Tensile (kN)	281600	397200	227300	
% Cased	26.77%	87.17%	100.00%	
Safety Factor				
Collapse	1.38	1.65	2.20	
Burst	1.38	4.25	4.48	
Tensile	4.55	2.22	11.74	
Satisfaction				
Collapse	OK	OK	OK	
Burst	OK	OK	OK	
Tensile	OK	OK	OK	