



APPROVAL TO ALTER CONDITION OF A WELL

This application is to be submitted to the Chief Conservation Officer at least 45 days before commencement of operations.

Well Name: Paramount et al Bovie C-76A Area: Fort Liard, NWT
Operator: Paramount Resources Ltd. Contractor: Cenalta
Drilling Rig or Unit: 42 Depth: 3464 m MD, 3077.56 m TVD
Coordinates: Lat: 60° 15' 14.83" Long: 122° 59' 22.34"
Date ADW Issued: February 19, 1998 Date of last Operation: January 10, 1999
Elevation-KE: 433.31 m (ASL) GL 426.8 m

TYPE OF OPERATION

Complete as a Horizontal gas well.

SUMMARY OF PROPOSED OPERATIONS

Move in Newsco coil tubing and drill out liner shoe.
Move in service rig, set a packer complete with tie back assembly directly above
liner top. Pressure test annulus to 7.0 MPa.
Run 88.9 mm tubing, tie into tie back assembly back to surface.
Rig up coil and clean out well with solvent.
Acid wash horizontal section.
Flow test as outlined in previously submitted Application to Alter Condition of Well.
Terminate well as per Part VIII of the Canada Oil and Gas Drilling Regulations.

Signed: *Phil Christie* Title: Drilling Manager
Responsible Officer
Name: Phil Christie Company: Paramount Resources Ltd.
Date: January 11, 1999 Phone: (403) 290-3600

APPROVAL

An approved copy of this notice is to be posted at each wellsite.


Date: Jan 19/99 Signed: *James B. Baker*
9211-P33-8-1 (RE) Chief Conservation Officer

File: 1850
WID: 1850
UWT 300C 7660 20122454

Well Status

Suspended ☐
Completed ☐
Abandoned ☐

NOT RECORDED
SUR MICROFILM



APPROVAL TO ALTER CONDITION OF A WELL

This application is to be submitted to the Chief Conservation Officer at least 45 days before commencement of operations.

Well Name: Paramount et al. Boyie C-76 A Area: Fort Liard, N.W.T.
Operator: Paramount Resources Ltd. Contractor: Precision Drilling
Drilling Rig or Unit: 379 or 507 Depth: 2629m
Coordinates: Lat: 60° 15' 14.83" Long: 122° 59' 22.34"
Date ADW Issued: February 20, 1998 Date of last Operation: March 7, 1998
Elevation-KB: 433.31 m (ASL) GL: 426.8 m

TYPE OF OPERATION

Continue with whipstock drilling.

SUMMARY OF PROPOSED OPERATIONS

Drill 152 mm hole with Invert through a closed system.
Drill to TD at 3350 m MD / 3100 m TVD.
Run 114.3 m liner - interval to be determined based on wellbore conditions.
Liner will be cemented through the Ft. Simpson to 2550 m.
Five metre sample intervals to be collected from kick-off point to T.D.

Signed: *S. Maaskant* Title: Drilling and Completions Consultant
Name: Shirley Maaskant Company: Paramount Resources Ltd.
Date: November 27, 1998 Phone: (403) 290-3600

APPROVAL

An approved copy of this notice is to be posted at each wellsite.

Date: December 11, 1998 Signed: *J. M. Baker*

Chief Conservation Officer

File: 9211-P33-8-2 (RE)
UWI: 300C766020122453
WID: 1850

Well Status

Suspended ☒
Completed ☐
Abandoned ☐

MICROFILMED
SUR MICROFILM