

PARA ET AL ARROWHEAD N-65

As at February 4, 1999

KB: 574.6 m

GL: 567.9 m

Sfc Casing Landed at 480

Liner Top at 1723

Int Casing Landed at 1890

Liner Top at 2300

Liner Landed at 2529

339.7 mm, 81.1 kg/m, J-55 casing.

244.5 mm, 64.74 kg/m, L-80 casing.

177.8 mm, 38.69 kg/m, N-80 casing.

139.7 mm, 25.3 kg/m, L-80 casing.

89 mm 13.84 kg/m, L-80 tubing To Surface

89 mm X 73 mm Crossover

73 mm Pupjoints

58.7 mm 'X' Nipple

73 mm Pupjoints

Cardium on-off connector w/ 58.7 mm 'X' profile

Cardium 'PQDH' Retrievable Packer

73 mm Pupjoints

58.7 mm 'XN' Nipple w/ 57.4 mm NoGo

73 mm Pupjoints

Drop Off Sub Assembly

TCP Gun Assembly

2579 - 2581

2594 - 2601

Slave Point Perforations

2612.5

Bridge Plug

2614 - 2615

Sulphur Point Perforations

2622

Bridge Plug

2625.5 - 2630

Sulphur Point Perforations

2631.5

Bridge Plug

2632.5 - 2637.5

Sulphur Point Perforations

2639

Cement Retainer

2640.0

Sulphur Point Perforations

2640.5

2769

Cardium PWPP Bridge Plug

2777 - 2782

Nahanni Perforations

2788 - 2790

2791 - 2792

2818

Cement Squeeze Perforations

2819

Liner Landed at 2856

TD = 2925

PBTD = 2840

2821.4