

**MERLIN PETROLEUM SERVICES LTD.
DAILY GEOLOGICAL WELL REPORT
2000-01-09**

SUNCOR NETLA P16

Report To: John McCrossan
Spud Date: 1999-12-21
Gd. Elevation: 602.3
Depth @ 06:00: 2080 m
Status @ 06:00: Drilling ahead.
24 hr Progress: 34 m

Report From: John McCrossan
Telephone: 284-9583
Days from Spud: 20
K.B. Elevation: 607.0
Formation: Elk Point
Average ROP: 3 m/hr

OPERATIONS SUMMARY - Last 24 Hours

Drilled ahead to 2058 m. Tripped for bit. RIH and drilled ahead to 2080

SURVEYS

MUD PROPERTIES

Type: Visplex
Density: 1210 kg/m³
Viscosity: 61 s/L
Water Loss: 9.7 cm³/30 min
pH: 10.5
Filter Cake: mm

SAMPLE TOPS

Formation	Sample Depth	TVD	Subsea	Prognosis Subsea	Change
Tetcho Carb.	974.0	974.0	-367.0	-369.0	2.0
Trout River	1077.0	1077.0	-470.0	-469.0	-1.0
Kakisa	1142.0	1142.0	-535.0	-541.0	6.0
Redknife	1171.0	1171.0	-564.0	-570.0	6.0
Fort Simpson	1379.0	1379.0	-772.0	-778.0	6.0
Muskwa	1892.0	1892.0	-1285.0	-1288.0	3.0
Slave Point	1923.0	1923.0	-1316.0	-1316.0	0.0
Elk Point	2053.0	2053.0	-1446.0	-1447.0	1.0

FORECAST ACTIVITIES

Drill ahead to T.D. (2099 m). Circulate sample. Wiper trip. Circulate and condition hole for logging. POOH. Log with