

**MERLIN PETROLEUM SERVICES LTD.
DAILY GEOLOGICAL WELL REPORT
2000-01-10**

SUNCOR NETLA P16

Report To: John McCrossan

Report From: John McCrossan

Spud Date: 1999-12-21

Telephone: 284-9583

Gd. Elevation: 602.3

Days from Spud: 21

Depth @ 06:00: 2099 m

K.B. Elevation: 607.0

Status @ 06:00: POOH to log.

Formation: Elk Point

24 hr Progress: 19 m

Average ROP: 2.6 m/hr

OPERATIONS SUMMARY - Last 24 Hours

Drilled to 2099 m (T.D.). Wiper tripped. Condition hole. POOH to

SURVEYS

None to

MUD PROPERTIES

Type: Visplex
Density: 1220 kg/m³
Viscosity: 67 s/L
Water Loss: 10.4 cm³/30 min
pH: 10.5
Filter Cake: mm

SAMPLE TOPS

Formation	Sample Depth	TVD	Subsea	Prognosis Subsea	Change
Trout River	1077.0	1077.0	-470.0	-469.0	-1.0
Kakisa	1142.0	1142.0	-535.0	-541.0	6.0
Redknife	1171.0	1171.0	-564.0	-570.0	6.0
Fort Simpson	1379.0	1379.0	-772.0	-778.0	6.0
Muskwa	1892.0	1892.0	-1285.0	-1288.0	3.0
Slave Point	1923.0	1923.0	-1316.0	-1316.0	0.0
Elk Point	2053.0	2053.0	-1446.0	-1447.0	1.0
T.D.	2099.0	2099.0	-1492.0	-1485.0	-7.0

FORECAST ACTIVITIES

POOH. Rig up Schlumberger.