



National Energy Board



Office national de l'énergie

WELL TERMINATION RECORD

This record is submitted in compliance with Section 184 of the Canada Oil and Gas Drilling Regulations.

Well Name: Chevron et al Liard M-25 Area: Liard Basin
Grid Area: 60°25", 123°35" Field/Pool: Delineation
Interest Identifier: Nahanni Final Coordinates: Lat: 60°25'38.54"N Long: 123°35'34.00"W
Surf.Coordinates: 60°24'50.8" 123°35'12.5"
Drilling Unit: Akita Drilling Rig #48 Elevations-KB/RT 917.84 (ASL) GL/Seafloor: 910.57
Spud Date: September 29, 1999 R.R.: December 21, 1999 Total Depth: 3770m

O.D. (mm)	Weight (kg/m)	Grade	Depth Set (m KB)	Cement (m³)
508.....	192.2		11.0.....	4.5
339.7.....	101.2	K-55.....	848.7	95T Class G
244.5.....	64.94/69.9	MN-80.....	3438.1	110T Class G
.....				

PLUGGING PROGRAM

Approval of the following program was obtained by (person) from
(person) of the , by means of
..... on 19 ..

Type of Plug	Interval (m KB)	Felt	Cement (m³)
.....			
.....			
.....			
.....			
.....			

Lost Circulation/Overpressure Zones: lost circulation upon entering Nahanni, cured with conventional techniques

Equipment left on Seafloor (Describe): N/A

Provision for Re-entry (Describe and attach sketch): N/A

Cores: Type: full diameter..... Intervals: 3450.0 – 3452.0
full diameter..... 3452.0 – 3457.0

Other Downhole Completion/Suspension Equipment: 88.9mm 19.27kg/m L80 tubing landed @ 3454.35mKB, 244.5mm permanent packer set @ 3421mKB.....

CERTIFICATION

I certify on the basis of personal knowledge of operations undertaken at the above named well that the above information is accurate.

Signed: Title: Well Construction Engineer

Name: Miles Sweep, P. Eng. Date: Jan 21, 2000

Company: Chevron Canada Resources

Acknowledged by:
JMBaker

Chief Conservation Officer

Well Status

Suspended ☐

Completed ☒

Abandoned ☐

Date: Feb 2/00

File: 9211-C04-1-3

WID: 1867

UWI 300L266030123300