



WELL TERMINATION RECORD

This record is submitted in compliance with Section 184 of the Canada Oil and Gas Drilling Regulations.

Well Name: Chevron et al Liard M-25 Area: Liard Basin
Grid Area: 60°25", 123°35" Field/Pool: Delineation
Interest Identifier: Nahanni Final Coordinates: Lat: 60°25'38.54"N Long: 123°35'34.00"W
Surf. Coordinates: 60°24'50.8" 123°35'12.5"
Drilling Unit: Akita Drilling Rig #48 Elevations-KB/RT 917.84 (ASL) GL/Seafloor: 910.57
Spud Date: September 29, 1999 R.R.: December 21, 1999 Total Depth: 3770m

O.D. (mm)	Weight (kg/m)	Grade	Depth Set (m KB)	Cement (m³)
508.....	192.2		11.0.....	4.5
339.7.....	101.2	K-55.....	848.7	95T Class G
244.5.....	64.94/69.9	MN-80.....	3438.1	110T Class G
.....				

PLUGGING PROGRAM

Approval of the following program was obtained by (person) from
(person) of the, by means of
..... on 19 ..

Type of Plug	Interval (m KB)	Felt	Cement (m³)
.....			
.....			
.....			
.....			
.....			
.....			

Lost Circulation/Overpressure Zones: lost circulation upon entering Nahanni, cured with conventional techniques
Equipment left on Seafloor (Describe): N/A
Provision for Re-entry (Describe and attach sketch): N/A
Cores: Type: full diameter..... Intervals: 3450.0 – 3452.0
full diameter..... 3452.0 – 3457.0
Other Downhole Completion/Suspension Equipment: 88.9mm 19.27kg/m L80 tubing landed @ 3454.35mKB, 244.5mm permanent packer set @ 3421mKB.....

CERTIFICATION

I certify on the basis of personal knowledge of operations undertaken at the above named well that the above information is accurate.

Signed: Title: Well Construction Engineer
Name: Miles Sweep, P. Eng. Date: Jan 21, 2000
Company: Chevron Canada Resources

Acknowledged by:
Chief Conservation Officer

Well Status

Suspended ☐
Completed ☒
Abandoned ☐

Date: Feb 2/00

File: 9211-C04-1-3
WID: 1867
UWI 300L266030123300