

141139

DAILY CHECKS	OPR.	R.M.
(1) Daily Walk Around Inspection	Initial	Initial
(2) Detailed Inspection-Weekly (using checklist)	Initial	Initial
(3) H/S Signs Posted (If required)	Initial	Initial
(4) Well License & Stick Diagram Posted	Initial	Initial
(5) Flare Lines Staked	Initial	Initial
(6) BOP Drills Performed	Initial	Initial
(7) Visually inspect BOP's - Flarelines & Degasser Lines	Initial	Initial
(1) Rig Site Health and Safety Meeting (one/month)		Initial
(2) C.A.O.D.C. Rig Safety Inspection Checklist (one/month)		Initial
(3) Mast Inspection Before Raising or Lowering		Initial
(4) Crown Saver Checked		Initial
(5) Motor Kills checked		Initial

[illegible]

TIME - HRS	CODE NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	TOTALS	SHALE SHAKER(S)		RENTALS/SERVICES			MORN	DAY	EVE	
	OPER.	RIG UP & TEAR DOWN	DRILL ACTUAL	REAMING	CORING	COND. MUD & CIRC.	TRIPS	RIG SERVICE	REPAIR RIG	CUT OFF DRILL LINE	DEV SURVEY	WIRE LINE LOGS	HAJN CASE & CEMENT	WAIT ON CEMENT	NIPPLE UP & G.P.	TEST B.O.P.	DRILL STEM TEST	PLUG BACK	SQUEEZE CEMENT	FISHING	DIR. WORK	SAFETY MTG.															
	MORN.																																				
	DAY																																				
EVE																																					
TOTAL																																					
																														SCREENS CHANGED ☐ YES ☐ NO							
																														TOP	TOP						
																														MIDDLE	MIDDLE						
																														BOTTOM	BOTTOM						

METRES DRILLED						TIME LOG				DETAILS OF OPERATION IN SEQUENCE AND REMARKS			
FROM	TO	D&D PM-R CORE-C	ROTARY R.P.M.	WT-ON BIT (1000 daN)		FROM	TO	ELAP. TIME	CODE NO.				
						0000	0800	8		WAIT ON DAYLIGHT + WAIT ON TRUCKS - FINISH CLEANING			
CIRCULATION PRESSURE (kPa)	PUMP NO. 1		PUMP NO. 2										
	LINER SIZE (mm)	S.P.M.	LINER SIZE (mm)	S.P.M.									
REDUCED PUMP SPEED													
	@		@										
DEVIATION SURVEY													
DEPTH (m)	DEVIATION (°)		DIRECTION										
NOTES													
DRILLER SIGNATURE						BOILER HRS. RAN ph STACK TEMP.		MAXIMUM EXPERIENCED HOOKLOAD		SAFETY TOPIC		M.A.C.P.	

METRES DRILLED						TIME LOG				DETAILS OF OPERATION IN SEQUENCE AND REMARKS			
FROM	TO	DR-G RM-R CORE-G	ROTARY R.P.M.	WT ON BIT (1000 daN)		FROM	TO	ELAP. TIME	CODE NO.				
						0800				MOVE AKITA #14 FOR AEC FROM CARCAJOU 0-47 to NORMAN WELLS WRACK SITE w/6 PENTASTAR TRUCKS			
CIRCULATION PRESSURE (kPa)	PUMP NO. 1		PUMP NO. 2										
	LINEAR SIZE (mm)	S.P.M.	LINEAR SIZE (mm)	S.P.M.									
REDUCED PUMP SPEED													
	@		@							WRACK RIG			
DEVIATION SURVEY													
DEPTH (m)	DEVIATION (°)		DIRECTION										
NOTES													
DRILLER SIGNATURE						BOILER		MAXIMUM EXPERIENCED HOOKLOAD		SAFETY TOPIC		M.A.C.P.	
HRS. RAN		ph	STACK TEMP.										

[illegible]

141138

[illegible]

141138

141135

LICENCE NO.: WELL NAME AND NO.: AEC WEST RENCARCAJOU 0-47

OPERATOR: AEC WEST CONTRACTOR: AKITA DRILLING

SURFACE LOCATION: UNIQUE ID.:

SIGNATURE OF OPERATOR'S REPRESENTATIVE: SIGNATURE OF CONTRACTOR'S RIG MANAGER:

DAILY CHECKS

OPR. R.M.

YEAR MONTH DAY

RIG NO. 14

FUEL @ 8:00

RIG BOILER

W E A T H E R

TEMPERATURE °C

CURRENT CONDITIONS

WIND DIRECTION

ROAD

LAST CASING TUBING OR LINER

O.D. (mm)

MIN. I.D. (mm)

kg/m

MAKE

GRADE

NO. OF JOINTS

TOTAL(m)

KB. TO CSG HEAD (m)

SET AT (m)

DC/DP SIZE (mm)

LINEAR MASS (kg/m)

GRADE

MIN. ID (mm)

TOOL JOINT (mm)

TYPE THREAD

NO. OF JOINTS

PUMP TYPE

PUMP MANUFACTURER

STROKE LTH. (mm)

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26

DRILLING ASSEMBLY (At End of Tour)

NO. BIT O.D. (mm) LENGTH

1 DIR Tools 26.00m 121 189.74m 1 X/O .47

24 D.P. STANDS 232.45m D.P. SINGLES 11.35m KELLIDOWN 11.35m TOTAL 460.26m WT.OFDC 10,000 1000 daN WT.OFSTRING 23,000 1000 daN

DRILLING ASSEMBLY (At End of Tour)

NO. BIT O.D. (mm) LENGTH

1 DIR Tools 26.00m 121 189.74m 1 X/O 121 .47

30 D.P. STANDS 290.59m D.P. SINGLES 5.95m KELLIDOWN 5.95m TOTAL 513.00m WT.OFDC 10,000 1000 daN WT.OFSTRING 23,000 1000 daN

DRILLING ASSEMBLY (At End of Tour)

NO. BIT O.D. (mm) LENGTH

1 DIR Tools 26.00m 121 189.74m 1 X/O 121 .47

35 D.P. STANDS 339.14m D.P. SINGLES 11.35m KELLIDOWN 11.35m TOTAL 566.95m WT.OFDC 10,000 1000 daN WT.OFSTRING 24,000 1000 daN

BIT RECORD

BIT NO. #1 NEW

SIZE (mm) 156

IADC CODE

MFG. SMITH

TYPE XR20TP

SERIAL NO. LX2708

JETS (mm)

DEPTH OUT (m)

DEPTH IN (m)

TOTAL METRES DRILLED (m)

TOTAL HOURS RUN

CUTTING STRUCTURE

HOLE CONDITION

HOLE DRAG

TORQUE AT BOTTOM

FILL ON BOTTOM (m)

MUD RECORD

MUD TYPE ☐ WATER BASED ☐ OIL BASED

TIME

DENSITY kg/m³

FUNNEL VIS. (S/L)

W.L. (cm²)

pH

MUD MATERIALS ADDED

PRODUCT AMOUNT X UNIT

DESILTER

CENTRIFUGE

DETAILS OF OPERATION IN SEQUENCE AND REMARKS

FROM TO DR-D RM-R CORE-C ROTARY R.P.M. WT. ON BIT (1000 daN)

465 513 0 30 10

0800 0815 1/4 24 BOP DRILL W/ CREW

0815 1545 7/2 30 DIR DRILL 156mm HOLE 465m - 513

1545 1600 1/4 10 ACCUM SURVEYS

7,000 152 120

REDUCED PUMP SPEED

DEVIATION SURVEY

DEPTH (m) DEVIATION (°) DIRECTION

486 3.3

495 2.5

508 1.5

NOTES

DRILLER SIGNATURE

HRS. RAN ph STACK TEMP. MAXIMUM EXPERIENCED HOOKLOAD SAFETY TOPIC M.A.C.P.

8 BLOWN 2x 17 LITRES

DRILLER SIGNATURE

HRS. RAN ph STACK TEMP. MAXIMUM EXPERIENCED HOOKLOAD SAFETY TOPIC M.A.C.P.

8 BLOWN 2x 19 LITRES

DRILLER SIGNATURE

HRS. RAN ph STACK TEMP. MAXIMUM EXPERIENCED HOOKLOAD SAFETY TOPIC M.A.C.P.

8 BLOWN 2x 18 LITRES

DAILY CHECKS	OPR.	R.M.
(1) Daily Walk Around Inspection	Initial	Initial
(2) Detailed Inspection-Weekly (using checkidat)	Initial	Initial
(3) HFS Signs Posted (if required)	Initial	Initial
(4) Well License & Stick Diagram Posted	Initial	Initial
(5) Flame Lines Staked	Initial	Initial
(6) BOF Drills Performed.	Initial	Initial
(7) Visually inspect BOF's - Flarelines & Degasser Lines	Initial	Initial
(1) Rig Site Health and Safety Meeting (one/crew/month)	Initial	Initial
(2) C.A.O.D.C. Rig Safety Inspection Checklist (one/mo/crew)	Initial	Initial
(3) Mast Inspection Before Raising or Lowering	Initial	Initial
(4) Crown Snivel Checked	Initial	Initial
(5) Motor Kills checked	Initial	Initial

[illegible]

M
O
R
N
I
N
G

T
O
U
R

METRES DRILLED					TIME LOG				DETAILS OF OPERATION IN SEQUENCE AND REMARKS					
FROM	TO	DRD RM-R CORE-C	ROTARY R.P.M.	WT-ON BIT (1000 daN)	FROM	TO	ELAP. TIME	CODE NO.						
308	405		49502-7		0000	0015	Y4	7	RIG SERVICE					
					0015	0030	Y4	22	B.O.P DRILL					
					0030	0745	Y4	20	DIR DRILL 222mm Hole F 308m - 405m					
					0745	0800	Y4	10	Accum Surveys.					
CIRCULATION PRESSURE (kPa) 5000 6,700 / 152 120					PUMP NO. 1 LINER SIZE (mm) S.P.M. 152 120					PUMP NO. 2 LINER SIZE (mm) S.P.M.				
REDUCED PUMP SPEED														
		@					@							
DEVIATION SURVEY														
DEPTH (m)		DEVIATION (°)		DIRECTION										
DRILLER SIGNATURE					BOILER HRS. RAN ph STACK TEMP.				MAXIMUM EXPERIENCED HOOKLOAD		SAFETY TOPIC		M.A.C.P.	
Damon Palmer.					8 BLOWN				2X 18 LITRES					

METRES DRILLED					TIME LOG				DETAILS OF OPERATION IN SEQUENCE AND REMARKS																		
FROM		TO		DR-D RM-R CORE-C	ROTARY R.P.M.	WT.OH BIT (1000 gms)		FROM	TO	ELAP. TIME	CODE NO																
415		465		D	50	4		0800	0815	1/4	7	RIG SERU															
								0815	1130	3 1/4	20	DIR. DRILL 222mm HOLE 415m-454m															
								1130	1215	3/4	5	CIRC															
								1215	1345	1 1/2	6	WIPER TRIP Flow @ 442, 402, 267, 98 IN @ 48, 276															
								1345	1430	3/4	20	DIR DRILL 222mm HOLE 454m-465															
								1430	1445	1/4	10	ACCUM SURVEYS															
								1445	1515	1/2	5	CIRC															
								1515	1600	3/4	6	HOIST TO RUN CASING Flow @ 465, 410, 248, 1200															
NOTES														✓ CROWN SAVER													
DRILLER SIGNATURE														HRS. RAN		BOILER ph		STACK TEMP.		MAXIMUM EXPERIENCED HOOKLOAD				SAFETY TOPIC		M.A.C.P.	
10000 / 11000														8				60000X 17 LITRES.									

METRES DRILLED						TIME LOG				DETAILS OF OPERATION IN SEQUENCE AND REMARKS			
FROM	TO	D&D R&A-R CORE-C	ROTARY R.P.M.	WT. ON BIT (1000 lbs)		FROM	TO	ELAP. TIME	CODE NO.				
465						1600	1630	12	6	HOLDT TO RUN CASING LAYDOWN 159mm COLLARS			
						1630	1730	1	23	LAYDOWN DIR TOOLS.			
CIRCULATION PRESSURE (kPa)	PUMP NO. 1		PUMP NO. 2			1730	1945	2 1/4	12	RIG TO + RUN CSG. (PRE JOB SAFETY MTG)			
	LINE SIZE (mm)	S.P.M.	LINE SIZE (mm)	S.P.M.		1945	2030	44	5	CIRC.			
						2030	21:30	1 0 1/2	12	Cement CSG (PRE JOB SAFETY MTG)			
						21:30	2400	25	13	W.O.C			
REDUCED PUMP SPEED										8 HRS			
	@		@			RUN 37 JSS 177.8mm, 34.14 Kg/m, JSS, STG C NEW CASING.							
DEVIATION SURVEY						TOTAL LENGTH 463.68m. LANDED @ 463.10m.							
DEPTH (m)	DEVIATION (")		DIRECTION			PUMPED 10.9T (10m³) EFG w/0.9% B139, 1.0% COC1, & 0.2% D40.							
						Disp w/9.25m³ FLOC WATER. 200m³ GOOD CEMENT RETURNS							
						@ SURFACE.							
NOTES						SLIP & CUT 11m DRILL LINE VCROWN SAUER							
DRILLER SIGNATURE						BOILER		MAXIMUM EXPERIENCED HOOKLOAD		SAFETY TOPIC		M.A.C.P.	
D. Baker						HRS. RAN		STACK TEMP.					
						8		BLOWN 2 x 21 LITRES					

141133

141132

[illegible]

141132

Form with multiple sections including: NATIONAL ENGINEERING, APR - 7 2000, METERS DRAINED, TIME LOG, DETAILS OF OPERATION IN SEQUENCE AND REMARKS, and various handwritten notes and signatures.