PARAMOUNT RESOURCES LTD.

SURFACE CASING REPORT

O.D.: 244.5 MM

WELL NAME: PARA et al MOUNT COTY LOC: I - 02 DATE: 10-25-00

JTS ON LOC	M ON LOC	CASING WT.	GRADE	RANGE	THREAD	T & C	MAKE	JTS. RUN	DEPTH LANDED	M RUN IN WELL
39	513.18	53.57	J-55	3	LT&C		IPSCO	39	514.12	513.18

SHOE: MAKE:	WEATHERFORD	TYPE:	THREADED	LENGTH, M	0.50
COLLAR: MAKE:	WEATHERFORD	TYPE:	THREADED	LENGTH, M	0.44
LANDING JOINT (WHEN USED) LENGTH, M				LENGTH, M	
OVERALL LENGTH OF CASING STRING, M				TOTAL, M	514.12
METERS UP FROM K.B. (SUBTRACT)		0.3 M			0.30
SETTING DEPTH: LOG:		DRILLER:	514.12		513.82
SHOE JOINT: OVERALL:	M (SUBTRACT)			SHOE JOINT	
FLOAT COLLAR: LOG:	M	DRILLER:	514.12 M		513.82
K.B. TO CASING FLG:	5 M	CUT OFF:	6 M		

CENTRALIZERS & TURBOLIZERS:

MAKE: CARDIUM NUMBER 7

POSITIONS:

1,2,4,7,11,16,21.

SCRATCHERS:

MAKE: CARDIUM NUMBER 12

POSITIONS:

JOINTS WELDED:

REMARKS:

LANDED ON BOTTOM.
FLOAT & SHOE THREAD LOCKED.

OPERATORS REP: AL IRONSIDE

SURF CSG RPT