

# Ryan Energy Technologies Inc.

Comp:	CANADIAN FOREST OIL LTD.
LSD:	GRID AREA N60/40 W123/30
Job #:	3134
Co.Rep:	CLAUDE LEBEUF / CALLEN PICHE
Depth in:	2538.00
Depth out:	
Date In:	11/28/00
Date Out:	

**BHA:#**  
**47**

ITEM	DESCRIPTION	VENDOR	SERIAL #	OD/D	CONN	LENGTH	TOTAL L
1	HP61A 1X11.1, 2X11.9	REED	9284	P 311.2	6 5/8 Reg	0.36	0.36
1	BIT SUB	w / FLOAT		B 226	6 5/8 Reg	0.84	1.20
1	Restrictor Sub	Ryan	1622804	B 103	7 H90	0.62	1.82
1	Monel MWD	Ryan	2122805	P 228	7H90	9.43	11.25
1	Isolation Sub	Ryan	47-001	B 72	7H90	2.37	13.62
1	NMDC	Ryan	17003	P 228	7H90	9.32	22.94
1	Shock Sub	Faster	10572	B 103	7H90	3.81	26.75
1	3 POINT REAMER		1516	P 227	7H90	2.59	29.34
1	228mm DC	Akita		B 74	7H90	9.02	38.36
1	3 POINT REAMER		10056	P 227/311	7H90	2.43	40.79
2	228mm DCs	Akita		B 73	7H90	18.67	59.46
1	Jar	Faster	10883	P 223	7H90	5.63	65.09
5	228mm DCs	Akita		B 64	7H90	45.98	111.08
1	X/O Sub	Akita		P 223	7H90	1.40	112.48
17	178mm DCs	Akita		B 74	5H90	160.44	272.92
1	X/O Sub	Akita		P 177	5H90	1.31	274.23
6	HWDP	Akita		B 76	4.5IF	55.12	329.35
				P 159/170	5H90		
				B 81	4.5IF		
				P 114	4.5IF		
				B 76	4.5IF		

B.T.B:	N/A	Meterage:	W kg/m3	1655	Rlg:	AKITA # 58
DAO:	N/A	Drllg Hrs:	Q m3/min	2.0	Pump #1	F 1000
B.T.S:	6.7	ROP:	spm:	200	Liner / Stk:	127 / 254
INC:		Bit W:	PP On:		Pump #2	F 1000
AZM:		WOB:	PP Off:	11,000	Liner / Stk:	127 / 254

**Comments**

BIT CONDITION:

CIRCULATING HOURS: