



OUTGOING FACSIMILE - MESSAGE - À EXPÉDIER

TO / À	Date: <i>Feb 11 2008</i>	Number of Pages (Incl cover) / Nombre de pages (incluant la couverture): <i>3</i>
	Message To / Destinataire: <i>Bob Mahnie</i>	Facsimile Number / Numéro de télécopier: <i>867-669-2409</i>
	Organization / Organisation: <i>DIAND, YK</i>	
F R O M / D E	Message from / Expéditeur: <i>Jenna Wahl</i>	Telephone Number / Numéro de téléphone: <i>403-299-3192</i>
	Branch / Direction: OPERATIONS BUSINESS UNIT	Facsimile Number / Numéro de télécopier: (403) 292-5876

Comments/Commentaires:

*Anadarko Netlor approval for
A-68*

Exploratory ☒Delineation ☐Development ☐Service ☐

APPROVAL TO DRILL A WELL

This application is submitted under Section 82 of the *Canada Oil and Gas Drilling Regulations*. When approved under Section 83 of the Regulations, it is the requisite approval for the commencement of drilling operations.

Well Name: ANADARKO NETLA A -68
Operator: ANADARKO CANADA CORPORATION Program No.: N/A
Contractor: AKITA DRILLING LTD. Interest identifier: _____
Drilling Rig or Unit: 55 Estimated Well Cost: \$3,000,000
Location-Unit: A Section: 68 Grid 60° 50' 122° 30'
Coordinates: Lat.: 60° 47' 07.4" N Long.: 122° 41' 38.9"
Area: NETLA Field / Pool: NPW
Elevation-KB/RT: 653.5 m (ASL) GL / Seafloor: 648.7 m
Approx. Spud Date: January 15, 2002 Est. Days on Location: 25
Anticipated Total Depth: 2404 m Target Devonian Slave Point

EVALUATION PROGRAM

Ten-metre sample N/A
Five-metre sample Surface Casing Shoe (550 m) to Total Depth
Canned sample intervals -
Conventional cores at -
Logs and Tests SP Induction Resistivity, CNL-LDT-PEF, Sonic, GR, CAL

CASING AND CEMENTING PROGRAM

O.D. (mm)	Weight (kg/m)	Grade	Setting Depth (m KB)	Cementing
<u>406.4 mm</u>	<u>Conductor Pipe</u>		<u>± 20 mKB</u>	<u>Pressure</u>
<u>244.5 mm</u>	<u>59.6 kg/m</u>	<u>K-55</u>	<u>±550 mKB</u>	<u>550 - Surface</u>
<u>178 mm</u>	<u>38.7 kg/m</u>	<u>L-80</u>	<u>±1957 mKB</u>	<u>1957 - 500 m</u>

B.O.P. Equipment: 279.4 mm x 21 mPa BOP Stack (1 - Annular, 1 - Double - Pipe and Blind, 1 - Single - Pipe), 1 - 34.5 mPa Double Gut Choke Manifold.

Other Information: Request Authorization to Set Surface Casing at 550 m Based on Suncor Netla K-77.

Signed: Stan Weich Title: Senior Drilling Officer
Responsible Officer

Name: Stan Weich Company: Anadarko Canada Corporation
Date: November 30, 2001 Phone: (403) 231-0190

APPROVAL

An approved copy of this notice is to be posted at each wellsite.

Date: Feb 11/02
File: 9211-A069-1-1
WID: 1936
UWI: 300A686050122300

Signed: T. Baker
Chief Conservation Officer

BOARD
NCH
DEC 03 2001