

PARAMOUNT ANADARKO BOVIE F-66

As Drilled (Rig Released: February 21, 2002)

ACTUAL LOG TOPS

PRIMARY *

Ft. St. John Group

Log Depth

0

Fantasque
Upper Flett
Lower Flett

n/p
583
772

Shunda
Pekisko
BANFF

977
1142
1175

EXSHAW

1596

KOTCHO

1675

TETCHO

2050

KAKISA

2154

FT. SIMPSON

2178

MUSKWA

2851

SLAVE PT **

2871

WATT MTN.

2971

SULFUR PT.**

2976

Muskeg

3061

NAHANNI *

3069

HEADLESS

3149

LANDRY

3159

ARNICA

3224

Bear Rock

3287

Total log Depth

3353

DEPTH

HOLE SIZES

CASING SIZES

Surface Casing:
339 mm, 81.1kg/m, K55
Cement: 50 tonnes
0:1:0 "G"(10m3 returns)

502

444.5

1098

311

1st Intermediate :
244.5 mm, 53.6 kg/m
J-55 LT&C
Cement: 35 tonnes
0:1:0 "G" plus add.

2759 Top of Liner

2870

222

2nd Intermediate :
177.8, 38.69 kg/m L80
Cement: 41 tonnes
Thermal 40

3368

152

Liner:
114.3, 17.26 kg/m L80
Cement: 10 tonnes
Thermal 40