

String Details

ANADARKO ARROWHEAD RIVER I-75

ORIG COMPLETION 25/01/03

<no data>

String Name	Installed Date	String Status	Length	String Landed Depth	Suspension Point	String Depth Correction
SURFACE CASING	31/01/03	INSTALLED	655.3 m	655.3 m		0.0 m
INTERMEDIATE CASING	15/02/03	INSTALLED	2,590.3 m	2,583.6 m		0.0 m
PACKER ASSEMBLY	28/02/03	INSTALLED	2,559.5 m	2,559.5 m	SURFACE EQUIPMENT	0.0 m

SURFACE CASING Status: INSTALLED Install Date: 31/01/03 String Length: 655.3 m

# of Joints	Name	Length	Min. I.D.	Nom. Size	Grade	Weight	Depth
47	CASING JOINT(S)	640.460 m	0.00 mm	244.48 mm	L80	59.53 kg/m	0.00 m
1	CASING FLOAT COLLAR	0.380 m	0.00 mm	244.48 mm	L80	59.53 kg/m	640.46 m
1	CASING JOINT(S)	13.990 m	0.00 mm	244.48 mm	L80	59.53 kg/m	640.84 m
1	CASING FLOAT SHOE	0.470 m	0.00 mm	244.48 mm	L80	59.53 kg/m	654.83 m

INTERMEDIATE CASING Status: INSTALLED Install Date: 15/02/03 String Length: 2,590.3 m

# of Joints	Name	Length	Min. I.D.	Nom. Size	Grade	Weight	Depth
1	CASING JOINT(S)	14.120 m	0.00 mm	177.80 mm	L80	38.69 kg/m	-6.67 m
1	CSG HANGER/ STUB CSG	1.490 m	0.00 mm	177.80 mm	L80	38.69 kg/m	7.45 m
188	CASING JOINT(S)	2,545.840 m	0.00 mm	177.80 mm	L80	38.69 kg/m	8.94 m
1	CASING FLOAT COLLAR	0.330 m	0.00 mm	177.80 mm	L80	38.69 kg/m	2,554.78 m
2	CASING JOINT(S)	28.280 m	0.00 mm	177.80 mm	L80	38.69 kg/m	2,555.11 m
1	CASING FLOAT SHOE	0.210 m	0.00 mm	177.80 mm	L80	38.69 kg/m	2,583.39 m

PACKER ASSEMBLY Status: INSTALLED Install Date: 28/02/03 String Length: 2,559.5 m

# of Joints	Name	Length	Min. I.D.	Nom. Size	Grade	Weight	Depth
1	TUBING HANGER	0.280 m	153.90 mm	177.80 mm	L80	43.16 kg/m	0.00 m
1	TUBING JOINT(S)	0.280 m	0.00 mm	88.90 mm		0.00 kg/m	0.28 m
1	TUBING JOINT(S)	9.050 m	74.75 mm	88.90 mm	L80	11.46 kg/m	0.56 m
1	PUP JOINT	0.450 m	74.75 mm	88.90 mm	L80	11.46 kg/m	9.61 m
1	PUP JOINT	2.360 m	74.75 mm	88.90 mm	L80	11.46 kg/m	10.06 m
1	PUP JOINT	3.030 m	74.75 mm	88.90 mm	L80	11.46 kg/m	12.42 m
268	TUBING JOINT(S)	2,529.460 m	74.75 mm	88.90 mm	N80	11.46 kg/m	15.45 m
1	ON-OFF TOOL	0.630 m	162.89 mm	177.80 mm	H40	25.30 kg/m	2,544.91 m
1	PACKER	0.770 m	0.00 mm	219.08 mm		35.72 kg/m	2,545.54 m
1	CROSSOVER	0.110 m	0.00 mm	19.05 mm		0.00 kg/m	2,546.31 m
1	PUP JOINT	3.000 m	0.00 mm	60.33 mm		0.00 kg/m	2,546.42 m
1	PROFILE NIPPLE	0.280 m	48.29 mm	60.33 mm	L80	6.99 kg/m	2,549.42 m
1	TUBING JOINT(S)	9.620 m	48.29 mm	60.33 mm	L80	6.99 kg/m	2,549.70 m
1	RE-ENTRY GUIDE	0.200 m	48.29 mm	60.33 mm	L80	6.99 kg/m	2,559.32 m