

9211-P33-4-2

Off copy

WELLSITE GEOLOGICAL REPORT

PARAMOUNT ET AL CAMERON L - 47

Lat. $60^{\circ} 06' 31.55''$ North
Long. $117^{\circ} 30' 46.21''$ West.

Hugh Corkin.
Calgary, Alberta.
March 8, 1989.

SOUTHERN CROSS GEOLOGICAL CONSULTING LTD.

~~HUGH CORKIN - GEOLOGICAL CONSULTANT~~

P.O.Box 6983, Station D, Calgary, Alberta. T2P 2G2.

March 8, 1989

Paramount Resources Ltd.,
4100 First Canadian Centre,
350 - 7 Avenue S.W.,
Calgary, Alberta. T2P 3W5.

Dear Sirs:

Re: Paramount et al Cameron L-47

Enclosed herewith is a summary of all pertinent geological data from the subject well.

The well, which was spudded at 1300 hours February 11, 1989, was drilled to a total depth of 1565 metres into the Pre-Cambrian Granite. The prime objectives were the Upper Devonian, Slave Point, and the Middle Devonian, Keg River Dolomite. The Middle Devonian Sulphur Point reservoir existed as a secondary objective. No cores were cut but a total of five drillstem tests were run, four after Wireline Logs were obtained.

The well was drilled with Air from the Surface Casing Shoe (390.05m) to the top of the Wabamun, which was found to be water saturated. At 496 metres, the top of the Wabamun, the system was converted to Foam (soap detergent) and drilled down to 1165 metres which was approximately the limit for the compressors. No cuttings were available between 495 metres and 1165 metres while Foam was being utilized to clear the bore hole. The hole was then converted to a regular "chem-gel" mud system at 1165 metres, some distance above the Beaverhill Lake and drilled to total depth (1565 metres).

The first drillstem test was run during penetration to evaluate the stringers of porosity in the Sulphur Point which exhibited fair to good intercrystalline and vuggy porosity in association with indications of slight condensate staining. The test produced a recovery which included 187 metres mud cut water and 45 metres of drilling mud confirming the formation to be water saturated. The remaining four drillstem tests were run after Wireline Logs had been evaluated. One of these tests resulted in a misrun, two


confirmed the Keg River to be oil bearing and the fourth indicated the Slave Point had very limited reservoir qualities. The 85 metres of Inhibitor cut mud obtained from the Slave Point test is inconsistent with porosity observed in the drill cuttings and what was indicated on the mechanical logs, leading to the assumption that this formation had been badly damaged by filtrate invasion.

The data obtained from the drillstem tests, ditch cuttings, gas detector and wireline logs justified running production casing to total depth. The well is currently classified as Standing, waiting on evaluation, and will be completed at some future date. The rig was released at 0530 hours March 6, 1989.

Wellsite geological supervision was performed by Hugh Corkin under the direction of Mr. Glenn A. Downey of Paramount Resources Ltd.

Thank you for the opportunity of serving your Company.

Yours very truly,


Hugh Corkin. P.Geol.

INDEX

I GENERAL

Well Data Summary
Authority to Drill a Well
Drilling Prognosis
Drilling Program

II GEOLOGICAL DATA

Electric Log Tops
Wellsite Lithology Description
Composite Well Log and Drilling Time Log (Pocket)
Gas Reports
Geological Summary

III DRILLING AND ENGINEERING

Daily Drilling Reports
Drillstem Test Summaries
Deviation Surveys
Drilling Bit Summary

IV REPORTS BY THIRD PARTY SERVICES

Schlumberger: Polsar Induction-SFL (Pocket)
Schlumberger: Borehole Comp. Sonic Log (Pocket)
Schlumberger: Comp. Neutron-Litho-Density Log (Pocket)
Schlumberger: Microlog (Pocket)
Schlumberger: Velocity Monitor Log (Pocket)
Schlumberger: Cyberlook Log (Pocket)

SOUTHERN CROSS GEOLOGICAL CONSULTING LTD

WELL DATA SUMMARY

Well Name: PARAMOUNT ET AL CAMERON L - 47
Location: Lat. 60° 06' 31.55" N, Long. 117° 39' 18.63" W
Operator: Paramount Resources Limited
Drilling Licence: No. 1396
Elevation: K.B. 723.00m Ground 719.32m
Co-ordinates: As above.
Total Depth: Driller 1565m Logger 1562.5m
Status: Standing waiting on evaluation.
Spud Date: 1300 hours February 11, 1989
Rig Released: 0530 hours March 6, 1989
Hole Size: 311 mm to 390.05 m; 222 mm to 1565 m; --- mm to ---
Surface Casing: Ran 30 joints of 244.5 mm, 53.57 kg/m
J-55 LT&C Prudential casing (Total of 392 m)
Landed at 390.05 m K.B., cemented with 31 tonnes
of Class "G" cement + 3% CaCl₂. Plug down at 1515 hrs
February 14, 1989.
Production Casing: Ran 121 joints of 139.7 mm, 20.38 kg/m
J-55 ST&C Ipsco casing. (Total of 1564.3 m)
Landed at 1562.5 m K.B., cemented with 12 tonnes
of 0-1-0 cement + 1% NSL + .01% SPC

Cores: NONE Core # ____ ____ Rec. _____ m _____ (Formation)
Core # ____ ____ Rec. _____ m _____ (Formation)
Core # ____ ____ Rec. _____ m _____ (Formation)
Core # ____ ____ Rec. _____ m _____ (Formation)

Tests: Drillstem Test # 1 1408m - 1430m Sulphur Point
(Interval) (Formation)
Recovered 187m Mud Cut Water, 45m Clobbered Drilg Mud
Drillstem Test # 2 1486m - 1510m Keg River
(Interval) (Formation)
Recovered 1 cubic metre very gassified oil
Drillstem Test # 3 1510m - 1534m Keg River
(Interval) (Formation)
Recovered 108m total fluid. 18m Inhibitor, 45m O.C.M.
45m brackish oil.
Drillstem Test # 4 1335m - 1359m Slave Point
(Interval) (Formation)
Recovered 72m Inhibitor Cut Mud. Misrun.
Drillstem Test # 5 1335m - 1359m Slave Point
(Interval) (Formation)
Recovered 85m Inhibitor Cut Mud
Drillstem Test # _____
(Interval) (Formation)
Recovered _____

Logs: Schlumberger:-
Phasor Induction - SFL
1:600 390 m to 1560.7 m; 1:240 390 m to 1560.7 m
Borehole Compensated Sonic Log
1:600 390 m to 1551.2 m; 1:240 390 m to 1551.2 m
Compensated Neutron-Litho-Density Log
1:600 390 m to 1562.5 m; 1:240 390 m to 1562.5 m
Other Logs listed under the heading "Additional Info"

Abandonment Plugs: Plug # _____ with _____ tonnes of
(Interval)
NONE

Felt at _____ m after _____ hours

Plug # _____ with _____ tonnes of
(Interval)

Felt at _____ m after _____ hours

Plug # _____ with _____ tonnes of
(Interval)

Felt at _____ m after _____ hours

Plug # _____ with _____ tonnes of
(Interval)

Felt at _____ m after _____ hours

Plug # _____ with _____ tonnes of
(Interval)

Felt at _____ m after _____ hours

Drilling Contractor: Sierra Drilling Limited Rig No. 2

Ivan LeBlanc Toolpusher

Wellsite Geologist: Hugh Corkin

Wellsite Engineer: Michael Cholach

Additional Information:

Schlumberger Logs continued:-

Microlog 390m - 1556m; Cyberlook 1310m - 1562.5m;

Velocity Survey 390m - 1563.5m.

This well was drilled with Air from the Surface Casing Shoe (390.05m)
to 1165m. The well was then converted to mud and drilled to Total
Depth (1565m).



Canada Oil and Gas
Lands Administration

Administration du pétrole
et du gaz des terres du Canada

D.A. 1396

Nova Scotia Newfoundland Gulf of St. Lawrence	<input type="checkbox"/> West Coast <input type="checkbox"/> Northern <input type="checkbox"/> Hudson Bay	<input type="checkbox"/> Exploratory <input checked="" type="checkbox"/> Development <input type="checkbox"/> Drillneation <input type="checkbox"/> Service
---	---	--

AUTHORITY TO DRILL A WELL

APPLICATION

This application is submitted with Section 82 of the Canada Oil and Gas Drilling Regulations. When approved under Section 83 of the Regulations, it is the requisite authority for the commencement of drilling operations.

Well Name in Full: **PARAMOUNT ET AL. CAMERON L-47**
 Operator: **PARAMOUNT RESOURCES LTD.** Drilling Program No.: **N/A**
 Contractor: **SIERRA DRILLING LTD.** Permit or Lease No.: **N/A**
 Drilling Rig or Unit: **RIG #2** Estimated Well Cost: **LESS THAN ONE (1) MILLION DOLLARS**
 Location-Unit: **L** Section: **47** Grid Area: **60 10' 117 30'**
 Coordinates: Lat: **60° 06' 31.55" N** Long: **117° 39' 18.63" W**
 Area: **CAMERON HILLS** Field/Pool: **N/A**
 Elevation /KB: **723.33** (ASL) Substrat: **GROUND** **719.32** (ASL)
 Approx. Spud Date: **89-02-10** Estimated Days on Location: **25**
 Anticipated Total Depth: **1528 m KB** Target Horizon(s): **SLAVE POINT**
 UWI: **300L476010117300** **SULPHUR POINT**

EVALUATION PROGRAM

Ten-metre sample Intervals **N/A**

Five-metre sample Intervals **FROM UNDER CONDUCTOR CASING TO T.D.**

Canned sample Intervals **AT 10 M. INTERVALS FOR GEOCHEMICAL ANALYSIS**

Conventional cores at **NOT ANTICIPATED**

Logs and Tests **AS SPECIFIED IN DRILLING PROGRAM: VELOCITY SURVEY, DIL/CDL-CNS-GR, TESTS TO CONDUCTED ACROSS ZONES INDICATING POTENTIAL HYDROCARBONS. (IE TARGET ZONES)**

CASING AND CEMENTING PROGRAM

Setting Depth

O.D.	Weight:	Grade:	m KB	Cementing Program (Volumes):
244	53.57	J-55	390 m	CLASS G 100% EXCESS + 2% CACL
139.7	20.83	J-55	1528 m	CLASS G + 0.75% T-10.20% EXCESS

PLEASE REFER TO DETAILED DRILLING PROGRAM

.....
 B.O.P. Equipment: **ONE (1)**

..... **2000 ft**

..... **C/V**

Other Information:

..... **346.1**

.....

.....

Sign:

D

Department of Energy
Minerals and Resources
Ministère de l'Énergie
des Mines et des Ressources

CAMERON HILLS

GEOLOGICAL PROGNOSIS

SP 253 LINE 84-28

PARAMOUNT ET AL CAMERON L-47

Elevations: Ground: 722.00 (estimate) K.B.: 723.0 m

	<u>Sub-Sea</u>	<u>Drilling Depth</u>	
Wabamum	+ 235 m	491.0 m	<u>493 m</u>
Slave Point	- 614 m	1,340.0 m	<u>1342 m</u>
Watt Mountain		1,390.0 m	<u>1392 m</u>
Bistcho-Sulphur Point		1,400.0 m	<u>1402 m</u>
Muskeg		1,415.0 m	<u>1417 m</u>
Keg River		1,495.0 m	<u>1497 m</u>
Chinchaga		1,560.0 m	<u>1562 m</u>
Pre-Devonian		1,604.0 m	<u>1606 m</u>
T.D.		1,620.0 m	<u>1622 m</u>

Testing during penetration at decretion of the wellsite geologist.

Suggested Logs: DILL T.D. - Surface Casing
 CNL-FDC T.D. - Surface Casing
 VELOCITY SURVEY T.D. - Surface Casing
 COMPENSATED
 SONIC NEUTRON T.D. - Surface Casing
 MICROLOG T.D. - Surface Casing

Wellsite Geologist:

DETAILED DRILLING PROGNOSIS

Well Name: Paramount et al Cameron B-8

Location: Coordinates Latitude $60^{\circ} 10' 06.80''$ N
Longitude $117^{\circ} 30' 46.21''$ W

And

Well Name: Paramount et al Cameron L-47

Location: Coordinates Latitude $60^{\circ} 10' N$
Longitude $117^{\circ} 30' W$ Approximately

I GENERAL

Business

Mobile/Home

a) Contractor: Sierra Drilling (403) 526-0489

Toolpusher: Ivan LeBlanc XJ8-7257

b) Field Reps: Southridge 263-3035 (24 Hours)

Operational: Michael Cholach XJ4-2477

Geological:

c) Reports & Logs: Daily drilling reports are to be phoned in to Paramount by 08:30, after which the report shall be faxed to C.O.G.L.A. in Yellowknife by Paramount - Calgary Office. Tour Sheets shall be submitted to the Chief as per S 174(2). Geological reports, describing lithology and any other pertinent information, shall be submitted to C.O.G.L.A. in Yellowknife on a weekly basis S 179 (1), (2).

d) Direction to Lease: At the intersection of the MacKenzie Highway and Alberta - N.W.T. border turn west (left hand turn). Follow this road for approximately 30 km. The Camp will be just to the right of the access road. From the campsite turn west (left hand turn) and follow the access road about 0.5 km to the drill site.

- e) Credit Card No. A.F.E. No.
- f) A geograph is to be used and charts inserted into the drillfield file.
- g) One copy of the tour sheet to be sent to the Chief by Paramount Calgary Office and one inserted into the field file.
- h) Notify the Chief and Paramount 24 hours prior to spud.

II SURFACE HOLE

- a) Cellar: 0.9 m x 1.8 m diameter, drainage from the cellar will be made possible with the use of a 460 mm diameter culvert from the cellar to the drilling sump.
- b) Conductor Pipe: The rathole drilling contractor shall drill and set approximately 25 m of 346.1 mm conductor pipe. In accordance with S 106(1)(a) a diverter system shall be installed.
- c) Hole Size: 311 m hole, form surface to 390 m.
- d) Casing: In accordance with sections 69 and 70(1)C surface casing will be set at 380 m and cemented to surface. Centralize shoe joint, third joint and fifth joint.

<u>Size</u>	<u>Interval</u>	<u>Mass</u>	<u>Grade</u>	<u>Connection</u>
244.5	Surface 390 m	53.57	K-55	ST & C

Refer to the cementing program for a detailed description of the cementing procedure.

Wait on cement a minimum of 12 hours. Cut off casing and weld on the following casing barrel: ODS 21.0 MPa, 279.5 mm x 244.5 mm Slip on Bowl c/w 2 x 50.8 m 34.5 MPa EFSO Flanged Casing valves. Nipple up BOP (detailed diagram enclosed in section seven of this report). Pressure test and function

test BOP pursuant to sections 60 and 105 as stated in the Regulations.

III MAIN HOLE

- a) Hole Size: 222 mm 390 m to 1528 mKB (estimated).
- b) Leak Off Test: After drilling out the shoe, drill 5 m of new hole and perform a leak off test in accordance with S 122(2) of the "Regulations". Note results and record in tour book. Post maximum hold back pressure in the dog house and at the manifold.
- c) Bits: Drill out utilizing a FDT or equivalent and increasing hardness to J-22 etc. as per consultant's discretion. Review nearby bit records for optimum selection.
- d) Drilling Fluid: Refer to the mud program for a detailed description of the drilling fluid system.
- e) Deviation: Deviation surveys will be taken in accordance with section 128 (1)(2) of the Regulations.
- f) Pressure Testing: As required by S 116 (1)(c) of the Regulations, casing is to be pressure tested once every 1000 rotating hours.
- g) Samples: Samples shall be taken at 5 m intervals beginning at surface. These drill cuttings will be collected in accordance with Section 223(1).
- h) Total Depth: The total depth as been tentatively set at 1528 mKB (estimated).
- i) Downhole Tools: Use shock sub on main hole while drilling our the shoe through to T.D.
- j) Logging: DIS SFL INDUCTION LATERLOG

1:240 - Logarithmic Scale - T.D. to surface casing shoe.
1:600 - Linear Scale - T.D. to surface casing shoe.
Resistivity Scale: 0 - 50 ohm - meters.
Conductivity Scale: 0 - 500 - 1000 millisiemens/m.
SP: Possible 10 - 15 millivolt scale per division.

CNL-FDC

1:240 - T.D. to surface casing.
Roll #1 - 1:240.
Bulk Density - 1000 - 3000 kg/m³ with correction curve.
Gamma Scale - 0 - 150 API units.
Roll #2 - 1:240.
Limestone porosity scale:
Run a repeat at T.D. (memorizer in).

BHCS-GRC

1:240 T.D. to surface casing shoe.
1:600 T.D. to surface casing shoe.
Using standard S.I. scales.

MICROLOG

1:240 T.D. to surface casing shoe.

VELOCITY SURVEY

Note: Logs to be run and scales to be used may be redetermined upon reaching T.D. subject to prevailing hole conditions and interpretation of sample lithology logs.

FLUID SAMPLES AND ANALYSES

Three one litre mud samples are to be caught at 15 minute intervals for Rm and Rmf measurements, while circulating prior to logging.

k) Mud Logging:

A mud logging unit will be on location and available to begin gas detection as specified by the Calgary Office (pursuant to S 75(3)(e), S 1900). This facility has the capability to:

- a) Measure the methane and total gas from 0 - 100% gas in air.
- b) Accurately record gas readings in air.

c) Ascertain the presence of H_2S gas.

In addition to the above mentioned, a hydrocarbon log will furnish the following information:

- a) Measure of total gas from the drilling fluid.
- b) Chromotographic analysis of hydrocarbons in the mud.
- c) A record of the amount of all combustible gases and the amount of methane from the drilling fluid.
- d) An interpretive lithology with associated drilling data and hole conditions.

1) Testing:

Primary zones of interest are the Slave Point and Sulphur Point formations. DST's will only run if called by Calgary Office. Run bottom hole test with dual packers, safety joint, jars, pump out sub, extra recorder and bottom hole sampler for maximum information. Report all flow rates and any water salinity. Times to be given by Calgary Office. FSI to 1 1/2 times FF. Measure BHT. Samples to be caught at top, middle and bottom of recovery and sent immediately to Chemex Labs. Water resistivity measurement required. Ensure all information on sample bottles. After log evaluation if more than one test anticipated test utilizing inflatable packers.

m) Abandonment:

If the well proves to be non-productive the abandonment procedure will be determined by the Calgary Office after consultation with the Chief Conservation engineer (pursuant to section 129 and section 203 - 216 inclusive of the regulations).

A suggested abandonment procedure includes running three (3) plugs in the manner described below:

Plug #1 - Run a bottom plug of Class "G" to 2% $CaCl_2$ to cover the interval from total depth to 100 m above total depth.

Plug #2 - run a 100 m plug of Class "G" + 3% $CaCl_2$ across the porous zones. Run in with drill pipe and tag the top of the plug.

Plug #3 - Run and set a 60 m plug of Class "G" + 3% CaCl_2 , cementing 30 m below and 30 m above the 244 mm surface casing shoe.

Plug #4 - Pull up hole to the 25 m mark and run Permafrost cement to surface.

n) Casing:

Make 15 stand dummy trip and circulate a minimum of 1 hour prior to cementing, or until hole is circulated clean. The annular velocity with 139.7 mm casing cannot exceed 40 m/min while circulating the hole clean.

Casing string:

<u>Size</u>	<u>Interval</u>	<u>Mass</u>	<u>Grade</u>	<u>Connection</u>
139.77	0 - 1528 m	20.83 kg/m	J-55	ST & C

Placement of scratchers and centralizers will be determined by the Calgary Office prior to running casing.

Well Name: PARAMOUNT ET AL CAMERON L - 47

Location: Lat. 60° 06' 31.55" N; Long. 117° 39' 18.63" W

ELECTRIC LOG TOPS

K.B. Elevation 723.00m

S A M P L E D E S C R I P T I O N

Samples Lagged 1 Min. per 30 Metres

K.B: 723.00m

395 - 410 SHALE - medium to dark grey, slight silty texture, micromicaceous, fairly carbonaceous, non-calcareous, fissile to sub-fissile, brittle, soft; Trace Inoceramus fragments.

410 - 420 SHALE - medium to dark grey, very silty texture, slightly micromicaceous, carbonaceous in part, non-calcareous, fissile to blocky, soft to very soft.

420 - 425 SHALE - medium to dark grey and black, silty texture, micromicaceous, carbonaceous throughout, non-calcareous, fissile to sub-fissile, very soft.

425 - 445 SHALE - light grey to greyish brown and some light green, very silty texture, micromicaceous, slightly carbonaceous, non-calcareous, platy, medium soft to hard; Minor SILTSTONE - interbedded stringers, translucent to light grey, quartzose, carbonaceous in part, well cemented with clayey matrix, platy, hard, tight; Trace SANDSTONE - lens, translucent to rarely transparent, quartzose, very fine grained and grading to Siltstone, slightly carbonaceous, sub-angular, well sorted, well cemented with calcareous matrix, platy, hard, tight; Trace Shell fragments.

445 - 465 SHALE - medium to dark grey, very silty texture, slightly micromicaceous, carbonaceous, non-calcareous, platy, medium soft to soft; Trace SANDSTONE - stringers, transparent to translucent and occasionally light grey, quartzose, very fine to fine grained, sub-angular, medium sorted, cemented with slightly calcareous and silty matrix, blocky, hard, tight.

465 - 475 SHALE - medium to dark grey, silty texture, slightly micromicaceous, carbonaceous in part, non-calcareous, fissile to platy, soft to very soft.

475 - 495

SHALE - medium to dark grey, very silty texture, slightly micromicaceous, very carbonaceous, non-calcareous, blocky to sub-fissile, soft to medium soft, brittle in part;
Minor SANDSTONE - interbedded stringers, transparent to mainly translucent, quartzose, very fine to fine grained, sub-rounded to sub-angular, medium sorted, cemented with limy matrix, rarely carbonaceous, medium hard, tight;
Trace PYRITE - nodules and bluish grey BENTONITE.

NOTE: AIR DRILLING ENCOUNTERED WATER AT TOP OF WABAMUN SO FOAM WAS ADDED WHICH RESULTED IN NO CUTTINGS FROM 495m to 1165m.

1165 - 1185

SHALE - 90%, medium to very dark grey, silty texture, micromicaceous, non-calcareous, sub-fissile to platy, medium soft;
SILTSTONE - 10%, interbedded stringers, translucent to mainly very light grey, quartzose, micromicaceous, rarely carbonaceous, sub-angular, well sorted, well cemented with calcareous matrix, platy, hard, tight;
Trace SANDSTONE - transparent to translucent, quartzose, very fine grained, sub-angular, well sorted, cemented with calcareous matrix, argillaceous, platy, medium hard, tight, no shows.

1185 - 1200

SHALE - light to mainly dark grey, smooth to slightly silty in part, micromicaceous, rarely carbonaceous, non-calcareous, sub-fissile to platy, medium soft to soft;
Minor SILTSTONE - scattered stringers, translucent to very light grey, quartzose, micaceous, slightly carbonaceous, argillaceous, sub-angular, well sorted, cemented with calcareous matrix, platy, hard, tight.

1200 - 1215

SHALE - light to medium grey, smooth, very slightly micromicaceous, carbonaceous in part, non-calcareous, sub-fissile to platy, medium soft;
SANDSTONE - 5%, transparent to translucent, quartzose, fine grained, sub-angular, well sorted, slightly carbonaceous, well cemented with calcareous matrix, platy, hard, tight;
Rare COAL - jet black, lustrous, conchoidal fracture, angular, brittle.

1215 - 1235

SHALE - light to medium grey, smooth, slightly micromicaceous, occasional carbonaceous partings, non-calcareous, platy, medium soft;
SANDSTONE - 5%, interbedded stringers, transparent to

translucent, quartzose, very fine to mainly fine grained, sub-angular to sub-rounded, medium sorted, cemented with calcareous matrix, grading to Siltstone in part, blocky, hard, tight.

1235 - 1250 SHALE - 80%, medium to dark grey, slight silty texture, micromicaceous, carbonaceous occasionally, non-calcareous, platy, medium soft to soft; SILTSTONE - 20%, interbedded stringers, translucent to mainly light grey, quartzose, sub-angular, well sorted, rarely micaceous, well cemented with calcareous matrix, rarely pyritic, platy, medium hard, tight.

1250 - 1265 SHALE - 75%, medium grey, smooth, carbonaceous, non-calcareous, very slightly micromicaceous, platy, soft; SILTSTONE - 25%, stringers, translucent to light grey, quartzose, micromicaceous, grading to very fine grained Sandstone in part, sub-angular, well sorted, argillaceous, cemented with calcareous matrix, platy, medium hard, tight, no shows.

1265 - 1275 SHALE - 60%, medium to dark grey, smooth, carbonaceous, rarely micromicaceous, non-calcareous, sub-fissile to platy, soft; SILTSTONE - 40%, translucent to very light grey, quartzose, micromicaceous, argillaceous, slightly carbonaceous in part, rarely pyritic, sub-angular, well sorted, cemented with calcareous matrix, tight.

BEAVERHILL LAKE : 1275m

1275 - 1305 SHALE - 75%, dark grey, smooth, slightly carbonaceous, non-calcareous, platy, soft; SANDSTONE - 25%, stringers, translucent to light grey, quartzose, very fine grained, grading to Siltstone in part, sub-angular, well sorted, slightly micromicaceous, argillaceous, well cemented with calcareous matrix, blocky, hard, tight; Trace MARL - light green, smooth, calcareous, soft.

MUSKWA : 1305m

1305 - 1320 SHALE - 80%, medium to dark grey, smooth, slightly micromicaceous, carbonaceous partings throughout, non-calcareous, sub-fissile to platy, medium soft; SANDSTONE - 5%, translucent to mainly light grey, quartzose, very fine grained, grading to Siltstone

in part, micaceous, argillaceous, sub-angular, well sorted, calcareous matrix, platy, hard, tight; LIMESTONE - 15%, stringers, translucent to creamy white, crypto to microcrystalline, argillaceous, platy, hard, tight; Trace MARL - light green, smooth, calcareous, soft; Trace Crinoid fragments.

1320 - 1330 SHALE - 80%, medium to dark grey, smooth, slightly micromicaceous, non-calcareous, platy, medium soft; SILTSTONE - 10%, stringers, translucent to light grey, quartzose, micaceous, slightly carbonaceous, sub-angular, well sorted, calcareous matrix, platy, hard, tight; LIMESTONE - 10%, white to greyish white, crypto to microcrystalline, very argillaceous, platy, medium hard, tight; Rare Crinoid fragments.

SLAVE POINT : 1330m

1330 - 1345 LIMESTONE - cream to occasionally medium brown, crypto to microcrystalline, very argillaceous, rarely bioclastic, granular in part, trace poor lemon-yellow fluorescence, no cut or staining, platy, medium hard, tight; Trace PYRITE - nodules; Scattered Shell fragments.

1345 - 1355 LIMESTONE - cream to light and medium brown, microcrystalline to very finely granular, very argillaceous, commonly bioclastic with scattered well developed porous Algal stringers, poor to fair intergranular and vuggy porosity, poor to fair permeability, fair iridescent pulsating fluorescence, milky white curling cut, trace condensate staining associated with porosity, mainly tight and hard but porous stringers brittle. Gas readings in 23-27 unit range.

1355 - 1360 LIMESTONE - cream to medium brown, microcrystalline to very finely granular, slightly bioclastic in part, very argillaceous, trace scattered Algal stringers containing poor intergranular and vuggy porosity, limited permeability, very dull fluorescence, no cut or staining, platy, hard, mainly tight; Minor LIMESTONE - light to medium grey, microcrystalline, silty texture, calcarenitic, very slightly pyritic in part, platy, medium soft to soft, tight, no shows.

FORT VERMILLION : 1360m

1360 - 1380 LIMESTONE - 80%, mainly creamy white to medium brown, microcrystalline to very finely crystalline, sucrosic texture, argillaceous, rarely bioclastic, chalky in part, platy, medium hard, tight, no shows;
SHALE - 15%, light to medium grey, smooth, non-calcareous, sub-fissile to platy, medium soft;
ANHYDRITE - 5%, translucent to greyish white, microcrystalline;
Trace green SHALE.

WATT MOUNTAIN : 1380m

1380 - 1385 LIMESTONE - 60%, light to medium brown, lithographic to cryptocrystalline, argillaceous, platy, hard, tight, no shows;
LIMESTONE - 40%, white to creamy white, microcrystalline, amorphous, chalky texture, platy, very soft to soft, tight;
Trace MARL - green, smooth, calcareous, medium soft to soft;
Trace PYRITE - nodules.

BISTCHO : 1385m

1385 - 1405 LIMESTONE - 90%, creamy white to occasionally very light brown, crypto to microcrystalline, amorphous and chalky in part, argillaceous, rarely pelletoidal, platy, medium soft to hard, tight;
DOLOMITE - 10%, interbedded stringers, medium to mainly dark brown, crypto to finely crystalline, anhydritic, platy, hard, tight, no shows;
Minor PYRITE - disseminated and nodules.

SULPHUR POINT : 1405m

1405 - 1430 DOLOMITE - medium to dark brown, very fine to finely crystalline, sucrosic texture characteristic, anhydritic, rhombic crystals detectable, stringers of fair to good intercrystalline and vuggy porosity, fair permeability, white iridescent fluorescence, slight white cut, a good reservoir but possibly flushed. A drilling break through interval in the 7 to 8 minute range from 15 minutes. Gas in the 10 to 13 unit range.

1430 - 1440 DOLOMITE - medium to dark brown, very fine to finely crystalline, sucrosic texture common, anhydritic, minor stringers poor intercrystalline and vugular porosity, limited permeability, no shows, platy, hard, mainly tight, porosity appears flushed; Trace LIMESTONE - stringers, creamy white to medium brown, microcrystalline, bioclastic in part, amorphous chalky texture dominant, argillaceous, platy, medium soft, tight.

MUSKEG : 1440m

1440 - 1450 ANHYDRITE - 75%, translucent to cream and light grey, crypto to microcrystalline, microsucrosic, platy, medium hard to medium soft; DOLOMITE - 25%, stringers, light to medium brown, very finely crystalline, anhydritic, sucrosic texture, platy, hard, tight.

1450 - 1460 ANHYDRITE - 80%, translucent to creamy white and tan, crypto to microcrystalline, rarely very finely crystalline, slightly chalky in part, platy, medium hard, tight; DOLOMITE - 20%, medium to dark brown, micro to very finely crystalline, sucrosic texture in part, anhydritic, trace poor intercrystalline porosity, rarely vugular, no shows, platy, hard, mainly tight.

1460 - 1485 SHALE - Cavings, medium grey, smooth, rarely micromicaceous, very slightly calcareous in part, sub-fissile to platy, medium soft; ANHYDRITE - 80%, interbedded, translucent to creamy white and tan, crypto to microcrystalline, platy, medium hard, tight; DOLOMITE - 20%, stringers, medium to dark brown, very fine to finely crystalline, anhydritic, platy, hard, tight; Trace SHALE - green, smooth, calcareous, soft; Trace PYRITE.

KEG RIVER: 1485m

1485 - 1495 ANHYDRITE - 50%, interbedded, translucent to creamy white and tan, crypto to microcrystalline, platy, medium hard, tight; DOLOMITE - 50%, light to medium brown, lithographic to very finely crystalline, anhydritic, platy, very hard to hard, tight; SHALE - cavings common.

1495 - 1500 DOLOMITE - medium brown, very fine to mainly finely crystalline, sucrosic texture characteristic, anhydritic, trace poor to fair intercrystalline and vuggy porosity, dull lemon fluorescence, slight staining and cut, a fair reservoir, platy, hard, mainly tight, low Gas values in the 3 to 4 unit range; Trace ANHYDRITE - creamy white, microcrystalline, platy, medium hard, tight; Trace PYRITE - nodules.

1500 - 1515 DOLOMITE - translucent to medium and dark brown, very fine to finely crystalline, sucrosic texture common, anhydritic, trace scattered fair to good vuggy and intercrystalline porosity, fair permeability, fair lemon fluorescence, white smokey cut, light oil staining, platy, hard, mainly tight; Trace SHALE - green, smooth, dolomitic, medium soft.

1515 - 1523 DOLOMITE - translucent to medium and dark brown, very fine to finely crystalline, scattered poor intercrystalline and vuggy porosity, slight yellow fluorescence and white smoky cut; Trace ANHYDRITE - creamy white to light grey and semi-translucent, microcrystalline, platy, medium hard, tight; Trace SHALE - green, smooth, dolomitic, medium soft.

1523 - 1535 DOLOMITE - 60%, very dark to chocolate brown, lithographic, slightly calcareous in part, anhydritic, platy, very hard, dense; LIMESTONE - 30%, interbedded, creamy white to very light brown, microcrystalline, argillaceous, slightly dolomitic in part, occasionally bioclastic, platy, medium hard, tight; DOLOMITE - 10%, stringers, translucent to light brown, very fine to finely crystalline, anhydritic, platy, hard, tight; Trace MARL - lenses, light grey and green, smooth, calcareous, medium soft; Trace PYRITE - nodules.

1535 - 1547 DOLOMITE - 80%, light, medium and dark brown, very fine to finely crystalline, anhydritic, slightly siliceous, platy, very hard, tight; SANDSTONE - 20%, translucent, quartzose, very fine to fine grained, sub-angular, well sorted, minor fair intergranular porosity, questionable permeability, slight bright lemon-yellow fluorescence, no cut or staining, slight calcareous matrix, anhydritic; Trace ANHYDRITE.

PRE-CAMBRIAN : 1547m

1547 - 1565 GRANITE - salmon pink, quartz-feldspar-hornblend
rich with minor biotite;
Minor QUARTZITE - translucent to light grey, very
siliceous, very hard, dense.

TOTAL DEPTH : 1565m

PARAMOUNT ET AL CAMERON L - 47

GAS REPORTS

<u>Date</u>	<u>Depth</u>	<u>Total Units</u>	<u>Comments</u>
Feb. 20	1165-1168	4-19	Trip Gas
	1168-1170	3-4	Background
	1170-1210	1-2	Background
	1210-1214	3	Background
	1214-1217	4-5	Background
	1217-1236	1-2	Background
Feb. 21	1236-1238	3-5	Background
	1238-1290	1-3	Background
	1290-1291	3-4	Background
	1291-1310	1-3	Background
	1310-1312	4-7	Minor Show
	1312-1317	2-4	Background
	1317-1318	4-6	Minor Show
	1318-1330	1-4	Background
Feb. 22	1330-1350	1-7	Background
	1350-1351	7-9	Show
	1351-1353	10-27	Strong Show
	1353-1354.5	17-18	Show
	1354.5-1359	21-50	Trip Gas
	1359-1362	10-17	Show
	1362-1372	1-3	Background

GAS REPORTS - continued

<u>Date</u>	<u>Depth</u>	<u>Total Units</u>	<u>Comments</u>
Feb. 23	1372-1396	1-3	Background
	1396-1400	4-9	Minor Show
	1400-1411	2-4	Background
	1411-1424	5-12	Show
	1424-1428	10-13	Show
	1428-1430	6-12	Show
Feb. 25	1430-1438	4-6	Minor Show
	1438-1439	7-9	Show
	1439-1440	5-12	Show
	1440-1441	3	Background
	1441-1443	1-2	Background
	1443-1473	0-1	Background
	1473-1478	0	Mud Vis. 115
Feb. 26	1478-1490	0	Mud Vis. 115
	1490-1494	2-5	Background
	1494-1499	5-7	Minor Show
	1499-1502	2-3	Background
	1502-1505	5-15	Show
	1505-1506	6-9	Minor Show
	1506-1511	3-4	Background
	1511-1532	1-2	Background
	1532-1535	0	Bsl KR Platform

GEOLOGICAL SUMMARY

The subject well was drilled primarily as a test of the Upper Devonian, Slave Point and the Middle Devonian, Keg River dolomite, with the reservoir of the Middle Devonian Sulphur Point existing as a secondary objective.

The hole was drilled with "Air" from the Surface Casing Shoe to the top of the Wabamun. The top of the Wabamun, at 496 metres, was water saturated which necessitated converting to Foam (soap detergent). Foam was used down to 1165 metres, at which point conversion was made to a regular "chem-gel" mud system, which was used to total depth, 1565 metres. No cuttings or gas readings were obtained between 495 metres and 1165 metres, which covered the Wabamun, Twin Falls and Hay River intervals of the hole.

The Slave Point was encountered at 1330.3 metres (-607.3m) and was approximately 29 metres thick. The formation consisted of a limestone sequence which was tight at the top but a few metres down had some well developed porous Algal stringers. The limestone was cream to medium brown, microcrystalline to very finely granular, slightly bioclastic with scattered well developed porous Algal stringers. Poor to fair intergranular and vuggy porosity with limited permeability was exhibited and was associated with a fair iridescent pulsating fluorescence. This porosity was not tested until after Log evaluations were completed and all that was recovered from the drillstem test was 85 metres of inhibitor cut drilling mud, which suggests the reservoir was badly damaged by invasion.

The Sulphur Point was encountered at 1405 metres (-682m) and consisted of a dolomite sequence which had a characteristic sucrosic texture. The dolomite was medium to dark brown, very fine to finely crystalline with fair to good intercrystalline and vuggy porosity which appeared to be effective. A slight fluorescence and cut was obtained but the reservoir appeared to be flushed. The porosity in the Sulphur Point was tested during penetration and confirmed previous predictions that the reservoir was water saturated by producing a recovery of 187 metres of mud cut water and 45 metres of drilling mud.

The Keg River was penetrated at 1485 metres (-762m) and appeared in cuttings to have been deposited in a bank environment as there was no indication of any biostromal or biohermal buildup even

where porosity existed. The lithology consisted of a dolomitic sequence which varied in colour from a light to a dominant dark brown, was mainly very fine to finely crystalline, commonly anhydritic and had traces of scattered poor to fair intercrystalline and vuggy porosity throughout, and in most cases appeared to be permeable. Associated with the upper porosity was some slight light oil staining which produced a dull lemon fluorescence and a smokey white cut. A total of two drillstem tests evaluated the Keg River after Wireline Logs had been evaluated and both indicated the presence of a hydrocarbon reservoir. Further evaluating will be required before any conclusions can be drawn as to the commercial viability of this well.

All other formations were essentially tight or were flushed as confirmed by samples and wireline logs. Porosities and hydrocarbon shows were checked with a fluoroscope and CCl_4 .

Based on the above information and previous knowledge of the reservoirs in the general area, production casing was run to total depth (1565m K.B.). The well is currently classified as Standing - waiting on evaluation. The rig was released at 0530 hours March 6, 1989.

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 12, 1989

DAYS FROM SPUD: 1

DEPTH: 137m PROGRESS: 137m HRS ON BTM: 6-1/4

OPERATION AT 0800 HRS: Waiting for Matting.

MUD PROPERTIES: Wgt 1040 Vis 44 W.L. --- F.C. --- pH ---

SURVEYS: 38m = 1/4°, 65m = 1/8°, 119m = 1/8°, 137m = 1/8°.

REMARKS: Spudded at 1300 hours February 11, 1989.

Drilled to 137m and cellar started caving around the Conductor Pipe, undermining the Matting.
Pulled out of hole and laid down derrick and waited for arrival of addition Matting.

Official: Ground Elevation : 719.32m
K.B. to Ground : 3.68m
Kelly Bushing : 723.00m

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 13, 1989

DAYS FROM SPUD: 2

DEPTH: 306m PROGRESS: 169m HRS ON BTM: 8-3/4

OPERATION AT 0800 HRS: Drilling 311mm hole.

MUD PROPERTIES: Wct 1160 Vis 52 W.L. --- F.C. --- pH ---

SURVEYS: 164m = 1/4°, 202m = 3°, 230m = 2-1/2°.

REMARKS: Waited for Matting and welded same. Cut off and rewelded Conductor Pipe. Backfilled Cellar with gravel. R.I.H. and drilled to 306m.

GEOLOGIST: H. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 14, 1989

DAYS FROM SPUD: 3

DEPTH: 390m PROGRESS: 90m HRS ON BTM: 7-3/4

OPERATION AT 0800 HRS: Running Surface Casing.

MUD PROPERTIES: Wgt 1160 Vis 83 W.L. --- F.C. --- pH ---

SURVEYS: 258m = 1-1/4°, 334m = 3/4°, 372m = 3/4°.

REMARKS: Drilled, circulated and P.O.H.
Running 244.5mm surface casing.

GEOLOGIST: A. Larkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 15, 1989

DAYS FROM SPUD: 4

DEPTH: 390m PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Heading up B.O.P.'s.

MUD PROPERTIES: Wgt --- Vis --- W.L. --- F.C. --- pH ---

SURVEYS: ----

REMARKS: Surface Casing: Ran 30 jts 244.5mm, 53.57 kg/m,
J-55 LT&C Prudential Casing.
Ran total of 392m casing.
Landed at 390.05m K.B.
Cemented with 31 tonnes Class "G"
cement + 3% CaCl₂. Plug down at
1515 hours February 14, 1989.
W.O.C. Cut off casing. Welded
on Bowl. Headed up B.O.P.'s.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 16, 1989

DAYS FROM SPUD: 5

DEPTH: 392m PROGRESS: 2m HRS ON BTM: 3-1/2

OPERATION AT 0800 HRS: Preparing to drill out.

MUD PROPERTIES: Wgt 1110 Vis 62 W.L. --- F.C. --- pH ---

SURVEYS: -----

REMARKS: Headed up B.O.P's. Pressure tested Blind Rams. R.I.H. with Bit and pressure tested Pipe Rams to 7000 kPa. Drilled out Float Collar, Cement and Guide Shoe. Drilled to 392m. Rigged in Excel Pressure Testing. Ran Leak-off Test. P.O.H. 200m and blew out water. R.I.H. to 390m and blowing hole dry. Geologging equipment hooked up ready to go.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 17, 1989

DAYS FROM SPUD: 6

DEPTH: 819m PROGRESS: 427m HRS ON BTM: 18-3/4

OPERATION AT 0800 HRS: Drilling 222mm hole with Foam.

MUD PROPERTIES: Wgt 1110 Vis 50 W.L. --- F.C. --- pH ---

SURVEYS: 560m = $3/4^{\circ}$, 723m = $3/4^{\circ}$.

REMARKS: Formation Top:
Wabamun 497m (=226m).

Drilled with Air to top of Wabamun and encountered water. Converted to Foam at 505m and continued drilling ahead.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 18, 1989

DAYS FROM SPUD: 7

DEPTH: 992m PROGRESS: 173m HRS ON BTM: 9-1/4

OPERATION AT 0800 HRS: Drilling 222mm hole with Foam.

MUD PROPERTIES: Wgt 1100 Vis 51 W.L. --- F.C. --- pH ---

SURVEYS: 838m = 1/2.

REMARKS: Drilled to 838m and torque increased. P.O.H. and found bearings missing from one cone. R.I.H. and cleaned bridges to bottom - 752m to 838m. Drilled to 992m R.O.P. 18.7m/hour.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 19, 1989

DAYS FROM SPUD: 8

DEPTH: 1165m PROGRESS: 173m HRS ON BTM: 8-1/4

OPERATION AT 0800 HRS: Running in hole to drill with Mud.

MUD PROPERTIES: Wgt 1100 Vis 50 W.L. 10.5 F.C. 1.0 pH 9.0

SURVEYS: 992m = $1/4^{\circ}$, 1097m = 2° .

REMARKS: Drilled and circulated to 1165m. R.O.P. 32.9m/hour.
Mud up at 1165m.
Removed diverter to Blooey Line and installed Flow
Nipple. R.I.H. with Bit.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 20, 1989

DAYS FROM SPUD: 9

DEPTH: 1238m PROGRESS: 73m HRS ON BTM: 15

OPERATION AT 0800 HRS: Drilling 222mm hole with mud.

MUD PROPERTIES: Wgt 1130 Vis 60 W.L. 7.6 F.C. 2.0 pH 10.0

SURVEYS: 1173m = 3/4°.

REMARKS: R.I.H. Reamed from 650m to 1165m.
Repaired Swivel - 3/4 hour.
Drilled to 1238m. R.O.P. 4.9m/hour.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 21, 1989

DAYS FROM SPUD: 10

DEPTH: 1338m PROGRESS: 100m HRS ON BTM: 20-3/4

OPERATION AT 0800 HRS: Drilling 222mm hole.

MUD PROPERTIES: Wct 1150 Vis 54 W.L. 9.0 F.C. 2.0 PH 11.0

SURVEYS: 1270m = 2-1/2°, 1317m = 1°.

REMARKS: Repaired Pump. Drilled to 1338m. R.O.P. 4.8m/hour.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 22, 1989

DAYS FROM SPUD: 11

DEPTH: 1375m PROGRESS: 37m HRS ON BTM: 15

OPERATION AT 0800 HRS: Drilling 222mm hole.

MUD PROPERTIES: Wgt 1160 Vis 60 W.L. 8.5 F.C. 2.0 pH 11.0

SURVEYS: ----

REMARKS: Drilled to 1354m. Tripped for Bit. No tight spots.
Drilled to 1375m R.O.P. 2.5m/hour.

Formation Tops:-

Muskwa : 1305m (-582m)
Slave Point : 1330m (-607m)

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 23, 1989

DAYS FROM SPUD: 12

DEPTH: 1430m PROGRESS: 55m HRS ON BTM: 12-3/4

OPERATION AT 0800 HRS: Handling DST Tools.

MUD PROPERTIES: Wgt 1170 Vis 68 W.L. 7.0 F.C. 2.0 pH 11.0

SURVEYS: 1420m = 1.

REMARKS: Formation Tops:-
Fort Vermillion : 1360m (-637m)
Watt Mountain : 1380m (-657m)
Bistcho : 1385m (-662m)
Sulphur Point : 1405m (-682m)

Drilled to 1430m. R.O.P. 4.3m/hour. Circulated bottom hole sample. Dummy trip to 1300m. Circulated hole clean. P.O.H. to Drill Collars - slipped and cut line.

Rigged in Baker Oil Tools.
Picking up Test Tools.

GEOLOGIST: H. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 24, 1989

DAYS FROM SPUD: 13

DEPTH: 1430m PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Running in hole with Bit #5.

MUD PROPERTIES: Wgt 1170 Vis 68 W.L. 7.0 F.C. 2.0 pH 11.0

SURVEYS: ----

REMARKS: Made up Test Tool. R. I. H. Worked on Flare Stack.
Ran DST #1 1408m - 1430m Sulphur Point.
Complete data on DST #1 on the attached report.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 25, 1989

DAYS FROM SPUD: 14

DEPTH: 1480m PROGRESS: 50m HRS ON BTM: 19-1/2

OPERATION AT 0800 HRS: Drilling 222mm hole.

MUD PROPERTIES: Wgt 1120 Vis 115 W.L. 7.6 F.C. 2.0 pH 10.5

SURVEYS: ----

REMARKS: Formation Top:-
Muskeg 1440m (-717m)

R.I.H. Circulating - plugged jet.
Drilled to 1480m. R.O.P. 2.6m/hour.

GEOLOGIST: A. Coakley

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 26, 1989

DAYS FROM SPUD: 15

DEPTH: 1532m PROGRESS: 52m HRS ON BTM: 16-1/2

OPERATION AT 0800 HRS: Tripping for Bit.

MUD PROPERTIES: Wgt 1140 Vis 55 W.L. 7.6 F.C. 2.0 pH 11.0

SURVEYS: 1519m = 1-1/4"

REMARKS: Formation Top:-
Keg River 1485m (-762m)
Drilled to 1532m R.O.P. 3.2m/hour.
Trip for Bit.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 27, 1989

DAYS FROM SPUD: 16

DEPTH: 1565m TD PROGRESS: 33m HRS ON BTM: 16-1/2

OPERATION AT 0800 HRS: Circulating bottom hole sample.

MUD PROPERTIES: Wgt 1150 Vis 70 W.L. 9.0 F.C. 2.0 PH 11.0

SURVEYS: ----

REMARKS: Formation Tops:-
Pre-Cambrian : 1547m (-824m)
Total Depth : 1565m (-842m)

Wait for Junk Sub. R.I.H. Broke circulation and worked Junk Sub. Drilled to 1565m (F.T.D.).
R.O.P. 2m/hour.

Reached Total Depth at 0700 hours February 27, 1989.

Schlumberger to be on location at 1600 hours today.

GEOLOGIST: A. Larkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: February 28, 1989

DAYS FROM SPUD: 17

DEPTH: 1565m PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Waiting on Tester.

MUD PROPERTIES: Wgt 1150 Vis 70 W.L. 9.0 F.C. 2.0 pH 11.0

SURVEYS: 1565m = 1-1/4°.

REMARKS: P.O.H. and rigged up Schlumberger.

Logs run:	Phasor Induction-SFL	389.1m - 1560.7m
	BHC-Sonic-GR/Cal	389.1m - 1551.2m
	CNL-LDT-GR-Ten	389.1m - 1562.5m
	Microlog-GR-Ten	389.1m - 1556.2m
	Cyberlook	1310.0m - 1562.5m
	Sat Velocity Monitor	390.0m - 1563.5m

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 1, 1989

DAYS FROM SPUD: 18

DEPTH: 1565m TD PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Waiting on daylight to reverse circulate
fluid from drill pipe.

MUD PROPERTIES: Wgt 1150 Vis 70 W.L. 9.0 F.C. 2.0 pH 11.0

SURVEYS: ----

REMARKS: Waited on Tester. Ran clean out trip.
Rig in Scott Testers. R.I.H. with DST #2 -
1486m - 1510m Keg River. See DST Data Sheet.

GEOLOGIST: A. Larkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 2, 1989

DAYS FROM SPUD: 19

DEPTH: 1565m TD PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Pulling DST #3.

MUD PROPERTIES: Wgt 1150 Vis 70 W.L. 9.0 F.C. 2.0 pH 11.0

SURVEYS: ----

REMARKS: Recovered DST #2. R.I.H. with DST #3 1510m - 1534m
Keg River. See DST Data Sheet.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 3, 1989

DAYS FROM SPUD: 20

DEPTH: 1565m TD PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: P.O.H. with Test Tools.

MUD PROPERTIES: Wgt 1165 Vis 65 W.L. 70 F.C. 2.0 pH 10.5

SURVEYS: ----

REMARKS: P.O.H. with DST #3 and laid down Test Tool.
DST #3 1510m - 1534m Keg River.
See DST Data Sheet for complete details.

Ran clean out trip. R.I.H. with DST #4
1335m - 1359m Slave Point. Unable to pressure
up Packers for a seat. P.O.H. - Misrun.

GEOLOGIST: A. Lorkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 4, 1989

DAYS FROM SPUD: 21

DEPTH: 1565m TD PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Waiting on Float Collar.

MUD PROPERTIES: Wgt 1165 Vis 65 W.L. 7.0 F.C. 2.0 pH 10.5

SURVEYS: ----

REMARKS: Ran DST #5 1325m - 1359m in Slave Point.
Recovered 85m Inhibited Mud. See DST Data Sheet
for complete details. Rigged out Tester.
Rigged up to run Production Casing.

GEOLOGIST: A. Cooken

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 5, 1989

DAYS FROM SPUD: 22

DEPTH: 1565m TD PROGRESS: ---- HRS ON BTM: ----

OPERATION AT 0800 HRS: Running production casing.

MUD PROPERTIES: Wgt 1165 Vis 65 W.L. 7.0 F.C. 2.0 pH 10.5

SURVEYS: ----

REMARKS: Waited on Float Collar. Running production casing.

GEOLOGIST: A. Corkin

SOUTHERN CROSS GEOLOGICAL CONSULTING LIMITED

DAILY DRILLING REPORT

LOCATION: PARAMOUNT ET AL CAMERON
L - 47

DATE: March 6, 1989

DAYS FROM SPUD: 23

DEPTH: 1565m TD PROGRESS: ---- HPS ON BTM: ----

OPERATION AT 0800 HRS: Rig released at 0500 hours March 6, 1989.

MUD PROPERTIES: Wgt --- Vis --- W.L. ---- F.C. --- pH ---

SURVEYS: ----

REMARKS: Production Casing:-
Ran 121 joints of 139.7mm, 20.38 kg/m, J-55,
ST&C Ipsco casing. Landed at 1562.5m K.B.
Cemented with 12 tonnes Oilwell cement.

Rig released : 0530 hours March 6, 1989.

Status: Standing - Pending Evaluation.

FINAL REPORT

GEOLOGIST: H. Corkin

DRILL STEM TEST RESULTS

Well Name: PARAMOUNT ET AL CAMERON L - 47

Dst. # One

Interval: 1408m - 1430m

Test Type: Conventional Straddle
Inflatable Straddle
X Conventional Bottom Hole
Inflatable Bottom Hole

Zone(s): Sulphur Point

Times: Preflow: 10 mins.
Initial Shut-in: 70 mins.
Valve Open: 60 mins.
Final Shut-in: 120 mins.

Results: Preflow: Weak Air Blow increasing to moderate in 3 minutes.
N.G.T.S.

V.O.: Weak to strong Air Blow in 1 minute. Strong
throughout. N.G.T.S.

Recovered: 187m Mud Cut Water, 45m Clobbered Drilling Mud.

Pressures: Initial Hydrostatic (IHP): 16650 kPa
Final Hydrostatic (FHP): 16680 kPa
Preflow (Pref.): Initial : 1489 kPa; Final : 1659 kPa
Initial Shut-in (I.S.I.P.): 9853 kPa
Final Shut-in (F.S.I.P.): 9853 kPa
Initial Flow (IFP): 1659 kPa
Final Flow (FFP): 2513 kPa

Remarks: Conclusive Test. Test interval water saturated.
Salinity 100,000 ppm.

BHT : 40°C

DRILL STEM TEST RESULTS

Well Name: PARAMOUNT ET AL CAMERON L - 47

Dst. # TWO

Interval: 1486m - 1510m

Test Type: Conventional Straddle
X Inflatable Straddle
 Conventional Bottom Hole
 Inflatable Bottom Hole

Zone(s): Keg River

Times: Preflow: 45 mins.
Initial Shut-in: mins.
Valve Open: mins.
Final Shut-in: 365 mins.

Results: Preflow: Strong Air Blow in 3 minutes, G.T.S. in 11 minutes,
O.T.S. in 40 minutes.

V.O.: Continued through from PreFlow.

Recovered: One cubic metre very gassified Oil. 3½% Drilling Mud.

No indication of Water. 33.5° API Gravity at 60°F.

Pressures: Initial Hydrostatic (IHP): 17700 kPa
Final Hydrostatic (FHP): 17482 kPa
Preflow (Pref.): (a) 5318 kPa (b) 8340 kPa
Initial Shut-in (I.S.I.P.): 10766 kPa
Final Shut-in (F.S.I.P.): -----
Initial Flow (IFP): -----
Final Flow (FFP): -----

Remarks: H₂S content 15,000 ppm to 35,000 ppm. Shut-in Test Tool.

Waiting for daylight and Tank to reverse circulate fluid
from Drill Pipe. Oil dark brown colour.

BHT : 42°C.

DRILL STEM TEST RESULTS

Well Name: PARAMOUNT ET AL CAMERON L - 47

Dst. # Three

Interval: 1510m - 1534m

Test Type: Conventional Straddle
X Inflatable Straddle
Conventional Bottom Hole
Inflatable Bottom Hole

Zone(s): Keg River

Times: Preflow: 20 mins.

Initial Shut-in: 50 mins.

Valve Open: 2nd : 25 mins. 3rd: 60 mins.) Flare Line

Final Shut-in: 2nd: 30 mins. 3rd: 120 mins.) plugged w/Ice.

Results: Preflow: Weak Air Blow increasing to Strong Air Blow.

N.G.T.S.

V.O.: Strong Air Blow decreasing to Weak Air Blow.

N.G.T.S.

Recovered: 108m Total Recovery - 18m Inhibitor water cut mud,

45m oil cut mud, 45m brackish oil.

Pressures: Initial Hydrostatic (IHP): 17990 kPa

Final Hydrostatic (FHP): 17700 kPa

Preflow (Pref.): 1519 kPa

Initial Shut-in (I.S.I.P.): 5318 kPa

**See Remarks Below.

Final Shut-in (F.S.I.P.): 6942 kPa

Initial Flow (IFP):

Final Flow (FFP):

Remarks: ** 2nd Flow Start 1063 kPa ; 2nd Flow End 1063 kPa

2nd Shut In 3570 kPa

Final Flow Start 1291 kPa ; Final Flow End 1291 kPa

Shut-in after 5 minutes on V.O. Shut-in to thaw Flare Line.

BHT : 42°C

DRILL STEM TEST RESULTS

Well Name: PARAMOUNT ET AL CAMERON L - 47

Dst. # Four Interval: 1335m - 1359m

Test Type: Conventional Straddle
 Inflatable Straddle
Conventional Bottom Hole
Inflatable Bottom Hole

Zone(s): Slave Point

Times: Preflow: _____ mins.
Initial Shut-in: _____ mins.
Valve Open: _____ mins.
Final Shut-in: _____ mins.

Results: Preflow: _____

V.O.: _____

Recovered: 72m Inhibitor cut mud.

Pressures: Initial Hydrostatic (IHP): 15809 kPa

Final Hydrostatic (FHP): 15809 kPa

Preflow (Pref.): 911 kPa

Initial Shut-in (I.S.I.P.): -----

Final Shut-in (F.S.I.P.): -----

Initial Flow (IFP): -----

Final Flow (FFP): -----

Remarks: Misrun. Could not pressure up Packer. Tried to reset
Tool and blew bottom packer in the attempt.

DRILL STEM TEST RESULTS

Well Name: PARAMOUNT ET AL CAMERON L - 47

Dst. # Five Interval: 1335m - 1359m

Test Type: Conventional Straddle
 Inflatable Straddle
Conventional Bottom Hole
Inflatable Bottom Hole

Zone(s): Slave Point

Times: Preflow: 10 mins.
Initial Shut-in: 55 mins.
Valve Open: 60 mins.
Final Shut-in: 120 mins.

Results: Preflow: Weak air blow throughout.

V.O.: Weak air blow throughout.

Recovered: 85m Inhibited cut mud.

Pressures: Initial Hydrostatic (IHP): 15955 kPa
Final Hydrostatic (FHP): 15809 kPa
Preflow (Pref.): 911 kPa
Initial Shut-in (I.S.I.P.): 10914 kPa
Final Shut-in (F.S.I.P.): 10399 kPa
Initial Flow (IFP): 1215 kPa
Final Flow (FFP): 1215 kPa

Remarks: Successful Test. No permeability

DEVIATION SURVEYS

<u>Depth Metres</u>	<u>Deviation Degrees</u>	<u>Change Degrees</u>	<u>Interval Metres</u>	<u>Hole Size Millimetres</u>
37	1/4	+ 1/4	37	311
65	1/8	- 1/8	28	311
119	1/8	----	54	311
137	1/8	----	18	311
164	1/4	+ 1/4	27	311
202	3	+ 2-3/4	38	311
230	2-1/2	- 1/2	28	311
258	1-1/4	- 1-1/4	28	311
334	3/4	- 1/2	76	311
372	3/4	----	38	311
560	3/4	----	188	222
723	3/4	----	163	222
838	1/2	- 1/4	115	222
992	1/4	- 1/4	154	222
1097	2	+ 1-3/4	105	222
1173	3/4	- 1-1/4	76	222
1270	2-1/2	+ 1-3/4	157	222
1317	1	- 1-1/2	97	222
1420	1	----	103	222
1519	1-1/4	+ 1/4	99	222
1565	1-1/4	----	46	222

PARAMOUNT ET AL CAMERON L - 47


BIT SUMMARY

<u>No.</u>	<u>Type</u>	<u>Size</u>	<u>In</u>	<u>Out</u>	<u>Metres</u>	<u>Hours</u>	<u>T-B-G</u>
1A	HP11	311	0	137	137	15-3/4	4-3-I
2A	HP11	311	137	372	235	22-3/4	6-3-I
3A	S64	311	372	390	18	23-1/2	1-1-I
1	HP43A	222	390	838	448	36	6-7-1/4
2	HP43A	222	838	1165	327	16	4-3-I
3	HP52A	222	1165	1354	189	96	6-8-1/8
4	H52A	222	1354	1430	76	116	4-3-I
5	F-2	222	1430	1532	102	151	8-3-I
6	HP52A	222	1532	1565	33	17	2-2-I



WATER ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER	
		G89-2275-1	
LICENCE NUMBER		OPERATOR NAME	
EA 1390		PARAMOUNT RESOURCES LTD.	
LOCATION		WELL NAME	
60-6-31-55-117-39-18.6		PARAMOUNT et al CAMERON L-47	
FIELD OR AREA		POOL OR ZONE	
CAMERON		SULPHUR POINT	
NAME OF SAMPLER		TEST RECOVERY	
TEST TYPE	NO.		
DST	1	232 METRES	
Y N			
MULTIPLE RECOVERY		<input checked="" type="checkbox"/> <input type="checkbox"/>	
TEST INTERVAL (metres)		SAMPLING POINT	
1408 - 1430		DOWNHOLE SAMPLER #228	
PERFORATIONS (metres)		AMT. & TYPE OF CUSHION	
DATE SAMPLED (Y-M-D)		TYPE OF PRODUCTION	
89-02-24		PUMPING FLOWING GAS LIFT SWAB	
DATE RECEIVED (Y-M-D)		PRODUCTION RATES	
89-03-01		WATER m ³ /d	OIL m ³ /d
DATE REPORTED (Y-M-D)		SEPARATOR	TREATER
89-03-10		RESERVOIR	SOURCE
ANALYST		GAS 10 ³ m ³ /d	SAMPLED RECEIVED
D. SHMYR		OTHER INFORMATION	
ION	Mg/l	Mass Fraction	Meq/l
Na	26 106	0.2960	1 135.61
K	978	0.0111	25.04
Ca	7 207	0.0817	359.63
Mg	910	0.0103	74.80
Ba			
Sr			
Fe	PRESENT		
ION	Mg/l	Mass Fraction	Meq/l
Cl	50 500	0.5726	1 424.10
Br			
I			
HCO ₃	744	0.0084	12.20
SO ₄	1 745	0.0198	36.30
CO ₃	0	0.0000	0.00
OH	0	0.0000	0.00
H ₂ S	TRACE		



TOTAL SOLIDS Mg/l

EVAPORATED @ 110°C	EVAPORATED @ 180°C
93 220	
AT IGNITION	CALCULATED
76 840	88 190

ORGANICS: NIL

RELATIVE DENSITY	REFRACTIVE INDEX
1.078 @ 25°C	1.3521 @ 25°C

OBSERVED pH	RESISTIVITY (Ohm m)
7.7 @ 18°C	0.083 @ 25°C

REMARKS

BAKER OIL TOOLS
 DOWNHOLE SAMPLER #228
 WAS RECEIVED AT
 ATMOSPHERIC PRESSURE.
 CONTAINED IN A
 CHAMBER WAS 2.25
 LITRES OF H₂S CUT
 BLACKISH WATER.

HCO₃ ANALYSIS INDICATIVE
 OF A SALT WATER.

SO₄
 CO₃



CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER				
		689-2275				
LICENCE NUMBER	OPERATOR NAME					
EA 1390	PARAMOUNT RESOURCES LTD.					
LOCATION	WELL NAME					
60-6-31.55-117-39-18.6	PARAMOUNT et al CAMERON L-47					
FIELD OR AREA	POOL OR ZONE	NAME OF SAMPLER				
CAMERON	SULPHUR POINT					
TEST TYPE	NO.	TEST RECOVERY				
DST	1	232 METRES				
MULTIPLE RECOVERY	<input checked="" type="checkbox"/> X	SAMPLING POINT	AMT. & TYPE OF CUSHION			
		SEE BELOW	(@ 25°C)			
TEST INTERVAL (metres)	TYPE OF PRODUCTION					
1408 - 1430	PUMPING	FLOWING	GAS LIFT			
PERFORATIONS (metres)	SWAB					
PRODUCTION RATES						
WATER	m ³ /d	OIL	m ³ /d	GAS	10 ³ m ³ /d	RECEIVED
GAUGE PRESSURE	kPa	SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED
TEMPERATURE	°C	SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED
DATE SAMPLED (Y-M-D)	DATE RECEIVED (Y-M-D)	DATE REPORTED (Y-M-D)	ANALYST	OTHER INFORMATION		
89-02-24	89-03-01	89-03-10	K. SINCLAIR			

SAMPLE #1 - SAMPLED FROM TOP.

SAMPLE CONSISTED OF WATERY MUD WITH A BROWN COLORED FILTRATE.

RESISTIVITY OF THE FILTRATE: 0.911 OHM-METRES @ 25 C.

SAMPLE #2 - SAMPLED FROM MIDDLE.

SAMPLE CONSISTED OF H₂S CUT WATER WITH A YELLOW COLORED FILTRATE.

RESISTIVITY OF THE FILTRATE: 0.085 OHM-METRES @ 25 C.

SAMPLE #3 - SAMPLED FROM BOTTOM.

SAMPLE CONSISTED OF MUD WITH A BROWN COLORED FILTRATE.

RESISTIVITY OF THE FILTRATE: 0.723 OHM-METRES @ 25 C.



OIL ANALYSIS

LABORATORY NUMBER

C89-4295-1

CONTAINER IDENTITY

LICENCE NUMBER

OPERATOR NAME

PARAMOUNT RESOURCES LTD.

LOCATION

WELL NAME

ELEVATIONS (metres)
K.B. GRD.

60-06-31-55 -117 39

PARAMOUNT ET AL CAMERON 1-47

723

719.3

FIELD OR AREA

POOL OR ZONE

NAME OF SAMPLER

COMPANY

CAMERON

KEG RIVER

SCOTT TESTERS

TEST TYPE

NO.

TEST RECOVERY

DST

2

REVERSED 1 M3 GAS CUT OIL, H2S

MULTIPLE
RECOVERY

X

SAMPLING POINT

AMT. & TYPE OF CUSHION

MUD RESISTIVITY

@ 25°C

BUBBLE HOSE #4

TEST INTERVAL (metres)
1486 - 1510

TYPE OF PRODUCTION

PUMPING

FLOWING

GAS LIFT

SWAB

PERFORATIONS (metres)

WATER

m³/d

OIL

m³/d

GAS

10³m³/d

SEPARATOR

TREATER

RESERVOIR

SOURCE

SAMPLED

RECEIVED

SEPARATOR

TREATER

RESERVOIR

SOURCE

SAMPLED

RECEIVED

GAUGE PRESSURE

TEMPERATURE

°C

DATE SAMPLED (Y-M-D)

DATE RECEIVED (Y-M-D)

DATE REPORTED (Y-M-D)

ANALYST

OTHER INFORMATION

89-03-01

89-03-03

89-03-06

S. SARGIOS

SAMPLE PROPERTIES

DISTILLATION

COLOR OF CLEAN OIL

B.S. & W. (VOLUME FRACTION)

BROWN

WATER

SEDIMENT

TOTAL

0.032 0.020 0.052

VOLUME
FRACTION
DISTILLEDTEMP.
°C

L.B.P.

72

0.05

118

0.10

145

0.15

176

0.20

203

0.25

228

0.30

251

0.35

273

0.40

293

0.45

314

0.50

333

0.55

350

0.60

363

METHOD

MODIFIED ASTM D-86

BAROM. PRESS. kPa (mm)

ROOM TEMP. °C

89.9

22

DISTILLATION SUMMARY

(VOLUME FRACTION)

200°C NAPHTHA 275°C KEROSENE 350°C LIGHT GAS OIL

0.195

0.165

0.190

RECOVERED

RESIDUE

DISTILLATION LOSS

RVP kPa

CONRADSON

RAMSBOTTOM

VISCOSITY

TEMP. °C	ABSOLUTE mPa.s	KINEMATIC mm²/s
10	19.4	22.6
20	9.60	11.3
40	4.95	5.90

F.B.P. 366

BASE TYPE: MIXED

CHARACTERIZATION FACTOR: 11.9

BS & W DETERMINED ON SAMPLE AS RECEIVED. REMAINDER OF ANALYSIS DETERMINED ON SAMPLE AFTER CLEANING BY CENTRIFUGING.



CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER							
		C89-4295-2							
LICENCE NUMBER	OPERATOR NAME								
	PARAMOUNT RESOURCES LTD.								
LOCATION	WELL NAME								
60-06-31.55 -117 39	PARAMOUNT ET AL CAMERON L-47								
FIELD OR AREA	POOL OR ZONE								
CAMERON	KEG RIVER								
TEST TYPE	NO.	TEST RECOVERY							
DST	2	REVERSED 1 M3 GAS CUT OIL, H2S							
MULTIPLE RECOVERY	<input checked="" type="checkbox"/>	SAMPLING POINT	AMT. & TYPE OF CUSHION						
TEST INTERVAL (metres)	TYPE OF PRODUCTION								
1486 - 1510	PUMPING	FLOWING	GAS LIFT	SWAB					
PERFORATIONS (metres)	PRODUCTION RATES								
	WATER	m ³ /d	OIL	m ³ /d	GAS	10 ³ m ³ /d			
GAUGE PRESSURE	SEPARATOR	kPa	TREATER		RESERVOIR		SOURCE	SAMPLED	RECEIVED
TEMPERATURE	SEPARATOR	°C	TREATER		RESERVOIR		SOURCE	SAMPLED	RECEIVED
DATE SAMPLED (Y-M-D)	DATE RECEIVED (Y-M-D)	DATE REPORTED (Y-M-D)	ANALYST	OTHER INFORMATION					
89-03-01	89-03-03	89-03-06	S. SARGIOUS						

	BS & W (VOLUME FRACTION)			DENSITY @ 15°C		
	WATER	SEDIMENT	TOTAL	REL.	ABS.	GRAVITY
BUBBLE HOSE #1	0.011	0.015	0.026	0.859	858	33.2
BUBBLE HOSE #2	0.028	0.036	0.064	0.858	857	33.4
BUBBLE HOSE #3	0.016	0.016	0.032	0.857	856	33.6
BUBBLE HOSE #5	0.066	0.038	0.104	0.856	855	33.8
BUBBLE HOSE #6	0.180	0.260	0.440	0.856	855	33.8
TOP OF TOOL	0.080	0.460	0.540	0.856	855	33.8

CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER	
PVT #7		C89-4362	
LICENCE NUMBER	OPERATOR NAME		
	PARAMOUNT RESOURCES LTD.		
LOCATION	WELL NAME		
	PARAMOUNT ET AL CAMERON L-47		
FIELD OR AREA	POOL OR ZONE	NAME OF SAMPLER	
CAMERON			
TEST TYPE	NO.	TEST RECOVERY	
DST	2		
MULTIPLE RECOVERY	<input type="checkbox"/> Y <input type="checkbox"/> N	SAMPLING POINT	
TEST INTERVAL (metres)		AMT. & TYPE OF CUSHION	
1486 - 1510		(at 25°C)	
PERFORATIONS (metres)		MUD RESISTIVITY	
TYPE OF PRODUCTION			
PUMPING		FLOWING	
GAS LIFT		SWAB	
PRODUCTION RATES			
WATER	m ³ /d	OIL	m ³ /d
SEPARATOR		TREATER	
RESERVOIR		SOURCE	
GAS		SAMPLED	
RECEIVED	10 ³ m ³ /d		
GAUGE PRESSURE	kPa		
SEPARATOR		TREATER	
RESERVOIR		SOURCE	
SOURCE		SAMPLED	
RECEIVED	23		
DATE SAMPLED (Y-M-D)	DATE RECEIVED (Y-M-D)	DATE REPORTED (Y-M-D)	ANALYST
89-03-05	89-03-08	89-03-22	K. BRUNNER
OTHER INFORMATION			

BUBBLE POINT DETERMINATION @ 42°C: 10 322 KPA

rec ~2.5 l oil

density .856 33.75 °API

BS + w


sed .005 wtr .095 Total .10



WATER ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER	
		CB9-4295-3	
LICENCE NUMBER	OPERATOR NAME		
LOCATION	PARAMOUNT RESOURCES LTD.		
60-06-31-55 -117 39	WELL NAME	PARAMOUNT ET AL CAMERON L-47	
FIELD OR AREA	POOL OR ZONE	NAME OF SAMPLER	
CAMERON	KEG RIVER	TEST RECOVERY	
TEST TYPE	NO		
DST	2	REVERSED 1 M3 GAS CUT OIL, H2S	
MULTIPLE RECOVERY	<input checked="" type="checkbox"/>	SAMPLING POINT	AMT. & TYPE OF CUSHION
TEST INTERVAL (metres)		MUD RESISTIVITY	
1486 - 1510		" 25°C	
PERFORATIONS (metres)		BUBBLE HOSE #6	
		TYPE OF PRODUCTION	
		PUMPING	FLOWING
		GAS LIFT	SWAB
		PRODUCTION RATES	
		WATER m3/d	OIL m3/d
		SEPARATOR	TREATER
		RESERVOIR	SOURCE
		SAMPLED	RECEIVED
		GAUGE PRESSURE kPa	
		SEPARATOR	TREATER
		RESERVOIR	SOURCE
		SAMPLED	RECEIVED
DATE SAMPLED (Y-M-D)		DATE RECEIVED (Y-M-D)	
89-03-01		89-03-03	
DATE REPORTED (Y-M-D)		ANALYST	
89-03-06		S. SARGIOUS	
OTHER INFORMATION			
ION	Mg/l	Mass Fraction	Meq/l
Na	11 400	0.3029	495.90
K	160	0.0043	4.10
Ca	1 273	0.0338	63.52
Mg	381	0.0101	31.32
Ba			
Sr			
Fe	MUCH		
ION	Mg/l	Mass Fraction	Meq/l
Cl	13 400	0.3560	377.88
Br			
I			
HCO ₃	1 220	0.0324	20.01
SO ₄	9 802	0.2604	203.88
CO ₃	0	0.0000	0.00
OH	0	0.0000	0.00
H ₂ S	PRESENT		
TOTAL SOLIDS Mg/l			
EVAPORATED @ 110°C		EVAPORATED @ 180°C	
43 730			
AT IGNITION		CALCULATED	
37 540		37 636	
ORGANICS: MUCH			
RELATIVE DENSITY		REFRACTIVE INDEX	
1.031 \pm 2°C		1.3398 \pm 2°C	
OBSERVED ρ m		RESISTIVITY (Ohm m)	
7.9 \pm 23°C		0.220 \pm 25°C	
REMARKS			
BROWN COLORED FILTRATE RECOVERED FROM THE WATER PORTION OF THE SAMPLE.			

LOGARITHMIC PATTERN Meq/l



CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER	
		C89-4295-4	
LICENCE NUMBER		OPERATOR NAME	
		PARAMOUNT RESOURCES LTD.	
LOCATION		WELL NAME	
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47	
FIELD OR AREA		POOL OR ZONE	
CAMERON		KEG RIVER	
TEST TYPE		TEST RECOVERY	
DST		REVERSED 1 M3 GAS CUT OIL, H2S	
NO.			
T N			
MULTIPLE RECOVERY		<input checked="" type="checkbox"/> X	
TEST INTERVAL (metres)		SAMPLING POINT	
1486 - 1510			
PERFORATIONS (metres)		AMT. & TYPE OF CUSHION	
		MUD RESISTIVITY @ 25°C	
TYPE OF PRODUCTION			
PUMPING		FLOWING	
GAS LIFT		SWAB	
PRODUCTION RATES			
WATER		m ³ /d	
OIL		m ³ /d	
GAS		10 ³ m ³ /d	
SEPARATOR		TREATER	
RESERVOIR		SOURCE	
SAMPLED		RECEIVED	
GAUGE PRESSURE kPa			
TEMPERATURE °C			
DATE SAMPLED (Y-M-D)		DATE RECEIVED (Y-M-D)	
89-03-01		89-03-03	
DATE REPORTED (Y-M-D)		ANALYST	
89-03-06		S. SARGIOUS	
OTHER INFORMATION			

TOP OF TOOL

RESISTIVITY: 0.226 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM THE WATER PORTION OF THE SAMPLE.



GAS ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER					
DHS #119		C89-4296-1					
LICENCE NUMBER		OPERATOR NAME					
		PARAMOUNT RESOURCES LTD.					
LOCATION		WELL NAME					
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47					
FIELD OR AREA		POOL OR ZONE					
CAMERON		KEG RIVER					
TEST TYPE		TEST RECOVERY					
DST		108 M					
MULTIPLE RECOVERY		<input checked="" type="checkbox"/> <input type="checkbox"/>					
TEST INTERVAL (metres)		SAMPLING POINT					
1510 - 1534		DOWN HOLE SAMPLER #119					
PERFORATIONS (metres)		AMT. & TYPE OF CUSHION					
		(a) 25°					
DATE SAMPLED (Y-M-D)		DATE RECEIVED (Y-M-D)					
89-03-03		89-03-03					
DATE REPORTED (Y-M-D)		ANALYST					
89-03-09		B. ANDERSON					
OTHER INFORMATION							
COMP	MOLE FRACTION		PETROLEUM LIQUID CONTENT m³/m³	GROSS HEATING VALUE MJ/m³ 15°C AND 101.325 kPa			
	AIR FREE AS RECEIVED	AIR FREE ACID GAS FREE		MEASURED	CALCULATED	DETERMINED DEW POINT	
	H ₂	0.0094		0.0097		40.68	°C
	He	0.0004		0.0004			80. kPa
	N ₂	0.0172		0.0178			
	CO ₂	0.0285		0.0000			
	H ₂ S	0.0049		0.0000			
	C ₁	0.8667		0.8967			
	C ₂	0.0403		0.0417			
	C ₃	0.0180		0.0186	66.2		
	IC ₄	0.0035		0.0036	15.3		
	NC ₄	0.0053		0.0055	22.3		
	IC ₅	0.0017		0.0018	8.3		
	NC ₅	0.0013		0.0013	6.3		
	C ₆	0.0008		0.0008	4.4		
C ₇	0.0019	0.0020	11.7				
C ₈	0.0001	0.0001	0.7				
C ₉	0.0000	0.0000	0.0				
C ₁₀₊	0.0000	0.0000	0.0				
TOTAL	1.0000	1.0000	135.2				
H ₂ S g/m³		7.12					
RELATIVE MOLECULAR MASS		TOTAL GAS		18.82	c. 100.91		
C ₅₊ ML/MOL		0.742					
GROSS HEATING VALUE AS PER AGA REPORT #5							
39.44 MJ/M3 @ 15°C AND 101.325 kPa							
THE DOWN HOLE SAMPLER WAS RECEIVED WITH AN OPENING PRESSURE OF 700 kPaG @ 20°C. IT CONTAINED 641970 ML GAS, 1944 ML OIL AND 756 ML MUDDY WATER @ 20°C & 88.5 kPa.							
GOR: 283.51 M3/M3 @ 15°C & 101.325 kPa							

CHEMICAL & GEOLOGICAL LABORATORIES LTD.



OIL ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER					
		C89-4296-2					
LICENCE NUMBER	OPERATOR NAME						
	PARAMOUNT RESOURCES LTD.						
LOCATION	WELL NAME						
60-06-31.55 -117 39	PARAMOUNT ET AL CAMERON L-47						
FIELD OR AREA	POOL OR ZONE						
CAMERON	KEG RIVER						
TEST TYPE	NO.	TEST RECOVERY					
DST	3	108 M					
MULTIPLE RECOVERY		Y N					
SAMPLING POINT							
DOWN HOLE SAMPLER #119							
AMT. & TYPE OF CUSHION							
MUD RESISTIVITY @ 25°C							
TEST INTERVAL (metres)		TYPE OF PRODUCTION					
1510 - 1534		PUMPING	FLOWING				
PERFORATIONS (metres)		GAS LIFT	SWAB				
		PRODUCTION RATES					
WATER		m³/d	OIL	m³/d	GAS	10³m³/d	
GAUGE PRESSURE kPa		SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED	RECEIVED
TEMPERATURE °C		SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED	RECEIVED
DATE SAMPLED (Y-M-D)	DATE RECEIVED (Y-M-D)	DATE REPORTED (Y-M-D)	ANALYST	OTHER INFORMATION			
89-03-03	89-03-03	89-03-09	S. SARGIOUS				

SAMPLE PROPERTIES

B.S. & W. (VOLUME FRACTION)			
COLOR OF CLEAN OIL	WATER	SEDIMENT	TOTAL
BROWN	0.172	0.108	0.280
DENSITY at 15°C			
RELATIVE	ABSOLUTE kg/m³		
AS RECEIVED	AS RECEIVED	AFTER CLEANING	854
		0.855	
A.P.L GRAVITY		34.0	
TOTAL SULFUR		POUR POINT °C	
(MASS FRACTION)	g/kg	U.S.B.M.	A.S.T.M.
0.0122	12.2	-13	
CARBON RESIDUE (MASS FRACTION)			
RVP kPa	CONRADSON	RAMSBOTTOM	
	0.0256		
VISCOSITY			
TEMP. °C	ABSOLUTE mPa.s	KINEMATIC mm²/s	
10	13.6	15.8	
20	8.54	10.0	
40	4.46	5.32	

DISTILLATION

VOLUME FRACTION DISTILLED	TEMP. °C
1.B.P.	58
0.05	99
0.10	123
0.15	152
0.20	177
0.25	204
0.30	231
0.35	256
0.40	284
0.45	309
0.50	332
0.55	348
0.60	358
0.65	
0.70	
0.75	
0.80	
0.85	
0.90	
0.95	
1.00	
F.B.P.	
CRACKED	360

METHOD: MODIFIED ASTM D 86

BAROM. PRESS. kPa (mm) ROOM TEMP. °C

88.9 25

DISTILLATION SUMMARY (VOLUME FRACTION)

20°C NAPHTHA	27°C KEROSENE	35°C LIGHT GAS OIL
0.245	0.145	0.160

RECOVERED RESIDUE DISTILLATION LOSS

BASE TYPE: MIXED

CHARACTERIZATION FACTOR: 11.9

BS & W DETERMINED ON SAMPLE AS RECEIVED. REMAINDER OF ANALYSIS DETERMINED ON SAMPLE AFTER CLEANING BY CENTRIFUGING.

CHEMICAL & GEOLOGICAL LABORATORIES LTD.



OIL ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER	
		C89-4296-3	
LICENCE NUMBER		OPERATOR NAME	
		PARAMOUNT RESOURCES LTD.	
LOCATION		WELL NAME	
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47	
FIELD OR AREA		POOL OR ZONE	
CAMERON		KEG RIVER	
TEST TYPE		NAME OF SAMPLER	
DST	3		
TEST RECOVERY			
TEST TYPE NO.			
108 M			
MULTIPLE RECOVERY			
<input checked="" type="checkbox"/> X			
SAMPLING POINT		AMT. & TYPE OF CUSHION	
COLLARS #3			
TEST INTERVAL (metres)		MUD RESISTIVITY @ 25°C	
1510 - 1534			
PERFORATIONS (metres)			
TEST INTERVAL (metres)		TYPE OF PRODUCTION	
1510 - 1534		PUMPING	FLOWING
		GAS LIFT	SWAB
GAUGE PRESSURE		WATER	m³/d
		SEPARATOR	OIL
TEMPERATURE		SEPARATOR	m³/d
		TREATER	GAS
DATE SAMPLED (Y-M-D)		RESERVOIR	10³m³/d
89-03-03		SOURCE	
DATE RECEIVED (Y-M-D)		SAMPLED	
89-03-03		RECEIVED	
DATE REPORTED (Y-M-D)		ANALYST	OTHER INFORMATION
89-03-06		S. SARGIUS	

SAMPLE PROPERTIES

B.S. & W. (VOLUME FRACTION)			
COLOR OF CLEAN OIL	WATER	SEDIMENT	TOTAL
BROWN	0.080	0.900	0.980
----- DENSITY @ 15°C -----			
RELATIVE	ABSOLUTE kg/m³		
AS RECEIVED	AFTER CLEANING	AS RECEIVED	AFTER CLEANING
	0.866		865
A.P.I. GRAVITY			
31.9			
TOTAL SULFUR		POUR POINT °C	
(MASS FRACTION)	PPM	U.S.B.M.	A.S.T.M.
0.0127	12.7		
CARBON RESIDUE (MASS FRACTION)			
RVP kPa	CONRADSON	RAMSBOTTOM	
	0.0278		
VISCOSITY			
TEMP. °C	ABSOLUTE mPa.s	KINEMATIC mm²/s	
10	17.6	20.2	
20	10.1	11.7	
40	5.03	5.92	

DISTILLATION

VOLUME FRACTION DISTILLED	TEMP. °C	
1.B.P.		
0.05		
0.10		
0.15		
0.20		
0.25		
0.30		
0.35		
0.40		
0.45		
0.50		
0.55		
0.60		
0.65		
0.70		
0.75		
0.80		
0.85		
0.90		
0.95		
1.00		
F.B.P.		
CRACKED		
METHOD		
BAROM. PRESS. kPa (mm)		
ROOM TEMP. °C		
DISTILLATION SUMMARY (VOLUME FRACTION)		
200°C NAPHTHA	270°C KEROSENE	350°C LIGHT GAS OIL
RECOVERED	RESIDUE	DISTILLATION LOSS
BASE TYPE:		
CHARACTERIZATION FACTOR: 11.8		

BS & W DETERMINED ON SAMPLE AS RECEIVED. REMAINDER OF ANALYSIS DETERMINED ON SAMPLE AFTER CLEANING BY CENTRIFUGING.

INSUFFICIENT RECOVERABLE SAMPLE FOR FURTHER ANALYSIS.



CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER							
		C89-4296-6							
LICENCE NUMBER		OPERATOR NAME							
		PARAMOUNT RESOURCES LTD.							
LOCATION		WELL NAME							
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47							
FIELD OR AREA		POOL OR ZONE							
CAMERON		KEG RIVER							
NAME OF SAMPLER		ELEVATIONS (metres) K.B. 723 GRD. 719.3							
TEST TYPE		COMPANY							
DST		SCOTT TESTERS							
NO.	3	TEST RECOVERY							
Y	N								
MULTIPLE RECOVERY		SAMPLING POINT							
		AMT. & TYPE OF CUSHION							
		MUD RESISTIVITY (@ 25°C)							
TEST INTERVAL (metres) 1510 - 1534		TYPE OF PRODUCTION							
		PUMPING	FLOWING	GAS LIFT	SWAB				
PERFORATIONS (metres)		PRODUCTION RATES							
		WATER	m ³ /d	oil	m ³ /d	gas	10 ³ m ³ /d		
		GAUGE PRESSURE	kPa	SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED	RECEIVED
		TEMPERATURE	°C	SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED	RECEIVED
DATE SAMPLED (Y-M-D)		DATE RECEIVED (Y-M-D)		DATE REPORTED (Y-M-D)		ANALYST	OTHER INFORMATION		
89-03-03		89-03-03		89-03-06		S. SARGIOUS			

COLLARS #1

RESISTIVITY: 0.529 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER CONTAINING A TRACE OF HYDROCARBONS.

COLLARS #2

RESISTIVITY: 0.480 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER CONTAINING A TRACE OF HYDROCARBONS.



WATER ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER	
		C89-4344-1	
LICENCE NUMBER		OPERATOR NAME	
		PARAMOUNT RESOURCES LTD.	
LOCATION		WELL NAME	
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47	
FIELD OR AREA		POOL OR ZONE	
CAMERON		SLAVE POINT	
TEST TYPE		NAME OF SAMPLER	
DST		TEST RECOVERY	
NO. 4		72 M MUD CUT INHIBITOR	
MULTIPLE RECOVERY <input checked="" type="checkbox"/>			
TEST INTERVAL (metres) 1335 - 1359		SAMPLING POINT	
PERFORATIONS (metres)		AMT. & TYPE OF CUSHION	
COLLARS - BOTTOM		MUD RESISTIVITY $^{25^{\circ}\text{C}}$	
DATE SAMPLED (Y-M-D) 89-03-03		TYPE OF PRODUCTION	
DATE RECEIVED (Y-M-D) 89-03-07		PUMPING	
DATE REPORTED (Y-M-D) 89-03-09		FLOWING	
ANALYST S. SARGIOUS		GAS LIFT	
		SWAB	
GAUGE PRESSURE kPa		PRODUCTION RATES	
TEMPERATURE $^{\circ}\text{C}$		WATER m^3/d	
		OIL m^3/d	
		GAS $10^3 \text{m}^3/\text{d}$	
SEPARATOR		SEPARATOR	
TREATER		TREATER	
RESERVOIR		RESERVOIR	
SOURCE		SOURCE	
SAMPLED		SAMPLED	
RECEIVED		RECEIVED	
DATE SAMPLED (Y-M-D) 89-03-03		OTHER INFORMATION	
DATE RECEIVED (Y-M-D) 89-03-07			
DATE REPORTED (Y-M-D) 89-03-09			
ANALYST S. SARGIOUS			
ION	Mg/l	Mass Fraction	Meq/l
Na	7 125	0.3100	309.94
K	40	0.0017	1.02
Ca	240	0.0104	11.98
Mg	12	0.0005	0.99
Ba			
Sr			
Fe	MUCH		
Cl	900	0.0392	25.38
Br			
I			
HCO ₃	458	0.0199	7.51
SO ₄	14 210	0.6182	295.57
CO ₃	0	0.0000	0.00
OH	0	0.0000	0.00
H ₂ S	NIL		

TOTAL SOLIDS Mg/l

EVAPORATED @ 110°C	EVAPORATED @ 180°C
26 270	
AT IGNITION	CALCULATED
22 110	22 985


ORGANICS: MUCH

RELATIVE DENSITY $6 25^{\circ}\text{C}$	REFRACTIVE INDEX $1.3362 25^{\circ}\text{C}$
1.014	
8.2	23 °
	0.433 25°C

REMARKS

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER.

LOGARITHMIC PATTERN Meq/l





CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER						
		C89-4344-2						
LICENCE NUMBER		OPERATOR NAME						
		PARAMOUNT RESOURCES LTD.						
LOCATION		WELL NAME						
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47						
FIELD OR AREA		POOL OR ZONE						
CAMERON		SLAVE POINT						
NAME OF SAMPLER		COMPANY						
		SCOTT TESTERS						
TEST TYPE	NO.	TEST RECOVERY						
DST	4	72 M MUD CUT INHIBITOR						
multiple recovery	<input checked="" type="checkbox"/> X	SAMPLING POINT	AMT. & TYPE OF CUSHION					
		MUD RESISTIVITY @ 25°C						
TEST INTERVAL (metres)	TYPE OF PRODUCTION							
1335 - 1359	PUMPING	FLOWING	GAS LIFT					
PERFORATIONS (metres)	SWAB	PRODUCTION RATES						
	WATER	m³/d	OIL	m³/d	GAS	10³m³/d		
	SEPARATOR		TREATER		RESERVOIR			
GAUGE PRESSURE	kPa				SOURCE			
TEMPERATURE	°C				SAMPLED			
DATE SAMPLED (Y-M-D)	89-03-03	DATE RECEIVED (Y-M-D)	89-03-07	DATE REPORTED (Y-M-D)	89-03-09	ANALYST	S. SARGIOUS	OTHER INFORMATION

COLLARS - TOP

RESISTIVITY: 0.625 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER.

COLLARS - MIDDLE

RESISTIVITY: 0.609 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER.



OIL ANALYSIS

CONTAINER IDENTITY		LABORATORY NUMBER		
		C89-4345-2		
LICENCE NUMBER		OPERATOR NAME		
		PARAMOUNT RESOURCES LTD.		
LOCATION		WELL NAME		
60-06-31.55 -117 39		PARAMOUNT ET AL CAMERON L-47		
FIELD OR AREA		POOL OR ZONE		
CAMERON		SLAVE POINT		
TEST TYPE		NAME OF SAMPLER		
DST		TEST RECOVERY		
NO.				
Y <input type="checkbox"/>		85 M MUD CUT INHIBITOR		
N <input checked="" type="checkbox"/>				
MULTIPLE RECOVERY				
<input type="checkbox"/> X				
TEST INTERVAL (metres)		SAMPLING POINT		
1335 - 1359		DOWN HOLE SAMPLER #302		
PERFORATIONS (metres)		AMT. & TYPE OF CUSHION		
		MUD RESISTIVITY		
		@ 25°C		
DATE SAMPLED (Y-M-D)		TYPE OF PRODUCTION		
89-03-04		PUMPING	FLOWING	
DATE RECEIVED (Y-M-D)		GAS LIFT	SWAB	
89-03-07		PRODUCTION RATES		
DATE REPORTED (Y-M-D)		WATER m ³ /d	OIL m ³ /d	GAS 10 ⁴ m ³ /d
89-03-09		SEPARATOR	TREATER	RESERVOIR
ANALYST		SOURCE	SAMPLED	RECEIVED
S. SARGIOUS		SOURCE	SAMPLED	RECEIVED
OTHER INFORMATION				

SAMPLE PROPERTIES

B.S. & W. (VOLUME FRACTION)			
COLOR OF CLEAN OIL	WATER	SEDIMENT	TOTAL
BROWN	0.400	0.500	0.900
----- DENSITY at 15°C -----			
RELATIVE		ABSOLUTE kg/m ³	
AS RECEIVED	AFTER CLEANING	AS RECEIVED	AFTER CLEANING
	0.852		851
A.P.I. GRAVITY			
34.6			
TOTAL SULFUR		POUR POINT °C	
(MASS FRACTION)	PPM	U.S.B.M.	A.S.T.M.
0.0088	8.8	-13	
CARBON RESIDUE (MASS FRACTION)			
RVP kPa	CONRADSON	RAMSBOTTOM	
	0.0111		
VISCOSITY			
TEMP. °C	ABSOLUTE mPa.s	KINEMATIC mm ² /s	
10	12.2	14.2	
20	7.68	9.04	
40	3.92	4.69	

DISTILLATION


VOLUME FRACTION DISTILLED	TEMP. °C	
0.00		
0.05		
0.10		
0.15		
0.20		
0.25		
0.30		
0.35		
0.40		
0.45		
0.50		
0.55		
0.60		
0.65		
0.70		
0.75		
0.80		
0.85		
0.90		
0.95		
1.00		
F.B.P.		
CRACKED		
METHOD		
BAROM. PRESS. kPa (mm)		
ROOM TEMP. °C		
DISTILLATION SUMMARY (VOLUME FRACTION)		
200°C NAPHTHA	275°C KEROSENE	350°C LIGHT GAS OIL
RECOVERED	RESIDUE	DISTILLATION LOSS
BASE TYPE:		
CHARACTERIZATION FACTOR: 11.8		

BS & W DETERMINED ON SAMPLE AS RECEIVED. REMAINDER OF ANALYSIS DETERMINED ON SAMPLE AFTER CLEANING BY CENTRIFUGING. INSUFFICIENT RECOVERABLE OIL FOR FURTHER ANALYSIS.



WATER ANALYSIS

LOGARITHMIC PATTERN Meq/l



BROWN COLORED FIL-
TRATE RECOVERED FROM
THE WATER PORTION OF
THE SAMPLE.



CHEMICAL & GEOLOGICAL LABORATORIES LTD.



CONTAINER IDENTITY		LABORATORY NUMBER				
		C89-4345-4				
LICENCE NUMBER	OPERATOR NAME					
	PARAMOUNT RESOURCES LTD.					
LOCATION	WELL NAME					
60-06-31.55 -117 39	PARAMOUNT ET AL CAMERON L-47					
FIELD OR AREA	POOL OR ZONE	NAME OF SAMPLER				
CAMERON	SLAVE POINT	COMPANY				
TEST TYPE	NO.	TEST RECOVERY				
DST	5	85 M MUD CUT INHIBITOR				
MULTIPLE RECOVERY	<input checked="" type="checkbox"/>	SAMPLING POINT	AMT. & TYPE OF CUSHION			
TEST INTERVAL (metres)	MUD RESISTIVITY (μ 25°C)					
1335 - 1359						
PERFORATIONS (metres)	TYPE OF PRODUCTION					
	PUMPING	FLOWING	GAS LIFT			
			SWAB			
PRODUCTION RATES						
DATE SAMPLED (Y-M-D)	WATER	m ³ /d	OIL	m ³ /d	GAS	10 ³ m ³ /d
89-03-04	SEPARATOR		TREATER		RESEVOIR	
DATE RECEIVED (Y-M-D)	GAUGE PRESSURE	kPa	SEPARATOR		TREATER	
89-03-07	TEMPERATURE	°C	RESEVOIR		SOURCE	
DATE REPORTED (Y-M-D)	ANALYST		SOURCE		SAMPLED	
89-03-09	S. SARGIOUS		SAMPLED		RECEIVED	
OTHER INFORMATION						

TOP

RESISTIVITY: 0.645 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM A SAMPLE CONTAINING APPROXIMATELY 25% SEDIMENT.

MIDDLE

RESISTIVITY: 0.449 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER.

BOTTOM

RESISTIVITY: 0.389 OHM M @ 25C

BROWN COLORED FILTRATE RECOVERED FROM MUDDY WATER.



CALGARY — EDMONTON — GRANDE PRAIRIE

OIL ANALYSIS

CONTAINER IDENTIFICATION

PB #1

LABORATORY NUMBER

09839A

PARAMOUNT RESOURCES LTD.

OPERATOR NAME

UNIQUE WELL IDENTIFIER

WELL NAME

KB m ELEVATIONS
GRD m

PARAMOUNT CAMERON L-47

FIELD OR AREA

POOL OR ZONE

NAME OF SAMPLER

COMPANY

CAMERON

KEG RIVER

SAME

TEST TYPE

NO

TEST RECOVERY

TEST INTERVAL OR PERFS

1496.5-1499m

SAMPLING POINT

AMT & TYPE OF CUSHION

MUD RESISTIVITY/ Ω m

@25°C

GAUGE PRESSURE kPa	SEPARATOR	TREATER	RESERVOIR	SOURCE	SAMPLED	RECEIVED
TEMPERATURE °C						

DATE SAMPLED (Y-M-D)

DATE RECEIVED (Y-M-D)

DATE REPORTED (Y-M-D)

ANALYST

OTHER INFORMATION

89-04-05

89-04-11

R,C,B,L

COLOUR OF CLEAN OIL

DARK BROWN

SAMPLE PROPERTIES

B.S. & W. (VOLUME FRACTION)

WATER

SEDIMENT

TOTAL

0.009

TRACE

0.009

COLOUR NUMBER ASTM D-155

D 8 A.S.T.M.

DENSITY

ABSOLUTE kg/m^3

RELATIVE

AFTER CLEANING

AS RECEIVED

AFTER CLEANING

API GRAVITY @ 15°C

0.8563

855.5

33.75

TOTAL SULPHUR
(MASS FRACTION)

0.00886

TOTAL SALT g/m^3

U.S.B.M.

AST.M.

-9

POUR POINT / °C

RVP/kPa

CONRADSON

RAMSBOTTOM

VISCOSITY

TEMP / °C

ABSOLUTE/mPa*s

KINEMATIC/mm²s⁻¹

25

7.37

8.68

38

5.08

6.04

50

3.78

4.54

VOLUME FRACTION	TEMP / °C
0.05	122.3
0.10	151.6
0.15	174.9
0.20	197.1
0.25	221.4
0.30	243.6
0.35	263.8
0.40	284.0
0.45	300.2
0.50	319.4
0.55	336.6
0.60	355.8
0.65	363.9
0.70	372.0
0.75	379.1
0.80	383.1
0.85	391.2
0.90	
0.95	
1.00	
F.B.P.	391.2
CRACKED	

DISTILLATION

METHOD

A.S.T.M.-D86*

INITIAL BOILING POINT

85.9

ABS BAROM PRESS/kPa

89.1

ROOM TEMP / °C

19.0

DISTILLATION SUMMARY

(VOLUME FRACTION)

200°C NAPHTHA	275°C KEROSENE	350°C LIGHT GAS OIL
0.21	0.38	0.58

RECOVERED

0.90

RESIDUE

0.08

DISTILLATION LOSS

0.02

CHARACTERIZATION FACTOR

11.9

REMARKS: * THE DISTILLATION TEMPERATURES HAVE BEEN CORRECTED TO 101.3 KPA(ABS).

87-04-02

LLOYD JEFFRIES
MIKE CHOLECH

RE: Paramount et al CAMRON L-47

OPENED WELL AT 1200 HOURS. SITP 690 PS

TIME	PRESS	CHOKE	ORIFICE	SEP.	STAT.	DIFF	OIL	Cum oil
12:00	690	18/64	1.25					
* 12:30	400	18/64	"	55	56	8	9	9
13:00	405	21/64	"	58	56	14	14	23
** 13:30	425	"	"	56	56	14	14	39
*** 14:00	435	"	"	45	42	20	14	53
14:30	450	"	"	46	43	22	15	68
15:00	465	"	"	45	43	24	16	82
15:30	480	"	"	45	43	26	16	98
16:00	485	"	"	44	43	27	17	115
16:30	490	"	"	44	43	28	16	131

TOTAL OIL PRODUCTION 520 BBLs

698 B/D
avg

* BYPASSING FLOW TO FLOWING STACK

** H₂S - 30 ppm

*** REDUCED SEPARATION PRESSURE TO 44 PSI

M-31: TIGHTENED WELLHEAD BOLTS

89.04.01

LLOYD JEFFRIES
MIKE CHOLACH

FAX 262-7994

Paramount et al. Cameron 1-47

OPENED WELL AT 14:05 FLUID TO SEPARATOR AT 14:20. SHUT IN PRESSURE
620 PSI.

Flow Data

TIME	PRESS	CHOME	SEP PSIG	STATIC PSIG	DIFF	ORIFICE	BBL	COM OIL
14:05	620	16/64				14.25		
14:30		16/64				"	18	18
15:00	400	20/64	43	40	52	"	20	38
15:30	415	"	43	40	39	"	30	68
16:00	420	"	43	40	69	"	25	93
16:30	420	"	50	46	62	"	32	125
17:00	440	"	50	46	6.3	"	25	150
17:30	450	"	50	46	70	"	28	178
18:00	460	"	58	62	54	"	26	204
18:30	470	"	58	56	62	"	24	224
19:00	475	"	60	56	6.8	"	22	250

* INCREASED SEPARATOR PRESS TO 60 PSI

CUMULATIVE PRODUCTION TO DATE: 3.89 BBL'S

AVG 1200 BBL

DAILY COST \$6190

CUMULATIVE COST \$352,702

Paramount et al. Cameron 1-47

PLACED R AND F PROFILES IN TUBING. BOTH HELD (TUBING WAS TIED
OFF AT 750 m. USED ADDITIONAL INJECTION LINE TO CLEAR ICE)

DAILY COSTS MARCH 21 TO 31/89 \$19,650

G.O.R. ≈ 555

89-03-31

LLOYD JEFFRIES
MINE CHOLACUS

FAX 262-7994

PARAMOUNT et al CANNONON L-47

Note: TOTAL OR PRODUCTION TO 08:00 1100hrs 89-03-30
WAS 57 BBLs.

SUMMARY OF FLOW PERIODS.

TIME	CHORE	PRESS.	SP	DP	PROD (BBLs)
0800-1000	12K4	200	0.75"	30	14

RIGGED IN Nowaco FOR ACID-N₂ SQUEEZE (KEE RIVER FORMATION-
PERFORATIONS 1496.5M - 1499M), HELD SAFETY MEETING. PRESSURE
 TESTED LINES TO 20 MPa. PUMPED 0.5 m³ 28% HCl @ 4000
 kPa. CONTINUED PUMPING 1.2 m³ ACID + 100 m³/min N₂. STOPPED
 PUMPING WHEN PRESSURE REACHED 16 MPa. DISCUSSED
 HIGHER PUMPING PRESSURE. CONTINUED PUMPING 0.7 m³ HCl + 100 m³/min N₂
 TO 23 MPa. FEED RATE 0.1 m³/min. DISPLACED ACID WITH
 5.4 m³ N₂. AT 23 MPa. PRESSURE BROKE TO 6 MPa 35 MIN.
 FROM COMMENCEMENT OF ACID-N₂ SQUEEZE. SHUT IN WELL
 AND RIGGED TO FLOW. SET TO 7 MPa - 1000 PSI.

FLOWED WELL FROM 13:15 TO 14:45. FLUID AT SURFACE
 AT 13:35. FLOWED BACK 8.2 m³ FLUID (EMPTIED TANK).
 FLOW PRESSURE INCREASED FROM 200 PSI TO 350 PSI.

TIME	PRESS	CHORE	SP	DP	Vol	ORIFICE
13:35	200	32/64	-	-	-	1.25
14:45	350	32/64	38	75	8.2 m ³	"

509 B/0
 NOTE: WELL FLOWED 1 m³ EVERY 6 MIN FOR LAST 3 m³.


RIGGED IN ET UNIT. PRESSURE TESTED TO 21 MPa. RIN
 WITH E.T. STARTED PUMPING N₂ AT 500 m AT 20 m³/min.
 TAGGED PBTH AT 1507m. POH TO 1000 MPa/min. STOPPED
 PUMPING N₂, POH AND RIGGED OUT. WELL PRODUCED 3300L
 OIL WHILE PUMPING N₂

STARTED FLOWING WELL AT 18:45 HOURS. FLUID AT SURFACE
 AT 19:05 HOURS. INCREASED CHORE SETTING TO 32/64".
 SEPARATOR STARTED BY PASSING OIL. REDUCED CHORE
 OPENING TO 24/64". FLOW STABILIZED AT 410 PSI.
 STATIC PRESSURE 43. DIFFERENTIAL PRESSURE 38.
 ORIFICE SIZE 1.25" SHUT WELL IN 11 19:40 HOURS.
 PRODUCED 3500L OIL.

TOTAL OIL PRODUCTION FOR 89-03-31 IS 82,000L.
 COMMUNICATIVE PRODUCTION IS 13,000L.

DAILY COST - \$41,305
 COMMUNICATIVE COST - \$346,512

890330

LLOYD JEFFRIES
MIKE CHOLACH

FAX 262-7994

PARAMOUNT et al CHIMICRON L-47

COMPLETED HOOKING UP TANKS, SEPARATOR, WELLHEAD AND FLARE STACK. TRIED TO FLOW WELL, FITTINGS LEANING AROUND SEPARATOR. REPLACED 2 NIPPLES.

SIT TO 4800 KPA. STARTED FLOWING WELL AT 17:30 HOURS. PRESSURE DROPPED TO 0 IN 5 MINUTES; HOWEVER, FLAME STAYED LIT WITH A 3 FT FLAME. WELL STARTED MAKING OIL AT 18:00 HOURS. FLOW PRESSURE VARIED FROM 0 TO 80 PSI. FROM 18:00 HOURS TO 19:00 HOURS, FLOW PRESSURE 0; HOWEVER, THERE WAS CONSTANT FLUID MOVEMENT. AT 20:00 HOURS, FLOW PRESSURE INCREASED TO 150 PSI WITH GOOD FLUID MOVEMENT.

Summary:

TIME	FLOW PRESSURE	CHOKE	STATIC	GAS	Oil
18:00	20.80	24/64	40	25	
19:00	0	"	38	8	
20:00	150	"	38	80.30	688L

L-47 SITE HAS BEEN LEVELLED. GRASS SEEDING TO FOLLOW.

10 HOUR FLOW ON 1/2" CHOKE. THROUGH SEPARATE 44 BBL. AT APPROX. 6890 MCF/BBL. 890 CF/BBL

COSTS: MARCH 22 - 31 = \$24,715

CUMULATIVE COSTS = \$65,207

106 BBL/day

89.03-28

FAX

262-7994

TO: LLOYD JEFFRIES
MIKE CHOLACIA

RE: DAILY REPORTS

B-08: MOVED OUT RENTAL EQUIPMENT

L-47: SPOTTED TANKS SEPARATOR AND FLARE STACK

Ptarmigan Inn.

Fax - 874-3392

PARAMOUNT RESOURCES LTD.

WELL COMPLETION REPORT

WELL NAME: Paramount et al Cameron L-47 DATE: MARCH 22, 89PURPOSE OF JOB: CompletionCURRENT OPERATION: Rig Released 2400 Hes 89-03-21CONTRACTOR: Ball 'n #31 CHP kPaG h THP kPaG hREMARKS:

Flow well to 0900 Hes: SHUT in g Record Press
 PRODUCED 3.15 m^3 OIL, total RECOVERY 8.55 m^3 120.6 ft
 Mix 13 m^3 FRESH WATER w/ .5% Nwcor 200 Inhibitor
 Bleed OFF Well, UNSEAT Packer, Displace Annulus
 w/ 13.64 m^3 Inhibited WATER, RESET Packer & land
769 w/ Dognut. Press Test Packer, Annulus to 14 MPa, 15 min
 OK, Rig out BOP, Install g Make up WELL HEAD.
 Rig SWAB EQUIP, lower WATER level in ANNULUS w/ Rig
 Air & Tap off w/ Diesel, Pull & SWAB, Recover 6.75 m^3 total
 Recovery 15.3 m^3 , Well flowing, very gassy, SHUT in g
 Rig out SWAB EQUIP, Rig out Service Rig & EQUIP
 Rig Released 89-03-21 - 2400 Hes. Empty Service Rig Tank &
 TRANSFERRED 9 m^3 OIL to B-08 Lease Tank.
 FINAL LANDING DEPTH, BOP LANDED @ 1492.17 m KB, "R" NIPPLE
 @ 1491.92 m KB, Packed @ 1481.45 m KB, "F" nipple @ 1470.42 m KB
 SHUT in PRESS AFTER 8.5 Hes - 4600 kPa.

TOTAL LOAD FLUID (m^3): DAILY RECOVERY (m^3):
 RECOVERED TO DATE (m^3): 9 m³ (Oil) LOAD TO RECOVER (m^3):
 TOTAL DAILY COSTS? 123.30 TOTAL COSTS TO DATE 2023.72

-8 Clear.



OIL CO. PARAMOUNT RES. DATE 11/18/81 REPORT NO. 1
 ADDRESS _____ P.O. NO. _____ RIG NO. 31

#305 - 5208 - 53 AVENUE
RED DEER, ALBERTA T4N 5K2

WELL NAME & LOCATION CHILLICOTHE HILLS 6-47

TIME	SWAB NO.	FLUID LEVEL	DEPTH PULL FROM	MM IN TANK	PREVIOUS MM	M ³ PULLED	TOTAL M ³	REMARKS
5:20	1	Surf	383	114	108	.90	.70	, CHP 2 SWAB RUBS
5:40	2	780	1078	120	114	.90	1.80	
6:00	3	980	1295	126	120	.90	2.70	
6:30	4	1168	1416	132	126	.90	3.60	LITTLE BANG
6:55	5	THM	1295	138	132	.80	4.50	" "
7:30	1	982	1416	142	138	.60	5.10	Gassing after swab.
7:45	2	1168	PSIV	146	142	.60	5.10	Gassing after swab.
8:15	3	1168	PSIV	149	146	.45	6.15	" " " - Oil
9:00	4	1254	PSIV	153	149	.60	6.75	" " " - Oil
10:00	5	900KPA						Pressure Readings. Shut in @ 0900 hrs
10:45	2	1200KPA						153 Total in Big Tank.
11:00	3	1700 KPA						Pumped 65cm Water to Storage.
10:45	4	2000 KPA						85cm Oil Trucked away. Empty Big Tank.
11:00	5	2700 KPA						
11:15	6	2800 KPA						
11:30	7	3100 KPA						5:00 4500
11:45	8	3400 KPA						5:30 4500
12:00	9	3800 KPA						6:00 4600
12:15	10	4000 KPA						6:30 4600 KPa
12:30	11	4200 KPA						
12:45	12	4200 KPA						
1:00	13	4200 KPA						
1:15	14	4200 KPA						
1:30	15	4400 KPA						
1:45	16	4500 KPA						
2:00	17	4500 KPA						
2:30	18	4500 KPA						
3:00	19	4500 KPA						
3:30	20	4500 KPA						
4:00	21	4500						
4:30	22	4500						

PARAMOUNT RESOURCES LTD.

WELL COMPLETION REPORT

WELL NAME: PARAMOUNT ET AL Cameron Hills 1-47 DATE: MARCH 21, 89PURPOSE OF JOB: CompletionCURRENT OPERATION: SWAB TESTCONTRACTOR: Rollit 31 CHP kPa@ h THP kPa@ h

REMARKS:

CIRCA PBD 1507 mHR, PULL OUT 18 JTS TO 1343 m
 WORK JBG & SCRAPER THROUGH TIGHT SPOT SEVERAL
 TIMES, LOOSEN RETAL, & PUSH TO Btm,
 DISPLACE WELL w/ 17.4 m³ CLEAR PROD WATER
 PREPARE & PULL 150 ft JBG TO BIT & SCRAPER.
 BREAK OUT BIT & SCRAPER;

Rig Paramount Selectac, Down 101.6 mm HSC, 13.5pm
 23 QD. CORRELATE w/ DEPTH, PERFORATE 1496.5 TO
 1499.0 m, 2.5 m total of 34 SHOTS.

Rig out Norwest Shooters, PK/BNW ALL SHOTS FIRED.
 MAKE UP of 2" BAKER "R" nipple 2.25 ID, 1 ft 73 mm JBG,
 139.7 mm GRIBERSON UNIVI Packer, 1 ft 73 mm JBG,
 BAKER "F" nipple 3.31 ID, 154 ft JBG TO SURFACE,
 SET Packer, LWD JBG @ 1492.17 mKB, "R" Nipple @ 1491.92 mKB
 Packer RUBBERS @ 1481.45 mKB, "F" Nipple @ 1470.48 mKB. Rig to SWAB
 PULL 9 SWABS, RECOVERED 5.4 m³, WELL FLOWED .45 m³ OIL, FLUID LEVEL 8100 m

TOTAL LOAD FLUID (m³): _____ DAILY RECOVERY (m³): _____RECOVERED TO DATE (m³): _____ LOAD TO RECOVER (m³): _____REPORT FROM: Mark Gosselin RADIO PHONE: 551-8011

TAKEN BY: _____

TOTAL DAILY COSTS: 24279- TOTAL COSTS TO DATE: 267862--15° CLOUDY.



OIL CO. Paramount

DATE March 21 1989 REPORT NO. _____

ADDRESS _____

P.O. NO. _____

RIG NO. _____

#305 - 5208 - 53 AVENUE
BED DFER AIR FERTA TAN SK2

WELL NAME & LOCATION CAMERON HILLS 1-47

TIME	SWAB NO	FLUID 1 FVF	DEPTH PULL	MM IN TANK	PREVIOUS MM	M ³ PULLED	TOTAL M ³	REMARKS
11:5	1	80	460	114	110	1.35	1.35	
2:00	2	500	830	135	119	0.92	0.95	
2:15	3	780	780	127	125	0.60	2.85	
2:30	4	980	1254	133	129	0.60	3.45	Gasing
2:45	5	1168	1416	140	133	1.05	4.50	Gasing after swab
3:30	6	1168	PSN	145	140	0.75	5.25	Flowed after swab, New Cup.
4:00	7	11	PSN	148	145	0.15	5.70	Flowed Well - Oil - Sample #1
4:45		Pumped 68cm over to storage		80	148			Shut well in.
5:00	8		83	80	75	0.15		Flowed Well
5:45	9	1100	PSN	90	83	1.05	7.35	Flowed Well - Sample #2.
								272610 252610

PARAMOUNT RESOURCES LTD.

WELL COMPLETION REPORT

WELL NAME: PARAMOUNT ET AL CAMERON HILLS 6-47 DATE: MARCH 30, '89PURPOSE OF JOB: CompletionCURRENT OPERATION: Run Bit & Scaper to BtmCONTRACTOR: Roll'N #31 CHP _____ kPaG _____ h THP _____ kPaG _____ h

REMARKS:

WOC TO 1300' Has total 14,25' Hes, Measure 00, 1D
of Mill 9 subs. Make up 121 mm. FLAT Bottom Sinner Mill.
Pull up 6-13mm OC, 96.5' Hes, 134 1/3' 73' on 36g.
tag top of Retainer @ 1343' M.K.B., Break piece, Press
test to 10000 KPA OK; Mill out Criberson Cement
Retainer, Mill 1.7m Cement to 1345.4m.
Press test to 14000 KPA, Hold For 15 min, OK.
Run 18' 36g, Tag Bp @ 1505.5' M.K.B. (Pushed 13m
Cement Plug of to Btm with mill, Mill off cement
to Bridge Plug @ 1507' M.K.B. C.I.C. For 30 min.
Pull out, Work tight spot @ 1343' m, P00H,
Make up 121 mm Bit & Scaper, Run into 1343' m
Work tight spot, Cloc & SCRAP.
Run in 18' 36g

TOTAL LOAD FLUID (m³): _____DAILY RECOVERY (m³): _____RECOVERED TO DATE (m³): _____LOAD TO RECOVER (m³): _____REPORT FROM: Mark GosselinRADIO PHONE: 551 8011

TAKEN BY: _____

TOTAL DAILY COSTS: 133.05TOTAL COSTS TO DATE: 243.583

-27°C CCR.

PARAMOUNT RESOURCES LTD.

WELL COMPLETION REPORT

WELL NAME: PARAMOUNT ETAL Cameron Hills 1-42 DATE: MARCH 19, 89PURPOSE OF JOB: CompletionCURRENT OPERATION: WOC CEMENT down @ 31140 ft 89-03-18CONTRACTOR: Rollit #31 CHP kPaG h THP kPaG h

REMARKS: Pull 13 SWAB RECOVERED 14.55 m³ total of 42 SWABS
Pulled, total Recovered 57.3 m³ Fluid level @ 560.0 m +
Holding steady, SWAB RATE @ 1.5 m³/hr. Black Gassy
Formation water, Rig down SWAB EQUIP. INSERT
UNIVERSAL PACKER, PREPARE & PULL w/ 150 JTS, BREAK OUT
PACKER & 2 tail JTS. Rig up NORMWEST SHOOTERS.
Run 139.7 m BAKER MODEL "5" DRILLABLE BRIDGE PLUG.
SET @ 1507 mB, Run 139.7 m GIBBERSON TYPE "A"
CEMENT RETAINER, CORRELATE of depth, SET @ 1343 mB.
Rig out NORMWEST SHOOTERS, SERVICE & MAKE UP CEMENT
RETAINER SNAP LATCH STINGER, Run in w/ 140 JTS T69.
BREAK CIRC & CIRC WELL, Rig NORMSCO, SAFETY MEETING, PRESS
TEST TO 25000 KPA, STING INTO RETAINER, EST FEED RATE of .4m³
min @ 14000 KPA, Mix 4 T O-1-D + .7% NEL 1±.1% B5, 3m³ slurry
STING w/ 3.8m³ WATER @ 11000 KPA, .4 m³/min, STAGE 10 min last
1.3 m³ Final Press 15000 KPA. Pull out of RETAINER, BACKWASH .02m³
CEMENT, Rig out NORMSCO, PULL 140 JTS T69 to STINGER, WOC.

TOTAL LOAD FLUID (m³): _____ DAILY RECOVERY (m³): _____RECOVERED TO DATE (m³): _____ LOAD TO RECOVER (m³): _____REPORT FROM: Mark Gosselin RADIO PHONE: 551-8011

TAKEN BY: _____

TOTAL DAILY COSTS: 283.83,- TOTAL COSTS TO DATE: 230.278,-

PARAMOUNT RESOURCES LTD.

WELL COMPLETION REPORT

WELL NAME: Paramount E&L Cameron Hills L-47 DATE: MARCH 1A, '89PURPOSE OF JOB: CompletionCURRENT OPERATION: SWAB TEST KEG RIVERCONTRACTOR: Roll'n #31 CHP kPaG h THP kPaG h

REMARKS:

Pull 10 SWABS RECOVERED 4.5 m^3 , SWAB 769
 Day, very little gas, Rig Nowsco, Fill tank w/ 4.6 m^3
 Prod water, UNSEAT Packer, Safety meeting & Press
 test to 26000 kPa, Circ acid to Pore 4.23 m^3 , Set
 Packer, Squeeze total of 8.1 m^3 28% HCl, Max Press
 17000 kPa, Ave Press 11000 kPa, Max Rate $9 \text{ m}^3/\text{min}$
 initial shot in 9000 kPa, Press Bleed off to 0 kPa instantly
 Rig out Nowsco, Rig 73 mm SWAB equip.

Pull 29 SWABS, Total Load Fluid to Recover 13.73 m^3
 Recovered 45.15 m^3

Fluid level @ 563. m

New Recovery Fluid 32.4 m^3

Black Formation water X134000 m total slugs

TOTAL LOAD FLUID (m^3): 13.73 DAILY RECOVERY (m^3):

RECOVERED TO DATE (m^3): 45.15 LOAD TO RECOVER (m^3):

REPORT FROM: Mark Bosselin RADIO PHONE: 551-8011

TAKEN BY:

TOTAL DAILY COSTS: 24985 TOTAL COSTS TO DATE: 201895



AGAT Laboratories
CALGARY — EDMONTON — GRANDE PRAIRIE



WATER ANALYSIS

CONTAINER IDENTIFICATION

PP#1

LABORATORY NUMBER

WE730A

PARAMOUNT RESOURCES LTD.

OPERATOR NAME

UNIQUE WELL IDENTIFIER

WF

K8 m ELEVATIONS GRD m

723

FIELD OR AREA

PARAMOUNT et al CAMP

COMPANY

CAMERON HILLS

POOL OR ZONE

KEG RIVER

SAME

TEST TYPE

NO

SAMPLING POINT

OF & TYPE OF CUSHION

MUD RESISTIVITY/Ω m

@ 25° C

TEST INTERVAL OR PERFS

1542-1547
mKB

PUMPING

FLOWING

GAS LIFT

SWAB

WATER

m³/d

OIL

m³/d

GAS

10³ m³/d

GAUGE PRESSURE kPa

TEMPERATURE °C

SEPARATOR

TREATER

RESERVOIR

SOURCE

SAMPLED

RECEIVED

DATE SAMPLED (Y-M-D)

89-03-21

DATE RECEIVED (Y-M-D)

89-03-23

ANALYST

OTHER INFORMATION

ION	mg/L	MASS FRACTION	mmol/L
Na	29900.0	0.224	1300.0
K	1680.0	0.013	43.1
Ca	12400.0	0.093	310.0
Mg	3130.0	0.023	129.0
Ba	N. A.	N. A.	N. A.
Sr	N. A.	N. A.	N. A.
Fe	34.7	TRC*	0.6

ION	mg/L	MASS FRACTION	mmol/L
Cl	85200.0	0.637	2400.0
Br	N. A.	N. A.	N. A.
I	N. A.	N. A.	N. A.
HCO ₃	250.0	0.022	4.1
SO ₄	900.0	0.007	9.4
CO ₃	NIL	NIL	NIL
OH	NIL	NIL	NIL
H ₂ S	248.0	0.002	7.3

DISSOLVED

TOTAL SOLIDS

mg/L

EVAPORATED AT 110° C

EVAPORATED AT 180° C

AT IGNITION

CALCULATED

134220.0

RELATIVE DENSITY

1.097 @ 25° C

REFRACTIVE INDEX


N. A. @ 25° C

OBSERVED pH

6.56 @ 25° C

RESISTIVITY/Ωm

0.25 @ 25° C



SALINITY = 14.02%

TRC+= LESS THAN 0.1 N.D.= NOT DETECTED NIL= 0.0 TRC*= LESS THAN 0.001 N.A.= NOT ANALYZED

REMARKS:



AGAT Laboratories

CALGARY

EDMONTON

GRANDE PRAIRIE



WATER ANALYSIS

CONTAINER IDENTIFICATION

PB#2

LABORATORY NUMBER

W57308

PARAMOUNT RESOURCES LTD.

OPERATOR NAME

UNIQUE WELL IDENTIFIER

WELL NAME

KB m ELEVATIONS

GRD m

723

FIELD OR AREA

PARAMOUNT et al CAMERON HILLS

CAMERON HILLS

KEG RIVER

NAME OF SAMPLER

SAME

TEST TYPE

NO

TEST RECOVERY

TEST INTERVAL OR PERFS

1542-1547
mKB

SAMPLING POINT

AMT & TYPE OF CUSHION

MUD RESISTIVITY/Ω m

@ 25°C

TYPE OF PRODUCTION

PUMPING

FLOWING

GAS LIFT

SWAB

WATER

m3/d

OIL

m3/d

GAS

103 m3/d

SEPARATOR

TREATER

RESERVOIR

SOURCE

SAMPLED

RECEIVED

GAUGE PRESSURE kPa

TEMPERATURE °C

DATE SAMPLED (Y-M-D)

DATE RECEIVED (Y-M-D)

DATE REPORTED (Y-M-D)

ANALYST

OTHER INFORMATION

89-03-21

89-03-29

L

ION	mg/L	MASS FRACTION	mmol/L
Na	28600.0	0.223	1250.0
K	1530.0	0.012	39.2
Ca	11600.0	0.090	289.0
Mg	3030.0	0.024	125.0
Ba	N. A.	N. A.	N. A.
Sr	N. A.	N. A.	N. A.
Fe	2.6	TRC*	TRC+

ION	mg/L	MASS FRACTION	mmol/L
Cl	82000.0	0.639	2310.0
Br	N. A.	N. A.	N. A.
I	N. A.	N. A.	N. A.
HCO ₃	433.0	0.023	7.1
SO ₄	914.0	0.007	9.5
CO ₃	NIL	NIL	NIL
OH	NIL	NIL	NIL
H ₂ S	284.0	0.002	8.3

DISSOLVED

TOTAL SOLIDS

mg/L

EVAPORATED AT 110°C

EVAPORATED AT 180°C

AT IGNITION

CALCULATED

128000.0

RELATIVE DENSITY

1.095 @ 25°C

REFRACTIVE INDEX

N. A. @ 25°C

OBSERVED pH


6.74 @ 25°C

RESISTIVITY/Ω m

0.05 @ 25°C

LOGARITHMIC PATTERN mmol/L

SALINITY = 13.52%



REMARKS:

TRC+= LESS THAN 0.1 N.D.= NOT DETECTED NIL= 0.0 TRC*= LESS THAN 0.001 N.A.= NOT ANALYZED

WELL COMPLETION REPORT

WELL NAME: PARAMOUNT ET AL CAMERON HILLS L-47 DATE: MARCH 17, '89PURPOSE OF JOB: CompletionCURRENT OPERATION: SWAB TESTCONTRACTOR: Bull'n 31 CHP _____ kPaG _____ h THP _____ kPaG _____ h

REMARKS:

PULL 10 SWABS, SWAB FLUID LEVEL D/ TO 1536 m. SWAB
 the day, RECOVERED 4.65 m³ (169 VOLUME) PROD WATER.
 Rig in Nansen, SAFETY MEETING, PRESS TEST TO 20 MPa.
 Pump 3 m³ 28% HCl Acid, Displace w/ 4.67 m³
 PROD WATER, SQUEEZE TO 18000 kPa, Breakdown,
 PUMP RATE @ 1.6 m³ @ 13000 kPa. INITIAL SHUT IN 11500 kPa
 AFTER 15 min - 1000. Rig out Nansen
 Rig 23 mm SWAB EQUIP, TOTAL LOAD FLUID TO RECOVER
 7.67 m³, PULL 13 SWABS, RECOVERED 12.9 m³, FLUID
 LEVEL STABILIZED @ 900 m, NEW RECOVERY 5.23 m³ OF
 DIRTY BLACK GASSY FORMATION WATER, RIG OUT SWAB EQUIP
 UNSET PCKER, PULL OF 161 ft, BREAK OUT PCKER & TAIL JT.
 RIG NARWEST SHOOTERS, RUN 139.7 mm BAKER MODEL "S"
 Drillable BRIDGE PLUG, SET @ 1535.1 m, 3 RUNS & RUN
 101.6 mm HSC, 13.5PM, 23.6E, CORRELATE OF DEPTH, DEEP 1509.5-1515 m
 15.5 m total of 202 shots, Run 2 ft, Packer @ 158 ft, 269 @ 1525, Packer @ 1505.

TOTAL LOAD FLUID (m³): _____ DAILY RECOVERY (m³): _____RECOVERED TO DATE (m³): _____ LOAD TO RECOVER (m³): _____REPORT FROM: Mark Gosselin RADIO PHONE: 551-8011

TAKEN BY: _____

TOTAL DAILY COSTS: 49754. - TOTAL COSTS TO DATE: 176910. -

WELL COMPLETION REPORT

WELL NAME: PARAMOUNT E&I Cameron Hills 1-47 DATE: MARCH 16 1989PURPOSE OF JOB: CompletionCURRENT OPERATION: Swab Test - 27 Clear.CONTRACTOR: Pell'n #31 CHP _____ kPa@ _____ h THP _____ kPa@ _____ h

REMARKS: Wait on CEMENT to 1300 m/s; OPEN UP WELL, Run in slowly 25 JTS total of 163 ft/s, tag BSTD @ 1553 m/s, circ 30 min, PREPARE & PULL 163 ft/s to SCRAPER & BIT, BREAKOUT BIT & SCRAPER, GOGIA RIG INSPECTION & CREW BOP DRILL, OK - CREW IN POSITIONS & WELL SECURE IN 45 SECS, BIG NORWEST SHOOTERS, RUN CCL-C3L-VDL F/ 1553.3 m to 1300m, RUN 2000 KPA PRESS PASS w/ BEND LOG F/ 1553.3 m to 1340m, GOOD CEMENT BOND TO 1384m, NO BOND F/ 1384m to UPPER PERFS @ 1345m, BIG DOWN LOGGING TOOLS, PRESS 110 to 14000 KPA, BREAKDOWN @ 12000 KPA, FEED RATE of .075 m³/min @ 10000 KPA, BLEED OFF, RIG PERF UNIT, RUN 101.6 mm HSC, 13.5 PPM 23 GR, CORRELATE ON DEPTH, PERFORATE F/ 1542 - 1547 m/s - 5 m total of 62 SHOTS, RIG OUT PERF UNIT, CK GUN ALL SHOTS FIRED, MAKE UP 1st, 1000 ft Packer, PSN, RUN up 161 ft/s, LAND 269 @ 1547 m/s, Packer RUBBERS @ 1535 m/s. SET PACKER. RIG 23 mm SWAB EQUIP.

Swab Test.

TOTAL LOAD FLUID (m³): _____DAILY RECOVERY (m³): _____RECOVERED TO DATE (m³): _____LOAD TO RECOVER (m³): _____REPORT FROM: MARK GOSSELINRADIO PHONE: 551 8011

TAKEN BY: _____

TOTAL DAILY COSTS: 19065.-TOTAL COSTS TO DATE: 133156.-

