

PARA et al CAMERON B-38

Location: B-38 60° 10', 117° 30'

ADW #: 2002

Bottomhole Configuration (as of March 30, 2005)

Feb 19, 2007

KB: 729.89 m
GL: 725.29 m

431

NOTE:

All depths are in mKB
measured depth.

NOTE:

This well was drilled
directionally to a bottomhole
location in C-38. The well
was kicked off at 455 mKB, has an
'S' profile with a maximum
inclination of 40°, returning to
vertical at approximately 1500
mKB.

219.1 mm, 35.7 kg/m, J-55 casing set at
431 mKB. Cemented with 32 t class 'G'
cement + 2% CaCl₂. 3.0 m³ cement
returns to surface.

139.7 mm, 23.1 kg/m, LT&C, J-55 casing
set at 1652 mKB. Cemented with 30 t Thix
Lite + 1.0% SMS followed by 12 t
Expanandomix LWL + 0.1% CFL-2 + 0.2%
LTR + 0.2% SPC-II. 1.5 m³ cement returns
to surface.

73 mm, 9.67 kg/m, J-55, EUE tubing to surface

Perforated tubing
c 1515m Feb. 19/07

1517.5 - 1519.0

1522.5 - 1525.5

1594

1598

1603

1604

1609.5 - 1613.0

PBTD = 1643 mKB
TD = 1652 mKB

73 mm Blast joints

Sulphur Point Perforations

7 joints - 73 mm tubing

'CFU' Sliding sleeve w/ 58.72 mm 'F' profile
in OPEN position (bumper spring landed)

73 mm pupjoint

On-off connector w/ 57.15 mm 'F' profile
w/ plug in place

Weatherford 'QDG' packer

73 mm pupjoint

57.15 mm 'R' nipple w/ 55.8 mm NoGo

Wireline re-entry guide

Keg River Perforations

Casing set at 1652 mKB