

PARAMOUNT ET AL CAMERON B-25

60° 10' N, 117° 30' W

WID: 1756

Bottomhole Diagram (as of March 24, 2007)

KB: 757.70 m
GL: 754.30 m

Collar stop, plug, and
slip stop. Top of slip
stop at 102 mKB.

394

244.5 mm, 53.6 kg/m, J-55 casing set at
394 mKB. Cemented with 30 t class 'G'
cement + 2% CaCl₂. 4.3 m³ cement
returns to surface.

139.7 mm, 23.1 kg/m, IK-55 LT&C casing
set at 1646 mKB. Cemented with 25 t Lite
Master cement + 1% DEF-3 followed by 15
t T-E-L Master cement + 1.0% CaCl₂ +
0.15% DEF-3. Estimated cement top at
394 m.

73 mm, 9.67 kg/m, J-55, EUE tubing to surface

1376

58.7 mm 'VF' nipple

73 mm tubing joint

Cardium on-off connector with 57.1 mm 'R' profile
w/ 55.8 mm NoGo (w/ plug in place)

1386

Cardium 'DGP' retrievable packer

73 mm tubing joint

1397

Wireline re-entry guide

1405.0 - 1409.0

1414.5 - 1416.5

Sulphur Point Perforations

PBTD = 1624 mKB
Total Depth = 1649 mKB

Casing set at 1646 mKB