



Schematic - Current

Well Name: PARA ET AL CAMERON H-03

API/UWI 300H036010117300	Surface Legal Location Para et al Camerom H - 03	License # 1940	Field Name Cameron Hills	State/Province NWT
Well Configuration Type Vertical	Original KB Elevation (m) 768.97	KB-Ground Distance (m) 4.47	KB-Casing Flange Distance (m) 4.47	KB-Tubing Head Distance (m) 3.47

Most Recent Job

Job Category Completion/Workover	Primary Job Type Completion	Secondary Job Type Pump Repair	Start Date 1/9/2011	End Date 1/24/2011
-------------------------------------	--------------------------------	-----------------------------------	------------------------	-----------------------

TD: 1,662.00

Vertical - Original Hole, 4/12/2011 11:00:12 AM

MD (mKB)	TVD (mKB)	Incl (°)	DLS	Vertical schematic (actual)
			DLS (° ... * — *	
1.8				
3.6				
3.8				2-1; Tubing Hanger; 179.0; 73.0; 3.60-3.83; 0.23
4.5				
10.9				2-2; Tubing; 73.0; 62.0; 3.83-12.68; 8.85
12.7				
16.4				2-3; Tubing Pup Joint; 73.0; 62.0; 12.68-16.42; 3.74
422.6				1-1; Casing Joints; 244.5; 226.6; 4.47-422.60; 418.13
423.0				1-2; Float Shoe; 244.5; 422.60-423.00; 0.40
430.4				
964.0				2-4; Tubing; 73.0; 62.0; 16.42-1,398.21; 1,381.79
1,352.9				2-1; Casing Joints; 177.8; 161.7; 4.47-1,661.60; 1,657.13
1,398.2				
1,399.3				2-5; Anchor/catcher; 177.8; 73.0; 1,398.21-1,399.27; 1.06
1,415.0				2-6; Tubing; 73.0; 62.0; 1,399.27-1,427.94; 28.67
1,419.0				Perforated; 1,415.00-1,419.00; 1/15/2008
1,421.0				
1,421.5				Perforated; 1,421.00-1,425.00; 1/15/2008
1,425.0				
1,427.9				2-7; Pump Seating Nipple; 73.0; 62.0; 1,427.94-1,428.27; 0.33
1,428.3				
1,429.0				2-8; Perforated Joint; 73.0; 62.0; 1,428.27-1,429.50; 1.23
1,429.5				
1,438.9				2-9; Tubing; 73.0; 62.0; 1,429.50-1,438.94; 9.44
1,439.1				2-10; Wireline Guide; 73.0; 62.0; 1,438.94-1,439.07; 0.13
1,514.0				
1,517.0				
1,517.5				
1,526.0				Perforated; 1,526.00-1,545.00
1,545.0				
1,661.6				
1,662.0				2-2; Float Shoe; 177.8; 1,661.60-1,662.00; 0.40